


Robotics - Computational Motion Planning (Sampling-based)

Probabilistic Road Map (PRM)

- On every iteration, the system chooses a configuration in the configuration space **at random**
- And test whether it is in free space using the collision check function



- Green Spot: the random node
- Find route between this new node and the **closest** existing samples in the graph
- Green solid line: the new links that are added
- Dashed green lines: failure connection (due to collision check)

Pseudocode

- Repeat n times
 - Generate a random point in configuration space, x
 - If x is in free space
 - Find the k closest points in the roadmap to x according to the **Dist function**
 - Try to connect the new random sample to each of the k neighbors using the **LocalPlanner** procedure. Each successful connection forms a new edge in the graph.

Goal: Construct a graph of configuration space points and edges that capture the underlying topology of the free space

Dist Function

$$Dist(x, y) \in \mathbb{R}$$


- Common choice for distance function include:
 - The L1 distance : $Dist_1 = \sum_i |x_i - y_i|$
 - The L2 distance : $Dist_2 = \sqrt{\sum_i (x_i - y_i)^2}$
 - Handling angular displacements: $Dist(\theta_1, \theta_2) = \min(|\theta_1 - \theta_2|, (360 - |\theta_1 - \theta_2|))$

LocalPlanner

- Decide whether two points have a path between them

NOTE


- May not find a path even it exists (Or take a long time)



- Can be applied to systems with a relatively high number of degrees of freedom


Rapidly Exploring Random Trees (RRT)

- Constructing **tree**, where every node is connected to a single parent and the tree is rooted at a given starting location



Pseudocode

- Add start node to tree
- Repeat n times
 - Generate a random configuration, x
 - If x is in freespace using the **CollisionCheck** function
 - Find y , the closest node in the tree to the random configuration x
 - If (**Dist** (x,y) > δ) - check if x is too far from y
 - Find a configuration z , that is along the path from x to y such that $\text{Dist}(z,y) \leq \delta$
 - $x = z$
 - If (**LocalPlanner**(x,y)) - Check if you can get from x to y
 - Add x to the tree with y as its parent.



You can use two trees grow simultaneously (one roots from start point, another roots from end point)

Use two trees pseudocode

- While not done
 - Extend Tree A by adding a new node x
 - Find the closest node in Tree B to x, y
 - If (**LocalPlanner**(x,y)) - Check if you can bridge 2 trees
 - Add edges between x and y
 - This completes a route between the root of Tree A and the root of Tree B. Return this route
 - Else
 - Swap Tree A and Tree B (grow together)

