

0.1 code

```
1 import numpy as np
2 from itertools import combinations
3
4 # -----
5 # 1) Low function (EH-style): bottom-most 1
6 # -----i
7
8 def low(col: np.ndarray):
9     idx = np.where(col == 1)[0]
10    return None if idx.size == 0 else int(idx.max())
11
12 def lows(M: np.ndarray):
13    return [low(M[:, j]) for j in range(M.shape[1])]
14
15 def is_reduced(M: np.ndarray):
16    L = [x for x in lows(M) if x is not None]
17    return len(L) == len(set(L))
18
19 # -----
20 # 2) Standard EH reduction (left-to-right, eliminate current column using
21 #      earlier columns)
22 # -----
23 def reduce_standard_left_to_right(M: np.ndarray):
24    R = (M.copy() % 2).astype(np.uint8)
25    m = R.shape[1]
26
27    for j in range(m):
28        while True:
29            lj = low(R[:, j])
30            if lj is None:
31                break
32            # find j0 < j with same low
33            j0 = None
34            for k in range(j):
35                if low(R[:, k]) == lj:
36                    j0 = k
37                    break
38            if j0 is None:
39                break
40            R[:, j] ^= R[:, j0]    # col_j <- col_j + col_j0
41
42 # -----
43 # 3) Variant "one-sweep" (your Q2 pseudocode): push col j into right columns
44 #      sharing the same low
45 # -----
46 def reduce_variant_one_sweep(M: np.ndarray):
47    R = (M.copy() % 2).astype(np.uint8)
48    m = R.shape[1]
49
50    for j in range(m):
51        while True:
52            lj = low(R[:, j])
53            if lj is None:
54                break
55            # find a right column j0 > j with same low
56            j0 = None
57            for k in range(j + 1, m):
58                if low(R[:, k]) == lj:
59                    j0 = k
                    break
```

```

60         if j0 is None:
61             break
62         R[:, j0] ^= R[:, j]    # col_j0 <- col_j0 + col_j
63     return R
64
65 # -----
66 # 4) Variant "sweep until stable": repeat the one-sweep pass until no changes
67 # -----
68 def reduce_variant_until_stable(M: np.ndarray, max_rounds: int = 200):
69     R = (M.copy() % 2).astype(np.uint8)
70     m = R.shape[1]
71
72     for _ in range(max_rounds):
73         changed = False
74         for j in range(m):
75             while True:
76                 lj = low(R[:, j])
77                 if lj is None:
78                     break
79                 j0 = None
80                 for k in range(j + 1, m):
81                     if low(R[:, k]) == lj:
82                         j0 = k
83                         break
84                 if j0 is None:
85                     break
86                 R[:, j0] ^= R[:, j]
87                 changed = True
88             if not changed:
89                 return R
90     raise RuntimeError("max_rounds reached; increase max_rounds if needed.")
91
92 # in 4-simplice, take the submatrix as the follow: 10 rows are 1-simplices, 10
93 # columns are 2-simplices
94 A = np.array([
95     [1, 1, 1, 0, 0, 0, 0, 0, 0, 0], # 12
96     [1, 0, 0, 1, 1, 0, 0, 0, 0, 0], # 13
97     [0, 1, 0, 1, 0, 1, 0, 0, 0, 0], # 14
98     [0, 0, 1, 0, 1, 1, 0, 0, 0, 0], # 15
99     [1, 0, 0, 0, 0, 0, 1, 1, 0, 0], # 23
100    [0, 1, 0, 0, 0, 0, 0, 1, 0, 1], # 24
101    [0, 0, 1, 0, 0, 0, 0, 0, 1, 1], # 25
102    [0, 0, 0, 1, 0, 0, 0, 1, 0, 0], # 34
103    [0, 0, 0, 0, 1, 0, 0, 0, 1, 0], # 35
104    [0, 0, 0, 0, 0, 1, 0, 0, 0, 1], # 45
105 R_X = reduce_standard_left_to_right(A)
106 R_Y = reduce_variant_one_sweep(A)
107 R_Z = reduce_variant_until_stable(A)
108 print("4-simplice")
109 print("lows(R_X):", lows(R_X))
110 print("standard:", R_X)
111 print("lows(R_Y):", lows(R_Y))
112 print("one-sweep:", R_Y)
113 print("lows(R_Z):", lows(R_Z))
114 print("until stable:", R_Z)

```

0.2 matrices

	123	124	125	134	135	145	234	235	245	345
12	1	1	1	0	0	0	0	0	0	0
13	1	0	0	1	1	0	0	0	0	0
14	0	1	0	1	0	1	0	0	0	0
15	0	0	1	0	1	1	0	0	0	0
A = 23	1	0	0	0	0	0	1	1	0	0
24	0	1	0	0	0	0	1	0	1	0
25	0	0	1	0	0	0	0	1	1	0
34	0	0	0	1	0	0	1	0	0	1
35	0	0	0	0	1	0	0	1	0	1
45	0	0	0	0	0	1	0	0	1	1

	123	124	125	134	135	145	234	235	245	345
12	1	1	1	0	0	0	0	0	0	0
13	1	0	0	1	1	0	0	0	0	0
14	0	1	0	1	0	1	0	0	0	0
15	0	0	1	0	1	1	0	0	0	0
standardreducedmatrix = 23	1	0	0	0	0	0	0	0	0	0
24	0	1	0	0	0	0	0	0	0	0
25	0	0	1	0	0	0	0	0	0	0
34	0	0	0	1	0	0	0	0	0	0
35	0	0	0	0	1	0	0	0	0	0
45	0	0	0	0	0	1	0	0	0	0

	123	124	125	134	135	145	234	235	245	345
12	1	1	1	0	0	0	0	0	0	0
13	1	0	0	1	1	0	1	1	1	0
14	0	1	0	1	0	1	1	0	1	1
15	0	0	1	0	1	1	0	1	0	1
onesweepmatrix = 23	1	0	0	0	0	0	1	1	1	0
24	0	1	0	0	0	0	1	0	1	0
25	0	0	1	0	0	0	0	1	0	0
34	0	0	0	1	0	0	0	0	0	1
35	0	0	0	0	1	0	0	0	0	1
45	0	0	0	0	0	1	0	0	0	0

	123	124	125	134	135	145	234	235	245	345
12	1	1	1	0	0	0	0	0	0	0
13	1	0	0	1	1	0	0	0	0	0
14	0	1	0	1	0	1	0	0	0	0
15	0	0	1	0	1	1	0	0	0	0
untilreducedmatrix = 23	1	0	0	0	0	0	0	0	0	0
24	0	1	0	0	0	0	0	0	0	0
25	0	0	1	0	0	0	0	0	0	0
34	0	0	0	1	0	0	0	0	0	0
35	0	0	0	0	1	0	0	0	0	0
45	0	0	0	0	0	1	0	0	0	0