

problem11

Generated by Doxygen 1.8.14

Contents

1	Hierarchical Index	1
1.1	Class Hierarchy	1
2	Class Index	3
2.1	Class List	3
3	Class Documentation	5
3.1	listCity Class Reference	5
3.1.1	Constructor & Destructor Documentation	5
3.1.1.1	listCity()	5
3.1.2	Member Function Documentation	6
3.1.2.1	getVaildDest()	6
3.1.2.2	getVisited()	6
3.1.2.3	setMap()	7
3.1.2.4	setName()	7
3.2	map Class Reference	8
3.2.1	Member Function Documentation	8
3.2.1.1	check()	8
3.2.1.2	getNextCity()	9
3.2.1.3	resetVisited()	9
3.2.1.4	setVisited()	10
3.3	Node Class Reference	11
	Index	13

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

listCity	5
map	8
Node	11

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:


listCity	5
map	8
Node	11

Chapter 3

Class Documentation

3.1 listCity Class Reference

Inheritance diagram for listCity:



Public Member Functions

- `listCity ()`
- `bool getVaildDest (std::string)`
Checks if the city named entered is one of the cities that the company serves.
- `void setName (std::string)`
It is going to set the name for the city.
- `void setMap (std::string, std::string)`
Will set the names of the cities for the neighboring cities in the flightFile.txt.
- `bool getVisited (std::string)`
Will get the bool value of that city.

Protected Attributes

- `Node * top [40]`
- `Node * cityList [40]`
- `int total`

3.1.1 Constructor & Destructor Documentation

3.1.1.1 listCity()

```
listCity::listCity ( )
```

Default

Parameters

<i>none</i>	
-------------	--

Returns

none

Precondition

called to make a default city

Postcondition

will have created a default city

3.1.2 Member Function Documentation

3.1.2.1 getVaildDest()

```
bool listCity::getVaildDest (
    std::string dest )
```

Checks if the city named entered is one of the cities that the company serves.

Parameters

<i>dest,name</i>	of city
------------------	---------

Returns

validDest, which is a bool value that tells the program if the city entered is valid

Precondition

Takes in a city string to test the validity

Postcondition

Will give a bool value based on the validity of the city name

3.1.2.2 getVisited()

```
bool listCity::getVisited (
    std::string n_city )
```

Will get the bool value of that city.

Parameters

<i>n_city</i>	
---------------	--

Returns

bool

Precondition

Will take in a city name to find the city

Postcondition

Will loop through the names of the cities to find the city and then will give the bool value of that city.

3.1.2.3 setMap()

```
void listCity::setMap (
    std::string origin,
    std::string dest )
```

Will set the names of the cities for the neighboring cities in the flightFile.txt.

Parameters

<i>origin</i>	
<i>dest</i>	

Returns

void

Precondition

Will take in both city names to set to the cityList post Will set the city names to the CityList

3.1.2.4 setName()

```
void listCity::setName (
    std::string name )
```

It is going to set the name for the city.

Parameters

<i>name, name</i>	of city
-------------------	---------

Returns

void

Precondition

Is going to take in a city name to set it

Postcondition


Will have set the name of the city to cityList

The documentation for this class was generated from the following files:

- problem11.h
- problem11.cpp

3.2 map Class Reference

Inheritance diagram for map:

**Public Member Functions**

- bool [check](#) (City, City)
- void [setVisited](#) (City)

When finding the cities, this function is called to set a flag, so it doesn't come back to this city. When we visit this city it will get a value of true, meaning that this city has been visited.

- void [resetVisited](#) ()
- City [getNextCity](#) (City)

Additional Inherited Members

3.2.1 Member Function Documentation

3.2.1.1 check()

```

bool map::check (
    City origin,
    City dest )
  
```

It is going to check if there is a path between the to cities.

Parameters

<i>origin</i>	
<i>dest</i>	

Returns

bool

Precondition

to check if there is a path between cities

Postcondition

marks cities visited every run through. If there it gets NO_CITY it will pop

opens the log1 to record the cities it goes too.

3.2.1.2 getNextCity()

```
City map::getNextCity (
    City t_city )
```

gets the next available city

Parameters

<i>t_city</i>	
---------------	--

Returns

the city

Precondition

Takes in a city to get next

Postcondition

Will check if the cities are equal and if the have already been cisited. IF all is true it will return that city. If not the will return NO_CITY

3.2.1.3 resetVisited()

```
void map::resetVisited ( )
```

is going to reset all the cities visited variable to false to check again for wrong and new paths.

Parameters

<i>none</i>	
-------------	--

Returns

void

Precondition

none

Postcondition

resets the bools of all the cities

3.2.1.4 setVisited()

```
void map::setVisited (
    City CityVisited )
```

When finding the cities, this function is called to set a flag, so it doesn't come back to this city. When we visit this city it will get a value of true, meaning that this city has been visited.

Parameters

<i>CityVisited</i>	
--------------------	--

Returns

void

Precondition

Takes in a string to find the city in the list

Postcondition

Will loop through the names of the cities to find the city and then will set that cities private member ,visited, to true.

The documentation for this class was generated from the following files:

- problem11.h
- problem11.cpp

3.3 Node Class Reference

Friends

- class **listCity**
- class **map**

The documentation for this class was generated from the following files:

- problem11.h
- problem11.cpp

Index

- check
 - map, [8](#)
- getNextCity
 - map, [9](#)
- getVaildDest
 - listCity, [6](#)
- getVisited
 - listCity, [6](#)
- listCity, [5](#)
 - getVaildDest, [6](#)
 - getVisited, [6](#)
 - listCity, [5](#)
 - setMap, [7](#)
 - setName, [7](#)
- map, [8](#)
 - check, [8](#)
 - getNextCity, [9](#)
 - resetVisited, [9](#)
 - setVisited, [10](#)
- Node, [11](#)
- resetVisited
 - map, [9](#)
- setMap
 - listCity, [7](#)
- setName
 - listCity, [7](#)
- setVisited
 - map, [10](#)