

Decision forests

Cynthia Rudin




Machine Learning Course, Duke

Decision Forests

- Complex and powerful prediction tool
- Black-box
- Uses a simple but powerful idea: if you average many different yet accurate models, it reduces variance.

- Example: Will the customer wait for a table at a restaurant?
 - OthOptions: Other options, True if there are restaurants nearby.
 - Weekend: This is true if it is Friday, Saturday or Sunday.
 - Area: Does it have a bar or other nice waiting area to wait in?
 - Plans: Does the customer have plans just after dinner?
 - Price: This is either \$, \$\$, \$\$\$, or \$\$\$\$
 - Precip: Is it raining or snowing?
 - Genre: French, Mexican, Thai, or Pizza
 - Wait: Wait time estimate: 0-5 min, 5-15 min, 15+
 - Crowded: Whether there are other customers (no, some, or full)

Credit: Adapted from Russell and Norvig



New observation:
 Mexican, \$\$, Full, 5-15 min
 No plans, Yes other options

Majority Vote: Yes

Decision Forests

A **bootstrap sample** of size n : Draw n points *with replacement* at random from the training data.

(So you have some repeated points, and that's ok.)

Decision Forests

For $t=1$ to T :

- Draw a bootstrap sample of size n from the training data.
- Grow a tree ($tree_t$) using this splitting and stopping procedure:
 - Choose m features at random (out of p)
 - Evaluate the splitting criteria on all of them
 - Split on the best feature
 - If the node has less than n_{min} then stop splitting.

Output all the trees.

To predict on a new observation x , use the majority vote of the trees on x .

Decision Forests

Make trees diverse, which reduces variance

Comparison with decision trees:

- Bootstrap resamples
- Splitting considers only m possible (randomly chosen) features
- No pruning
- Majority vote of several trees is used to make predictions


Make trees fit more tightly, reduces bias

Variable Importance / Model Reliance

- How much does a model f rely on a variable?

Model Reliance(f, j)

$$= \text{Error}(f, \text{data}^{\text{scramble } j}) - \text{Error}(f, \text{data})$$



Decision Forests: Measuring Variable Importance

- Let us measure the “importance” of variable j .
- Take the data not used to construct tree_t . Call it “out-of-bag”, OOB_t .
- Compute error_t of model tree_t on data OOB_t .
- Now randomly permute only the j^{th} feature values.

Decision Forests: Measuring Variable Importance

- Let us measure the “importance” of variable j .
- Take the data not used to construct tree_t . Call it “out-of-bag”, OOB_t .
- Compute error_t of model tree_t on data OOB_t .
- Now randomly permute only the j^{th} feature values.

Reorder
me!

OOB




$$\begin{pmatrix} x_{11} & x_{12} & x_{13} \\ x_{21} & x_{22} & x_{23} \\ x_{31} & x_{32} & x_{33} \end{pmatrix}$$

Decision Forests: Measuring Variable Importance

- Let us measure the “importance” of variable j .
- Take the data not used to construct tree_t . Call it “out-of-bag”, OOB_t .
- Compute error_t of model tree_t on data OOB_t .
- Now randomly permute only the j^{th} feature values.

Reorder
me!


$$\begin{pmatrix} x_{11} & x_{32} & x_{13} \\ x_{21} & x_{12} & x_{23} \\ x_{31} & x_{22} & x_{33} \end{pmatrix}$$

Decision Forests: Measuring Variable Importance

- Let us measure the “importance” of variable j .
- Take the data not used to construct tree_t . Call it “out-of-bag”, OOB_t .
- Compute error_t of model tree_t on data OOB_t .
- Now randomly permute only the j^{th} feature values. Call this $\text{OOB}_{t,\text{permuted}}$.
- Compute $\text{error}_{t,\text{permuted}}$, using model tree_t on data $\text{OOB}_{t,\text{permuted}}$.
- The “raw importance” of variable j is then the average over trees of the difference:

$$\frac{1}{T} \sum_{\text{trees } t} \left(\text{error}_t - \text{error}_{t,\text{permuted}} \right)$$

Decision Forests: Measuring Variable Importance

- General notion of importance of a variable for a model.
- Specialized version for decision forests, where it is computed on out-of-bootstrap sample.

Decision Forests

Advantages

- Complex and powerful prediction tool, highly nonlinear
- Has notion of variable importance

Disadvantages

- Black-box
- Tends to overfit unless tuned carefully (not always intuitive with the R package)
- Slow