

Documentation for Analysis.py

Yili Yang

June 2017

1 Introduction

This code file is used to do sensitivity analysis about the EZ-climate model.

2 Methods

additional_ghg_emission: additional ghg caused by emission is the mitigation level now times the ghg level change w.r.t the emission in this period.

```
def additional_ghg_emission(m, utility):
    """Calculate the emission added by every node.

    Parameters
    -----
    m : ndarray or list
        array of mitigation
    utility : `Utility` object
        object of utility class

    Returns
    -----
    ndarray
        additional emission in nodes

    """
    additional_emission = np.zeros(len(m))
    cache = set()
    for node in range(utility.tree.num_final_states, len(m)): # the number of final
        path = utility.tree.get_path(node)
        for i in range(len(path)):
            if path[i] not in cache:
```

```

        additional_emission[path[i]] = (1.0 - m[path[i]]) * uti
        cache.add(path[i])
    return additional_emission

```

store_trees: save the values in BaseStorageTree to a csv file.

```

def store_trees(prefix=None, start_year=2015, **kwargs):
    """Saves values of `BaseStorageTree` objects. The file is saved into the 'data'
    in the current working directory. If there is no 'data' directory, one is crea

    Parameters
    -----
    prefix : str, optional
        prefix to be added to file_name
    start_year : int, optional
        start year of analysis
    **kwargs
        arbitrary keyword arguments of `BaseStorageTree` objects

    """
    if prefix is None:
        prefix = ""
    for name, tree in kwargs.items():
        tree.write_columns(prefix + "trees", name, start_year)

```

delta_consumption: Calculate the changes in consumption and the mitigation cost component of consumption when increasing period 0 mitigation with δ_m . *returns a tuple contains :*

storage tree of changes in consumption per delta m

ndarray of costs in first periods

new utility at the start point

```

def delta_consumption(m, utility, cons_tree, cost_tree, delta_m):
    """Calculate the changes in consumption and the mitigation cost component
    of consumption when increaseing period 0 mitigation with `delta_m`.

    Parameters
    -----
    m : ndarray or list
        array of mitigation
    utility : `Utility` object
        object of utility class
    cons_tree : `BigStorageTree` object
        consumption storage tree of consumption values
        from optimal mitigation values
    cost_tree : `SmallStorageTree` object

```

```

        cost storage tree of cost values from optimal mitigation values
    delta_m : float
        value to increase period 0 mitigation by

    Returns
    -----
    tuple
        (storage tree of changes in consumption per delta m, ndarray of c

    """
    m_copy = m.copy()
    m_copy[0] += delta_m

    new_utility_tree, new_cons_tree, new_cost_tree, new_ce_tree = utility.utili

    for period in new_cons_tree.periods:
        new_cons_tree.tree[period] = (new_cons_tree.tree[period]-cons_tree.

    first_period_intervals = new_cons_tree.first_period_intervals
    cost_array = np.zeros((first_period_intervals, 2))
    for i in range(first_period_intervals):
        potential_consumption = (1.0 + utility.cons_growth)**(new_cons_tree
        cost_array[i, 0] = potential_consumption * cost_tree[0]
        cost_array[i, 1] = (potential_consumption * new_cost_tree[0] - cost

    return new_cons_tree, cost_array, new_utility_tree[0]

```

constraint_first_period: Calculate the changes in consumption, the mitigation cost component of consumption, and new mitigation values when constraining the first period mitigation to ‘first_node’.

```

def constraint_first_period(utility, first_node, m_size):
    """Calculate the changes in consumption, the mitigation cost component of
    and new mitigation values when constraining the first period mitigation to

    Parameters
    -----
    m : ndarray or list
        array of mitigation
    utility : `Utility` object
        object of utility class
    first_node : float
        value to constrain first period to

    Returns
    -----

```

```

tuple
    (new mitigation array, storage tree of changes in consumption, nd

"""
#fix the first period
fixed_values = np.array([first_node])
fixed_indicies = np.array([0])
ga_model = GeneticAlgorithm(pop_amount=150, num_generations=100, cx_prob=0.
                                num_feature=m_size,
                                fixed_indicies=fixe

gs_model = GradientSearch(var_nums=m_size, utility=utility, accuracy=1e-7,
                            iterations=250, fixed_val
                            print_progress=True)

#run opt again
final_pop, fitness = ga_model.run()
sort_pop = final_pop[np.argsort(fitness)][::-1]
new_m, new_utility = gs_model.run(initial_point_list=sort_pop, topk=1)
return new_m

```

find_ir: Find the price of a bond that creates equal utility at time 0 as adding ‘payment’ to the value of consumption in the final period. The purpose of this function is to find the interest rate. embedded in the ‘EZUtility’ model. The first variable here is the utility with the final payment and the second variable is the utility with the initial payment.

find_term_structure: Find the price of a bond that creates equal utility at time 0 as adding ‘payment’ to the value of consumption just before the final period. The purpose of this function is to find the interest rate. embedded in the ‘EZUtility’ model. The first variable here is the utility with fix payment just before the final period and the second variable is the utility with the initial payment.

find_bec: Used to find a value for consumption that equalizes utility at time 0 in two different solutions. The first variable here is utility with one init consumption and the second variable is the utility with another init consumption

perpetuity_yield: Find the yield of a perpetuity starting at year ‘start_date’. The first variable here is the final price and the second is $\frac{\frac{100}{(perp_yield+100.)^{start_date}}*(perp_yield+100)}{perp_yield}$. All of the function above is finding a point on the axis where the first variable equals the second using brentq method from scipy package.

```

def find_ir(m, utility, payment, a=0.0, b=1.0):
    """Find the price of a bond that creates equal utility at time 0 as adding
    consumption in the final period. The purpose of this function is to find
    embedded in the `EZUtility` model.

```

Parameters

```

m : ndarray or list
        array of mitigation
utility : `Utility` object
        object of utility class
payment : float
        value added to consumption in the final period
a : float, optional
        initial guess
b : float, optional
        initial guess -  $f(b)$  needs to give different sign than  $f(a)$ 

Returns
-----
tuple
        result of optimization

Note
----
requires the 'scipy' package

"""

def min_func(price):
    utility_with_final_payment = utility.adjusted_utility(m, final_cons
    first_period_eps = payment * price
    utility_with_initial_payment = utility.adjusted_utility(m, first_pe
    return utility_with_final_payment - utility_with_initial_payment

return brentq(min_func, a, b)

def find_term_structure(m, utility, payment, a=0.0, b=1.5):
    """Find the price of a bond that creates equal utility at time 0 as adding
    consumption just before the final period. The purpose of this function is
    embedded in the `EZUtility` model.

Parameters
-----
m : ndarray or list
        array of mitigation
utility : `Utility` object
        object of utility class
payment : float
        value added to consumption in the final period
a : float, optional
        initial guess

```

```

    b : float, optional
        initial guess - f(b) needs to give different sign than f(a)

Returns
-----
tuple
    result of optimization

Note
----
requires the 'scipy' package

"""

def min_func(price):
    period_cons_eps = np.zeros(int(utilty.decision_times[-1]/utilty.p
    period_cons_eps[-2] = payment
    utility_with_payment = utilty.adjusted_utility(m, period_cons_eps=
    first_period_eps = payment * price
    utility_with_initial_payment = utilty.adjusted_utility(m, first_pe
    return utility_with_payment - utility_with_initial_payment

return brentq(min_func, a, b)

def find_bec(m, utilty, constraint_cost, a=-0.1, b=1.5):
    """Used to find a value for consumption that equalizes utility at time 0

Parameters
-----
m : ndarray or list
    array of mitigation
utilty : `Utility` object
    object of utility class
constraint_cost : float
    utility cost of constraining period 0 to zero
a : float, optional
    initial guess
b : float, optional
    initial guess - f(b) needs to give different sign than f(a)

Returns
-----
tuple
    result of optimization

```

```

Note
----
requires the 'scipy' package

"""

def min_func(delta_con):
    base_utility = utility.utility(m)
    new_utility = utility.adjusted_utility(m, first_period_consadj=delt
    print(base_utility, new_utility, constraint_cost)
    return new_utility - base_utility - constraint_cost

return brentq(min_func, a, b)

def perpetuity_yield(price, start_date, a=0.1, b=10.0):
    """Find the yield of a perpetuity starting at year `start_date`.

    Parameters
    -----
    price : float
        price of bond ending at `start_date`
    start_date : int
        start year of perpetuity
    a : float, optional
        initial guess
    b : float, optional
        initial guess - f(b) needs to give different sign than f(a)

    Returns
    -----
    tuple
        result of optimization

    Note
    ----
    requires the 'scipy' package

    """

    def min_func(perp_yield):
        return price - (100. / (perp_yield+100.))**start_date * (perp_yield

    return brentq(min_func, a, b)

```

2.1 Climate Output Class

Calculate and save output from the EZ-Climate model

2.1.1 Inputs and Outputs

Inputs:

- **utility** : ('Utility' object) object of utility class

Outputs: Calculated values based on optimal mitigation. For every **node** the function calculates and saves:

- average mitigation
- average emission
- GHG level
- SCC

For every **period** the function also calculates and saves:

- expected SCC/price
- expected mitigation
- expected emission

2.1.2 Attributes

- **utility** : ('Utility' object) object of utility class
- **prices** : ndarray SCC prices
- **ave_mitigations** : (ndarray) average mitigations
- **ave_emissions** : (ndarray) average emissions
- **expected_period_price** : (ndarray) expected SCC for the period
- **expected_period_mitigation** : (ndarray) expected mitigation for the period
- **expected_period_emissions** : (ndarray) expected emission for the period

```
def calculate_output(self, m):  
    """Calculated values based on optimal mitigation. For every **node** the j  
        * average mitigation  
        * average emission  
        * GHG level  
        * SCC
```


as attributes.

*For every **period** the function also calculates and saves*

- * expected SCC/price*
- * expected mitigation*
- * expected emission*

as attributes.

Parameters

m : ndarray or list
array of mitigation

"""

```
bau = self.utility.damage.bau
tree = self.utility.tree
periods = tree.num_periods

self.prices = np.zeros(len(m))
self.ave_mitigations = np.zeros(len(m))
self.ave_emissions = np.zeros(len(m))
self.expected_period_price = np.zeros(periods)
self.expected_period_mitigation = np.zeros(periods)
self.expected_period_emissions = np.zeros(periods)
additional_emissions = additional_ghg_emission(m, self.utility)
self.ghg_levels = self.utility.damage.ghg_level(m)

for period in range(0, periods):
    years = tree.decision_times[period]
    period_years = tree.decision_times[period+1] - tree.decision_times[period]
    nodes = tree.get_nodes_in_period(period)
    num_nodes_period = 1 + nodes[1] - nodes[0]
    period_lens = tree.decision_times[:period+1]

    for node in range(nodes[0], nodes[1]+1):
        path = np.array(tree.get_path(node, period))
        new_m = m[path]
        mean_mitigation = np.dot(new_m, period_lens) / years
        price = self.utility.cost.price(years, m[node], mean_mitigation)
        self.prices[node] = price
        self.ave_mitigations[node] = self.utility.damage.average_mitigation(node, m)
```

```

        self.ave_emissions[node] = additional_emissions[node] / (pe

probs = tree.get_probs_in_period(period)
self.expected_period_price[period] = np.dot(self.prices[nodes[0]:no
self.expected_period_mitigation[period] = np.dot(self.ave_mitigatio
self.expected_period_emissions[period] = np.dot(self.ave_emissions[

def save_output(self, m, prefix=None):
    """Function to save calculated values in `calculate_output` in the file `p
    in the 'data' directory in the current working directory.

    The function also saves the values calculated in the utility function in
    `prefix` + 'tree' in the 'data' directory in the current working directory.

    If there is no 'data' directory, one is created.

    Parameters
    -----
    m : ndarray or list
        array of mitigation
    prefix : str, optional
        prefix to be added to file_name

    """
    utility_tree, cons_tree, cost_tree, ce_tree = self.utility.utility(m, retur

    if prefix is not None:
        prefix += "_"
    else:
        prefix = ""

    write_columns_csv([m, self.prices, self.ave_mitigations, self.ave_emissions
        prefix+"node_period_output", ["Node", "Mitigation", "Pri
        "Average Emission", "GHG Level"], [range(len(m))])

    append_to_existing([self.expected_period_price, self.expected_period_mitiga
        prefix+"node_period_output", header
        "Expected Emission"], index=[range(

    store_trees(prefix=prefix, Utility=utility_tree, Consumption=cons_tree,
        Cost=cost_tree, CertainEquivalence=ce_tree)

```

2.2 Risk Decomposition Class

new risk decomposition method, need the new paper to document it.

```
class RiskDecomposition(object):
    """Calculate and save analysis of output from the EZ-Climate model.

    Parameters
    -----
    utility : `Utility` object
            object of utility class

    Attributes
    -----
    utility : `Utility` object
            object of utility class
    sdf_tree : `BaseStorageTree` object
            SDF for each node
    expected_damages : ndarray
            expected damages in each period
    risk_premium : ndarray
            risk premium in each period
    expected_sdf : ndarray
            expected SDF in each period
    cross_sdf_damages : ndarray
            cross term between the SDF and damages
    discounted_expected_damages : ndarray
            expected discounted damages for each period
    net_discount_damages : ndarray
            net discount damage, i.e. when cost is also accounted for
    cov_term : ndarray
            covariance between SDF and damages

    """

    def __init__(self, utility):
        self.utility = utility
        self.sdf_tree = BigStorageTree(utility.period_len, utility.decision)
        self.sdf_tree.set_value(0, np.array([1.0]))

        n = len(self.sdf_tree)
        self.expected_damages = np.zeros(n)
        self.risk_premiums = np.zeros(n)
        self.expected_sdf = np.zeros(n)
        self.cross_sdf_damages = np.zeros(n)
```

```

self.discounted_expected_damages = np.zeros(n)
self.net_discount_damages = np.zeros(n)
self.cov_term = np.zeros(n)

self.expected_sdf[0] = 1.0

def sensitivity_analysis(self, m):
    """Calculate sensitivity analysis based on the optimal mitigation.
    periods given by the utility calculations, the function calculate

        * discount prices
        * net expected damages
        * expected damages
        * discounted expected damages
        * risk premium
        * cross SDF & damages
        * covariance between SDF and damages

    as attributes.

    Parameters
    -----
    m : ndarray or list
        array of mitigation
    utility : `Utility` object
        object of utility class
    prefix : str, optional
        prefix to be added to file_name

    """

    utility_tree, cons_tree, cost_tree, ce_tree = self.utility.utility(
    cost_sum = 0
    # Calculate the changes in consumption and the mitigation cost con
    self.delta_cons_tree, self.delta_cost_array, delta_utility = delta_
    # Calculate the marginal utilities
    mu_0, mu_1, mu_2 = self.utility.marginal_utility(m, utility_tree, c
    sub_len = self.sdf_tree.subinterval_len
    i = 1
    # for every period in sdf_tree (except the init point),
    for period in self.sdf_tree.periods[1:]:
        node_period = self.sdf_tree.decision_interval(period)
        period_probs = self.utility.tree.get_probs_in_period(node_p
        expected_damage = np.dot(self.delta_cons_tree[period], peri

```

```

self.expected_damages[i] = expected_damage # calculate the

if self.sdf_tree.is_information_period(period-self.sdf_tree
    total_probs = period_probs[:,2] + period_probs[1::2]
    mu_temp = np.zeros(2*len(mu_1[period-sub_len]))
    mu_temp[:,2] = mu_1[period-sub_len]
    mu_temp[1::2] = mu_2[period-sub_len]
    sdf = (np.repeat(total_probs, 2) / period_probs) *
    period_sdf = np.repeat(self.sdf_tree.tree[period-su
else:
    sdf = mu_1[period-sub_len]/mu_0[period-sub_len]
    period_sdf = self.sdf_tree[period-sub_len]*sdf

self.expected_sdf[i] = np.dot(period_sdf, period_probs)
self.cross_sdf_damages[i] = np.dot(period_sdf, self.delta_c
self.cov_term[i] = self.cross_sdf_damages[i] - self.expecte

self.sdf_tree.set_value(period, period_sdf)

if i < len(self.delta_cost_array):
    self.net_discount_damages[i] = -(expected_damage +
    cost_sum += -self.delta_cost_array[i, 1] * self.exp
else:
    self.net_discount_damages[i] = -expected_damage * s

self.risk_premiums[i] = -self.cov_term[i]/self.delta_cons_t
self.discounted_expected_damages[i] = -expected_damage * se
i += 1

def save_output(self, m, prefix=None):
    """Save attributes calculated in `sensitivity_analysis` into the j
    in the `data` directory in the current working directory.

    Furthermore, the perpetuity yield, the discount factor for the la
    expected damage and risk premium for the first period is calculat
    prefix + `tree` in the `data` directory in the current working di
    one is created.

    Parameters
    -----
    m : ndarray or list
        array of mitigation
    prefix : str, optional
        prefix to be added to file_name

```

```

"""
end_price = find_term_structure(m, self.utility, 0.01)
perp_yield = perpetuity_yield(end_price, self.sdf_tree.periods[-2])

damage_scale = self.utility.cost.price(0, m[0], 0) / (self.net_discounted_ed)
scaled_discounted_ed = self.net_discount_damages * damage_scale
scaled_risk_premiums = self.risk_premiums * damage_scale

if prefix is not None:
    prefix += "_"
else:
    prefix = ""

write_columns_csv([self.expected_sdf, self.net_discount_damages, self.cross_sdf_damages, self.discounted_expected_sdf, scaled_discounted_ed, scaled_risk_premiums],
                  ["Year", "Discount Prices", "Net Discounted Expected SDF", "Cross SDF & Damages", "Discounted Expected SDF", "Scaled Risk Premiums"], [self.utility.cost.price(0, m[0], 0)], pre
                  header=["Zero Bound Price", "Perp Yield", "Zero Bound Yield", "Zero Bound SCC"], start_char='\n')

store_trees(prefix=prefix, SDF=self.sdf_tree, DeltaConsumption=self.utility.cost.price(0, m[0], 0))

```

2.3 Constraint Analysis Class

2.4 Output

- Constraint Cost (optimum cost - cost with constraint on first period)
- Delta Consumption (value for consumption that equalizes utility at time 0 in two different solutions)
- Delta Consumption \$b (Delta Consumption * consumption per ton constant / emit level on init point)
- Delta Emission Gton (optimum emit level on the init point)
- Deadweight Cost (Delta Consumption * consumption per ton constant / optimum mitigation level on init point)
- Marginal Impact Utility (change of utility when add 0.01 on the init consumption)

- Marginal Benefit Emissions Reduction (change when change mitigation level on init point by 0.01 / change when change consumption level on init point by 0.01 * consumption per ton constant)
- Marginal Cost Emission Reduction (change on price when add constraint on the first period)

where consumption per ton constant is equal to $\frac{cons_at_0}{emit_at_0}$

```
class ConstraintAnalysis(object):
    def __init__(self, run_name, utility, const_value, opt_m=None):
        self.run_name = run_name
        self.utility = utility
        self.cfp_m = constraint_first_period(utility, const_value, utility.
        self.opt_m = opt_m
        if self.opt_m is None:
            self.opt_m = self._get_optimal_m()

        self.con_cost = self._constraint_cost()
        self.delta_u = self._first_period_delta_udiff()

        self.delta_c = self._delta_consumption()
        self.delta_c_billions = self.delta_c * self.utility.cost.cons_per_t
            * self.utility.dama
        self.delta_emission_gton = self.opt_m[0]*self.utility.damage.bau.em
        self.deadweight = self.delta_c*self.utility.cost.cons_per_ton / sel

        # adjusted benefit when +0.01 to the mitigation level at time zero
        self.delta_u2 = self._first_period_delta_udiff2()
        self.marginal_benefit = (self.delta_u2 / self.delta_u) * self.utili
        self.marginal_cost = self.utility.cost.price(0, self.cfp_m[0], 0)

    def _get_optimal_m(self):
        try:
            header, index, data = import_csv(self.run_name+"_node_perio
        except:
            print("No such file for the optimal mitigation..")
        return data[:, 0]

    def _constraint_cost(self):
        opt_u = self.utility.utility(self.opt_m)
        cfp_u = self.utility.utility(self.cfp_m)
        return opt_u - cfp_u

    def _delta_consumption(self):
        return find_bec(self.cfp_m, self.utility, self.con_cost) # value fo
```

```

def _first_period_delta_udiff(self):
    u_given_delta_con = self.utility.adjusted_utility(self.cfp_m, first
    cfp_u = self.utility.utility(self.cfp_m)
    return u_given_delta_con - cfp_u

def _first_period_delta_udiff2(self):
    m = self.cfp_m.copy()
    m[0] += 0.01 # adjusted with a fixed number
    u = self.utility.utility(m)
    cfp_u = self.utility.utility(self.cfp_m)
    return u - cfp_u

def save_output(self, prefix=None):
    if prefix is not None:
        prefix += "_"
    else:
        prefix = ""

    write_columns_csv([self.con_cost, [self.delta_c], [self.delta_c_bil
        [self.deadweight], self.delta_u,
        prefix + self.run_name + "_const
        ["Constraint Cost", "Delta Consum
        "Delta Emission Gton", "Deadweig
        "Marginal Benefit Emissions Redu

```