

# Compsci 571 HW6


Yilin Gao (yg95)

April 5, 2018


## 1 Neural Networks and Universal Approximation Theorem

### 1.1

(a) The NN architecture is like following:



The implementation is in `q1.ipynb`. The approximated function is as following:



The minimal number of hidden neurons is 2, because the bump is a combination of 2 step functions, and each neuron (with the sigmoid activation function) is able to approximate one step function with any given step direction, location and height.

(b) In the NN,  $w_{01}$  determines the steepness of the step-up part of the bump,  $w_{02}$  determines the steepness of the step-down part of the bump.  $-\frac{b_{01}}{w_{01}}$  determines the step-up location,  $-\frac{b_{02}}{w_{02}}$  determines the step-down location. And  $w_{13}$  and  $w_{23}$  determine the height of the bump.

### 1.2

(a)


- (b)
- (c)

## 2 EM


## 3 Clustering

- (a) See the implementation in q3.ipynb.
- (b) See the implementation in q3.ipynb.
- (c) The empirical clustering results on the dataset with both algorithms are as following:

K-Means:



Hierarchical Agglomerative Clustering:



From the visualization, we can tell the hierarchical agglomerative clustering algorithm performs better. On this specific dataset, the possible reason for the discrepancy is that K-Means assumes the variance of each X variable is spherical. However, the given data doesn't satisfy this assumption.

- (d) Possible preprocessing on data to make K-Means perform better: normalize each X variable to mean = 0 and variance = 1.