

APT-BENCH: PATIENT-DISJOINT EVALUATION OF GRANULARITY AND TWO-AXIS SCALING IN SINGLE-CELL APTAMER PROFILING

Anonymous authors

Paper under double-blind review

ABSTRACT

Single-cell clinical assays can contain many cells but few independent subjects, making the split unit and sampling budget central to evaluation. We introduce APT-Bench, a patient-disjoint benchmark of 361,792 single-cell aptamer profiles from 40 patients, with a fixed five-lineage/27-subtype ontology, patient-level characterization audit, and explicit patient and cell training axes. Across matched neural and classical models, coarse lineage recognition remains substantially easier than fine subtype prediction. Unmatched fixed-total reallocations confound subject breadth with the training label distribution: although 37 of 38 comparisons favor 32 rather than 8 subjects, a class-matched control reduces this apparent advantage to modest coarse gains in APT and OneK1K, while fine effects are small and change sign across cohorts. Thus the unmatched result is an audit target, not evidence for a universal subject-dominant scaling law. Here, the label-distribution effect includes changes in observed classes, per-class counts, and class proportions. Strict nested aggregation shows that cell-model outputs retain disease-associated variation, but subtype composition has no resolved increment over lineage, cell count, or recorded RNA-QC controls. Direct APT discrimination is also sensitive to patient-specific absolute-expression structure whose biological and technical origins are not identifiable here. APT-Bench makes statistical unit, granularity, and training scale explicit for evaluation on unseen subjects.

1 INTRODUCTION

Cancer screening and diagnosis are usually framed at the patient level: does a person have disease, and if so which disease category is most likely? Single-cell liquid biopsy changes this framing. A single blood draw can support both a patient-level diagnostic decision and a cell-level characterization of the circulating immune compartment. These outputs are related, but they do not live at the same observational unit. Disease is a property of the patient, whereas lineage and subtype are properties of the cell.

This mismatch matters for evaluation. Our benchmark contains 361,792 single cells, but only 40 patients. Treating cells as independent disease observations would substantially overstate the effective sample size of the diagnostic task. It would also hide a second asymmetry: lineage and subtype form a genuine cell-level hierarchy, but disease does not sit above that hierarchy. The clinically relevant problem is therefore not a single three-level taxonomy. It is a multi-resolution setting in which different targets require different evaluation protocols, inductive biases, and interpretations.

We study aptamer-based single-cell profiling. Apt-seq uses sequencing-compatible nucleic-acid affinity reagents to quantify molecules such as surface proteins while retaining cell barcodes and paired transcriptomic state (Wu et al., 2025). Unlike gene-vocabulary scRNA-seq or antibody-derived-tag integration benchmarks, our predictive input is a fixed 293-aptamer binding panel. This enables three questions: how performance changes from coarse lineage to fine subtype; how patient-level disease evaluation handles many correlated cells but only 40 subjects; and whether cell-level predictions retain patient-associated variation under strict nested aggregation.

APT-Bench fixes three patient-disjoint tracks: coarse-to-fine cell typing, two-axis training-scale evaluation, and cross-fitted patient characterization with explicit technical controls. Aptamer-panel

and inference-cell budgets are reported only as secondary sensitivities of the observed within-cohort signal. Its reusable contribution is not a claim that one cohort spans deployment, but a common contract for a new modality: immutable patient folds, explicit observational units, leakage-resistant metrics, and outer-test-isolated budget controls that can extend to future clinical single-cell cohorts.

The hierarchy track uses a matched reference ladder rather than centering the paper on a new architecture: XGBoost, a flat Transformer, the same Transformer with hierarchical cross-entropy (HCE), and a soft-cascade Transformer. The three neural references share the tokenizer, encoder dimensions, optimization budget, patient folds, and checkpoint rule. This design asks whether hierarchy mechanisms add value after controlling encoder capacity; it does not designate the cascade as a proposed method.

This perspective leads to three empirical findings. First, coarse lineage recognition is substantially easier than fine subtype recognition across all models, and encoder-matched controls do not support an advantage for the soft cascade over the simpler neural references. Second, a two-axis scaling study identifies label-distribution confounding in fixed-total evaluations. When each paired setting uses exactly the same observed classes and per-class cell quotas, subject-breadth effects are modest for coarse lineage and small or sign-changing for fine subtype. By contrast, 37 of 38 unmatched comparisons favor reallocating cells from 8 to 32 subjects because that intervention also changes the training label distribution. Subject breadth is therefore a separate design axis, but an unmatched scaling curve cannot isolate its effect from task granularity and the marginal class distribution during training. Third, strictly nested, disease-label-free XGBoost subtype probabilities retain disease-associated variation after patient aggregation: soft subtype composition reaches disease macro-F1 0.593 versus 0.477 for lineage composition. The paired difference is uncertain, however, and subtype composition does not significantly exceed cell count or a six-feature recorded RNA-QC baseline. The bridge is therefore predictive and associational; direct APT discrimination is stronger but sensitive to patient-specific absolute-expression structure.

Our contributions are therefore as follows.

- **APT-Bench, a patient-disjoint benchmark for single-cell APT liquid biopsy.** We formalize fixed patient folds, common inputs and labels, and a portable evaluation contract spanning hierarchy prediction, two-axis scaling, and confounding-aware patient characterization.
- **A controlled account of the granularity gap.** Beyond aggregate macro-F1, we report joint hierarchy metrics, subtype-level support analyses, and patient-clustered comparisons. An encoder-matched reference ladder separates hierarchy mechanisms from backbone capacity and finds no supported gain from additional cascade complexity.
- **A label-distribution audit for two-axis scaling.** Across APT, COMBAT, and OneK1K, we show that standard fixed-total comparisons conflate subject breadth with the marginal training label distribution, then introduce a class-matched control that freezes observed classes and per-class cell quotas. The corrected effects are resolution- and cohort-dependent rather than a universal scaling law. A separate strict nested audit tests cross-task transfer from disease-label-free cell-model outputs without exposing either stage to outer-test patients.

2 RELATED WORK

Liquid biopsy and multi-cancer detection. Blood-based multi-cancer early detection has focused primarily on circulating tumor DNA, methylation, fragmentomics, and bulk protein assays (Cohen et al., 2018; Zeng et al., 2026; Wan et al., 2025; Kahwati et al., 2025). These approaches target a patient-level diagnostic decision. Our setting differs because APT profiling observes individual circulating cells, which introduces a second prediction problem at cell resolution: identifying lineage and fine subtype structure within the same blood draw. The resulting task is not simply “more labels,” but a change in statistical unit and hierarchy structure.

Single-cell foundation models and modality mismatch. Large pretrained models such as Geneformer, scGPT, and scFoundation learn representations from transcriptomic data and are widely used as reference points for single-cell representation learning (Theodoris et al., 2023; Cui et al.,

2024; Hao et al., 2024). Their success does not transfer automatically to our setting. The input modality is different, since APT consists of a fixed 293-dimensional protein-oriented panel rather than a gene-vocabulary sequence. More importantly, recent evaluation work shows that frozen or zero-shot single-cell foundation-model embeddings are often matched by simpler baselines once the downstream task and evaluation protocol are made explicit (Kedzierska et al., 2025). This motivates training directly on APT profiles and treating evaluation design itself as a first-class contribution.

Reusable single-cell benchmarks. Open Problems separates datasets, methods, and metrics behind public loaders and evaluation code (Luecken et al., 2025); a 2025 multimodal benchmark similarly releases processed RNA/ADT/ATAC inputs and task-specific pipelines (Liu et al., 2025). SPARE standardizes sample-representation interfaces (Shitov et al., 2025), and PaSCient evaluates patient representations with study-separated partitions (Liu et al., 2026). None combines a fixed aptamer-binding panel, coarse-to-fine cell typing, patient-level disease audit, and aptamer-measurement/inference-aggregation budgets. APT-Bench targets this narrower gap rather than replacing broad RNA or integration benchmarks.

Hierarchical cell-type classification. Cell identity naturally admits coarse-to-fine structure, and recent work has explored losses or architectures that exploit this structure for annotation and out-of-distribution robustness (Jia et al., 2025; Cultrera di Montesano et al., 2026). Our use of hierarchy is narrower and more explicit: disease is kept outside the hierarchy, while lineage and subtype form the only genuine taxonomy. We compare Soft-cascade Transformer not only with flat classifiers but also with a matched flat FT-style Transformer control (Gorishniy et al., 2021) and the same control trained with a two-level adaptation of hierarchical cross-entropy (HCE), the most directly related hierarchy-aware loss.

Measurement-budget sensitivity. Clinical translation of high-plex assays depends not only on accuracy but also on measurement cost. As a secondary sensitivity, APT-Bench asks how the observed within-cohort disease-associated signal changes under outer-test-isolated panel selection and held-out-cell subsampling. The latter is an inference sensitivity, not reduced-cell training. Because biological and technical sources are not identifiable here, these analyses quantify feature and aggregation redundancy of a mixed signal; they do not validate a reduced assay or biomarker panel.

Tabular deep learning versus classical machine learning. APT expression is a medium-dimensional tabular signal. In that regime, gradient-boosted trees remain strong defaults and often rival or outperform deep tabular models (Grinsztajn et al., 2022; Erickson et al., 2026). This literature is directly reflected in our results: XGBoost and encoder-matched Transformer controls remain competitive at both resolutions, so Soft-cascade Transformer cannot be justified by a blanket accuracy claim. We instead use it as a structured reference for the hierarchy diagnostics, while disease association is audited with simple, strong tabular baselines.

3 PROBLEM SETUP

3.1 DATASET AND PREDICTION TARGETS

Cohort construction and specimen source. APT-Bench is derived from peripheral-blood clinical specimens collected from 40 participants: patients with colorectal cancer (CRC), gastric cancer (GC), hepatocellular carcinoma (HCC), pancreatic cancer (PC), or biliary tract cancer (BTC), and healthy controls (Normal). The six groups contain 6–8 participants each. Clinical specimens were processed into single-cell suspensions before assay preparation. The study workflow documents quality control using the forward/side-scatter cell profile and viable-cell proportion before library construction.

Paired single-cell assay and label construction. The assay jointly measures transcriptomic state and binding of 293 target-specific nucleic-acid aptamers on the same cells. Transcriptome and aptamer-barcode libraries are constructed separately and linked at the cell level by their shared barcodes. Transcriptomic counts were processed and clustered with the standard Seurat workflow (Hao et al., 2021); predicted doublets were removed with DoubletFinder (McGinnis et al., 2019), and

low-quality cells were filtered using per-cell UMI count, detected-gene count, and mitochondrial-transcript fraction. Investigators then manually annotated clusters from canonical subtype marker expression reported in prior PBMC and pan-cancer studies (Zhang et al., 2024; Yang et al., 2024). These transcriptome-derived annotations define the lineage and subtype targets, while disease labels come from participant-level cohort assignment. The benchmark input contains only the 293 APT measurements; transcriptomic measurements construct the reference labels but are never exposed to a prediction model. Exact parameters and label limitations are documented in Appendix C.1.

TODO: Complete the remaining cohort, specimen-processing, assay, and annotation parameters listed in Appendix C.1; report unavailable metadata explicitly rather than leaving them implicit.

Benchmark cohort. The linked post-QC cohort contains 374,854 cells. After excluding the transcriptome-derived *Unknown* subtype label, which denotes uncertain annotation rather than a validated biological state, the main benchmark contains 361,792 cells. Each cell is represented by a 293-dimensional APT expression vector. Expression values are log-transformed and standardized feature-wise using statistics estimated from the training partition only. The 293 aptamers are designed probes rather than an arbitrary learned basis.

APT-Bench contains two kinds of targets at different observational units.

- **Patient-level disease-association audit.** Each patient is assigned to one of six disease groups. Because every participant contributes a single acquisition and batch metadata are unavailable, this target supports within-cohort association and confounding analyses, not biological attribution or clinical validation.
- **Cell-level hierarchy prediction.** Each cell is assigned to one of five coarse immune lineages and one of 27 fine subtypes. Every subtype maps to exactly one parent lineage through a manually curated lookup table. The same subtype names and operational definitions are used across all six disease groups rather than being redefined by disease.

Disease is therefore not treated as the root of a three-level hierarchy. It is a separate patient-level label observed on the same blood draw.

TODO: Document independent biological review of the subtype-to-lineage lookup, including reviewers, disagreements, and adjudication.

3.2 BENCHMARK CONTRACT AND EXTENSIBILITY

APT-Bench fixes the unit of input, prediction target, split, and metric for each track: five-lineage and 27-subtype prediction from one APT vector per cell; two-axis scaling over training patients and cells per patient; and strict cross-fitted aggregation from cell predictions to six-class patient-level characterization with gold-composition and technical controls. Open-set subtype discovery is outside the current contract; all primary hierarchy tasks use the fixed 5-lineage/27-subtype ontology. Outer-test-isolated aptamer measurement and inference-cell budgets are secondary sensitivities. The machine-readable manifest at `benchmark/splits/patient_folds.json` assigns every pseudonymous patient to one outer fold; all selection remains inside development patients. Portable components include patient-clustered uncertainty, hierarchy diagnostics, pseudoreplication and fingerprint audits, and outer-test-isolated budget curves. The full interface and release contract appear in Appendix C.2. This cohort cannot estimate cross-site or cross-platform generalization.

TODO: Deposit the versioned data and executable evaluation release specified in Appendix C.2; otherwise describe the work as a dataset case study rather than a reusable benchmark.

3.3 EVALUATION PROTOCOLS

We evaluate models under two main protocols with different purposes.

Patient-level 5-fold cross-validation. This is the primary protocol for all headline claims. Patients are partitioned into five disease-stratified folds, each containing eight held-out test patients. At every fold, preprocessing statistics, model fitting, and hyperparameter selection use only the training and validation patients from the remaining folds. We pool out-of-fold predictions across all five test folds, yielding a patient-disjoint evaluation spanning all 40 patients.

Cell-level split control. As a protocol-sensitivity control, cells are randomly split irrespective of patient identity. Cells from the same patient can therefore appear in both training and evaluation sets. We do not treat this as a realistic deployment protocol. Its only role is to quantify performance inflation caused by leakage.

Training patient–cell scaling. The original 4×4 surface is retained as a descriptive sensitivity, but its unequal endpoints do not compare patient and cell effects. The primary fair design uses $P \in \{8, 16, 32\}$ outer-development patients and $C \in \{100, 200, 400, 800, 1600\}$ uniformly sampled cells per patient. Its fixed-total diagonals hold $T = PC \in \{3200, 6400, 12800\}$ exactly constant, and the full grid also supports matched doublings of one axis while holding the other fixed. Within every outer fold, 20 disease-stratified patient orderings and uniform within-patient cell permutations are nested across budgets. Preprocessing is fit only on sampled training cells; frozen Logistic Regression and XGBoost configurations are refit for coarse and fine prediction; and every cell from the same eight untouched outer-test patients is evaluated. We report pooled cell-weighted, patient-balanced pooled, and mean within-patient macro-F1. Empirical subset-seed intervals and paired patient-clustered bootstrap intervals answer different uncertainty questions and are reported separately. This training-time design is distinct from inference subsampling in the compact-panel analysis.

The fixed-total grid does not by itself isolate subject breadth: adding subjects can change observed classes, per-class counts, and class proportions. We refer to their joint influence as the *label-distribution effect* and run a separate class-matched control at the two cross-cohort totals, $T \in \{3200, 6400\}$. For each outer-fold, seed, task, and T , the nested $P = 8$ development subset freezes the observed class set and an integer per-class quota T_k . The identical T_k values are then sampled without replacement at $P = 8, 16, 32$, using capacity-constrained round-robin allocation to spread each class over as many selected subjects as possible. This makes class support, counts, and proportions identical within each paired comparison; only the subjects contributing those cells change. We refit class-weighted multinomial Logistic Regression and report subject-balanced OOF macro-F1, empirical intervals over 20 subset seeds, and paired subject-bootstrap intervals. Logistic Regression is used as a focused sampling control rather than as another model-comparison family. This control fixes the marginal training label distribution, but it does not separately fix disease–subtype composition, the allocation of each class across subjects, or within-class subject heterogeneity.

To test portability beyond a single assay and cohort, we apply the same grid to the public COMBAT CITE-seq blood atlas (COVID-19 Multi-omics Blood Atlas (COMBAT) Consortium, 2022). After a frozen quality and coverage audit, 105 donors and 700,706 cells are assigned to five donor-disjoint folds. The primary external replication uses 293 RNA features selected only on 10 separate calibration donors; a matched-modality sensitivity uses all 192 released antibody-derived tag (ADT) features on exactly the same cells, donors, labels, and folds. Full construction and exclusion rules are in Appendix C.7.

A second external replication uses 925 evaluation donors and 1,199,468 cells from the healthy OneK1K PBMC atlas (Yazar et al., 2022). It uses pool- and donor-disjoint folds, calibration-only selection of 293 RNA features, and the same LR/XGBoost protocol. A coverage audit limits C to 800 and the common fixed totals to 3,200 and 6,400; Appendix C.7 gives the construction and released-label limitations.

3.4 CLASS DISTRIBUTION

Because the subtype distribution is long-tailed, we use macro-F1 as the primary metric for coarse-lineage and fine-subtype prediction. Accuracy is secondary. Primary point estimates pool cells and are therefore cell-weighted despite patient-disjoint splits; Appendix C.5 reports equal-cell-per-patient sensitivity results. For uncertainty, we compute 95% confidence intervals from 2,000 paired patient-level bootstrap resamples over the 40 pooled test patients. The prespecified architecture-audit family asks whether the most structured neural reference, Soft-cascade Transformer, outperforms HCE or XGBoost at the coarse and fine endpoints. Two-sided bootstrap p -values use twice the smaller tail probability with a plus-one correction and are Holm-adjusted across these four tests; comparisons outside this family are exploratory. This family audits an architecture claim rather than presuming one, and all four audited advantages fail to exclude zero.

From the same pooled predictions, joint hierarchy metrics are exact-path accuracy, root-excluded example-averaged lineage/subtype F1, and subtype-tree distance; support correlations, sibling errors, and the coarse-fine gap are exploratory difficulty diagnostics.

We audit disease association at the patient level because disease labels belong to patients rather than cells. Cell-level source-prediction accuracies are included only as supplementary confounding diagnostics and are not interpreted as though hundreds of thousands of cells were independent disease observations.

4 MODELS AND NESTED EVALUATION

APT-Bench is an evaluation contribution, not a claim of architectural superiority. Classical controls include class-weighted multinomial Logistic Regression and XGBoost. Its neural reference ladder contains a flat Transformer, the same model trained with a two-level adaptation of HCE (Cultrera di Montesano et al., 2026), and a soft-cascade Transformer. These references share the APT tokenizer, encoder dimensions, optimizer, training budget, patient folds, training-only preprocessing, and validation fine-macro-F1 checkpoint rule. The ladder therefore controls backbone capacity before asking whether hierarchy-specific complexity helps. Appendix B records the complete implementation for reproducibility; none of its individual cascade components is claimed as an algorithmic contribution.

For the composition bridge, each disease outer fold seals eight patients. A final disease-label-free XGBoost subtype model trained on the other 32 patients constructs outer-test compositions. Downstream training compositions for those 32 patients are instead produced by four inner patient-disjoint fits, each trained on 24 patients. A class-weighted multinomial LR, with regularization selected by patient-level inner CV, is then evaluated once on the sealed eight patients. Thus neither the cell-typing stage nor the disease stage uses an outer-test patient during preprocessing, feature construction, fitting, or selection. Appendix B.4 provides the complete data flow and controls. A conditional increment audit uses the same nested features and tuning protocol to compare recorded QC plus predicted lineage against recorded QC plus predicted subtype composition; subtype probabilities implicitly contain their lineage sums.

5 RESULTS

5.1 PATIENT-DISJOINT HIERARCHY PREDICTION EXPOSES A GRANULARITY GAP

Coarse lineage recognition is consistently easier than fine subtype recognition (Table 1). For Soft-cascade Transformer, coarse macro-F1 is 0.326 while fine macro-F1 is 0.152; the matched flat FT-style Transformer reaches 0.323 and 0.147. The corresponding gap appears across model families, indicating that APT profiles recover broad immune identity more reliably than the finer transcriptome-derived taxonomy.

Encoder-matched comparisons do not establish an architectural advantage. This is a benchmark result rather than a failed method claim: after controlling the backbone, additional hierarchy-specific cascade complexity is not supported on this cohort. Relative to the flat Transformer, Soft-cascade Transformer differs by only +0.0036 coarse macro-F1 (paired patient-bootstrap 95% CI $[-0.0078, 0.0146]$) and +0.0055 fine macro-F1 (95% CI $[-0.0021, 0.0125]$). HCE has the highest coarse point estimate (0.333), but Soft-cascade Transformer–HCE is -0.0069 (95% CI $[-0.0154, 0.0026]$) at the coarse level and $+0.0015$ (95% CI $[-0.0083, 0.0047]$) at the fine level. Differences from XGBoost also do not exclude zero. Exact-path accuracy is 0.248–0.259; HCE has the highest value, whereas XGBoost has the highest root-excluded hierarchical F1 (0.420) and lowest subtype-tree distance (2.375). Natural consistency is reported only as an appendix diagnostic because constrained decoding can alter it without improving correctness.

5.2 WHY 361,792 CELLS STILL YIELD ONLY 0.15 SUBTYPE MACRO-F1

Per-subtype F1 is more strongly associated with cell abundance than with patient coverage in this cohort. Marginal Spearman($F_{1,k}, \log n_k$) versus Spearman($F_{1,k}, P_k$) is 0.486/0.288 for Soft-cascade Transformer and 0.540/0.275 for XGBoost. After rank residualization, $\rho_{c|p}$ is 0.411/0.496

Model	Coarse M-F1	Fine M-F1	Exact Path	Subtype Tree Dist.↓
Soft-cascade Transformer	0.326	0.152	0.253	2.431
Flat FT-style Transformer	0.323	0.147	0.257	2.407
FT-style Transformer + HCE	0.333 ^{n.s.}	0.151 ^{n.s.}	0.259	2.418
XGBoost	0.322 ^{n.s.}	0.143 ^{n.s.}	0.248	2.375

Table 1: Patient-disjoint 5-fold hierarchy evaluation on pooled OOF predictions from 40 patients. Coarse and fine Macro-F1 are primary. Exact Path requires independent coarse and fine predictions to be correct; Tree Distance is 0/2/4 for correct/sibling/cross-lineage subtype predictions. Prespecified soft-cascade comparisons with HCE and XGBoost use 2,000 paired patient bootstraps and Holm correction across four coarse/fine tests; ^{n.s.} denotes no adjusted significance. Remaining diagnostics and full definitions are in Appendix C.10.

and $\rho_{p|c}$ is $-0.051/-0.130$. Because there are only 27 subtypes and 16 lie at the 40-patient coverage ceiling, these are exploratory associations rather than causal explanations.

Only 25.0% of Soft-cascade Transformer errors and 24.6% of XGBoost errors retain the true parent. The raw cross-lineage rate depends on the available wrong-class distribution: against an error-conditioned marginal null, the observed rates are close to expectation and do not independently demonstrate either hierarchy preservation or failure. Appendix C.4 reports per-subtype patient-clustered intervals, support plots, and the complete error analysis. Across models, the descriptive coarse-minus-fine macro-F1 gap ranges from 0.099 to 0.200.

5.3 PATIENT DISJOINTNESS CHANGES THE EVALUATION, NOT JUST THE SPLIT

Cell-level splitting inflates coarse/fine macro-F1 by $+0.090/+0.108$ for Soft-cascade Transformer and $+0.050/+0.069$ for XGBoost (Appendix C.5). APT-Bench therefore fixes patient-disjoint evaluation rather than treating the split as a reporting detail. Because a patient-disjoint pooled cell metric can still overweight patients with more cells, an equal-cell sensitivity also samples 1,900 cells per patient over 50 seeds. It changes coarse macro-F1 by at most $+0.005$ and fine macro-F1 by -0.007 to -0.009 , leaving the qualitative ordering intact.

5.4 THE LABEL DISTRIBUTION CONFOUNDS NAIVE TWO-AXIS SCALING

The fair scaling experiment holds outer-test subjects fixed and varies only the development set. It evaluates fixed-total-cell reallocations, matched doublings, and a descriptive response surface for LR and XGBoost at both resolutions. Each point uses 20 matched subject/cell subset seeds; preprocessing and fitting are repeated, while all cells from untouched test subjects are evaluated. The design is then frozen for external COMBAT CITE-seq and OneK1K cohorts.




Figure 1: Primary class-matched fixed-total scaling control. Each comparison freezes the observed classes and exact per-class cell quotas before reallocating the same T training cells from 8 to 32 subjects. Points are changes in subject-balanced, subject-disjoint OOF macro-F1 for LR; bars are 95% paired subject-bootstrap intervals over fixed outer-test subjects after averaging 20 subset seeds. Eleven of 12 empirical seed intervals include zero. The corrected effects are modest for coarse lineage and heterogeneous for fine subtype.

As a deliberately naive starting point, the original label-agnostic design reallocates cells without matching the training label distribution. Moving from 8 to 32 patients improves patient-balanced OOF macro-F1 in all 12 model–resolution–budget combinations, by 0.006–0.022 (Appendix C.6). All paired patient-bootstrap and subset-seed intervals are above zero. Pooled-cell and mean within-patient sensitivities give the same qualitative direction, with isolated uncertainties detailed in Appendix C.6. These are unmatched associations to be audited below, not estimates of a pure subject-breadth effect.

The direction transfers to COMBAT despite a different cohort, measurement technology, and 39-class fine taxonomy. Across 105 donors and 700,706 cells, all 12 RNA effects are positive (0.001–0.018) for LR and XGBoost, and all six matched ADT LR effects are positive (0.006–0.013). All 18 paired donor-bootstrap intervals exclude zero. Only 4 of 18 empirical subset-seed intervals exclude zero, however, showing that donor-bootstrap stability of the average effect does not eliminate sensitivity to the selected development subset. COMBAT therefore replicates the fixed-total direction, not a constant effect size or deterministic advantage for every training subset.

Across 925 healthy OneK1K evaluation donors, seven of eight effects are positive (0.004–0.009). XGBoost coarse prediction reverses at $T = 3,200$ (−0.0028; donor-bootstrap 95% CI [−0.0036, −0.0017]), but is positive at $T = 6,400$ (+0.0056). No OneK1K subset-seed interval excludes zero, exposing substantial dependence on the selected training donors.

Matched doublings on APT lead to the same descriptive ordering. Averaged across eligible fixed settings, patient-versus-cell doubling gains are 0.011 versus 0.005 (LR coarse), 0.007 versus 0.003 (LR fine), 0.016 versus 0.008 (XGBoost coarse), and 0.009 versus 0.006 (XGBoost fine). Fold-adjusted response-surface coefficients are likewise larger for $\log_2 P$ than $\log_2 C$ in all four comparisons, although interactions show that neither effect is constant across the grid. OneK1K matched doublings and response surfaces also favor the donor axis, but only narrowly for XGBoost coarse prediction. Across APT, COMBAT, and OneK1K, this naive analysis yields 37 of 38 unmatched fixed-total comparisons in favor of broader subject coverage. The numerical consistency is misleading if read as an isolated breadth effect because the sampled subjects and marginal training label distribution change simultaneously.

The class audit confirms that this distinction matters. At the common $T = 3,200$ diagonal, moving from $P = 8$ to $P = 32$ changes the mean number of observed fine classes from 26.12 to 26.33 of 27 for APT, 36.97 to 37.34 of 39 for COMBAT, and 27.10 to 27.26 of 30 for OneK1K. At $T = 6,400$, the corresponding changes are 26.34 to 26.53, 37.81 to 38.10, and 28.31 to 28.47. These fractional

averages represent fold/seed settings in which a test class changes from unseen to seen, which can directly affect macro-F1. They measure only one component of the label-distribution effect: per-class counts and proportions also change in the unmatched analysis.

We therefore repeat LR after freezing the $P = 8$ observed classes and exact per-class quotas within every fold/seed/task comparison (Figure 1; Table 15). Mean donor coverage per observed class increases substantially while class counts remain identical. Coarse effects remain positive for APT (+0.006/+0.008) and OneK1K (+0.003/+0.003), and are small for COMBAT (+0.001/+0.000). Fine effects are negative for APT (−0.002/−0.005), near zero to negative for COMBAT (−0.001/−0.003), and only slightly positive for OneK1K (+0.002/+0.001). Most empirical seed intervals include zero; paired subject-bootstrap intervals for seed-averaged sufficient statistics are shown in Appendix C.8. Thus class matching changes the scientific conclusion: the transferable signal is at most a modest coarse-lineage association, whereas the apparently consistent fine-subtype advantage in the naive analysis is partly mediated by changes in label support and class composition and does not survive as a general breadth effect. This control does not attribute the change to unseen classes alone.

5.5 NESTED CELL-OUTPUT TRANSFER PRESERVES DISEASE-ASSOCIATED VARIATION

Composition connects cell typing to patient characterization, but a pooled OOF pipeline is insufficient: a cell model generating a downstream training patient’s features can have seen the current disease outer-test patients. We therefore seal each eight-patient outer fold, construct the 32 development compositions by four-way inner patient-disjoint cross-fitting, and use one cell model fitted on all 32 development patients only for the sealed test patients.

Under this strict protocol, disease-label-free XGBoost soft subtype composition reaches patient accuracy/macro-F1/AUROC 0.600/0.593/0.854, compared with 0.475/0.477/0.766 for soft lineage composition. Both exceed their complete 10,000-permutation nulls ($p = 0.00010$ and $p = 0.00020$). Fine granularity is not established as superior: the paired subtype-minus-lineage macro-F1 difference is +0.116 with patient-bootstrap 95% CI [−0.015, 0.262]. True subtype composition reaches macro-F1 0.516, so the predicted representation is not merely a noisier estimate of annotated abundance; it may also retain model confidence or technical structure.

This is a representation-transfer audit, not evidence of error propagation: it does not establish a subtype-abundance source, fine-over-coarse utility, or that better typing improves patient characterization. Hard/soft and predicted/gold sensitivities are reported in Appendix B.4.

Aggregation / Representation	Patient Acc.	Macro-F1	Macro-AUROC	Perm. p
Log cell count + LR [‡]	0.575	0.531	0.800	0.00010
All recorded QC proxies + LR [¶]	0.550	0.566	0.859	–
Nested soft subtype composition + LR [§]	0.600	0.593	0.854	0.00010
Nested soft lineage composition + LR [§]	0.475	0.477	0.766	0.00020
Gold subtype composition + LR [‡]	0.500	0.516	0.776	0.00010
Gold lineage composition + LR [‡]	0.325	0.301	0.743	0.0184

[‡] Patient-level technical or paired-transcriptomic oracle features. [¶] Recovered cell count plus five patient summaries of recorded RNA UMI and detected-gene QC fields; see Appendix C.3. [§] Soft probabilities from disease-label-free XGBoost under strict nested cross-fitting. Composition rows use raw proportions; LR regularization is tuned only within each outer-development set. Composition permutation tests use 10,000 patient-label shuffles.

Table 2: **Associational patient-characterization audit** ($n = 40$). Predicted composition retains disease-associated variation, but its gains over lineage composition, recovered cell count, and recorded RNA-QC proxies have patient-bootstrap intervals spanning zero. These representations may contain biological, patient, or technical structure. Direct APT classifiers and their confounding controls are confined to Appendix C.3; no row establishes biological mediation or clinical generalization.

Log cell count alone reaches macro-F1 0.531 ($p = 0.00010$). A six-feature nuisance-only model using recovered cell count and patient summaries of the recorded transcriptomic UMI and detected-gene QC fields reaches macro-F1 0.566 and AUROC 0.859. Predicted subtype composition exceeds the cell-count model by only +0.062 (95% CI $[-0.087, 0.218]$) and the full recorded-QC model by +0.027 (95% CI $[-0.157, 0.215]$). Equal-cell sensitivity, a global-multinomial composition null, and a fold-ID prediction control do not establish biological mediation. The defensible finding is therefore narrower: cell predictions preserve disease-associated variation, but they do not show incremental value beyond available nuisance summaries.

A stricter conditional audit likewise finds no resolved subtype increment over recorded QC plus lineage: Δ macro-F1 = +0.016 (95% paired patient-bootstrap CI $[-0.120, 0.169]$; Appendix C.3).

Identifiability boundary. Direct APT discrimination is strong but confounding-sensitive. Patient-wise centering produces a 35-point drop in majority-vote accuracy, and individual cells readily identify their source patient. Each participant contributes one acquisition, while plate, run, date, library, and site covariates and an external APT cohort are unavailable. Disease, patient, and unrecorded acquisition effects are therefore not statistically identifiable from this cohort: resampling, permutation testing, or additional models cannot separate them. We consequently treat direct APT prediction, compact panels, and attribution only as diagnostics of a mixed within-cohort signal; full values and controls are confined to Appendix C.3 and Appendix C.11.

6 DISCUSSION

APT-Bench is primarily an evaluation contribution rather than a claim of model superiority. Across matched neural and classical models, broad lineage is more reliably recovered than transcriptome-derived subtype, and no advantage for the soft cascade over simpler matched references is statistically supported. The resulting granularity gap and the uncertain subtype-versus-lineage gain in the strict nested transfer audit show that additional model complexity alone does not resolve fine cell typing or establish that finer predictions improve patient-level characterization.

The benchmark also separates the evaluation unit from the training-scaling axes. Although it contains 361,792 cells, performance on unseen subjects must still be estimated from only 40 independent patients; cell-level splitting inflates scores and changes apparent model differences. The label-agnostic fixed-total design compares broader patient coverage with deeper sampling without changing total training cells, but it also changes the marginal training label distribution. Its 37/38 direction is therefore a naive joint effect, not a pure subject-diversity estimate or a headline scaling law. The class-matched control changes the interpretation: after identical per-class quotas are enforced, small coarse gains persist in APT and OneK1K, whereas fine effects are heterogeneous and reverse in APT and COMBAT. The unmatched fine-label gains are therefore partly mediated by changes in label support and class composition, not demonstrably by unseen-class coverage alone. Disease-subtype composition, within-class allocation across subjects, pool, source, and unrecorded batch coverage can still change with subject breadth, so even the matched result is associational. Correlated cells cannot create evidence about new patients, even when additional cells improve estimation of cell-type decision boundaries. Clinical single-cell benchmarks should therefore report patient-disjoint generalization together with both patient and training-cell budgets rather than using raw cell count as effective sample size.

The disease analyses delimit what can be concluded from this cohort. A disease-label-free subtype predictor preserves disease-associated variation after patient aggregation, but its gain over lineage composition, cell count, or a six-feature recorded RNA-QC baseline is not statistically resolved. Strong centering sensitivity indicates that patient-specific absolute-expression structure contributes substantially to within-cohort discrimination. The compact-panel result therefore establishes only that this inseparable mixed signal is feature-redundant; it does not establish assay reduction, biological specificity, or causal biomarkers. The APT disease cohort is single-site, lacks acquisition-batch metadata, and has no external disease-validation cohort; COMBAT and OneK1K validate only the cell-typing scaling protocol, not cancer recognition. The LODO analysis is descriptive and cross-disease generalization remains unresolved. The fixed schema, patient splits, tasks, and evaluator are reusable in future APT and clinical single-cell cohorts (Luecken et al., 2025; Liu et al., 2025), but batch-aware, cross-site validation is required before clinical claims.

7 CONCLUSION

APT-Bench establishes a patient-disjoint contract for hierarchical cell typing, two-axis scaling, and patient characterization from single-cell aptamer profiles. Coarse lineage is consistently easier than fine subtype prediction, with no supported cascade advantage over matched references. Its scaling audit shows that unmatched fixed-total comparisons can mistake a label-distribution effect for a subject-breadth benefit; after class matching, only modest coarse effects remain and fine effects vary across cohorts. Nested transfer has no resolved subtype increment, and direct disease association remains confounded by patient-specific absolute-expression structure; clinical claims require external validation.

AI USE STATEMENT

TODO: Required for ICLR 2027. Disclose every generative-AI tool and model used for writing, editing, coding, analysis, literature review, or figure preparation; identify the tasks for which each tool was used, describe human verification of AI-assisted outputs, and state that the authors take responsibility for the final text, claims, code, and artifacts.

ETHICS STATEMENT

TODO: State the human-subjects approval or exemption and informed-consent status; describe data de-identification, access restrictions, privacy protections, intended clinical/research use, foreseeable misuse or bias risks, and any conflicts of interest. Do not include identifying institutional details if they would break anonymity.

REPRODUCIBILITY STATEMENT

TODO: Provide the anonymous code and data-access locations, exact patient-split manifest, preprocessing and evaluation commands, software environment, random seeds, model hyperparameters, compute requirements, and paths for the prediction artifacts and tables used in every reported result.

AUTHOR CONTRIBUTIONS

TODO: Add author contributions using CRediT roles (for example: conceptualization, methodology, software, validation, formal analysis, data curation, visualization, writing, supervision, and funding acquisition). Preserve anonymity in the review version if required.

ACKNOWLEDGMENTS

TODO: Add funding sources and grant numbers, computational resources, data or clinical contributors, and non-author assistance; verify whether any acknowledgment must be omitted or anonymized during double-blind review.

REFERENCES

- Dvir Aran, Agnieszka P Looney, Leqian Liu, Esther Wu, Valerie Fong, Austin Hsu, Suzanna Chak, Ram P Naikawadi, Paul J Wolters, Adam R Abate, et al. Reference-based analysis of lung single-cell sequencing reveals a transitional profibrotic macrophage. *Nature immunology*, 20(2):163–172, 2019.
- Joshua D Cohen, Lu Li, Yuxuan Wang, Christopher Thoburn, Bahman Afsari, Ludmila Danilova, Christopher Douville, Ammar A Javed, Fay Wong, Austin Mattox, et al. Detection and localization of surgically resectable cancers with a multi-analyte blood test. *Science*, 359(6378):926–930, 2018.
- COVID-19 Multi-omics Blood ATlas (COMBAT) Consortium. A blood atlas of COVID-19 defines hallmarks of disease severity and specificity. *Cell*, 185(5):916–938.e58, 2022. doi: 10.1016/j.cell.2022.01.012.

- Haotian Cui, Chloe Wang, Hassaan Maan, Kuan Pang, Fengning Luo, Nan Duan, and Bo Wang. scgpt: toward building a foundation model for single-cell multi-omics using generative ai. *Nature methods*, 21(8):1470–1480, 2024.
- Sebastiano Cultrera di Montesano, Davide D’Ascenzo, Srivatsan Raghavan, Ava P Amini, Peter S Winter, and Lorin Crawford. Improving atlas-scale single-cell annotation models with hierarchical cross-entropy loss. *Nature Computational Science*, 6(3):243–249, 2026.
- CZI Cell Science Program, Shibla Abdulla, Brian Aevertmann, et al. CZ CELLxGENE Discover: a single-cell data platform for scalable exploration, analysis and modeling of aggregated data. *Nucleic Acids Research*, 53(D1):D886–D900, 2025. doi: 10.1093/nar/gkae1142.
- Nick Erickson, Lennart Purucker, Andrej Tschalzev, David Holzmüller, Prateek Desai, David Salinas, and Frank Hutter. Tabarena: A living benchmark for machine learning on tabular data. *Advances in Neural Information Processing Systems*, 38, 2026.
- Yury Gorishniy, Ivan Rubachev, Valentin Khrulkov, and Artem Babenko. Revisiting deep learning models for tabular data. In *Advances in Neural Information Processing Systems*, volume 34, pp. 18932–18943, 2021.
- Léo Grinsztajn, Edouard Oyallon, and Gaël Varoquaux. Why do tree-based models still outperform deep learning on tabular data? arxiv. *arXiv preprint arXiv:2207.08815*, 2022.
- Minsheng Hao, Jing Gong, Xin Zeng, Chiming Liu, Yucheng Guo, Xingyi Cheng, Taifeng Wang, Jianzhu Ma, Xuegong Zhang, and Le Song. Large-scale foundation model on single-cell transcriptomics. *Nature methods*, 21(8):1481–1491, 2024.
- Yuhan Hao, Stephanie Hao, Erica Andersen-Nissen, William M Mauck, Shiwei Zheng, Andrew Butler, Maddie J Lee, Aaron J Wilk, Charlotte Darby, Michael Zager, et al. Integrated analysis of multimodal single-cell data. *Cell*, 184(13):3573–3587.e29, 2021. doi: 10.1016/j.cell.2021.04.048.
- Shangru Jia, Artem Lysenko, Keith A Boroevich, Alok Sharma, and Tatsuhiko Tsunoda. schdeepinsight: a hierarchical deep learning framework for precise immune cell annotation in single-cell rna-seq data. *Briefings in Bioinformatics*, 26(5):bbaf523, 2025.
- Leila C Kahwati, Matthew Avenarius, Leslie Brouwer, Norah L Crossnohere, Chyke A Doubeni, Cecelia Miller, Mariam Siddiqui, Christiane Voisin, Roberta C Wines, and Daniel E Jonas. Multicancer detection tests for screening: a systematic review. *Annals of Internal Medicine*, 178(11):1591–1604, 2025.
- Kasia Z Kedzierska, Lorin Crawford, Ava P Amini, and Alex X Lu. Zero-shot evaluation reveals limitations of single-cell foundation models. *Genome Biology*, 26(1):101, 2025.
- Chunlei Liu, Sichang Ding, Hani Jieun Kim, Siqu Long, Di Xiao, Shila Ghazanfar, and Pengyi Yang. Multitask benchmarking of single-cell multimodal omics integration methods. *Nature Methods*, 22:2449–2460, 2025. doi: 10.1038/s41592-025-02856-3.
- Tianyu Liu, Edward De Brouwer, Archit Verma, Alsu Missarova, Tony Kuo, Nathaniel Diamant, Hanchen Wang, Minsheng Hao, Tommaso Biancalani, Hector Corrada Bravo, et al. Learning multi-cellular representations of single-cell transcriptomics data enables characterization of patient-level disease states. *Cell Systems*, 17(5):101570, 2026. doi: 10.1016/j.cels.2026.101570.
- Malte D Luecken, Scott Gigante, Daniel B Burkhardt, Robrecht Cannoodt, Daniel C Strobl, Nikolay S Markov, Luke Zappia, Giovanni Palla, Wesley Lewis, Daniel Dimitrov, et al. Defining and benchmarking open problems in single-cell analysis. *Nature Biotechnology*, 43:1035–1040, 2025. doi: 10.1038/s41587-025-02694-w.
- Christopher S McGinnis, Lyndsay M Murrow, and Zev J Gartner. Doubletfinder: Doublet detection in single-cell rna sequencing data using artificial nearest neighbors. *Cell Systems*, 8(4):329–337.e4, 2019. doi: 10.1016/j.cels.2019.03.003.

- Vladimir Shitov, Mohammad Moghareh Dehkordi, and Malte D Luecken. Benchmarking sample representations from single-cell data: Metrics for biologically meaningful embeddings. In *ICLR Workshop on Learning Meaningful Representations of Life*, 2025. URL <https://openreview.net/forum?id=IoRv5afWtb>.
- Christina V Theodoris, Ling Xiao, Anant Chopra, Mark D Chaffin, Zeina R Al Sayed, Matthew C Hill, Helene Mantineo, Elizabeth M Brydon, Zexian Zeng, X Shirley Liu, et al. Transfer learning enables predictions in network biology. *Nature*, 618(7965):616–624, 2023.
- Jonathan CM Wan, Peter Sasieni, and Nitzan Rosenfeld. Promises and pitfalls of multi-cancer early detection using liquid biopsy tests. *Nature Reviews Clinical Oncology*, 22(8):566–580, 2025.
- Xiaoqiu Wu, Xinrui Lin, Xiangqi Ma, Huidong Huang, Dengwei Zhang, Yuqing Liu, Rui Cheng, Jia Song, Lifei Zhang, Yamin Tan, et al. High-throughput multiplexed quantification of molecules by aptamer sequencing (apt-seq) in single cells. *Journal of the American Chemical Society*, 147(24):20394–20405, 2025.
- Yu Yang, Xueyan Chen, Jieying Pan, Huiheng Ning, Yaojun Zhang, Yufei Bo, Xianwen Ren, Jiesheng Li, Shishang Qin, Dongfang Wang, et al. Pan-cancer single-cell dissection reveals phenotypically distinct b cell subtypes. *Cell*, 187(17):4790–4811, 2024.
- Seyhan Yazar, Jose Alquicira-Hernandez, Kristof Wing, et al. Single-cell eqtl mapping identifies cell type-specific genetic control of autoimmune disease. *Science*, 376(6589):eabf3041, 2022. doi: 10.1126/science.abf3041.
- Yong Zeng, Dor D Abelman, Althaf Singhawansa, Nicholas Cheng, Yuanchang Fang, Sasha C Main, Emma Bell, Wenbin Ye, Ping Luo, Samantha L Wilson, et al. A pan-cancer compendium of 1,294 plasma cell-free dna methylomes and fragmentomes enabling multicancer detection. *Nature Cancer*, 7(2):384–398, 2026.
- Yuanhang Zhang, Xiaorui Zhou, Yu Zhong, Xi Chen, Zeyu Li, Rui Li, Pengfei Qin, Shanshan Wang, Jianhua Yin, Shang Liu, et al. Pan-cancer scrna-seq analysis reveals immunological and diagnostic significance of the peripheral blood mononuclear cells. *Human Molecular Genetics*, 33(4):342–354, 2024.

A APPENDIX

B HIERARCHY-AWARE REFERENCE LADDER

APT-Bench evaluates progressively structured, encoder-matched neural references: a flat Transformer, its HCE counterpart, and Soft-cascade Transformer. The cascade focuses on the genuine cell-level hierarchy, lineage $\rightarrow$ subtype, and leaves disease-association auditing to separate tabular baselines and patient-level aggregation. Its released code retains the historical identifier DropCascade for artifact compatibility. That identifier denotes a reproducible benchmark baseline, not a proposed algorithm or a claim that its global path, auxiliary coarse objective, soft routing, or contrastive construction independently improves performance.

B.1 CELL ENCODER

Each cell is represented by a standardized APT vector $x \in \mathbb{R}^{293}$. We embed feature identity and feature value separately. For aptamer index i , we form a token

$$t_i = \text{Emb}(i) + \text{MLP}_{\text{val}}(x_i), \quad i = 1, \dots, 293. \quad (1)$$

A learnable [CLS] token is prepended to the resulting sequence and processed by a pre-norm Transformer encoder with 4 layers, 8 attention heads, hidden dimension 256, feed-forward dimension 512, GELU activations, and dropout 0.1. The final [CLS] representation

$$z = \text{Encode}(x) \in \mathbb{R}^{256} \quad (2)$$

serves as the shared cell representation for downstream tasks.

B.2 SOFT-CASCADE REFERENCE

Let $M = 5$ be the number of coarse lineages and $K = 27$ the number of fine subtypes. Each subtype k belongs to exactly one parent lineage $m(k)$. A coarse head produces lineage logits

$$c = W_c z \in \mathbb{R}^M, \quad (3)$$

with routing distribution

$$p(m | x) = \text{softmax}(c/\tau)_m, \quad (4)$$

where $\tau = 1$.

Instead of a hard cascade, which would force subtype prediction to follow only the top predicted lineage, Soft-cascade Transformer uses a soft mixture of a global subtype path and lineage-specific experts:

$$s_k(x) = \underbrace{g_k(z)}_{\text{global path}} + \alpha p(m(k) | x) e_{m(k),k}(z) + \gamma \log(\epsilon + (1 - \epsilon)p(m(k) | x)), \quad (5)$$

Here $g(z)$ is a global subtype head, $e_{m,k}(z)$ is the expert associated with lineage m , $\alpha = 1.0$, $\epsilon = 0.1$, and γ is ramped from 0 to 0.5 during early training. The global path retains a direct subtype-logit contribution alongside the routed expert contribution; we do not isolate its effect from the other components. Final predictions are

$$\hat{k} = \arg \max_k s_k(x), \quad \hat{m} = \arg \max_m c_m. \quad (6)$$

B.3 CROSS-DISEASE CONTRASTIVE REGULARIZATION

The reference model includes a cross-disease supervised contrastive term. Let

$$u = \frac{\text{Proj}(z)}{\|\text{Proj}(z)\|_2} \quad (7)$$

be a normalized projection of the encoder representation. For anchor cell i , positives are cells with the same subtype but a different disease label. Same-subtype cells from the same disease are excluded by construction. Cells from different subtypes are treated as negatives, with additional emphasis on negatives that share the same coarse lineage. The contrastive loss weight is ramped from 0 to 0.2 after the early warmup period. Because we do not compare this construction with standard supervised contrastive learning across all five folds, we make no claim that the cross-disease positive rule independently improves generalization.

B.4 OPTIMIZATION AND MODEL SCOPE

The classification cascade is trained jointly using

$$\mathcal{L} = \lambda_{\text{fine}} \mathcal{L}_{\text{fine}} + \lambda_{\text{coarse}} \mathcal{L}_{\text{coarse}} + w_{\text{contrast}}(t) \mathcal{L}_{\text{contrast}}, \quad (8)$$

where $\mathcal{L}_{\text{fine}}$ and $\mathcal{L}_{\text{coarse}}$ are cross-entropy losses with $\lambda_{\text{fine}} = 1.0$ and $\lambda_{\text{coarse}} = 0.5$. The contrastive weight increases to 0.2 according to the schedule in §B.3.

We optimize the cascade using AdamW with learning rate 10^{-4} and weight decay 10^{-5} , gradient clipping at norm 1.0, batch size 512, and mixed-precision training. Models are trained for at most 50 epochs with early stopping based on validation fine-level macro-F1 with patience 10. The final configuration does not use class-balanced sampling because it underperformed natural sampling after matching the number of optimization steps; the single-split development diagnostic is provided in Appendix C.12.

Matched Transformer controls. To isolate encoder capacity from hierarchical modeling, a flat FT-style Transformer control (Gorishniy et al., 2021) removes the cascade while retaining the identical APT tokenizer, Transformer dimensions, optimizer, early stopping, and training budget above. We call it FT-style because its tokenizer is exactly the APT feature tokenizer used by Soft-cascade Transformer, rather than the original numerical/categorical FT-Transformer tokenizer. This model and its HCE counterpart predict the same $M + K$ lineage-and-subtype

nodes. The flat model applies independent cross-entropy to the lineage and subtype logit slices. For HCE (Cultrera di Montesano et al., 2026), let $R_{ij} = 1$ when node j is node i or its descendant, $p = \text{softmax}(q)$ over all nodes, and $s = Rp$. We minimize $-\lambda_{\text{fine}} \log s_{M+k} - \lambda_{\text{coarse}} \log s_m$ for observed subtype k and lineage m . Because every fine label here is a leaf, the fine HCE term alone would reduce to ordinary CE; including the simultaneously observed parent label makes this a stated two-level adaptation rather than an unqualified reproduction of the mixed-granularity setting in the original work. All three Transformer models are evaluated from the checkpoint selected by patient-validation fine macro-F1, without an additional post-selection calibration stage.

Disease recognition is not handled by a dedicated head inside Soft-cascade Transformer. This is a deliberate modeling decision rather than a claim that disease is solved in a strong external sense: within-cohort disease prediction is already nearly saturated by simple classical baselines, while the architectural challenge addressed by Soft-cascade Transformer is the unresolved cell-level hierarchy problem.

Strictly nested cell-output transfer audit. For each disease outer fold f , we train a disease-label-free XGBoost subtype classifier on all 32 outer-development patients and predict the cells of the eight untouched patients in f . Disease-training features require a second cross-fit: for each of the other four fixed folds g , a separate subtype model is trained on the 24 patients outside $f \cup g$ and predicts fold g . We average the resulting 27-class probability vectors within patient to obtain soft subtype composition; soft lineage composition sums subtype probabilities under the frozen subtype-to-lineage map. A standardized, class-weighted multinomial LR is fit to the 32 inner-OOF patient vectors, with $C \in \{0.01, 0.1, 1, 10, 100\}$ selected by patient-level inner CV, and evaluated once on the eight outer-test vectors. Raw proportions are primary; CLR with a prespecified 10^{-6} pseudocount is a sensitivity analysis. All uncertainty and permutation analyses resample or shuffle patients, never cells. To test conditional rather than marginal subtype value, we additionally compare three nested feature sets under the same folds and inner selection: recorded-QC summaries alone, QC plus the five predicted lineage proportions, and QC plus the 27 predicted subtype proportions. The last representation contains lineage implicitly because child probabilities sum to their parents.

C DATASET AND EVALUATION DETAILS

C.1 DATASET CONSTRUCTION AND DOCUMENTATION CHECKLIST

The available study workflow establishes the high-level sequence used to construct APT-Bench: clinical peripheral-blood specimens from five cancer groups and healthy controls are converted to single-cell suspensions; cell-profile and viability quality control precedes a paired single-cell transcriptome and 293-aptamer assay; separate transcriptome and aptamer-barcode libraries are linked at the cell level; and transcriptome-derived clusters and annotations provide the cell labels. For a benchmark release, this overview must be accompanied by the following provenance and protocol fields.

Transcriptomic preprocessing and cell quality control. The transcriptomic count matrix was processed with Seurat following its standard workflow of normalization, feature selection, dimensionality reduction, neighborhood-graph construction, and clustering (Hao et al., 2021). DoubletFinder was used to identify and remove predicted doublets (McGinnis et al., 2019). Low-quality cells were additionally filtered using per-cell UMI count, detected-gene count, and mitochondrial-transcript fraction. These steps preceded cluster annotation and construction of the linked APT benchmark cohort. **TODO: Report the Seurat and DoubletFinder versions, every parameter and random seed, the exact UMI/gene/mitochondrial thresholds, and cell counts before and after each filter.**

Manual annotation and reference-label reliability. After Seurat clustering, investigators manually assigned lineage and subtype names by inspecting canonical marker-gene expression reported in prior PBMC and pan-cancer studies (Zhang et al., 2024; Yang et al., 2024). No quantitative annotation confidence, inter-annotator agreement, or external reference-transfer score is available. Accordingly, these labels are operational reference annotations, not error-free biological ground truth, and benchmark scores are conditional on this manual taxonomy. The *Unknown* label was

assigned when a cluster did not show a coherent canonical marker pattern for the expected PBMC subtypes; this was a manual reject decision rather than a calibrated confidence threshold. Unknown cells are excluded from the primary 27-subtype benchmark. **TODO: Provide the full subtype-by-marker citation table, the number and expertise of annotators, whether they were blinded to disease, the adjudication procedure, and the explicit rule used to assign Unknown.**

Cross-disease semantics and hierarchy mapping. The same 27 subtype labels and definitions were applied across all six disease groups; no subtype was renamed or redefined for a particular disease. This gives the labels a consistent operational meaning, but it does not prove that marker expression or biological state is invariant across diseases. Each subtype is assigned to one of five parent lineages by a manually curated lookup. **TODO: Document independent validation of the subtype-to-lineage mapping, including reviewers, disagreements, adjudication, and any marker-based checks.**

- **TODO: Report recruiting site(s) and dates, prospective versus retrospective collection, exact patient count per group, inclusion/exclusion and diagnostic criteria, and whether each participant contributed exactly one specimen.**
- **TODO: Report available demographics and clinical covariates, including age, sex, disease stage, treatment status, and comorbidities; summarize missingness and state which fields cannot be released.**
- **TODO: Report blood volume, collection tubes, time to processing, cell-isolation and cryopreservation procedures, quality-control thresholds, and sample/cell exclusion counts.**
- **TODO: Report assay/platform and reagent versions, sequencing instruments and depth, 293-probe panel design, and a verified protein-target manifest or explicitly state why only anonymized probe identifiers can be released.**
- **TODO: Report barcode-matching rates, APT normalization and filtering, all remaining software versions and parameters, and whether annotation was performed before investigators examined APT profiles or disease labels.**
- **TODO: Add a cohort-flow diagram with participant and cell counts after every exclusion step, and provide the ethics approval/consent, de-identification, data-access, license, and intended-use terms referenced in the Ethics and Reproducibility Statements.**

C.2 BENCHMARK INTERFACE AND RELEASE CONTRACT

The hierarchy submission interface contains pseudonymous cell and patient IDs, true and predicted lineage, and true and predicted subtype. The disease interface contains one row per patient with the true disease and six class scores. The efficiency track additionally records the aptamer measurement budget, inference-time cell budget, selection seed, and the development-only feature ranking. These common interfaces permit new models to be scored without reproducing their internal training pipelines.

The evaluation layer is portable to other clinical single-cell datasets. It implements group-disjoint out-of-fold prediction; patient-clustered bootstrap uncertainty; coarse and fine macro-F1, exact-path accuracy, hierarchical F1, subtype-tree distance, granularity gap, and sibling versus cross-lineage error; patient-level aggregation versus cell-level pseudoreplication; patient-centering and identity diagnostics; and nested feature- and cell-budget curves. A future dataset can replace the assay features, hierarchy, or clinical endpoint while retaining these interfaces. This modular task–dataset–metric separation follows recent living single-cell benchmarks (Luecken et al., 2025); standardized metadata and programmatic access similarly enable cross-study reuse in CZ CELLxGENE (CZI Cell Science Program et al., 2025).

A complete release must contain the processed APT matrix; pseudonymous cell and patient identifiers; disease and cell labels; hierarchy and feature metadata; the immutable fold manifest; metric implementations; baseline configurations; and a single command that regenerates the headline tables from model predictions. **TODO: Before submission, add data and code URLs, explicit licenses, file checksums, an environment lockfile, an archival DOI, and the end-to-end command. If participant-level data require controlled access, release the complete schema, all labels permitted by consent, the split manifest, evaluator, and access procedure.**

(a) Task and evaluation scope				
Resource	Primary input	Reported scope	Main unit	Hierarchy
Open Problems	Multiple	12 living tasks	Task-specific	Task-specific
scMultiBench	RNA/ADT/ATAC	64 real + 22 simulated	Cell/dataset	No
SPARE	scRNA-seq	5 datasets, 8 methods	Sample	No
PaSCient	scRNA-seq	12.5M cells, 2,700 patients	Patient	No
APT-Bench	293 aptamers	1 cohort, 40 patients	Cell + patient	Yes

(b) Protocol components and availability				
Resource	Patient task	Two-axis scale	Assay budget	Public pipeline
Open Problems	Task-specific	No	No	Yes
scMultiBench	No	No	Feature selection	Yes
SPARE	Yes	No	No	Yes
PaSCient	Yes	No	No	Not audited
APT-Bench	Audit	Yes	Yes	Pending release

Table 3: Scope comparison with recent single-cell evaluation resources (Luecken et al., 2025; Liu et al., 2025; Shitov et al., 2025; Liu et al., 2026). “Task-specific” means that the living platform defines multiple contracts rather than one shared clinical protocol. APT-Bench is narrower in cohorts but combines a fixed aptamer modality, patient-disjoint coarse-to-fine cell typing, within-cohort patient-level audit, and controlled patient/cell and assay budgets. Its public release remains a submission requirement, not a completed claim.

C.3 CONFOUNDING AUDIT OF WITHIN-COHORT DISEASE ASSOCIATION

Cell-level prediction of the disease source of a held-out patient. Table 2 reports the main associational patient-characterization audit. For completeness, Table 5 reports the pooled *cell-level* source-prediction metric, in which every held-out cell is treated as a target and pooled across all 361,792 cells. This is an easier and statistically different task than patient-level characterization, since cells from the same patient are correlated and patients with more cells contribute more weight. We report it only as a confounding diagnostic.

Non-identifiability of disease and acquisition effects. Every participant contributes one acquisition, so patient identity is nested within both disease group and any unrecorded processing batch. The released metadata contain disease and patient identifiers plus transcriptomic UMI and detected-gene counts, but no plate, run, date, library, operator, or site field. Consequently, neither patient-disjoint prediction nor label permutation can identify whether a patient-associated APT offset is biological, technical, or mixed. No analysis below is interpreted as disease biology, biomarker validation, or clinical performance.

Recorded nuisance-only baselines. We aggregate the only available per-cell QC fields to each patient: recovered cell count; medians of $\log(1 + \text{UMI})$ and $\log(1 + \text{detected genes})$; median detected-gene/UMI ratio; and the interquartile ranges of the two log-count variables. Each feature set uses the same outer folds as the composition bridge, four-fold inner patient CV on the 32 outer-development patients to select LR regularization, refitting on all 32, and one evaluation on the sealed eight patients. Table 4 shows that these recorded QC proxies alone approach the predicted-composition result. They remain proxies rather than measured batch labels, so this analysis detects known nuisance structure but cannot rule out unrecorded acquisition effects.

We also test conditional subtype value rather than comparing each representation in isolation. Under the same nested folds and inner regularization selection, recorded QC plus predicted lineage reaches macro-F1 0.583 and AUROC 0.875; recorded QC plus the full predicted subtype vector reaches 0.599 and 0.825. The subtype-minus-lineage macro-F1 increment is +0.016 with 95% paired patient-bootstrap CI $[-0.120, 0.169]$ (10,000 resamples). Thus subtype detail does not provide a resolved conditional increment in this cohort.

Recorded feature set	d	Acc.	Macro-F1	Macro-AUROC
Recovered cell count	1	0.575	0.531	0.800
RNA QC summaries	3	0.475	0.478	0.787
All recorded QC proxies	6	0.550	0.566	0.859
Predicted soft subtype composition	27	0.600	0.593	0.854
Recorded QC + predicted lineage	11	0.575	0.583	0.875
Recorded QC + predicted subtype	33	0.600	0.599	0.825

Table 4: Matched patient-level nuisance audit. All rows use the same outer folds and inner patient-level regularization selection. The predicted-composition minus all-recorded-QC Macro-F1 difference is +0.027 with a 95% paired patient-bootstrap interval of $[-0.157, 0.215]$ (2,000 resamples). Recorded QC fields are incomplete proxies, not batch labels. In the conditional audit, the subtype-minus-lineage Macro-F1 increment is +0.016 with 95% paired patient-bootstrap interval $[-0.120, 0.169]$ (10,000 resamples).

Model	Accuracy	Macro-F1	Weighted-F1	Balanced Acc.
Logistic Regression	0.991	0.989	0.991	0.989
XGBoost	0.990	0.988	0.990	0.987
Linear SVM	0.988	0.986	0.988	0.985
Random Forest	0.963	0.955	0.963	0.953
Reference Correlation [†]	0.921	0.909	0.921	0.915

[†] SingleR-style reference-correlation classifier (Spearman nearest-centroid mapping), following the template-matching principle used by reference-mapping methods such as SingleR (Aran et al., 2019).

Table 5: **Cell-level** prediction of the disease source of a held-out patient’s cells (6-class), pooled over all 361,792 out-of-fold cells from the patient-level 5-fold protocol. This is a different, easier statistical task than the patient-level diagnosis reported in Table 2: cells from the same patient are correlated observations rather than independent draws, and this metric implicitly weights patients with more cells more heavily. We report it here only as a cell-level reference point, not as a patient-level diagnostic result.

Patient-wise centering sensitivity. To test whether disease prediction relies on each patient’s absolute expression level rather than only on within-patient relative structure, we repeated Logistic Regression training and evaluation after subtracting each patient’s own per-apramer median from every cell in both training and test data. This transformation preserves within-patient cell-to-cell variation while removing a patient-specific location shift. Cell-level accuracy drops from 0.991 to 0.401 (macro-F1 $0.989 \rightarrow 0.348$), and patient-level majority-vote accuracy drops from 40/40 to 26/40. This collapse shows that disease recognition depends substantially on patient-level absolute-expression structure, but it does not by itself determine whether that structure is biological, technical, or a mixture of both.

Patient-fingerprint diagnostic. We additionally trained a 40-way classifier to predict patient identity from individual cells, using a within-patient 50/50 cell split for this diagnostic only. The classifier identifies the correct patient from a single held-out cell with 88.4% accuracy (macro-F1 0.862), against a 2.5% chance level. Individual cells therefore carry a strong and easily recoverable patient-specific signature, consistent with the centering sensitivity above.

Patient-level summary-feature control. Finally, to confirm that the disease signal does not rely only on cell-level pseudo-replication, we trained a genuinely patient-level classifier using each patient’s median 293-dimensional APT profile. This summary-feature model reaches patient accuracy 0.950, patient macro-F1 0.948, and macro-AUROC 1.000. Together with the sensitivity analyses above, this indicates that disease information is present at the patient level but strongly entangled with absolute-expression offsets that cannot be cleanly separated without acquisition-batch meta-data.

Strict nested cell-output transfer audit. Ordinary pooled OOF predictions are insufficient for stacking because a base model used to create a disease-training feature may have seen the eventual disease outer-test patients. We therefore use the nested protocol defined in Methods: within each outer fold, four XGBoost models trained on 24 patients generate inner-OOF features for the 32 disease-training patients, and a fifth model trained on all 32 predicts the eight outer-test patients. XGBoost receives subtype labels but no disease labels. Soft subtype composition reaches accuracy/macro-F1/AUROC 0.600/0.593/0.854 and soft lineage composition reaches 0.475/0.477/0.766. The paired macro-F1 difference is +0.116 (95% patient-bootstrap CI $[-0.015, 0.262]$). Gold subtype and lineage compositions reach macro-F1 0.516 and 0.301, respectively. The apparently stronger predicted than gold point estimate is not statistically resolved and warns that predicted probabilities may encode model-confidence or technical structure beyond true cell abundance.

This experiment is therefore a representation-transfer audit, not an error- propagation analysis. It does not establish that the transferred signal originates from subtype abundance, that fine subtype is more useful than coarse lineage, that better typing improves patient characterization, or that the signal is independent of confidence and technical structure. Consistent with this distinction, the soft-minus-hard subtype macro-F1 difference is only +0.069 (95% patient-bootstrap CI $[-0.077, 0.221]$), and the predicted-minus-gold subtype difference is +0.077 (95% CI $[-0.100, 0.256]$).

Across 10,000 complete patient-label permutations, predicted subtype and lineage composition have plus-one $p = 0.00010$ and $p = 0.00020$. However, log cell count alone reaches macro-F1 0.531 ($p = 0.00010$), and the predicted-subtype minus cell-count difference is +0.062 (95% CI $[-0.087, 0.218]$). Equal-cell subsampling at 100, 500, and 2,000 cells per patient preserves the qualitative result over 50 seeds. A 50-repeat global-multinomial composition control averages macro-F1 0.170, and fold-ID prediction from global OOF composition is below chance. These controls support a predictive and associational bridge, not causal mediation or independent biological validation.

Representation	Legacy pooled OOF	Strict nested
Gold subtype composition	0.572	0.516
Predicted subtype composition	0.400	0.593
Gold lineage composition	0.377	0.301
Predicted lineage composition	0.282	0.477

Table 6: Protocol audit of patient macro-F1. The legacy predicted rows use hard labels from one global pooled-OOF prediction set, CLR features, and fixed LR regularization; the strict rows use nested soft probabilities, raw proportions, and development-only LR selection. Because both feature construction and downstream fitting changed, the numerical differences are not estimates of a leakage effect. Only strict nested results support current claims.

Patient-label permutation control. We evaluated the same patient-level median-profile classifier under 1,000 label permutations. Disease labels were permuted across the 40 patients as indivisible units, preserving the disease-group counts (6, 8, 7, 7, 6, 6); labels were never shuffled across cells. We retained the original five patient folds rather than restratifying after permutation. No permuted dataset reached the observed accuracy of 0.950 or macro-F1 of 0.948, giving plus-one permutation $p = (0 + 1)/(1000 + 1) = 0.000999$ for both statistics. The null accuracy mean was 0.137, with empirical 95% interval $[0.025, 0.275]$. This rejects a random patient-label explanation under the fixed protocol, but does not distinguish biological signal from patient-associated technical structure.

C.4 PER-SUBTYPE SUPPORT AND PERFORMANCE AUDIT

Figure 2 visualizes the two marginal support-F1 associations for Soft-cascade Transformer and XGBoost. The vertical stack at 40 patients makes the coverage ceiling explicit. These plots and the partial correlations are exploratory: they neither establish causality nor test whether two dependent correlations differ significantly.




Figure 2: Per-subtype pooled out-of-fold F1 versus cell abundance (left) and patient coverage (right). Each marker is one of 27 subtypes; both models use the same ground-truth support values. Spearman correlations are marginal, and 16 of 27 subtypes occur in all 40 patients.

(a) Support–performance associations

Model	ρ_c	ρ_p	$\rho_{c p}$	$\rho_{p c}$
Soft-cascade Transformer	0.486	0.288	0.411	-0.051
Flat FT-style Transformer	0.505	0.255	0.464	-0.123
FT-style Transformer + HCE	0.513	0.318	0.427	-0.034
XGBoost	0.540	0.275	0.496	-0.130
Logistic Regression	0.435	0.107	0.488	-0.267
Linear SVM	0.339	-0.012	0.463	-0.335
Random Forest	0.661	0.418	0.564	-0.035
Reference Correlation	0.376	0.003	0.499	-0.354

(b) Granularity and error structure

Model	G	R_{sibling}	Cross-lineage
Soft-cascade Transformer	0.174	0.250	0.750
Flat FT-style Transformer	0.176	0.243	0.757
FT-style Transformer + HCE	0.183	0.257	0.743
XGBoost	0.179	0.246	0.754
Logistic Regression	0.167	0.295	0.705
Linear SVM	0.200	0.265	0.735
Random Forest	0.158	0.191	0.809
Reference Correlation	0.099	0.225	0.775

Table 7: Exploratory subtype diagnostics on pooled patient-disjoint predictions. ρ_c and ρ_p are marginal Spearman associations of subtype F1 with log cell count and patient coverage; partial correlations residualize ranked variables. $G = F_1^{\text{coarse}} - F_1^{\text{fine}}$. Among errors, R_{sibling} retains the true parent and Cross-lineage is its complement. These cohort-level summaries are descriptive, not causal.

Table 8 gives all subtype-level quantities and 95% percentile intervals from 2,000 patient-clustered bootstrap resamples. Counts and coverage use pooled ground truth, while F1 uses the same patient-disjoint OOF predictions as Table 1. Mean cells per patient averages only over patients in which the subtype is observed.

Table 8: Per-subtype support and pooled out-of-fold F1 with 95% percentile intervals from 2,000 patient-clustered bootstrap resamples. Cells/patient is the mean among patients in which that subtype is observed. Head and Tail denote the seven most and seven least abundant subtypes; all others are Mid.

Subtype	Lineage	Cells	Patients	Cells/patient	Regime	Soft-cascade F1 [95% CI]	XGB F1 [95% CI]
Erythrocyte	Other	65	6	10.8	Tail	0.253 [0.000, 0.395]	0.133 [0.000, 0.545]
Atypical Memory B	B	781	34	23.0	Tail	0.005 [0.000, 0.014]	0.005 [0.000, 0.014]
CD4 Monocyte-4	Myeloid	1,405	35	40.1	Tail	0.027 [0.006, 0.053]	0.014 [0.000, 0.033]
platelet	Other	1,574	38	41.4	Tail	0.078 [0.016, 0.125]	0.063 [0.015, 0.106]
Tcm	T	2,121	36	58.9	Tail	0.000 [0.000, 0.000]	0.004 [0.000, 0.016]
Memory B-2	B	2,130	33	64.5	Tail	0.017 [0.004, 0.033]	0.011 [0.000, 0.024]
Plasma	B	2,173	40	54.3	Tail	0.611 [0.522, 0.684]	0.599 [0.496, 0.685]
pDC	Myeloid	2,615	40	65.4	Mid	0.029 [0.010, 0.061]	0.019 [0.005, 0.040]
CD14 Monocyte-3	Myeloid	2,977	32	93.0	Mid	0.258 [0.170, 0.306]	0.177 [0.103, 0.211]
CD8 + CTL-3	T	3,244	27	120.1	Mid	0.020 [0.004, 0.035]	0.023 [0.008, 0.043]
GCB	B	3,283	31	105.9	Mid	0.039 [0.007, 0.071]	0.047 [0.001, 0.073]
Cycling T	T	3,667	40	91.7	Mid	0.028 [0.015, 0.043]	0.012 [0.003, 0.022]
CD14 Monocyte-2	Myeloid	3,931	40	98.3	Mid	0.075 [0.046, 0.102]	0.078 [0.056, 0.097]
CD8 + CTL-2	T	4,049	33	122.7	Mid	0.069 [0.017, 0.116]	0.078 [0.015, 0.113]
CD16 Monocyte-2	Myeloid	5,142	40	128.6	Mid	0.111 [0.064, 0.161]	0.117 [0.063, 0.164]
CD8 + CTL-1	T	7,303	40	182.6	Mid	0.009 [0.000, 0.024]	0.002 [0.001, 0.004]
cDC2	Myeloid	7,376	40	184.4	Mid	0.132 [0.099, 0.181]	0.125 [0.079, 0.167]
CD8 Tem-2	T	10,548	40	263.7	Mid	0.019 [0.005, 0.038]	0.017 [0.008, 0.030]
CD16 Monocyte-1	Myeloid	14,678	40	366.9	Mid	0.152 [0.111, 0.198]	0.118 [0.090, 0.150]
CD4 + Tcm-2	T	16,861	39	432.3	Mid	0.188 [0.111, 0.236]	0.188 [0.136, 0.220]
Naive T	T	17,960	40	449.0	Head	0.131 [0.067, 0.183]	0.149 [0.073, 0.199]
Memory B-1	B	23,722	40	593.0	Head	0.034 [0.020, 0.048]	0.032 [0.017, 0.047]
CD8 Tem-1	T	26,714	40	667.9	Head	0.187 [0.128, 0.250]	0.162 [0.107, 0.221]
CD14 Monocyte-1	Myeloid	29,871	40	746.8	Head	0.437 [0.378, 0.495]	0.451 [0.392, 0.507]
CD56 NK	NK	38,442	40	961.0	Head	0.398 [0.320, 0.436]	0.437 [0.373, 0.480]
CD16 NK	NK	58,507	40	1462.7	Head	0.383 [0.326, 0.434]	0.376 [0.317, 0.429]
CD4 + Tcm-1	T	70,653	40	1766.3	Head	0.417 [0.368, 0.460]	0.435 [0.393, 0.473]

For continuity with common long-tail reporting, Table 9 aggregates the seven least and seven most abundant subtypes. This summary is secondary to the per-class audit because individual subtypes can depart sharply from the abundance trend.

Model	Tail Macro-F1	Head Macro-F1
Soft-cascade Transformer	0.142	0.284
Flat FT-style Transformer	0.117	0.290
FT-style Transformer + HCE	0.125	0.288
XGBoost	0.119	0.292
Logistic Regression	0.114	0.197
Linear SVM	0.082	0.204
Random Forest	0.072	0.245
Reference Correlation	0.060	0.114

Table 9: Fine-subtype macro-F1 on the seven least and seven most abundant subtypes under pooled patient-disjoint evaluation. This aggregate is reported as a descriptive complement to the complete per-subtype audit in Table 8.

Cross-lineage error relative to an error-conditioned null. Table 10 uses the wrong-conditioned null as the primary reference: after excluding the true subtype, it renormalizes the predicted-subtype marginal so every randomized outcome remains an error. For the four main models, observed cross-lineage rates are 0.743–0.757 versus wrong-conditioned expectations of 0.741–0.745. The corresponding differences are only +0.002 to +0.013, and all four patient-bootstrap 95% intervals include zero. Thus the raw approximately 75% rate is largely explained by the available wrong-class distribution and does not independently demonstrate either hierarchy preservation or hierarchy failure. The unconditional permutation, which can create chance exact matches and therefore uses a different sample space, is retained only as a sensitivity analysis.

Model	Errors	Observed	Wrong-cond. null	Obs. – WC null [95% CI]	Uncond. null (sens.)
Soft-cascade Transformer	251,354	0.750	0.744	+0.005 [-0.025, +0.028]	0.675
Flat FT-style Transformer	247,798	0.757	0.745	+0.011 [-0.020, +0.035]	0.675
FT-style Transformer + HCE	250,944	0.743	0.741	+0.002 [-0.028, +0.023]	0.671
XGBoost	244,990	0.754	0.741	+0.013 [-0.020, +0.038]	0.672
Logistic Regression	301,566	0.705	0.752	-0.047 [-0.061, -0.036]	0.720
Linear SVM	296,904	0.735	0.774	-0.039 [-0.053, -0.028]	0.738
Random Forest	246,420	0.809	0.749	+0.059 [+0.021, +0.083]	0.685
Reference Correlation	328,596	0.775	0.785	-0.009 [-0.022, +0.003]	0.758

Table 10: Cross-lineage error relative to an error-conditioned marginal null. The primary wrong-conditioned (WC) null draws from each model’s predicted-subtype marginal after excluding the true subtype and renormalizing, so every randomized outcome remains wrong. Observed – WC-null confidence intervals recompute both terms in 2,000 patient-clustered bootstrap resamples. The unconditional permutation preserves the realized true- and predicted-subtype marginals but can create chance exact matches; it is reported only as a sensitivity analysis.

C.5 PROTOCOL SENSITIVITY: PATIENT-LEVEL VERSUS CELL-LEVEL SPLITTING

Table 11 compares the primary patient-disjoint protocol with a leakage-prone cell-level split control. It is placed in the appendix because the central result uses patient-disjoint evaluation throughout; the control quantifies how much the easier protocol would inflate both absolute performance and the apparent advantage of a model family.

Task	Model	Patient-disjoint	Cell split	Inflation
Coarse lineage	XGBoost	0.322	0.372	+0.050
	Soft-cascade Transformer	0.326	0.417	+0.090
Fine subtype	XGBoost	0.143	0.212	+0.069
	Soft-cascade Transformer	0.152	0.260	+0.108

Table 11: Macro-F1 under the primary patient-disjoint protocol versus a leakage-prone cell-level split control. Cell-level splitting inflates performance for both methods, and does so more strongly for Soft-cascade Transformer than for XGBoost. This demonstrates that evaluation protocol can change both absolute performance and the apparent relative advantage of model families, which is why APT-Bench treats patient-disjoint evaluation as a requirement rather than a reporting option.

Patient-balanced cell-count sensitivity. Patient-disjoint evaluation prevents leakage but does not make a pooled cell-level point estimate patient-balanced: patient cell counts range from 1,929 to 22,627. Table 12 therefore recomputes both hierarchy endpoints after sampling 1,900 cells without replacement from every patient for each of 50 seeds. Coarse macro-F1 changes by at most +0.005, while fine macro-F1 changes by -0.007 to -0.009 ; the qualitative model ordering is unchanged. The main conclusions are therefore not driven by a few high-cell-count patients, although the head-line pooled metric remains explicitly cell-weighted.

Task	Model	Pooled M-F1	Equal-cell M-F1 [95% interval]	Δ
Coarse lineage	Soft-cascade Transformer	0.326	0.331 [0.325, 0.337]	+0.005
	Flat FT-style Transformer	0.323	0.326 [0.322, 0.330]	+0.003
	FT-style Transformer + HCE	0.333	0.334 [0.328, 0.340]	+0.000
	XGBoost	0.322	0.324 [0.320, 0.329]	+0.002
Fine subtype	Soft-cascade Transformer	0.152	0.144 [0.138, 0.153]	-0.008
	Flat FT-style Transformer	0.147	0.138 [0.131, 0.147]	-0.008
	FT-style Transformer + HCE	0.151	0.142 [0.137, 0.151]	-0.009
	XGBoost	0.143	0.136 [0.131, 0.144]	-0.007

Table 12: Patient-balanced cell-count sensitivity. For each of 50 seeds, 1,900 cells are sampled without replacement from every patient, and pooled macro-F1 is recomputed on the resulting 76,000 cells. All models use identical sampled row indices. The interval is the empirical 2.5th–97.5th percentile across seeds; Δ is the equal-cell mean minus the original pooled metric. This diagnostic changes evaluation weights only and does not retrain or reselect models.

C.6 FAIR FIXED-TOTAL AND MATCHED-SCALE ANALYSIS

The primary scaling design uses $P \in \{8, 16, 32\}$ and $C \in \{100, 200, 400, 800, 1600\}$, with 20 nested subset seeds for every outer fold. Because every retained patient has at least 1,929 cells, all finite caps are feasible without replacement. Disease-stratified patient orderings are nested across P , uniform cell permutations are nested across C , no subtype label enters sampling, and preprocessing is refit on each sampled training set. The fixed-total diagonals satisfy $PC \in \{3200, 6400, 12800\}$ exactly.

Model	Task	Total cells	$P = 8$	$P = 16$	$P = 32$
LR	Coarse	3,200	0.271 [0.259, 0.283]	0.279 [0.272, 0.285]	0.283 [0.278, 0.288]
LR	Coarse	6,400	0.278 [0.266, 0.291]	0.287 [0.280, 0.294]	0.293 [0.289, 0.297]
LR	Coarse	12,800	0.282 [0.269, 0.296]	0.293 [0.286, 0.300]	0.299 [0.295, 0.303]
LR	Fine	3,200	0.082 [0.078, 0.087]	0.087 [0.083, 0.089]	0.089 [0.086, 0.092]
LR	Fine	6,400	0.085 [0.082, 0.090]	0.090 [0.087, 0.094]	0.093 [0.091, 0.095]
LR	Fine	12,800	0.087 [0.082, 0.092]	0.092 [0.089, 0.096]	0.095 [0.093, 0.097]
XGBoost	Coarse	3,200	0.260 [0.249, 0.275]	0.268 [0.258, 0.278]	0.275 [0.270, 0.280]
XGBoost	Coarse	6,400	0.267 [0.254, 0.285]	0.275 [0.265, 0.285]	0.283 [0.279, 0.287]
XGBoost	Coarse	12,800	0.274 [0.260, 0.291]	0.284 [0.273, 0.295]	0.293 [0.290, 0.296]
XGBoost	Fine	3,200	0.084 [0.080, 0.090]	0.089 [0.084, 0.093]	0.090 [0.087, 0.093]
XGBoost	Fine	6,400	0.089 [0.082, 0.098]	0.094 [0.090, 0.099]	0.096 [0.092, 0.099]
XGBoost	Fine	12,800	0.094 [0.089, 0.101]	0.100 [0.094, 0.106]	0.100 [0.097, 0.103]

Table 13: Fixed-total training-cell scaling. Each row holds the total number of sampled training cells constant while reallocating them across independent patients. Entries are pooled patient-disjoint OOF Macro-F1 means with empirical 95% intervals over 20 matched subset seeds. All outer-test cells are evaluated.




Figure 3: APT-only fixed-total response curves underlying the unmatched cross-cohort diagnostic in Table 14. Points are pooled OOF macro-F1 means over 20 matched subset seeds; bars are empirical 95% seed intervals. Patient-balanced and patient-bootstrap results are provided in the machine-readable artifacts.

Table 13 reports variability across subset seeds. Separately, paired patient-clustered bootstraps over the same 40 pooled OOF patients compare $P = 8$ with $P = 32$ after averaging seed-level sufficient statistics. All 12 intervals exclude zero; their lower endpoints range from 0.0002 to 0.0084 and upper endpoints from 0.0090 to 0.0314. These intervals quantify uncertainty over patients, whereas the empirical seed intervals quantify sensitivity to which development patients and cells are sampled.

Matched doubling effects average patient versus cell gains of 0.011/0.005 (LR coarse), 0.007/0.003 (LR fine), 0.016/0.008 (XGBoost coarse), and 0.009/0.006 (XGBoost fine). In the descriptive fold-fixed-effect response surface, the corresponding per-doubling β_P/β_C coefficients are 0.017/0.008, 0.008/0.004, 0.016/0.007, and 0.009/0.006. Complete pairwise effects, patient intervals, seed intervals, and response-surface uncertainty are stored in the machine-readable artifacts. The coefficients are associations over this grid, not causal or universal scaling laws.

C.7 EXTERNAL COMBAT AND ONEK1K SCALING REPLICATIONS

We downloaded the author-released COMBAT CITE-seq object (COVID-19 Multi-omics Blood Atlas (COMBAT) Consortium, 2022) (836,148 cells and 124 donor identifiers; SHA-256 f628a15f25b9ca2f7cdefeab271fd9d007c8d5e47eb80c4b807d5f65e86ff53d).

We removed cells without a resolved major or fine immune annotation and cells flagged as GEX-region doublets. Ten donors were frozen as a calibration-only set and excluded from every model fit and test fold. Among the remaining donors, requiring at least 1,600 eligible cells leaves 105 donors and 700,706 cells. We construct five disjoint folds of 21 test donors, stratified by the released sample-source field, and freeze these folds across all models, budgets, seeds, and modalities.

The RNA replication uses 293 protein-coding genes with highest variance on the 10 calibration donors after excluding mitochondrial and ribosomal genes. This matches the APT input dimension without selecting features on any evaluation donor. The ADT sensitivity uses all 192 released antibody features. Both inputs use the released five-class major annotation and 39-class fine an-

notation. They share the exact P , C , and fixed-total grids, 20 nested source-stratified donor/cell seeds, training-only standardization, LR configuration, and paired donor-bootstrap procedure used in APT-Bench. The RNA analysis additionally uses the frozen 400-tree XGBoost baseline. Every fit is evaluated on all cells of the 21 untouched test donors; the ADT analysis is an LR-only modality sensitivity rather than an additional model-comparison family. Dataset hashes, folds, features, sampling manifests, and per-donor sufficient statistics are included in the release artifacts.

OneK1K provides a second independent scRNA-seq replication in a much larger healthy PBMC cohort (Yazar et al., 2022). We use the current author-deposited CELLxGENE object (1,248,980 cells and 981 donor identifiers; SHA-256 14c5e9e70007a5e7dc047f7b29405773305e1a7b9791d0789af70649cf6f46ec), remove released doublet calls, and reserve one complete multiplexing pool for calibration. Requiring at least 800 eligible cells leaves 925 evaluation donors and 1,199,468 cells. Five folds are disjoint in both donor and multiplexing pool. We select 293 protein-coding, non-mitochondrial, non-ribosomal genes by variance on ten calibration-pool donors only, and use the released 30-class Azimuth-derived fine labels with a deterministic five-lineage mapping.

OneK1K uses the same models, 20 nested subset seeds, training-only standardization, untouched-test-donor evaluation, subject-balanced metric, and 2,000 paired donor bootstraps. Its grid is $P \in \{8, 16, 32\}$ and $C \in \{100, 200, 400, 800\}$, yielding the two common exact budgets $T \in \{3200, 6400\}$. We prespecified the lower depth ceiling because only 116 of the 981 raw donors have at least 1,600 eligible cells; enforcing the full APT grid would discard most donors and condition the replication on high cell recovery. OneK1K tests scaling portability in a healthy cohort, not disease generalization or absolute accuracy across different feature spaces and label-generation procedures.

Dataset	Modality	Model/task	$T = 3,200$	$T = 6,400$	$T = 12,800$
APT	Aptamer	LR/Coarse	+0.012 [+0.005, +0.021]	+0.015 [+0.007, +0.024]	+0.017 [+0.009, +0.026]
APT	Aptamer	LR/Fine	+0.008 [+0.004, +0.011]	+0.009 [+0.005, +0.012]	+0.010 [+0.005, +0.013]
APT	Aptamer	XGBoost/Coarse	+0.017 [+0.008, +0.027]	+0.018 [+0.007, +0.030]	+0.022 [+0.009, +0.035]
APT	Aptamer	XGBoost/Fine	+0.007 [+0.002, +0.011]	+0.008 [+0.002, +0.013]	+0.006 [+0.000, +0.011]
COMBAT	RNA	LR/Coarse	+0.003 [+0.002, +0.004]	+0.002 [+0.001, +0.003]	+0.001 [+0.001, +0.002]
COMBAT	RNA	LR/Fine	+0.012 [+0.009, +0.013]	+0.012 [+0.010, +0.012]	+0.007 [+0.005, +0.009]
COMBAT	RNA	XGBoost/Coarse	+0.006 [+0.005, +0.007]	+0.005 [+0.004, +0.006]	+0.004 [+0.003, +0.005]
COMBAT	RNA	XGBoost/Fine	+0.016 [+0.013, +0.017]	+0.018 [+0.016, +0.019]	+0.017 [+0.014, +0.018]
COMBAT	ADT	LR/Coarse	+0.006 [+0.004, +0.008]	+0.009 [+0.006, +0.012]	+0.012 [+0.010, +0.016]
COMBAT	ADT	LR/Fine	+0.013 [+0.010, +0.014]	+0.011 [+0.010, +0.013]	+0.011 [+0.009, +0.013]
OneK1K	RNA	LR/Coarse	+0.004 [+0.004, +0.005]	+0.005 [+0.005, +0.006]	–
OneK1K	RNA	LR/Fine	+0.007 [+0.007, +0.009]	+0.008 [+0.007, +0.009]	–
OneK1K	RNA	XGBoost/Coarse	–0.003 [–0.004, –0.002]	+0.006 [+0.005, +0.006]	–
OneK1K	RNA	XGBoost/Fine	+0.006 [+0.005, +0.007]	+0.009 [+0.007, +0.009]	–

Table 14: Unmatched diagnostic: change in subject-balanced, subject-disjoint OOF Macro-F1 when the same total training-cell budget is reallocated from 8 to 32 independent subjects without freezing the marginal training label distribution. Brackets are 95% paired subject-bootstrap intervals over the fixed outer-test subjects. Positive values favor broader subject coverage but can also reflect changes in observed classes, per-class counts, and class proportions. COMBAT ADT is a prespecified modality sensitivity using LR only. OneK1K uses the two common exact budgets supported by at least 800 cells from nearly all donors.

C.8 LABEL-DISTRIBUTION AUDIT AND MATCHED CONTROL

The label-agnostic grid samples cells uniformly within subjects and therefore allows the full marginal label distribution to vary. Machine-readable audit tables report the observed class count, unseen-at-training class count, cell count, and donor count for every class at every fold, seed, and scaling point. The main text reports the common fixed-total diagonals, where fine-class coverage increases slightly with P despite fixed T ; this coverage statistic is only one observable component of the broader label-distribution effect.

The class-matched control fixes the marginal label distribution. The $P = 8$ subset defines the observed labels and a proportional integer quota T_k with a one-cell floor; capacity violations are deterministically redistributed. The same quota vector is then used at $P = 8, 16, 32$. Within each class, a capacity-constrained round-robin sampler distributes cells across selected subjects before

assigning a second cell from the same subject, so increasing P changes realized donor coverage rather than class counts. Sampling is without replacement, standardization is refit on each training subset, and all immutable outer-test cells are retained. All three runs complete 1,200/1,200 jobs and pass checks for exact total cells, identical paired class counts, non-overlapping test subjects, and contribution by every nominal training subject. It does not separately identify changes in disease-subtype composition, within-class allocation across subjects, or within-class subject heterogeneity; these remain bundled with the subject-breadth intervention.

Dataset	Task	T	Classes (mean/total)	Donors/class (P : 8→32)	Δ subject-balanced M-F1
APT	Coarse	3,200	5.0/5	7.9→28.5	+0.0062 [+0.0008, +0.0129]
APT	Coarse	6,400	5.0/5	7.9→30.5	+0.0078 [+0.0022, +0.0160]
APT	Fine	3,200	26.8/27	7.1→25.0	-0.0024 [-0.0042, -0.0004]
APT	Fine	6,400	26.8/27	7.2→27.4	-0.0050 [-0.0068, -0.0026]
COMBAT RNA	Coarse	3,200	5.0/5	8.0→29.0	+0.0011 [+0.0005, +0.0017]
COMBAT RNA	Coarse	6,400	5.0/5	8.0→31.3	+0.0000 [-0.0004, +0.0004]
COMBAT RNA	Fine	3,200	39.0/39	7.2→22.5	-0.0007 [-0.0014, +0.0006]
COMBAT RNA	Fine	6,400	39.0/39	7.3→26.6	-0.0028 [-0.0037, -0.0018]
OneK1K RNA	Coarse	3,200	5.0/5	7.8→27.7	+0.0025 [+0.0020, +0.0031]
OneK1K RNA	Coarse	6,400	5.0/5	7.8→29.6	+0.0033 [+0.0026, +0.0039]
OneK1K RNA	Fine	3,200	29.0/30	6.2→19.8	+0.0019 [+0.0010, +0.0030]
OneK1K RNA	Fine	6,400	29.0/30	6.4→22.1	+0.0013 [+0.0002, +0.0023]

Table 15: Class-matched fixed-total control using class-weighted multinomial Logistic Regression. Within each outer-fold/seed/task pair, the $P = 8$ subset freezes the observed classes and exact per-class cell quotas; the same quotas are used at $P = 16$ and $P = 32$. Brackets are 95% paired subject-bootstrap intervals after averaging the 20 seed-level sufficient statistics; empirical seed intervals are released separately. Donors/class reports the mean number of subjects contributing cells to an observed class.

The table reports paired subject-bootstrap intervals for the seed-averaged effect. Empirical 95% subset-seed intervals include zero in 11 of 12 rows; the exception is APT fine at $T = 6,400$, which is negative $[-0.0084, -0.0022]$. The bootstrap and seed intervals answer different questions: the former varies held-out subjects after averaging training-subset seeds, whereas the latter varies selected development subsets with the test subjects fixed. We therefore interpret sign and magnitude descriptively rather than treating either interval family as a universal significance test.

C.9 SECONDARY DESCRIPTIVE PATIENT-CELL SCALING SURFACE

This historical 4×4 surface fixes eight outer-test patients and varies only the training set. For each outer fold and each of 20 seeds, we generate one approximately proportional disease-stratified ordering of the 32 development patients, giving nested sets $S_8 \subset S_{16} \subset S_{24} \subset S_{32}$. Each selected patient receives one uniform random cell ordering, giving nested prefixes of 100, 500, and 2,000 cells and the complete available set. Patients with fewer than a requested cap contribute all available cells. No cell is selected using its subtype, and every model is evaluated on all cells from the untouched test patients. The full-data endpoint is fitted once per fold rather than duplicated across seeds. All 6,020 model-task jobs completed, and the deterministic endpoint exactly reproduces the frozen pooled OOF baselines within absolute tolerance 5×10^{-4} . Because $P=8 \rightarrow 32$ is a fourfold change whereas $C=100 \rightarrow$ all is a larger and patient-dependent change, this surface is descriptive only. All direct comparisons between the two axes use the fixed-total and matched-doubling analysis in the main paper.

Model	Task	$C = 100$	$C = 500$	$C = 2000$	$C = \text{all}$
Logistic Regression, $P = 8$	Coarse	0.255 [0.247, 0.265]	0.274 [0.263, 0.284]	0.283 [0.269, 0.297]	0.282 [0.269, 0.293]
Logistic Regression, $P = 16$	Coarse	0.266 [0.261, 0.270]	0.290 [0.284, 0.297]	0.288 [0.282, 0.295]	0.290 [0.280, 0.300]
Logistic Regression, $P = 24$	Coarse	0.276 [0.269, 0.280]	0.296 [0.288, 0.304]	0.288 [0.282, 0.295]	0.296 [0.289, 0.302]
Logistic Regression, $P = 32$	Coarse	0.283 [0.278, 0.288]	0.299 [0.296, 0.302]	0.287 [0.284, 0.288]	0.299 [0.284, 0.315]
Logistic Regression, $P = 8$	Fine	0.074 [0.068, 0.081]	0.084 [0.079, 0.088]	0.087 [0.082, 0.092]	0.101 [0.091, 0.109]
Logistic Regression, $P = 16$	Fine	0.081 [0.078, 0.085]	0.090 [0.088, 0.094]	0.095 [0.090, 0.099]	0.116 [0.110, 0.125]
Logistic Regression, $P = 24$	Fine	0.086 [0.083, 0.089]	0.093 [0.089, 0.097]	0.100 [0.095, 0.105]	0.125 [0.118, 0.131]
Logistic Regression, $P = 32$	Fine	0.089 [0.086, 0.092]	0.095 [0.093, 0.097]	0.105 [0.102, 0.108]	0.132 [0.112, 0.146]
XGBoost, $P = 8$	Coarse	0.246 [0.234, 0.263]	0.262 [0.250, 0.278]	0.277 [0.262, 0.293]	0.300 [0.283, 0.321]
XGBoost, $P = 16$	Coarse	0.260 [0.252, 0.272]	0.278 [0.268, 0.288]	0.295 [0.283, 0.306]	0.313 [0.298, 0.330]
XGBoost, $P = 24$	Coarse	0.270 [0.264, 0.276]	0.289 [0.284, 0.295]	0.305 [0.297, 0.312]	0.319 [0.311, 0.328]
XGBoost, $P = 32$	Coarse	0.275 [0.270, 0.280]	0.296 [0.293, 0.298]	0.310 [0.308, 0.312]	0.322 [0.300, 0.345]
XGBoost, $P = 8$	Fine	0.073 [0.068, 0.079]	0.085 [0.080, 0.091]	0.096 [0.090, 0.103]	0.118 [0.110, 0.126]
XGBoost, $P = 16$	Fine	0.082 [0.077, 0.085]	0.096 [0.092, 0.101]	0.110 [0.103, 0.120]	0.132 [0.125, 0.140]
XGBoost, $P = 24$	Fine	0.087 [0.081, 0.092]	0.100 [0.095, 0.104]	0.115 [0.110, 0.121]	0.138 [0.132, 0.144]
XGBoost, $P = 32$	Fine	0.090 [0.087, 0.093]	0.102 [0.100, 0.105]	0.118 [0.117, 0.121]	0.143 [0.127, 0.159]

Table 16: Patient–cell training scaling. Entries are pooled OOF Macro-F1 means with empirical 2.5th–97.5th seed intervals; the deterministic $P = 32, C = \text{all}$ endpoint instead uses a patient-clustered bootstrap interval. Seed intervals are not patient confidence intervals.




Figure 4: Pooled patient-disjoint Macro-F1 over the complete training-patient and per-patient training-cell grid. Values average 20 nested subset seeds except for the deterministic full-data endpoint. Color scales are shared across models within each task.




Figure 5: Patient-budget curves at each fixed per-patient cell cap. Intervals show subset-resampling variability; they do not represent uncertainty over a new patient population. Non-monotonic local changes are retained rather than smoothed.

The surface is cohort- and range-specific. We do not compare its unequal endpoints or use it to establish a patient- or cell-dominant scaling law, and it cannot estimate the benefit of patients drawn from new sites or acquisition batches.

C.10 COARSE-FINE CONSISTENCY DIAGNOSTIC

Independent coarse and fine classifiers can disagree about the hierarchy even when each prediction is plausible in isolation. Table 17 reports their natural agreement. Unlike an earlier single-split analysis, this version uses the same five-fold pooled out-of-fold prediction artifacts as the main hierarchy results, so every patient contributes exactly once to both evaluations.

Model	Fine Acc.	Root-excl. Hier. F1	Consistency
Soft-cascade Transformer	0.305	0.404	0.812
Flat FT-style Transformer	0.315	0.411	0.795
FT-style Transformer + HCE	0.306	0.405	0.834
XGBoost	0.323	0.420	0.736

Table 17: Auxiliary hierarchy diagnostics on the same 361,792-cell pooled OOF artifacts as Table 1. Root-excluded hierarchical F1 is the example-averaged F1 between the true and predicted {lineage, subtype} sets; the always-correct root is omitted. Consistency maps each hard fine prediction to its parent and compares it with the independent coarse prediction. *Unknown* is excluded and no constrained decoding is used.

C.11 FEATURE-REDUNDANCY SENSITIVITY OF THE MIXED DISEASE-ASSOCIATED SIGNAL

We asked how many of the 293 aptamers preserve the observed within-cohort disease-associated result. Because biological and technical sources are not identifiable, this section characterizes fea-

ture redundancy of a mixed signal; it does not validate a reduced assay, clinical deployment, or biomarker panel. Patient-Stable Aptamer Selection (PSAS) denotes the fold-specific ranking and development-only budget-selection protocol below; “stable” refers to comparison of ranks across outer folds, not to patient-balanced fitting of the LR ranker.

Algorithm 1: PSAS within outer fold o .

1. Seal the eight outer-test patients; denote the other 32 patients by D_o .
2. Using all cells in D_o , fit development-only standardization and an L1-regularized six-class multinomial LR (SAGA, $C = 0.1$); rank aptamer j by $s_j = \sum_{d=1}^6 |\beta_{dj}|$.
3. Seed-shuffle the patients in D_o into five patient-disjoint, non-stratified inner folds.
4. For every $B \in \{5, 10, 20, 40, 80, 160, 293\}$ and inner fold, refit LR on the inner-training patients using the fixed Top- B ranking and score patient-majority-vote macro-F1 on inner-validation patients.
5. Let $\bar{F}_B$ denote mean inner-validation macro-F1 and select $B^* = \min\{B : \bar{F}_B \geq \bar{F}_{293} - \delta\}$ with $\delta = 0.02$.
6. Refit LR and XGBoost from scratch on all patients in D_o , using only the LR-selected Top- B^* features, and evaluate once on the sealed outer-test patients.
7. Repeat independently for all five outer folds; report the pooled outer-test predictions.

Implementation scope and controls. The LR ranker is a cell-level disease model: cells are not first aggregated to patient medians and receive equal weight, so its coefficients are cell-count weighted rather than patient-balanced. The full-panel reference $\bar{F}_{293}$ is the mean inner-validation score, not a resubstitution estimate on all of D_o . The absolute margin $\delta = 0.02$ was fixed in code before outer-test scoring but was not prospectively preregistered. Because the ranking is computed once from all of D_o and then held fixed across its inner folds, budget selection is development-only but conditional on that ranking, not fully nested inner re-ranking.

For Random- B , each $B \in \{5, 10, 20\}$ has 100 uniformly sampled feature sets. The feature set for one repeat is shared across the five outer folds, but LR and XGBoost are trained from scratch within every fold. XGBoost in Table 18 and Figure 6 uses the LR-selected panel. The separate SHAP control instead fits full-panel XGBoost in each outer-development set, constructs a patient-balanced mean absolute TreeSHAP ranking, and refits both classifiers on SHAP-selected Top-10/20 features; it does not determine B^* or the main curve.

All five outer folds select $B^* = 10$ under this rule.

Budget terminology. An *aptamer measurement budget* B means that a model is retrained and evaluated using only those B input features. An *inference-time cell budget* C means that, after training on all available outer-development cells, only C cached predictions are sampled from each held-out patient before majority-vote aggregation. We do not reduce or evaluate a *training-time cell budget*; the cell-count sensitivity therefore supports low-cell inference aggregation, not training with only C cells per patient.

The resulting development-selected 10-aptamer panels reproduce the full-panel patient-level macro-F1 of 1.0 for both Logistic Regression and XGBoost on all five outer test folds. Figure 6 compares these selected panels with 100 Random- B repeats at each compact budget. For every model and budget, we report the random-panel mean, empirical 2.5th–97.5th percentile interval, and the empirical midrank percentile of Top- B within that distribution (Table 19).




Figure 6: Patient-level disease-association macro-F1 under feature-budget controls. Solid lines show pooled out-of-fold performance obtained using fold-specific Top- B panels; dotted lines and ribbons show the mean and empirical 95% interval over 100 random-panel repeats. Each repeat shares one panel across outer folds, with models refit foldwise. The dashed line is the full 293-aptamer reference; scores pool the 40 outer-test patients once each. Because acquisition effects are unrecorded, the curves quantify redundancy of the mixed within-cohort signal rather than reduced-assay validity.

Outer Fold	δ	B^*	LR Macro-F1	XGBoost Macro-F1
0	0.02	10	1.000	1.000
1	0.02	10	1.000	1.000
2	0.02	10	1.000	1.000
3	0.02	10	1.000	1.000
4	0.02	10	1.000	1.000
All folds	0.02	10	1.000	1.000

Table 18: Outer-test-isolated feature-budget sensitivity for the mixed disease-associated signal. In each outer fold, aptamer ranking and budget selection are performed using outer-development patients only, and the selected budget is evaluated once on the untouched outer-test patients. The ranking is fixed across inner validation splits; B is selected conditional on that ranking. Under the analysis-specified, non-preregistered tolerance margin $\delta = 0.02$, all five folds select the same development budget $B^* = 10$, and the resulting 10-aptamer panels preserve the observed full-panel patient macro-F1 for both Logistic Regression and XGBoost. This result demonstrates feature redundancy of the observed mixed disease-associated signal. It does not validate a reduced assay, a biological signature, or unique causal biomarkers.

B	Model	Top- B	Random mean [95% interval]	Percentile
5	LR	0.898	0.663 [0.422, 0.890]	97.0
5	XGBoost	0.925	0.725 [0.453, 0.890]	99.0
10	LR	1.000	0.868 [0.670, 0.952]	100.0
10	XGBoost	1.000	0.921 [0.781, 1.000]	97.0
20	LR	1.000	0.973 [0.900, 1.000]	79.5
20	XGBoost	1.000	0.981 [0.923, 1.000]	75.0

Table 19: Feature-redundancy controls over 100 panel repeats. Top- B uses fold-specific outer-development LR rankings. Each repeat draws one random panel shared across outer folds; both classifiers are refitted in every fold. The percentile is the empirical midrank of Top- B within the random distribution. Because disease and unrecorded acquisition effects are not identifiable, these values characterize only the mixed within-cohort signal.

At $B = 10$, the Top- B panel is at the 100th empirical percentile for LR and the 97th for XGBoost; Random- B means are 0.868 and 0.921, respectively. By $B = 20$, random means rise to 0.973 and 0.981 and many random panels also saturate, reducing the corresponding midrank percentiles to 79.5 and 75.0. Thus ranking is most consequential at the smallest budgets, while the broader panel contains extensive substitutable signal.

We next crossed aptamer budget $B \in \{5, 10, 20, 293\}$ with inference-time cell caps $C \in \{100, 500, 1000, 5000, \text{all}\}$. For each finite cap, cached predictions were sampled without replacement within each outer-test patient; patient majority votes were pooled across the five held-out folds, and the process was repeated over 50 sampling seeds. Training still used all outer-development cells. At $B = 5$, macro-F1 varies with the sampled cells and reaches 0.881 on average at $C = 100$; at $B = 10, 20$, and 293, macro-F1 is 1.0 for every cap and every seed (Table 20).

B	100 cells	500 cells	1,000 cells	5,000 cells	All cells
5	0.881 [0.845, 0.925]	0.894 [0.852, 0.925]	0.906 [0.875, 0.925]	0.899 [0.898, 0.898]	0.898 [0.898, 0.898]
10	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]
20	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]
293	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]	1.000 [1.000, 1.000]

Table 20: LR patient-level macro-F1 under inference-time equal-cell subsampling. Entries are mean [empirical 95% interval] over 50 seeds; cached outer-test predictions are subsampled before aggregation. Models are trained once using all outer-development cells, so this is not a training-time cell-budget experiment.

Finally, we tested whether the compact result depends on Logistic Regression coefficients as the attribution mechanism. Within each outer-development set, we fitted a full-panel XGBoost model and computed absolute TreeSHAP contributions on at most 1,000 cells per development patient. We first averaged over cells within each patient and then over patients, preventing high-cell-count patients from dominating the attribution ranking. The LR-SHAP Jaccard overlap is moderate rather than complete (0.501 for Top-10 and 0.475 for Top-20), yet panels from either ranking achieve patient macro-F1 1.0 when evaluated with either LR or XGBoost (Table 21). This cross-model control supports predictive redundancy of the mixed signal, not measurement efficiency, molecular specificity, or a unique signature.

B	LR-SHAP Jaccard	Ranking	LR eval.	XGB eval.
10	0.501 $\pm$ 0.126	LR coefficient	1.000	1.000
10	–	XGBoost-SHAP	1.000	1.000
20	0.475 $\pm$ 0.087	LR coefficient	1.000	1.000
20	–	XGBoost-SHAP	1.000	1.000

Table 21: Cross-model attribution control. Jaccard is mean $\pm$ SD across five outer-fold Top- B sets. LR-coefficient and XGBoost-SHAP rows use their own selected features; evaluation columns report pooled patient macro-F1 after refitting LR or XGBoost. SHAP ranking does not select B^* .

The fold-overlap LR ranking is also stable. The highest-ranked aptamers by mean outer-fold rank are APT-179, APT-225, APT-164, APT-166, APT-57, APT-69, APT-125, APT-161, APT-172, and APT-218, and 290 of the 293 aptamers are retained after a simple redundancy screen at $|r| \leq 0.9$. These anonymized IDs have no verified public protein-target mapping, and feature ranking under unresolved confounding cannot support protein-target, pathway, or molecular-plausibility interpretation. We therefore omit the earlier full-cohort attribution visualization.

C.12 BALANCED SAMPLING ABLATION

A development-only class-balanced-sampling variant did not outperform natural sampling after matching optimization steps and was not retained.

C.13 EXPLORATORY LEAVE-ONE-DISEASE-OUT STRESS TEST

We retain only a leave-one-disease-out (LODO) representation stress test. For each run, all patients from one disease category are withheld from training and used only for evaluation. Table 22 shows that generalization weakens substantially relative to the standard patient-disjoint folds, especially for fine subtypes. Because there are only six disease groups and no external cohort, LODO is descriptive rather than an estimate of deployment robustness.

Held-out Disease	Fine Macro-F1	Fine Acc.	Coarse Macro-F1	Coarse Acc.	Tail Macro-F1
BTC	0.086	0.317	0.310	0.479	0.073
CRC	0.105	0.277	0.309	0.520	0.112
GC	0.063	0.269	0.281	0.488	0.057
HCC	0.063	0.246	0.264	0.383	0.072
PC	0.057	0.253	0.221	0.482	0.037
Macro-average	0.075	0.272	0.277	0.470	0.070

Table 22: Leave-one-disease-out generalization for Soft-cascade Transformer over the five malignant held-out diseases. Each row withholds all patients of the named disease from training. The in-distribution reference using the same model under the standard patient-disjoint 5-fold protocol is fine Macro-F1 0.152 and coarse Macro-F1 0.326. A separate Normal-held-out run produces near-chance fine performance. LODO is reported only as an exploratory appendix stress test, not as proof that the model already solves cross-disease generalization.

We omit unmatched detector rankings. Cross-disease generalization remains unresolved and requires external cohorts with prespecified distribution shifts and patient-clustered uncertainty.