

# Adversarial Bandits

Yingkai Li

EC4501/EC4501HM Semester 2, AY2024/25

# Adversarial Bandits

Consider an online decision process with  $T$  periods and  $n$  arms.

- the sequence of payoffs  $\{v_{i,t}\}_{i \in [n], t \in [T]}$  are determined by an **adversary**, where  $v_{i,t} \in [0, 1]$ .

# Adversarial Bandits

Consider an online decision process with  $T$  periods and  $n$  arms.

- the sequence of payoffs  $\{v_{i,t}\}_{i \in [n], t \in [T]}$  are determined by an **adversary**, where  $v_{i,t} \in [0, 1]$ .

At any time  $t \leq T$ :

- designer selects an arm  $i_t^*$ ;
- the designer receives a payoff of  $v_{i_t^*, t}$ .
- the designer only observes the payoffs for the selected arm.

# Regret Minimization

Optimal-in-hindsight Benchmark:

$$B_T = \max_{i \in [n]} \sum_{t \in T} v_{i,t}.$$

# Regret Minimization

Optimal-in-hindsight Benchmark:

$$B_T = \max_{i \in [n]} \sum_{t \in T} v_{i,t}.$$

(External) Regret:

$$R_T = B_T - \sum_{t \in T} v_{i_t^*, t}.$$

# Regret Minimization

Optimal-in-hindsight Benchmark:

$$B_T = \max_{i \in [n]} \sum_{t \in T} v_{i,t}.$$

(External) Regret:

$$R_T = B_T - \sum_{t \in T} v_{i_t^*, t}.$$

An algorithm has **no-regret** if  $R_T = o(T)$ .

- Is it possible to design no-regret algorithms with adversarial rewards under bandit feedback?
- The designer cannot predict future rewards based on historical observation.

# Intuitions

Algorithms for stochastic environments fail for adversarial bandits:

- E.g., for Explore-then-Exploit, the adversary may generate low rewards in the exploitation phase for arms that performs the best in the exploration phase.

# Intuitions

Algorithms for stochastic environments fail for adversarial bandits:

- E.g., for Explore-then-Exploit, the adversary may generate low rewards in the exploitation phase for arms that performs the best in the exploration phase.

Algorithms for expert learning algorithms:

- they require payoffs for all arms, which are not observable in bandit settings.



# Intuitions

Algorithms for stochastic environments fail for adversarial bandits:

- E.g., for Explore-then-Exploit, the adversary may generate low rewards in the exploitation phase for arms that performs the best in the exploration phase.

Algorithms for expert learning algorithms:

- they require payoffs for all arms, which are not observable in bandit settings.

**Idea:** adopt expert learning algorithms with [counterfactual estimations](#).

# Inverse Propensity Score (IPS) Estimator

How to estimate the reward for each arm in adversarial settings?

- the designer can only observe the realized reward for the chosen action.

# Inverse Propensity Score (IPS) Estimator

How to estimate the reward for each arm in adversarial settings?

- the designer can only observe the realized reward for the chosen action.

Inverse Propensity Score (IPS) Estimator:

$$\hat{v}_{i,t} = \frac{v_{i,t} \cdot \mathbf{1}(i_t^* = i)}{p_t(i)}$$

where  $p_t(i)$  is the probability of choosing arm  $i$  in period  $t$ .

## Lemma

*For any arm  $i$  and any sequence of rewards, the IPS estimator is unbiased, i.e.,*

$$\mathbf{E}[\hat{v}_{i,t}] = v_{i,t}.$$

## Other Estimators

Alternative estimator:

$$\hat{v}_{i,t} = 1 - \frac{(1 - v_{i,t}) \cdot \mathbf{1}(i_t^* = i)}{p_{i,t}}$$

Intuitively, this is the IPS estimator for the loss of  $y_{i,t} = 1 - v_{i,t}$ .

- this is also an unbiased estimator;
- $\hat{v}_{i,t} \leq 1$ .

# Exponential-weight Algorithm

Exponential-weight algorithm for Exploration and Exploitation (EXP3) with learning rate  $\eta$ :  
the probability of choosing action  $i$  at time  $t$  is

$$p_t(i) = \frac{\exp(\eta \cdot \hat{\mu}_{i,t})}{\sum_{j=1}^n \exp(\eta \cdot \hat{\mu}_{j,t})}.$$

where  $\hat{\mu}_{i,t} = \sum_{s < t} \hat{v}_{s,t}$ .

# Exponential-weight Algorithm

Exponential-weight algorithm for Exploration and Exploitation (EXP3) with learning rate  $\eta$ : the probability of choosing action  $i$  at time  $t$  is

$$p_t(i) = \frac{\exp(\eta \cdot \hat{\mu}_{i,t})}{\sum_{j=1}^n \exp(\eta \cdot \hat{\mu}_{j,t})}.$$

where  $\hat{\mu}_{i,t} = \sum_{s < t} \hat{v}_{s,t}$ .

**Remark:** EXP3 is similar to the Hedge algorithm, by replacing the empirical reward for each arm with its estimation.

# Exponential-weight Algorithm

Exponential-weight algorithm for Exploration and Exploitation (EXP3) with learning rate  $\eta$ : the probability of choosing action  $i$  at time  $t$  is

$$p_t(i) = \frac{\exp(\eta \cdot \hat{\mu}_{i,t})}{\sum_{j=1}^n \exp(\eta \cdot \hat{\mu}_{j,t})}.$$

where  $\hat{\mu}_{i,t} = \sum_{s < t} \hat{v}_{s,t}$ .

**Remark:** EXP3 is similar to the Hedge algorithm, by replacing the empirical reward for each arm with its estimation.

## Theorem

*The worst-case regret of EXP3 is  $O(\sqrt{nT \cdot \log n})$ .*

# Exponential-weight Algorithm

Recall the proof for Hedge in expert learning setting, we have

$$R_T \leq \frac{\log n}{\eta} + \frac{\eta}{2} \sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2.$$



# Exponential-weight Algorithm

Recall the proof for Hedge in expert learning setting, we have

$$R_T \leq \frac{\log n}{\eta} + \frac{\eta}{2} \sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2.$$

In expert learning setting without reward estimations,  $\sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2 \leq T$ .

# Exponential-weight Algorithm

Recall the proof for Hedge in expert learning setting, we have

$$R_T \leq \frac{\log n}{\eta} + \frac{\eta}{2} \sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2.$$

In expert learning setting without reward estimations,  $\sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2 \leq T$ .

In adversarial bandits, with reward estimations, we can show that

$$\mathbf{E} \left[ \sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2 \right] \leq nT.$$

# Exponential-weight Algorithm

Recall the proof for Hedge in expert learning setting, we have

$$R_T \leq \frac{\log n}{\eta} + \frac{\eta}{2} \sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2.$$

In expert learning setting without reward estimations,  $\sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2 \leq T$ .

In adversarial bandits, with reward estimations, we can show that

$$\mathbf{E} \left[ \sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot (\hat{v}_{i,t} - 1)^2 \right] \leq nT.$$

Combining inequalities, we have  $R_T \leq \frac{\log n}{\eta} + \frac{\eta nT}{2}$ .

When  $\eta = \sqrt{2nT \cdot \log n}$ , we have  $R_T \leq \sqrt{2nT \cdot \log n}$ .

## Variation of Loss

Let  $\hat{y}_{i,t} = 1 - \hat{v}_{i,t}$ . We have

$$p_t(i) \cdot \hat{y}_{i,t} = p_t(i) \cdot \frac{(1 - v_{i,t}) \cdot \mathbf{1}(i_t^* = i)}{p_t(i)} = (1 - v_{i,t}) \cdot \mathbf{1}(i_t^* = i) \leq 1.$$

Therefore, since  $\hat{y}_{i,t}$  is unbiased,

$$\mathbf{E} \left[ \sum_{t \in [T]} \sum_{i \in [n]} p_t(i) \cdot \hat{y}_{i,t}^2 \right] \leq \mathbf{E} \left[ \sum_{t \in [T]} \sum_{i \in [n]} \hat{y}_{i,t} \right] = \sum_{t \in [T]} \sum_{i \in [n]} y_{i,t} \leq nT.$$

# Swap Regret

Swap Regret:

$$\text{SR}_T = \max_{\pi: A \rightarrow A} \sum_{t \in T} v_{\pi(i_t^*), t} - \sum_{t \in T} v_{i_t^*, t}.$$

# Swap Regret

Swap Regret:

$$\text{SR}_T = \max_{\pi: A \rightarrow A} \sum_{t \in T} v_{\pi(i_t^*), t} - \sum_{t \in T} v_{i_t^*, t}.$$

Note that the (external) regret can be viewed as swap regret under the restriction that  $\pi(i) = \pi(i')$  for any  $i, i'$ .

# No Swap Regret

## Theorem (Blum and Mansour '07)

*When there are  $n$  actions and  $T$  periods, there is an algorithm that achieves swap regret at most  $O(n\sqrt{nT\log n})$ .*

Idea is similar to the reduction for expert learning.

# No Swap Regret

## Theorem (Blum and Mansour '07)

*When there are  $n$  actions and  $T$  periods, there is an algorithm that achieves swap regret at most  $O(n\sqrt{nT\log n})$ .*

Idea is similar to the reduction for expert learning.

**Subtle difference:** the aggregate distribution over arms is not the same as the individual algorithm generated

- from the perspective of each algorithm  $\mathcal{A}_i$ , the observed arm does not follow the distribution recommended by the algorithm.



# No Swap Regret

## Theorem (Blum and Mansour '07)

*When there are  $n$  actions and  $T$  periods, there is an algorithm that achieves swap regret at most  $O(n\sqrt{nT\log n})$ .*

Idea is similar to the reduction for expert learning.

**Subtle difference:** the aggregate distribution over arms is not the same as the individual algorithm generated

- from the perspective of each algorithm  $\mathcal{A}_i$ , the observed arm does not follow the distribution recommended by the algorithm.

Further adjust the feedback reward according to the aggregate distribution over arms for unbiased estimations within each algorithm  $\mathcal{A}_i$ .