# Correlated Equilibrium and Coarse Correlated Equilibrium

Yingkai Li

EC4501/EC4501HM

## Complete Information Game

A static game with complete information is denoted as  $\Gamma = (N, (A_i)_{i \in N}, (u_i)_{i \in N})$ 

- $\bullet$  N is the set of players;
- $A_i$  is the set of player i's actions;
- $u_i: A \to \mathbb{R}$  is player i's payoff function (where  $A = \times_{i \in N} A_i$ ).

### Complete Information Game

A static game with complete information is denoted as  $\Gamma = (N, (A_i)_{i \in N}, (u_i)_{i \in N})$ 

- $\bullet$  N is the set of players;
- $A_i$  is the set of player i's actions;
- $u_i:A\to\mathbb{R}$  is player i's payoff function (where  $A=\times_{i\in N}A_i$ ).

In game  $\Gamma$ , a (mixed) strategy of player i is denoted by  $\sigma_i \in \Delta(A_i)$ .

#### Definition

A strategy profile  $\sigma \in \Delta(A)$  is a correlated equilibrium if for any player i and any action  $a_i$  in the support of  $\sigma$ , we have

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i}) \mid a_i] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i}) \mid a_i], \quad \forall a_i' \in A_i.$$

### Definition

A strategy profile  $\sigma \in \Delta(A)$  is a correlated equilibrium if for any player i and any action  $a_i$  in the support of  $\sigma$ , we have

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i}) \mid a_i] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i}) \mid a_i], \quad \forall a_i' \in A_i.$$

Example: coordination game

	movie (M)	concert (C)
movie (M)	2,1	0,0
concert (C)	0,0	1,2

#### **Definition**

A strategy profile  $\sigma \in \Delta(A)$  is a correlated equilibrium if for any player i and any action  $a_i$  in the support of  $\sigma$ , we have

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i}) \mid a_i] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i}) \mid a_i], \quad \forall a_i' \in A_i.$$

### Example: coordination game

	movie (M)	concert (C)
movie (M)	2,1	0,0
concert (C)	0,0	1,2

### Examples of correlated equilibria:

- (MM) or (CC);
- with probability  $\frac{1}{2}$  (MM) and with probability  $\frac{1}{2}$  (CC).
- with probability  $\frac{1}{3}$  (MM), with probability  $\frac{1}{3}$  (MC), and with probability  $\frac{1}{3}$  (CC).

#### Theorem

If  $\sigma \in \Delta(A)$  is a Nash equilibrium, then  $\sigma$  must also be a correlated equilibrium.

#### Theorem

If  $\sigma \in \Delta(A)$  is a Nash equilibrium, then  $\sigma$  must also be a correlated equilibrium.

In Nash equilibrium, agents' strategies are independent.

• the requirement that

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i}) \mid a_i] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i}) \mid a_i], \quad \forall a_i' \in A_i$$

is the same as the condition for Nash equilibrium as the distribution over  $a_{-i}$  is the same conditional on any  $a_i$ .

### Coarse Correlated Equilibrium

#### Definition

A strategy profile  $\sigma \in \Delta(A)$  is a coarse correlated equilibrium if for any player i, we have

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i})] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i})], \quad \forall a_i' \in A_i.$$

## Coarse Correlated Equilibrium

#### Definition

A strategy profile  $\sigma \in \Delta(A)$  is a coarse correlated equilibrium if for any player i, we have

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i})] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i})], \quad \forall a_i' \in A_i.$$

#### Theorem

If  $\sigma \in \Delta(A)$  is a correlated equilibrium, then  $\sigma$  must also be a coarse correlated equilibrium.

## Coarse Correlated Equilibrium

#### Definition

A strategy profile  $\sigma \in \Delta(A)$  is a coarse correlated equilibrium if for any player i, we have

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i})] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i})], \quad \forall a_i' \in A_i.$$

#### Theorem

If  $\sigma \in \Delta(A)$  is a correlated equilibrium, then  $\sigma$  must also be a coarse correlated equilibrium.

Taking expectation over  $a_i$  for

$$\mathbf{E}_{\sigma}[u_i(a_i, a_{-i}) \mid a_i] \ge \mathbf{E}_{\sigma}[u_i(a_i', a_{-i}) \mid a_i], \quad \forall a_i' \in A_i.$$

### Learning in Games

Given a complete information game  $\Gamma$ , instead of considering equilibrium strategies, suppose all agents use learning algorithms for making decisions.

### Learning in Games

Given a complete information game  $\Gamma$ , instead of considering equilibrium strategies, suppose all agents use learning algorithms for making decisions.

Model as an adversarial bandit / expert learning from the perspective of each agent i':

- set of arms  $A_i$ ;
- realized payoff  $u_i(a_i^t, a_{-i}^t)$  for any period  $t \leq T$ .

## Convergence Under No-Regret

### Theorem

Given a complete information game  $\Gamma$ , if all agents adopt no-regret learning algorithms, the empirical action profile converges to the coarse correlated equilibrium when the time horizon  $T \to \infty$ .

## Convergence Under No-Regret

#### Theorem

Given a complete information game  $\Gamma$ , if all agents adopt no-regret learning algorithms, the empirical action profile converges to the coarse correlated equilibrium when the time horizon  $T \to \infty$ .

From the perspective of each agent i, treating the action profile of other agents as given, no-regret requires that

$$\frac{1}{T} \sum_{t \in [T]} u_i(a_{i,t}, a_{-i,t}) \ge \frac{1}{T} \sum_{t \in [T]} u_i(a_i, a_{-i,t}) - o(1), \quad \forall a_i \in A_i,$$

coinciding with the requirements for coarse correlated equilibrium.

# Convergence Under No-Swap-Regret

#### Theorem

Given a complete information game  $\Gamma$ , if all agents adopt no-swap-regret learning algorithms, the empirical action profile converges to the correlated equilibrium when the time horizon  $T \to \infty$ .

# Convergence Under No-Swap-Regret

#### Theorem

Given a complete information game  $\Gamma$ , if all agents adopt no-swap-regret learning algorithms, the empirical action profile converges to the correlated equilibrium when the time horizon  $T \to \infty$ .

From the perspective of each agent i, treating the action profile of other agents as given, no-swap-regret requires that

$$\frac{1}{T} \sum_{t \in [T]} u_i(a_{i,t}, a_{-i,t}) \ge \frac{1}{T} \sum_{t \in [T]} u_i(\pi_i(a_i), a_{-i,t}) - o(1), \quad \forall \pi_i : A_i \to A_i,$$

coinciding with the requirements for correlated equilibrium.

### Convergence

Not all correlated equilibria or coarse correlated equilibria are reachable under natural learning algorithms (You may attain those equilibria under bizarre algorithms).

### Convergence

Not all correlated equilibria or coarse correlated equilibria are reachable under natural learning algorithms (You may attain those equilibria under bizarre algorithms).

**Example:** second-price auction, two agents with value  $v_1 > v_2$ , each using Hedge algorithms [Kolumbus and Nisan '22]

- ullet the bid distribution of the high value agent converges to uniform distribution over  $[v_2,v_1]$ ;
- ullet the bid distribution of the low value agent converges to uniform distribution over  $[0,v_2].$