

# Prior Free Mechanism Design

Yingkai Li

EC4501/EC4501HM

# Robust Mechanism Design Frameworks

Let  $\mathbb{M}$  be the set of possible mechanisms (e.g., DSIC mechanisms). For any  $M \in \mathbb{M}$

- $M(v)$  is the performance of mechanism  $M$  given realized value profile  $v$ ;
- $M(F) \triangleq \mathbf{E}_{v \sim F}[M(v)]$ .

# Robust Mechanism Design Frameworks

Let  $\mathbb{M}$  be the set of possible mechanisms (e.g., DSIC mechanisms). For any  $M \in \mathbb{M}$

- $M(v)$  is the performance of mechanism  $M$  given realized value profile  $v$ ;
- $M(F) \triangleq \mathbf{E}_{v \sim F}[M(v)]$ .

## Bayesian Optimal

$$\text{OPT}_F = \operatorname{argmax}_{M \in \mathbb{M}} M(F).$$

# Robust Mechanism Design Frameworks

Let  $\mathbb{M}$  be the set of possible mechanisms (e.g., DSIC mechanisms). For any  $M \in \mathbb{M}$

- $M(v)$  is the performance of mechanism  $M$  given realized value profile  $v$ ;
- $M(F) \triangleq \mathbf{E}_{v \sim F}[M(v)]$ .

## Bayesian Optimal

$$\text{OPT}_F = \operatorname{argmax}_{M \in \mathbb{M}} M(F).$$

## Prior-independent Optimal

$$\beta = \min_{M \in \mathbb{M}} \max_{F \in \mathbb{F}} \frac{\text{OPT}_F(F)}{M(F)}$$

# Robust Mechanism Design Frameworks

Let  $\mathbb{M}$  be the set of possible mechanisms (e.g., DSIC mechanisms). For any  $M \in \mathbb{M}$

- $M(v)$  is the performance of mechanism  $M$  given realized value profile  $v$ ;
- $M(F) \triangleq \mathbf{E}_{v \sim F}[M(v)]$ .

## Bayesian Optimal

$$\text{OPT}_F = \operatorname{argmax}_{M \in \mathbb{M}} M(F).$$

## Prior-independent Optimal

$$\beta = \min_{M \in \mathbb{M}} \max_{F \in \mathbb{F}} \frac{\text{OPT}_F(F)}{M(F)}$$

## Prior-free Optimal (for Benchmark $B$ )

$$\gamma_B = \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

# Prior Free Mechanism Design

## Prior-free Optimal (for Benchmark $B$ )

$$\gamma_B = \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

- relates to worst-case competitive analysis [Sleator and Tarjan '85; Littlestone and Warmuth '94].

# Prior Free Mechanism Design

## Prior-free Optimal (for Benchmark $B$ )

$$\gamma_B = \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

Optimal mechanism depends on the ad hoc benchmark.

# Prior Free Mechanism Design

## Prior-free Optimal (for Benchmark $B$ )

$$\gamma_B = \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

Optimal mechanism depends on the ad hoc benchmark.

**Example:** single-item, two agents,  $v_{(1)} \geq v_{(2)}$ .

- $B(v) = v_{(1)}$ : no mechanism can approximate this benchmark.
- $B(v) = v_{(2)}$ : second-price auction is prior-free optimal.
- $B(v) = k \cdot v_{(2)}$ : randomly markup the second highest value by  $\sqrt{k}$  with probability  $\frac{1}{2}$  achieves a  $2\sqrt{k}$  approximation.



# Digital Auctions

$n$  agents, unlimited supply of items.

# Digital Auctions

$n$  agents, unlimited supply of items.

Optimal single price omniscient auction:

$$B^*(v) = \max_{1 \leq i \leq n} i \cdot v_{(i)}$$

where  $v_{(i)}$  is the  $i$ th highest value.

# Digital Auctions

$n$  agents, unlimited supply of items.

Optimal single price omniscient auction:

$$B^*(v) = \max_{1 \leq i \leq n} i \cdot v_{(i)}$$

where  $v_{(i)}$  is the  $i$ th highest value.

No mechanism can approximate the benchmark of  $B^*$ .

- consider the instance where the highest revenue only comes from the highest value.

# Digital Auctions

Optimal single price omniscient auction with at least two sales: [Goldberg, Hartline, Karlin, Saks and Wright '06]

$$B^{(2)}(v) = \max_{2 \leq i \leq n} i \cdot v_{(i)}.$$

# Digital Auctions

Optimal single price omniscient auction with at least two sales: [Goldberg, Hartline, Karlin, Saks and Wright '06]

$$B^{(2)}(v) = \max_{2 \leq i \leq n} i \cdot v_{(i)}.$$

Exclude the possibility of all revenue contribution comes from a single agent.

# Random Sampling

## ProfitExtract<sub>R</sub>

The Profit Extraction auction (ProfitExtract<sub>R</sub>), given target profit  $R$ , is defined as follows:

- 1 Find the largest  $k$  such that the highest  $k$  bidders' bids are at least  $R/k$ .
- 2 Charge these  $k$  bidders  $R/k$  and reject all others.

ProfitExtract<sub>R</sub> is incentive compatible given any  $R \geq 0$ .

# Random Sampling

## ProfitExtract<sub>R</sub>

The Profit Extraction auction (ProfitExtract<sub>R</sub>), given target profit  $R$ , is defined as follows:

- 1 Find the largest  $k$  such that the highest  $k$  bidders' bids are at least  $R/k$ .
- 2 Charge these  $k$  bidders  $R/k$  and reject all others.

ProfitExtract<sub>R</sub> is incentive compatible given any  $R \geq 0$ .

## RSPE

The Random Sampling Profit Extraction auction (RSPE) works as follows:

- 1 Partition bids uniformly at random into two sets:  $b'$  and  $b''$ .
- 2 Compute  $R'$  and  $R''$  as the optimal single price profits for  $b'$  and  $b''$ , respectively.
- 3 Compute the auction results by running ProfitExtract <sub>$R''$</sub>  on  $b'$  and ProfitExtract <sub>$R'$</sub>  on  $b''$ .

RSPE is incentive compatible.

# Random Sampling

Theorem (Goldberg, Hartline, Karlin, Saks and Wright '06)

*The Random Sampling Profit Extraction auction (RSPE) is a 4-approximation to  $B^{(2)}$ .*



# Random Sampling

Theorem (Goldberg, Hartline, Karlin, Saks and Wright '06)

*The Random Sampling Profit Extraction auction (RSPE) is a 4-approximation to  $B^{(2)}$ .*

Revenue from RSPE is at least  $\min\{R', R''\}$ .

# Random Sampling

Theorem (Goldberg, Hartline, Karlin, Saks and Wright '06)

*The Random Sampling Profit Extraction auction (RSPE) is a 4-approximation to  $B^{(2)}$ .*

Revenue from RSPE is at least  $\min\{R', R''\}$ .

Let  $p \geq 0, k \geq 2$  be the optimal price and number of winners in benchmark  $B^{(2)}$ .

Let  $k'$  be the number of those  $k$  winners in  $b'$  and  $k''$  be the number of those  $k$  winners in  $b''$ .

$$R' \geq p \cdot k' \text{ and } R'' \geq p \cdot k''.$$

# Random Sampling

**Theorem** (Goldberg, Hartline, Karlin, Saks and Wright '06)

*The Random Sampling Profit Extraction auction (RSPE) is a 4-approximation to  $B^{(2)}$ .*

Revenue from RSPE is at least  $\min\{R', R''\}$ .

Let  $p \geq 0, k \geq 2$  be the optimal price and number of winners in benchmark  $B^{(2)}$ .

Let  $k'$  be the number of those  $k$  winners in  $b'$  and  $k''$  be the number of those  $k$  winners in  $b''$ .

$$R' \geq p \cdot k' \text{ and } R'' \geq p \cdot k''.$$

Therefore, for any  $v$ ,

$$\frac{\text{RSPE}(v)}{B^{(2)}(v)} \geq \mathbf{E} \left[ \frac{\min\{k', k''\}}{k} \right] \geq \frac{1}{4}.$$

# Prior-free Optimal Mechanism

Given the benchmark of  $B^{(2)}$ , is RSPE the optimal mechanism?

# Prior-free Optimal Mechanism

Given the benchmark of  $B^{(2)}$ , is RSPE the optimal mechanism? **No.**

There exists a mechanism that guarantees a 2.42-approximation to the optimal [Chen, Gravin and Lu '14].

# Prior-free Optimal Mechanism

Given the benchmark of  $B^{(2)}$ , is RSPE the optimal mechanism? **No.**

There exists a mechanism that guarantees a 2.42-approximation to the optimal [Chen, Gravin and Lu '14].

- non-constructive proof.

# Prior-free Optimal Mechanism

Given the benchmark of  $B^{(2)}$ , is RSPE the optimal mechanism? **No.**

There exists a mechanism that guarantees a 2.42-approximation to the optimal [Chen, Gravin and Lu '14].

- non-constructive proof.

**Question:** is  $B^{(2)}$  the right benchmark for the prior-free model? Is the corresponding optimal mechanism for  $B^{(2)}$  the appropriate mechanism to adopt for such robust environments?

# Benchmark Optimization

**Question:** What makes a good benchmark?



# Benchmark Optimization

**Question:** What makes a good benchmark?

**Goal:** discriminate between good and bad mechanisms [[Hartline and Roughgarden '08](#)].

# Benchmark Optimization

**Question:** What makes a good benchmark?

**Goal:** discriminate between good and bad mechanisms [Hartline and Roughgarden '08].

- **too small:** many mechanisms can approx, doesn't discriminate.
- **too large:** no mechanism can approx, doesn't discriminate.

# Benchmark Optimization

**Question:** What makes a good benchmark?

**Goal:** discriminate between good and bad mechanisms [Hartline and Roughgarden '08].

- **too small:** many mechanisms can approx, doesn't discriminate.
- **too large:** no mechanism can approx, doesn't discriminate.

**Informal Goal:** formalize “too small”, optimize “too large”.

# Normalized Benchmarks

**Intuition:** benchmark must not be too small.

# Normalized Benchmarks

**Intuition:** benchmark must not be too small.

## Definition (Normalized Benchmark)

For distributions  $\mathbb{F}$ , benchmark  $B$  is normalized if  $B(F) \geq \text{OPT}_F(F)$  for all  $F \in \mathbb{F}$ .  $\mathbb{B}(\mathbb{F})$  is family of normalized benchmarks.

E.g., welfare is a normalized benchmark for revenue.

# Normalized Benchmarks

**Intuition:** benchmark must not be too small.

## Definition (Normalized Benchmark)

For distributions  $\mathbb{F}$ , benchmark  $B$  is normalized if  $B(F) \geq \text{OPT}_F(F)$  for all  $F \in \mathbb{F}$ .  $\mathbb{B}(\mathbb{F})$  is family of normalized benchmarks.

E.g., welfare is a normalized benchmark for revenue.

## Theorem (Hartline, Roughgarden '08)

*Prior-free  $\gamma$ -approximation of normalized benchmark for  $\mathbb{F}$   
 $\Rightarrow$  prior-independent  $\gamma$ -approximation for  $\mathbb{F}$ .*

# Normalized Benchmarks

**Intuition:** benchmark must not be too small.

## Definition (Normalized Benchmark)

For distributions  $\mathbb{F}$ , benchmark  $B$  is normalized if  $B(F) \geq \text{OPT}_F(F)$  for all  $F \in \mathbb{F}$ .  $\mathbb{B}(\mathbb{F})$  is family of normalized benchmarks.

E.g., welfare is a normalized benchmark for revenue.

## Theorem (Hartline, Roughgarden '08)

*Prior-free  $\gamma$ -approximation of normalized benchmark for  $\mathbb{F}$   
 $\Rightarrow$  prior-independent  $\gamma$ -approximation for  $\mathbb{F}$ .*

For any  $F \in \mathbb{F}$ ,

$$M(F) \geq \frac{1}{\gamma} \cdot B(F) \geq \frac{1}{\gamma} \cdot \text{OPT}_F(F).$$

# Benchmark Resolution

**Intuition:** benchmark must not be too big.



# Benchmark Resolution

**Intuition:** benchmark must not be too big.

Definition (Benchmark Resolution)

$$\gamma_B = \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}.$$

# Benchmark Resolution

**Intuition:** benchmark must not be too big.

## Definition (Benchmark Resolution)

$$\gamma_B = \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}.$$

- The resolution of welfare is  $\infty$ .
- The resolution of  $B^{(2)}$  in digital auction is 2.42.

# Benchmark Resolution

**Intuition:** benchmark must not be too big.

## Definition (Benchmark Resolution)

$$\gamma_B = \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}.$$

- The resolution of welfare is  $\infty$ .
- The resolution of  $B^{(2)}$  in digital auction is 2.42.

## Benchmark Optimization

Find **normalized benchmark** with **finest resolution**:

$$\gamma = \min_{B \in \mathbb{B}(\mathbb{F})} \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}.$$

# Equivalence Between Prior Independent and Prior Free

## Benchmark Optimization

$$\gamma = \min_{B \in \mathcal{B}(\mathbb{F})} \min_{M \in \mathcal{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

## Prior-independent Optimization

$$\beta = \min_{M \in \mathcal{M}} \max_{F \in \mathbb{F}} \frac{\text{OPT}_F(F)}{M(F)}$$

# Equivalence Between Prior Independent and Prior Free

## Benchmark Optimization

$$\gamma = \min_{B \in \mathcal{B}(\mathbb{F})} \min_{M \in \mathcal{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

## Prior-independent Optimization

$$\beta = \min_{M \in \mathcal{M}} \max_{F \in \mathbb{F}} \frac{\text{OPT}_F(F)}{M(F)}$$

Theorem (Hartline, Johnson and Li '20)

*Benchmark optimization = prior-independent optimization, i.e.,  $\gamma = \beta$*

# Equivalence Between Prior Independent and Prior Free

## Benchmark Optimization

$$\gamma = \min_{B \in \mathcal{B}(\mathbb{F})} \min_{M \in \mathcal{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

## Prior-independent Optimization

$$\beta = \min_{M \in \mathcal{M}} \max_{F \in \mathbb{F}} \frac{\text{OPT}_F(F)}{M(F)}$$

Theorem (Hartline, Johnson and Li '20)

*Benchmark optimization = prior-independent optimization, i.e.,  $\gamma = \beta$*

## Sketch:

- 1 prior-independent opt. program suggests a benchmark and algorithm, best benchmark and algorithm is no worse.
- 2 benchmark program suggests a algorithm that is a prior-independent approximation, optimal prior-independent approximation is no worse.

# Proof of (1)

## Benchmark Optimization

$$\gamma = \min_{B \in \mathbb{B}(\mathbb{F})} \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

## Prior-independent Optimization

$$\beta = \min_{M \in \mathbb{M}} \max_{F \in \mathbb{F}} \frac{\text{OPT}_F(F)}{M(F)}$$

$\gamma \leq \beta$ : prior-independent opt. program suggests a benchmark and algorithm, best benchmark and algorithm is no worse.

- let  $M$  be solution to prior-independent program with objective value  $\beta$
- define scaled-up benchmark:  $B(v) = \beta \cdot M(v)$
- $(M, B)$  are valid for benchmark program with objective  $\beta$
- optimal solution to benchmark program has  $\gamma \leq \beta$ .

## Proof of (2)

### Benchmark Optimization

$$\gamma = \min_{B \in \mathbb{B}(\mathbb{F})} \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}$$

### Prior-independent Optimization

$$\beta = \min_{M \in \mathbb{M}} \max_{F \in \mathbb{F}} \frac{\text{OPT}_F(F)}{M(F)}$$

$\beta \leq \gamma$ : benchmark program suggests a mechanism that is a prior-independent approximation, optimal prior-independent approximation is no worse.

- let  $(M, B)$  be solution to benchmark program with objective value  $\gamma$
- normalization of benchmark  $\Rightarrow M$  is prior-independent  $\gamma$ -approx.
- $M$  is valid solution for prior-independent program with objective  $\gamma$
- optimal solution to prior-independent program has  $\beta \leq \gamma$ .



# Open Questions

## Benchmark Optimization

Find **normalized benchmark** with **finest resolution**:

$$\gamma = \min_{B \in \mathbb{B}(\mathbb{F})} \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}.$$

**Question:** is this the right way for benchmark optimization?

# Open Questions

## Benchmark Optimization

Find **normalized benchmark** with **finest resolution**:

$$\gamma = \min_{B \in \mathbb{B}(\mathbb{F})} \min_{M \in \mathbb{M}} \max_{v \in \mathbb{V}} \frac{B(v)}{M(v)}.$$

**Question:** is this the right way for benchmark optimization?

Its connection to prior-independent analysis indicates that it loses some of desirable robustness properties when adopting the “optimal” benchmark.

- e.g., online learning [[Hartline, Johnson and Li '20](#)].