

Stochastic Signal Processing

Lesson 8 Memoryless and Linear Systems

Weize Sun

More examples from the last week

- 1: if the power spectrum of the stationary process $X(t)$ is $S_X(\omega) = \frac{1}{[1+\omega^2]^2}$, calculate the autocorrelation.

Tips:

$$S_Y(\omega) = \frac{1}{1+\omega^2} \Leftrightarrow \frac{1}{2} e^{-|\tau|} \quad S_X(\omega) = S_Y^2(\omega)$$

$$R_X(\tau) = R_Y(\tau) * R_Y(\tau) = \frac{1}{4} \int_{-\infty}^{\infty} e^{-|z|} e^{-|\tau-z|} dz \text{ (频域的乘对应时域的卷积)}$$

- 2: let $X(t)$ and $Y(t)$ be statistically independent stationary processes, with non-zero means m_X and m_Y . Define $Z(t) = X(t) + Y(t)$, given $S_X(\omega)$, calculate $S_{XY}(\omega)$ and $S_{XZ}(\omega)$.

More examples from the last week

- 1: if the power spectrum of the stationary process $X(t)$ is $S_X(\omega) = \frac{1}{[1+\omega^2]^2}$, calculate the autocorrelation.

Tips:

$$S_Y(\omega) = \frac{1}{1+\omega^2} \Leftrightarrow \frac{1}{2}e^{-|\tau|} \quad S_X(\omega) = S_Y^2(\omega); \quad R_X(\tau) = R_Y(\tau) * R_Y(\tau) = \frac{1}{4} \int_{-\infty}^{\infty} e^{-|z|} e^{-|\tau-z|} dz \text{ (频域的乘对应时域的卷积)}$$

Solution:

When $\tau \geq 0$:

$$\begin{aligned} R_X(\tau) &= \frac{1}{4} \left(\int_{-\infty}^0 e^z e^{-(\tau-z)} dz + \int_0^{\tau} e^{-z} e^{-(\tau-z)} dz + \int_{\tau}^{\infty} e^{-z} e^{\tau-z} dz \right) \\ &= \frac{1}{4} (e^{-\tau} + \tau e^{-\tau}) \end{aligned}$$

注:

$$\begin{aligned} \int_{-\infty}^0 e^z e^{-(\tau-z)} dz &= \int_{-\infty}^0 e^{-\tau} e^{2z} dz = \frac{e^{-\tau}}{2} \int_{-\infty}^0 e^{2z} d2z = \frac{e^{-\tau}}{2} \\ \int_0^{\tau} e^{-z} e^{-(\tau-z)} dz &= \int_0^{\tau} e^{-\tau} dz = \tau e^{-\tau} \\ \int_{\tau}^{\infty} e^{-z} e^{\tau-z} dz &= \frac{e^{\tau}}{2} \int_{\tau}^{\infty} e^{-2z} d2z = -\left(-\frac{e^{-\tau}}{2}\right) = \frac{e^{-\tau}}{2} \end{aligned}$$

More examples from the last week

- 1: if the power spectrum of the stationary process $X(t)$ is $S_X(\omega) = \frac{1}{[1+\omega^2]^2}$, calculate the autocorrelation.

Tips:

$$S_Y(\omega) = \frac{1}{1+\omega^2} \Leftrightarrow \frac{1}{2} e^{-|\tau|} \quad S_X(\omega) = S_Y^2(\omega)$$

$$R_X(\tau) = R_Y(\tau) * R_Y(\tau) = \frac{1}{4} \int_{-\infty}^{\infty} e^{-|z|} e^{-|\tau-z|} dz \text{ (频域的乘对应时域的卷积)}$$

Solution:

When $\tau \geq 0$:

$$\begin{aligned} R_X(\tau) &= \frac{1}{4} \left(\int_{-\infty}^0 e^z e^{-(\tau-z)} dz + \int_0^{\tau} e^{-z} e^{-(\tau-z)} dz + \int_{\tau}^{\infty} e^{-z} e^{\tau-z} dz \right) \\ &= \frac{1}{4} (e^{-\tau} + \tau e^{-\tau}) \end{aligned}$$

When $\tau \leq 0$:

$$R_X(\tau) = \frac{1}{4} (e^{\tau} - \tau e^{\tau})$$

→


$$R_X(\tau) = \frac{1}{4} (e^{-|\tau|} + |\tau| e^{-|\tau|})$$

More examples from the last week

- 2: let $X(t)$ and $Y(t)$ be statistically independent stationary processes, with non-zero means m_X and m_Y . Define $Z(t) = X(t) + Y(t)$, given $S_X(\omega)$, calculate $S_{XY}(\omega)$ and $S_{XZ}(\omega)$.

Solution:

$$\begin{aligned} R_{XY}(t_1, t_2) &= E[X(t_1)Y(t_2)] = E[X(t_1)]E[Y(t_2)] = m_X m_Y \\ &= R_{XY}(\tau) \end{aligned}$$


$$\begin{aligned} S_{XY}(\omega) &= \int_{-\infty}^{\infty} R_{XY}(\tau) e^{-j\omega\tau} d\tau = m_X m_Y \int_{-\infty}^{\infty} e^{-j\omega\tau} d\tau \\ &= 2\pi m_X m_Y \delta(\omega) \end{aligned}$$

$$R_{XZ}(t_1, t_2) = E[\cancel{X}(t_1)Z(t_2)] = E[X(t_1)X(t_2)] + E[X(t_1)Y(t_2)]$$

Memoryless and Linear Systems – Outline

- Introduction
- Memoryless Systems
- Linear Systems
- Differentiators (微分器)(next week)

Introduction

- Given a stochastic process $\mathbf{x}(t)$, we assign according to some rule to each of its samples $\mathbf{x}(t, \zeta_i)$ a function $\mathbf{y}(t, \zeta_i)$. We have thus created another process

$$\mathbf{y}(t) = T[\mathbf{x}(t)]$$


whose samples are the functions $\mathbf{y}(t, \zeta_i)$. ζ_i refers to the state i .

- The process $\mathbf{y}(t)$ so formed can be considered as the **output of a system (transformation) with input process $\mathbf{x}(t)$** .
- The system is completely specified in terms of the operator T , that is, the rule of correspondence between the samples(样本间的对应规则) of the input $\mathbf{x}(t)$ and the output $\mathbf{y}(t)$.

Introduction

$$\mathbf{y}(t) = T[\mathbf{x}(t)]$$

- The system is **deterministic** if it operates only on the variable t treating ζ as a parameter. This means that if two samples $\mathbf{x}(t, \zeta_1)$ and $\mathbf{x}(t, \zeta_2)$ of the input are identical in t , then the corresponding samples $\mathbf{y}(t, \zeta_1)$ and $\mathbf{y}(t, \zeta_2)$ of the output are also identical in t .
- The system is called **stochastic** if T operates on both variables t and ζ . This means that there exist two outcomes ζ_1 and ζ_2 such that $\mathbf{x}(t, \zeta_1) = \mathbf{x}(t, \zeta_2)$ identically in t but $\mathbf{y}(t, \zeta_1) \neq \mathbf{y}(t, \zeta_2)$. These classifications are based on the terminal properties of the system. If the system is specified in terms of physical elements or by an equation, then it is deterministic (stochastic) if the elements or the coefficients of the defining equations are deterministic (stochastic).
- Throughout this book we shall consider only **deterministic systems (确定性系统)**.
- In principle, the statistics of the output of a system can be expressed in terms of the statistics of the input. However, in general this is a complicated problem. We consider next two important special cases: Memoryless Systems and Linear Systems.



Memoryless Systems

- A system is called memoryless if its output is given by

$$\mathbf{y}(t) = g[\mathbf{x}(t)]$$

- where $g(x)$ is a function of x . Thus, at a given time $t = t_1$, the output $\mathbf{y}(t_1)$ depends only on $\mathbf{x}(t_1)$ and not on any other past or future values of $\mathbf{x}(t)$.
- The 1-D pdf $f_y(y; t)$ of $\mathbf{y}(t)$ can be expressed in terms of the corresponding density $f_x(x; t)$ of $\mathbf{x}(t)$ (see lesson 3), and

$$E\{\mathbf{y}(t)\} = \int_{-\infty}^{\infty} g(x) f_x(x; t) dx$$

- Similarly, since $\mathbf{y}(t_1) = g[\mathbf{x}(t_1)]$ and $\mathbf{y}(t_2) = g[\mathbf{x}(t_2)]$, the 2-D pdf $f_y(y_1, y_2; t_1, t_2)$ of $\mathbf{y}(t)$ can be determined in terms of the $f_x(x_1, x_2; t_1, t_2)$ of $\mathbf{x}(t)$ (see lesson 3), and

$$E\{\mathbf{y}(t_1)\mathbf{y}(t_2)\} = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} g(x_1)g(x_2)f_x(x_1, x_2; t_1, t_2)dx_1dx_2$$

Memoryless Systems – Stationary

- Suppose that the input to a memoryless system is an SSS (严格平稳) process $\mathbf{x}(t)$, the resulting output $\mathbf{y}(t)$ is also SSS.
- However, if $\mathbf{x}(t)$ is WSS (广义平稳), $\mathbf{y}(t)$ might not be stationary
 - $\mathbf{y}(t)$ might be WSS
 - $\mathbf{y}(t)$ can be not WSS

Memoryless Systems – Square-law detector

- A square-law detector is a memoryless system whose output equals

$$\mathbf{y}(t) = \mathbf{x}^2(t)$$

- Its 1-D and 2-D pdf can then be determined:

- For 1-D, if $y > 0$, then the system $y = x^2$ has the two solutions $\pm\sqrt{y}$, and

$$x'(y) = \pm \frac{1}{2\sqrt{y}}$$

- \rightarrow

$$f_y(y; t) = \frac{1}{2\sqrt{y}} [f_x(\sqrt{y}; t) + f_x(-\sqrt{y}; t)]$$

- For 2-D, if $y_1 > 0$ and $y_2 > 0$, then the system

$$y_1 = x_1^2; \quad y_2 = x_2^2$$


has the four solutions $(\pm\sqrt{y_1}, \pm\sqrt{y_2})$. Its Jacobian equals $\pm \frac{1}{4\sqrt{y_1 y_2}} \rightarrow$

$$f_y(y_1, y_2; t_1, t_2) = \frac{1}{4\sqrt{y_1 y_2}} \sum f_x(\pm\sqrt{y_1}, \pm\sqrt{y_2}; t_1, t_2)$$

where the summation has four terms.

Memoryless Systems – Square-law detector

- If $\mathbf{x}(t)$ is SSS, then $f_x(x; t) = f_x(x)$ is independent of t and $f_x(x_1, x_2; t_1, t_2) = f_x(x_1, x_2; \tau)$ depends only on $\tau = t_1 - t_2$. Hence $f_y(y)$ is independent of t and $f_y(y_1, y_2; \tau)$ depends only on $\tau = t_1 - t_2$.
 - Note: $\mathbf{x}(t)$ WSS $\neq \mathbf{y}(t)$ WSS
 - Note that memoryless systems and linear systems are two different things
- Suppose that $\mathbf{x}(t)$ is a normal stationary process with zero mean and autocorrelation $R_x(\tau)$. (For normal process, WSS = SSS), If $\mathbf{y}(t) = \mathbf{x}^2(t)$, then:



Memoryless Systems – Square-law detector

- If $\mathbf{y}(t) = \mathbf{x}^2(t)$, and $\mathbf{x}(t)$ is a normal stationary process:

- $f_x(x)$ is normal with variance $R_x(0)$
- $E\{\mathbf{y}(t)\} = R_x(0)$ and

$$f_y(y) = \frac{1}{\sqrt{2\pi R_x(0)y}} e^{-y/2R_x(0)} U(y) \quad (\text{understanding is OK})$$

- The random variables $\mathbf{x}(t + \tau)$ and $\mathbf{x}(t)$ are jointly normal with zero mean, and

$$\begin{aligned} E\{\mathbf{y}(t + \tau)\mathbf{y}(t)\} &= E\{\mathbf{x}^2(t + \tau)\mathbf{x}^2(t)\} \\ &= E\{\mathbf{x}^2(t + \tau)\}E\{\mathbf{x}^2(t)\} + 2E^2\{\mathbf{x}(t + \tau)\mathbf{x}(t)\} \end{aligned}$$

(understanding is OK, see page 183 of text book)

→

$$R_y(\tau) = R_x^2(0) + 2R_x^2(\tau)$$

- Note:

$$E\{\mathbf{y}^2(t)\} = R_y(0) = 3R_x^2(0)$$

$$\sigma_y^2 = 2R_x^2(0)$$

Memoryless Systems – Square-law detector

• Still in some researches / engineering applications

Baidu学术

高级搜索 | 平方率检波

百度一下

订阅

时间

2022以来 (1)

2021以来 (2)

2020以来 (7)

年 - 年 确认

领域

电子科学与技术 (56)

仪器科学与技术 (35)

地质资源与地... (34)

+

核心

中国科技核心... (94)

北大核心期刊 (87)

CSCD 索引 (74)

+

获取方式

免费下载 (155)

登录查看 (70)

付费下载 (0)

+

关键词

检波器

地震检波器

平方律检波器

+

类型

期刊 x

作者

刘兆琦

找到202条相关结果

按相关性

基于平方律检波的二相编码信号分段相关-视频积累方法研究

分析了载波多普勒下基于平方律检波的二相编码信号的分段相关-视频积累检测方法,推导了处理损耗公式,采用最大处理损耗最小化准则,分析了总积累时间给定和检测性...

朱祥维, 王飞雪 - 《电子学报》 - 被引量: 17 - 2005年

来源: 维普网 / 维普网 / 万方 / 知网 / 万方

收藏 引用 批量引用

Ka波段宽带、大动态平方律检波器的研制

介绍了一种宽带、大动态平方律检波器的电路设计,分析了宽带、大动态检波电路的工作原理,通过理论计算和模拟仿真得出,当射频输入源阻抗约是检波电路二极管动态电阻...

方勇, 黄建, 甘体国 - 《微波学报》 - 被引量: 8 - 2009年

来源: 维普网 / 维普网 / 万方 / 知网 / 《微波学报》官网

收藏 引用 批量引用

分式平方律检波电路

分式平方律检波电路:微波辐射计检波电路分式平方律低势垒肖特基检波二极管温度补偿电路赵航中国科学院东北地理与农业生态研究所科技开发动态

赵航 - 《科技开发动态》 - 被引量: 0 - 2004年

来源: 维普网 / 维普网 / 万方 / 掌桥科研 / doc.paperpass.com

收藏 引用 批量引用

小信号平方率检波原理在民航通导设备中的应用

射频信号是民航空管通信导航监视各类设备板件中不可或缺的信号,同时测量射频信号特征也是工程师排除设备故障的必要方法,为便测量更加方便,排故更加准确,本文采用小...

马有存, 康立学 - 《军民两用技术与产品》 - 被引量: 0 - 2017年

来源: 万方 / 维普网 / 维普网 / 万方 / 掌桥科研

Baidu学术

高级搜索 | 平方率检波

百度一下

订阅

时间

2022以来 (0)

2021以来 (1)

2020以来 (5)

年 - 年 确认

领域

电子科学与技术 (35)

信息与通信工程 (15)

仪器科学与技术 (12)

+

核心

北大核心期刊 (0)

SCI索引 (0)

EI索引 (0)

+

获取方式

免费下载 (24)

登录查看 (75)

付费下载 (0)

+

类型

专利 x

作者

李军

曹正军

邹闻中

+

找到121条相关结果

按相关性

[专利] 一种2-18GHz的平方律检波器

本发明公开了一种218GHz的平方律检波器,包括输入匹配网络,检波二极管和低通滤波器,检波二极管一端连接输入匹配网络,另一端连接低通滤波器,肖特基二极管采用Skyworks的P型肖特基低势垒检波二极管SMS7630079LF,检波器工作于零偏置状态,工作频率范围为218G...

李颖, 王晓青 - 被引量: 0 - 2020年

来源: 百度文库 / 掌桥科研 / doc.paperpass.com

收藏 引用 批量引用 文献获取

[专利] 一种射频系统群时延参数的测量方法

通过平方率检波器对具有新的时延的信号进行解调,通过第二射频源向功分器发送第一同步采样时钟信号,通过功分器将来自第二射频源的第一同步采样时钟信号分为两路,所述测量方法利用平方率检波器对调制后的信号进行解调,能避免引入误差,从而提高测量精度,...

陆晨曦, 李宏宇, 李闯, ... - 被引量: 0 - 2014年

来源: 百度文库 / cprs.patentstar.com / 掌桥科研

收藏 引用 批量引用 文献获取

[专利] 调幅信号包络检波方法和系统

获得第三信号,将第一延时信号进行平方运算,获得第一平方运算信号,将第三信号进行平方运算,获得第二平方运算信号,将第一平方运算信号与第二平方运算信号和并开方运算,获得调幅信号的包络信号,本方案能够避免检波过程中产生的包络信号失真,有效提高包络...

李军, 旁志强, 万文军 - 被引量: 0

来源: 百度文库 / cprs.patentstar.com / 掌桥科研

收藏 引用 批量引用 文献获取

Linear Systems

- If for any $\mathbf{a}_1, \mathbf{a}_2, \mathbf{x}_1(t), \mathbf{x}_2(t)$, where \mathbf{a}_1 and \mathbf{a}_2 are random variables, $\mathbf{y}(t)$ is the output of a system with input $\mathbf{x}(t)$, we have
$$L[\mathbf{a}_1\mathbf{x}_1(t) + \mathbf{a}_2\mathbf{x}_2(t)] = \mathbf{a}_1L[\mathbf{x}_1(t)] + \mathbf{a}_2L[\mathbf{x}_2(t)]$$
- The $\mathbf{y}(t) = L[\mathbf{x}(t)]$ is a **Linear System**. Usually, we call it **Linear System L** . Note that the system is deterministic and it operates only on the variable t .
- Here we do not consider any input with initial conditions. (我们这里不讨论带初始响应的系统)
- A system L is called **time-invariant** if its response to $\mathbf{x}(t + c)$ equals $\mathbf{y}(t + c)$.
- In this course we mainly discuss **linear time-invariant systems**.

Linear Systems

- It is well known that **the output of a linear system is a convolution**

$$\mathbf{y}(t) = \mathbf{x}(t) * h(t) = \int_{-\infty}^{\infty} \mathbf{x}(t - \alpha)h(\alpha)d\alpha \quad (8-1)$$

Where $h(t) = L[\delta(t)]$ is its impulse response.

- In the following, when writing $\mathbf{y}(t) = L[\mathbf{x}(t)]$, we refer to the convolution (8-1) in most cases.
- The following observations are immediate consequences of the linearity and time invariance of the system:

- If $\mathbf{x}(t)$ is a normal process, then $\mathbf{y}(t)$ is also a normal process.** This is an extension of the familiar property of linear transformations of normal random variables and can be justified if we approximate the integral in (8-1) by a sum:

$$\mathbf{y}(t_i) \approx \sum_k \mathbf{x}(t_i - \alpha_k)h(\alpha_k)\Delta(\alpha)$$

- If $\mathbf{x}(t)$ is SSS, then $\mathbf{y}(t)$ is also SSS.**
 - Indeed, since $\mathbf{y}(t + c) = L[\mathbf{x}(t + c)]$ for every c , we conclude that if the processes $\mathbf{x}(t)$ and $\mathbf{x}(t + c)$ have the same statistical properties, so do the processes $\mathbf{y}(t)$ and $\mathbf{y}(t + c)$.
- If $\mathbf{x}(t)$ is WSS, the processes $\mathbf{x}(t)$ and $\mathbf{y}(t)$ are jointly WSS.** (本课程一般只讨论稳态情况)

Linear Systems – property

- For any linear system:

$$E\{L[\mathbf{x}(t)]\} = L[E\{\mathbf{x}(t)\}]$$

Also written as

$$\mathbf{m}_y(t) = L[\mathbf{m}_x(t)]$$

- In other words, the expectation of the output $\mathbf{y}(t) = L[\mathbf{x}(t)]$ equals the response of the system to the mean $E\{\mathbf{x}(t)\}$ of the input, as

$$E\{\mathbf{y}(t)\} = \int_{-\infty}^{\infty} E\{\mathbf{x}(t - \alpha)\}h(\alpha)d\alpha = \mathbf{m}_x(t) * h(t)$$

Linear Systems – output autocorrelation

- We wish to express the autocorrelation $R_{yy}(t_1, t_2)$ of the output $\mathbf{y}(t)$ of a linear system in terms of the autocorrelation $R_{xx}(t_1, t_2)$ of the input $\mathbf{x}(t)$.
- In fact, it is easier to find first the cross-correlation $R_{xy}(t_1, t_2)$ between $\mathbf{x}(t)$ and $\mathbf{y}(t)$:

$$R_{xy}(t_1, t_2) = L_2[R_{xx}(t_1, t_2)] \quad (8-2)$$

Where L_2 means that the system operates on the variable t_2 when treating t_1 as a parameter, this means:

$$R_{xy}(t_1, t_2) = \int_{-\infty}^{\infty} R_{xx}(t_1, t_2 - \alpha)h(\alpha)d\alpha$$

- Then

$$R_{yy}(t_1, t_2) = L_1[R_{xy}(t_1, t_2)] \quad (8-3)$$

Where the system operates on t_1 :

$$R_{yy}(t_1, t_2) = \int_{-\infty}^{\infty} R_{xy}(t_1 - \alpha, t_2)h(\alpha)d\alpha$$

- 注意，对 $Y(t)$ 的autocorrelation，可以写作 R_{yy} 或者 R_y ，也可以写作 R_Y ，也有写作 R_{YY} 的

Linear Systems – output autocorrelation

Proof:

- If for any $\mathbf{a}_1, \mathbf{a}_2, \mathbf{x}_1(t), \mathbf{x}_2(t)$, where \mathbf{a}_1 and \mathbf{a}_2 are random variables, $\mathbf{y}(t)$ is the output of a linear system with input $\mathbf{x}(t)$, we have

$$L[\mathbf{a}_1\mathbf{x}_1(t) + \mathbf{a}_2\mathbf{x}_2(t)] = \mathbf{a}_1L[\mathbf{x}_1(t)] + \mathbf{a}_2L[\mathbf{x}_2(t)]$$

- Multiplying $\mathbf{y}(t) = L_t[\mathbf{x}(t)]$ by $\mathbf{x}(t_1)$ gives

$$\mathbf{x}(t_1)\mathbf{y}(t) = \mathbf{x}(t_1)L_t[\mathbf{x}(t)]$$

Note that, the $\mathbf{x}(t)$ and $\mathbf{y}(t)$ are the input & output process, but $\mathbf{x}(t_1)$, the sample of the process $\mathbf{x}(t)$ at time t_1 , as it already be sampled, is a constant! \rightarrow

$$\mathbf{x}(t_1)\mathbf{y}(t) = L_t[\mathbf{x}(t_1)\mathbf{x}(t)]$$

- where L_t means that the system operates on t . Hence

$$E\{\mathbf{x}(t_1)\mathbf{y}(t)\} = L_t[E\{\mathbf{x}(t_1)\mathbf{x}(t)\}]$$

- Setting $t = t_2$ gives (8-2). The proof of (8-3) is similar: We multiply $\mathbf{y}(t) = L_t[\mathbf{x}(t)]$ by $\mathbf{y}(t_2)$ and yields

$$E\{\mathbf{y}(t)\mathbf{y}(t_2)\} = L_t[E\{\mathbf{x}(t)\mathbf{y}(t_2)\}]$$

$$E\{L[\mathbf{x}(t)]\} = L[E\{\mathbf{x}(t)\}]$$

- and (8-3) follows with $t = t_1$

Linear Systems – output autocorrelation

Conclusion:

$$R_{XY}(t_1, t_2) = L_{t_2}[R_{XX}(t_1, t_2)] = L_{t_2}[R_X(t_1, t_2)], \text{ or } R_{XY}(t_1, t_2) = R_X(t_1, t_2) * h(t_2)$$

$$R_{YX}(t_1, t_2) = L_{t_1}[R_{XX}(t_1, t_2)] = L_{t_1}[R_X(t_1, t_2)], \text{ or } R_{YX}(t_1, t_2) = R_X(t_1, t_2) * h(t_1)$$


$$R_Y(t_1, t_2) = R_{YY}(t_1, t_2) = L_{t_1}[R_{XY}(t_1, t_2)] = L_{t_1}L_{t_2}[R_X(t_1, t_2)]$$

Or says:

$$R_{YY}(t_1, t_2) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} R_{XX}(t_1 - \alpha, t_2 - \beta) h(\alpha) h(\beta) d\alpha d\beta$$

Which is:

$$R_{YY}(t_1, t_2) = R_{XX}(t_1, t_2) * h(t_1) * h(t_2)$$



Linear Systems – output autocorrelation & autocovariance

- The autocovariance $C_{yy}(t_1, t_2)$ of $\mathbf{y}(t)$ is the autocorrelation of the process

$$\tilde{\mathbf{y}}(t) = L[\tilde{\mathbf{x}}(t)] = L[\mathbf{x}(t) - \mathbf{m}_x(t)] = \mathbf{y}(t) - \mathbf{m}_y(t)$$

- Therefore:

$$C_{xy}(t_1, t_2) = C_{xx}(t_1, t_2) * h(t_2); \quad C_{yx}(t_1, t_2) = C_{xx}(t_1, t_2) * h(t_1)$$

$$C_{yy}(t_1, t_2) = C_{xy}(t_1, t_2) * h(t_1)$$

- For complex processes, following the same approach we get:

$$R_{xy}(t_1, t_2) = R_{xx}(t_1, t_2) * h^*(t_2); \quad R_{yx}(t_1, t_2) = R_{xx}(t_1, t_2) * h(t_1)$$

$$R_{yy}(t_1, t_2) = R_{xx}(t_1, t_2) * h(t_1) * h^*(t_2)$$

$$C_{xy}(t_1, t_2) = C_{xx}(t_1, t_2) * h^*(t_2); \quad C_{yx}(t_1, t_2) = C_{xx}(t_1, t_2) * h(t_1)$$

$$C_{yy}(t_1, t_2) = C_{xx}(t_1, t_2) * h(t_1) * h^*(t_2)$$

Linear Systems – output autocorrelation*

An example requires understanding only (not in exam): A **real world stationary process** $v(t)$ with autocorrelation $R_{vv}(\tau) = q\delta(\tau)$ (white noise) is applied at $t = 0$ to a linear system with

$$h(t) = e^{-ct}U(t)$$

Then, for $0 < t_1 < t_2$, the **full autocorrelation** of the resulting output $y(t)$ equals

$$R_{yy}(t_1, t_2) = \frac{q}{2c} (1 - e^{-2ct_1}) e^{-c(t_2 - t_1)}$$

Proof: we assume that the input to the system is the **real world** process

$$\mathbf{x}(t) = v(t)U(t)$$

- Physical meaning of $h(t) = e^{-ct}U(t)$: at time 0, the system starts, for example, you power on the receiver at time 0 (在时间为0的时候打开接收机), then the receiver starts working. In this case, for any time before time 0, which is when the receiver is not turned on, there are no response of the system. (在系统开机之前, 系统不会有任何响应)
- Physical meaning of $\mathbf{x}(t) = v(t)U(t)$: at time 0, as the system starts, the system begin to receive input $v(t)$. Although the process $v(t)$ exists before time 0, for example, you speak (there is signal before time 0) before you turn on a microphone, the system cannot only receive the signal after it is turned on. (在系统开机之前, 系统不可能可以接收到任何信号, 即使该信号存在)

注: 这里讨论的是一个实际系统对应的例子, 但是, 在考试中, 我们不会涉及如此复杂的问题

*: 本页ppt理解即可

Linear Systems – output autocorrelation*

An example requires understanding only (not in exam): A **real world stationary process** $v(t)$ with autocorrelation $R_{vv}(\tau) = q\delta(\tau)$ (white noise) is applied at $t = 0$ to a linear system with

$$h(t) = e^{-ct}U(t)$$

Then, for $0 < t_1 < t_2$, the **full autocorrelation** of the resulting output $y(t)$ equals

$$R_{yy}(t_1, t_2) = \frac{q}{2c} (1 - e^{-2ct_1}) e^{-c(t_2 - t_1)}$$

Proof: we assume that the input to the system is the **real world** process

$$\mathbf{x}(t) = v(t)U(t)$$

- With this assumption, all correlations are 0 if $t_1 < 0$ or $t_2 < 0$.

- For $t_1 > 0$ and $t_2 > 0$,

$$R_{xx}(t_1, t_2) = E\{v(t_1)v(t_2)\} = q\delta(t_1 - t_2)$$


- Then $R_{xy}(t_1, t_2)$ equals the response of the system to $q\delta(t_1 - t_2)$ considered as a function of t_2 . Since $\delta(t_1 - t_2) = \delta(t_2 - t_1)$ and $L[\delta(t_2 - t_1)] = h(t_2 - t_1)$ (time invariance), we conclude that

$$R_{xy}(t_1, t_2) = qh(t_2 - t_1) = qe^{-c(t_2 - t_1)}U(t_2 - t_1)U(t_1)^{[1]}$$

[1]: 这里加的 $U(t_1)$ 是因为, 只有在 $t_1 > 0$ 时, $R_{xy}(t_1, t_2)$ 才会有取值, 反之是0! 对此的刻画就是加一个在 t_1 时刻的阶跃函数 $U(t_1)$

* : 本页ppt理解即可

Linear Systems – output autocorrelation*



注：此图说明的是，当 $0 < t_1 < t_2$ 时， $R_{xy}(t_1, t_2)$ 如左图所示；为了求 $R_{yy}(t_1, t_2)$ ，需要对 $R_{xy}(t_1, t_2)$ 和 $h(t)$ 做卷积，固定 $h(t)$ ，将 $R_{xy}(t_1, t_2)$ 左右翻转，因为 $0 < t_1 < t_2$ ，其尾部的一部分去到了负数域，被截断了（在真实应用中，不可能能读取到开机前的任何信息），变成了右图，然后以右图去和 $h(t)$ 做卷积

- The above figure shows $R_{xy}(t_1, t_2)$ as a function of t_1 and t_2 . As $R_{yy}(t_1, t_2) = R_{xy}(t_1, t_2) * h(t_1)$, we obtain

$$R_{yy}(t_1, t_2) = q \int_0^{t_1} e^{c(t_1 - \alpha - t_2)} e^{-c\alpha} d\alpha = q e^{c(t_1 - t_2)} \int_0^{t_1} e^{-2c\alpha} d\alpha$$


Which is $R_{yy}(t_1, t_2) = \frac{q}{2c} (1 - e^{-2ct_1}) e^{-c(t_2 - t_1)}$ (for $0 < t_1 < t_2$).

- Note that

$$E\{\mathbf{y}^2(t)\} = R_{yy}(t, t) = \frac{q}{2c} (1 - e^{-2ct}) = q \int_0^t h^2(\alpha) d\alpha$$

*：本页ppt理解即可

Linear Systems – output autocorrelation



注：此图说明的是，当 $0 < t_1 < t_2$ 时， $R_{xy}(t_1, t_2)$ 如左图所示；为了求 $R_{yy}(t_1, t_2)$ ，需要对 $R_{xy}(t_1, t_2)$ 和 $h(t)$ 做卷积，固定 $h(t)$ ，将 $R_{xy}(t_1, t_2)$ 左右翻转，因为 $0 < t_1 < t_2$ ，其尾部的一部分去到了负数域，被截断了（在真实应用中，不可能能读取到开机前的任何信息），变成了右图，然后以右图去和 $h(t)$ 做卷积

- The above figure shows $R_{xy}(t_1, t_2)$ as a function of t_1 and t_2 . As $R_{yy}(t_1, t_2) = R_{xy}(t_1, t_2) * h(t_1)$, we obtain

$$R_{yy}(t_1, t_2) = q \int_0^{t_1} e^{c(t_1 - \alpha - t_2)} e^{-c\alpha} d\alpha = q e^{c(t_1 - t_2)} \int_0^{t_1} e^{-2c\alpha} d\alpha$$

Which is $R_{yy}(t_1, t_2) = \frac{q}{2c} (1 - e^{-2ct_1}) e^{-c(t_2 - t_1)}$ (for $0 < t_1 < t_2$).

- It is not stationary! Related to time t_1 ! The input is stationary but the output is not!**
- This is called Transient analysis (瞬态分析) of stochastic processes, is not required in exam.
- In exam, we consider only the Steady state analysis (稳态分析) of stochastic processes, in this case

If input is stationary, output is stationary, for Steady state analysis (稳态分析) only

- 此后，除非特别说明，否则问的都是稳态分析

Linear Systems – output autocorrelation

- In exam, we consider only the Steady state analysis (稳态分析) of stochastic processes, in this case

If input is stationary, output is stationary, for Steady state analysis (稳态分析) only

Properties when WSS ($\tau = t_1 - t_2$): (real valued case)

$$R_{XY}(t_1, t_2) = R_X(t_1, t_2) * h(t_2) \quad \rightarrow \quad R_{XY}(\tau) = R_X(\tau) * h(-\tau)$$

$$R_{YX}(t_1, t_2) = R_X(t_1, t_2) * h(t_1) \quad \rightarrow \quad R_{YX}(\tau) = R_X(\tau) * h(\tau)$$

$$R_Y(t_1, t_2) = R_X(t_1, t_2) * h(t_1) * h(t_2) \quad \rightarrow \quad R_Y(\tau) = R_X(\tau) * h(\tau) * h(-\tau)$$

$$R_Y(t_1, t_2) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} R_X(t_1 - \alpha, t_2 - \beta) h(\alpha) h(\beta) d\alpha d\beta$$

$$R_Y(\tau) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} R_X(\tau + \alpha - \beta) h(\alpha) h(\beta) d\alpha d\beta$$

- 此后，除非特别说明，否则问的都是稳态分析
- 注意，对 $Y(t)$ 的autocorrelation，可以写作 R_{yy} 或者 R_y ，也可以写作 R_Y ，也有写作 R_{YY} 的

Linear Systems – output autocorrelation

- In exam, we consider only the Steady state analysis (稳态分析) of stochastic processes, in this case

If input is stationary, output is stationary, for Steady state analysis (稳态分析) only

Properties when WSS ($\tau = t_1 - t_2$): (complex valued case)

$$R_{XY}(t_1, t_2) = R_X(t_1, t_2) * h^*(t_2) \quad \rightarrow \quad R_{XY}(\tau) = R_X(\tau) * h^*(-\tau)$$

$$R_{YX}(t_1, t_2) = R_X(t_1, t_2) * h(t_1) \quad \rightarrow \quad R_{YX}(\tau) = R_X(\tau) * h(\tau)$$

$$R_Y(t_1, t_2) = R_X(t_1, t_2) * h(t_1) * h^*(t_2) \quad \rightarrow \quad R_Y(\tau) = R_X(\tau) * h(\tau) * h^*(-\tau)$$

$$R_Y(t_1, t_2) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} R_X(t_1 - \alpha, t_2 - \beta) h(\alpha) h^*(\beta) d\alpha d\beta$$

$$R_Y(\tau) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} R_X(\tau + \alpha - \beta) h(\alpha) h^*(\beta) d\alpha d\beta$$

- 此后，除非特别说明，否则问的都是稳态分析
- 注意，对 $Y(t)$ 的autocorrelation，可以写作 R_{yy} 或者 R_y ，也可以写作 R_Y ，也有写作 R_{YY} 的

Linear Systems – output autocorrelation

- Example 1: A stationary process $\mathbf{x}(t)$ with autocorrelation $R_{\mathbf{x}}(\tau) = q\delta(\tau)$ (white noise) is applied ~~at $t=0$~~ to a linear system with

$$h(t) = e^{-ct}U(t)$$

Please calculate the autocorrelation of the output, or says, calculate $R_{yy}(\tau)$ where $\tau = t_1 - t_2$.

Hint: in this case, the input is $\mathbf{x}(t)$! Not $\mathbf{x}(t)U(t)$!

Linear Systems – output autocorrelation

Previous example

An example requires understanding only (not in exam): A real world stationary process $v(t)$ with autocorrelation $R_{vv}(\tau) = q\delta(\tau)$ (white noise) is applied at $t = 0$ to a linear system with

$$h(t) = e^{-ct}U(t)$$

Then, for $0 < t_1 < t_2$, the full autocorrelation of the resulting output $\mathbf{y}(t)$ equals

$$R_{yy}(t_1, t_2) = \frac{q}{2c} (1 - e^{-2ct_1}) e^{-c|t_2 - t_1|}$$

Proof: we assume that the input to the system is the real world process

$$\mathbf{x}(t) = v(t)U(t)$$

- With this assumption, all correlations are 0 if $t_1 < 0$ or $t_2 < 0$.

Linear Systems – output autocorrelation

- Example 1: A stationary process $\mathbf{x}(t)$ with autocorrelation $R_X(\tau) = q\delta(\tau)$ (white noise) is applied ~~at $t=0$~~ to a linear system with

$$h(t) = e^{-ct}U(t)$$

Please calculate the autocorrelation of the output, or says, calculate $R_Y(\tau)$ where $\tau = t_1 - t_2$.

Hint: in this case, the input is $\mathbf{x}(t)$! Not $\mathbf{x}(t)U(t)$!

Solution: 积分下限从0开始, 是因为冲激响应有一个阶跃函数 $U(t)$

When $\tau \geq 0$:

$R_X(\tau + \alpha - \beta)$ 仅在 $\tau + \alpha = \beta$ 时 $\neq 0$

$$R_Y(\tau) = \int_0^{+\infty} \int_0^{+\infty} h(\alpha)h(\beta)R_X(\tau + \alpha - \beta)d\beta d\alpha = q \int_0^{+\infty} h(\alpha)h(\tau + \alpha)d\alpha$$

$$= q \int_0^{+\infty} e^{-c\alpha}U(\alpha)e^{-c(\tau+\alpha)}U(\tau + \alpha)d\alpha$$

$$= qe^{-c\tau} \int_0^{+\infty} e^{-2c\alpha}d\alpha = qe^{-\alpha\tau} \frac{1}{2c} \int_0^{+\infty} e^{-2c\alpha}d2c\alpha$$

$$= \frac{q}{2c} e^{-c\tau}$$

因为 $\tau \geq 0$, 对 $U(\tau + \alpha)$, α 的取值范围是 $[-\tau, \infty]$; $U(\alpha)$ 的取值范围是 $[0, \infty]$ 。所以, 整个积分的取值范围是 $[0, \infty]$ 。

Linear Systems – output autocorrelation

- Example 1: A stationary process $\mathbf{x}(t)$ with autocorrelation $R_X(\tau) = q\delta(\tau)$ (white noise) is applied ~~at $t=0$~~ to a linear system with

$$h(t) = e^{-ct}U(t)$$

Please calculate the autocorrelation of the output, or says, calculate $R_Y(\tau)$ where $\tau = t_1 - t_2$.

Hint: in this case, the input is $\mathbf{x}(t)$! Not $\mathbf{x}(t)U(t)$!

Solution:

When $\tau \geq 0$:

$$R_Y(\tau) = \frac{q}{2c} e^{-c\tau}$$

As autocorrelation is an even function, when $\tau < 0$

$$R_Y(\tau) = \frac{q}{2c} e^{c\tau}$$

Thus, generally:

$$R_Y(\tau) = \frac{q}{2c} e^{-c|\tau|}$$

Linear Systems – output autocorrelation

- Example 2: A stationary process $\mathbf{x}(t)$ with autocorrelation $R_X(\tau) = \sigma_X^2 e^{-\beta|\tau|}$ (white noise) is applied to a linear system with

$$h(t) = \begin{cases} \alpha e^{-\alpha t}, & t \geq 0 \\ 0, & t < 0 \end{cases}$$

Please calculate the autocorrelation of the output, or says, calculate $R_Y(\tau)$ where $\tau = t_1 - t_2$.

Hint:

$$\begin{aligned} R_Y(\tau) &= \int_0^\infty \int_0^\infty R_X(\tau + u - v) h(u) h(v) du dv = \alpha^2 \sigma_X^2 \int_0^\infty \int_0^\infty e^{-\beta|\tau+u-v|} e^{-\alpha(u+v)} du dv \\ &= \alpha^2 \sigma_X^2 \int_0^\infty \int_0^{\tau+u} e^{-\beta(\tau+u-v)} e^{-\alpha(u+v)} dv du + \alpha^2 \sigma_X^2 \int_0^\infty \int_{\tau+u}^\infty e^{-\beta(v-\tau-u)} e^{-\alpha(u+v)} dv du \end{aligned}$$

$$\begin{aligned} \int_0^\infty \int_0^{\tau+u} e^{-\beta(\tau+u-v)} e^{-\alpha(u+v)} dv du &= \frac{e^{-\alpha\tau}}{2\alpha(\beta - \alpha)} - \frac{e^{-\beta\tau}}{\beta^2 - \alpha^2} \\ \int_0^\infty \int_{\tau+u}^\infty e^{-\beta(v-\tau-u)} e^{-\alpha(u+v)} dv du &= \frac{e^{-\alpha\tau}}{2\alpha(\alpha + \beta)} \end{aligned}$$

注意，这里因为题干里面有 α 和 β ，所以在积分的时候，就用 u 和 v 代替了 α 和 β

Linear Systems – output autocorrelation

- Example 2: A **stationary process** $x(t)$ with autocorrelation $R_X(\tau) = \sigma_X^2 e^{-\beta|\tau|}$ (white noise) is applied to a linear system with

$$h(t) = \begin{cases} \alpha e^{-\alpha t}, & t \geq 0 \\ 0, & t < 0 \end{cases}$$

Please calculate the autocorrelation of the output, or says, calculate $R_Y(\tau)$ where $\tau = t_1 - t_2$.


Hint:

Solution:

$$\begin{aligned} R_Y(\tau) &= \int_0^\infty \int_0^\infty R_X(\tau + u - v) h(u) h(v) du dv = \alpha^2 \sigma_X^2 \int_0^\infty \int_0^\infty e^{-\beta|\tau+u-v|} e^{-\alpha(u+v)} du dv \\ &= \alpha^2 \sigma_X^2 \int_0^\infty \int_0^{\tau+u} e^{-\beta(\tau+u-v)} e^{-\alpha(u+v)} dv du + \alpha^2 \sigma_X^2 \int_0^\infty \int_{\tau+u}^\infty e^{-\beta(v-\tau-u)} e^{-\alpha(u+v)} dv du \end{aligned}$$

分段积分的技巧

$$\begin{aligned} \int_0^\infty \int_0^{\tau+u} e^{-\beta(\tau+u-v)} e^{-\alpha(u+v)} dv du &= \frac{e^{-\alpha\tau}}{2\alpha(\beta-\alpha)} - \frac{e^{-\beta\tau}}{\beta^2 - \alpha^2} \\ \int_0^\infty \int_{\tau+u}^\infty e^{-\beta(v-\tau-u)} e^{-\alpha(u+v)} dv du &= \frac{e^{-\alpha\tau}}{2\alpha(\alpha+\beta)} \end{aligned}$$


$$\begin{aligned} R_Y(\tau) &= \alpha^2 \sigma_X^2 \left(\frac{e^{-\alpha\tau}(\alpha+\beta)}{2\alpha(\beta^2 - \alpha^2)} - \frac{2\alpha e^{-\beta\tau}}{2\alpha(\beta^2 - \alpha^2)} + \frac{e^{-\alpha\tau}(\beta-\alpha)}{2\alpha(\beta^2 - \alpha^2)} \right) \\ &= \frac{\alpha \sigma_X^2}{\beta^2 - \alpha^2} (\alpha e^{-\beta\tau} - \beta e^{-\alpha\tau}) \end{aligned}$$

注意，这里因为题干里面有 α 和 β ，所以在积分的时候，就用 u 和 v 代替了 α 和 β

Linear Systems – output autocorrelation

- Example 2: A **stationary process** $x(t)$ with autocorrelation $R_X(\tau) = \sigma_X^2 e^{-\beta|\tau|}$ (white noise) is applied to a linear system with

$$h(t) = \begin{cases} \alpha e^{-\alpha t}, & t \geq 0 \\ 0, & t < 0 \end{cases}$$

Please calculate the autocorrelation of the output, or says, calculate $R_Y(\tau)$ where $\tau = t_1 - t_2$.

Solution:

$$\begin{aligned} R_Y(\tau) &= \alpha^2 \sigma_X^2 \left(\frac{e^{-\alpha\tau}(\alpha + \beta)}{2\alpha(\beta^2 - \alpha^2)} - \frac{2\alpha e^{-\beta\tau}}{2\alpha(\beta^2 - \alpha^2)} + \frac{e^{-\alpha\tau}(\beta - \alpha)}{2\alpha(\beta^2 - \alpha^2)} \right) \\ &= \frac{\alpha \sigma_X^2}{\beta^2 - \alpha^2} (\alpha e^{-\beta\tau} - \beta e^{-\alpha\tau}) \end{aligned}$$

When $\tau < 0$:

$$R_Y(\tau) = \frac{\alpha \sigma_X^2}{\alpha^2 - \beta^2} (\alpha e^{\beta\tau} - \beta e^{\alpha\tau})$$

Therefore:

$$R_Y(\tau) = \frac{\alpha \sigma_X^2}{\alpha^2 - \beta^2} (\alpha e^{-\beta|\tau|} - \beta e^{-\alpha|\tau|})$$

注意，这里因为题干里面有 α 和 β ，所以在积分的时候，就用 u 和 v 代替了 α 和 β

Reading

- This week:
 - Text book: 7.2
 - Red book: 3.1, 3.2.1
- Next week:
 - Text book: 7.3 (part of 'power spectrum together with systems')
 - Red book: 3.2.2, 3.2.3

Experiment

- Experiment 2