

# Assessed Exercise II

## CS5002 Advanced Programming

Dr. Paul Henderson

February 2023

- **Deadline:** 16:30 on 17<sup>th</sup> March 2023
- **Contribution to final course mark:** 25%
- **Solo or Group:** Solo work
- **Anticipated duration:** 3 hours

### Introduction

From the course Moodle page, download the files `CommandRunner.java` and `SlowCalculator.java`. The latter contains a class `SlowCalculator` implementing `Runnable`. Its constructor takes a number  $N$  as input and stores it. Method `run` performs a long, slow calculation on this number, then prints the result. You do *not* need to consider (or even understand) the mathematical details of what is being calculated!

In this exercise, you will write a class implementing the interface `CommandRunner`, that runs certain commands passed as strings. These are inputs from a user, requesting the calculation be performed for particular numbers. The inputs and outputs are read/written by a separate part of the program – you just have to use the passed string, and return a string.

As the calculation is slow, you will run it on background threads, so the user can continue to interact with the system while tasks are running. To take advantage of modern multi-core CPUs, the user may request several calculations be run in parallel. Each calculation will still run on one single thread – your goal is to let the user run multiple calculations in parallel, **not** to make the individual calculations faster.

### Task

You will write a class called `Solution` that implements the `CommandRunner` interface. The `runCommand` method of this class will be passed a string, corresponding to a command the user entered. It should perform the relevant command (see below), and return the specified output string. You should **not** modify the interface `CommandRunner` in any way.

The following table lists the commands the user may enter (i.e. that may be passed as the `command` argument to your `Solution.runCommand` method), and

the required behaviour of your `runCommand` method (note  $N$  is a long integer chosen by the user):

<b>start</b> $N$	start calculating with input $N$ , by calling <code>SlowCalculator.run</code> on a new thread; return message “ <b>Started</b> $N$ ”
<b>cancel</b> $N$	cancel the calculation with input $N$ that is currently running (do nothing if it already completed or if it was never started); return message “ <b>Cancelled</b> $N$ ”
<b>running</b>	just return a message indicating the total number of calculations currently running (excluding those already completed), and their inputs $N$ (in any order), in the form “3 calculations running: 83476 1000 176544”
<b>get</b> $N$	if the calculation for $N$ is finished, return message “ <b>result is</b> $M$ ” where $M$ is the integer result; if the calculation is not yet finished, return message “ <b>calculating</b> ”
<b>finish</b>	finish running all calculations previously requested by the user, and then <b>after</b> they are completed, return message “ <b>Finished</b> ”
<b>abort</b>	immediately stop all running calculations, and return message “ <b>Aborted</b> ”

For any command not given above (including malformed commands, e.g.  $N$  is not an integer), the method should return message “**Invalid command**”.

Note that the provided code for `SlowCalculator` prints the answer at the end of `run()`. You must **remove** this `print` statement, and replace it with a suitable mechanism to return the result so your `Solution` class can retrieve it. You should **not** modify the mathematical calculations performed by `SlowCalculator.calculate` or `SlowCalculator.isPrime`, but you will need to add support for interruption. You may change other parts of this class if you want (e.g. adding new fields or constructor parameters).

Here is an example of what should happen when your program runs; the highlighted lines are commands passed to `runCommand`, and the remaining lines are the messages it returns:

```
start 10456060
Started 10456060
running
1 calculations running: 10456060
get 10456060
result is 5
start 72345680
Started 72345680
```

```
start 534912560
Started 534912560
get 534912560
calculating
running
2 calculations running: 72345680 534912560
cancel 72345680
Cancelled 72345680
running
1 calculations running: 534912560
finish
Finished
```

## Notes

- We will not test on invalid/strange inputs, for which the behaviour is undefined, i.e. not specified above. This includes asking to start a calculation that is already running, or asking for the result of a cancelled (or never started) calculation
- Do ensure you return “Invalid command” (as mentioned above) if you receive a command that is not of the required form (e.g.  $N$  is missing or not an integer, or a command is misspelt)
- We will not run the program with an excessively large number of calculations in parallel (more than 50), so there is no need to explicitly limit the number of running threads
- Your program should not print any output directly, nor read from the console
- Do **not** use any deprecated methods, such as `Thread.stop()` (such methods are typically deprecated because they are dangerous, and so it is bad practice to use them)
- Remember the goal of this exercise is **not** to make each individual calculation parallel, but to run several independent calculations for different  $N$  in parallel!

## Submission

- You must implement a class `Solution` in file `Solution.java`, inheriting from `CommandRunner`. Do **not** put your code in a Java package (i.e. do not use the `package` keyword in any files).
- You will submit a single `.zip` file (**not** a tar, or a rar, or anything else), named `1234567.zip` where 1234567 is replaced by your 7-digit numeric student ID

- This `.zip` file shall contain no folders, (e.g. `src/`), but only the `.java` files containing your code, including `SlowCalculator.java` and `Solution.java`, and maybe others if you wish
- Note you are **not** required to include a `main` method anywhere
- Upload your `.zip` file to Moodle before the deadline!

### Mark Scheme

Your submission will be marked out of 40 points, broken down as follows:

- Code is provided in the correct form (`.zip` file containing `.java` files) and compiles successfully [10]
- `start`, `running`, `get` and `cancel` commands work as expected [20]
- `finish` and `abort` commands work as expected [10]

**If you do not follow the exercise specification precisely, you will lose marks (your submission will be processed by a computer program; it will assume you've followed the instructions).**