

HeatTok: Enhancing Remote Sensing Image Understanding via Thermodiffusion-based Tokenization

Yingying Yan*
Northwestern Polytechnical
University
Xi'an, China
yanyyy@mail.nwpu.edu.cn

Jiaqi Tang*
Hong Kong University of Science and
Technology
Hong Kong, China
jtang092@connect.ust.hk

Wei Wei[✉]
Northwestern Polytechnical
University
Xi'an, China
weiweinwpu@nwpu.edu.cn

Qianzhou Wang
Northwestern Polytechnical
University
Xi'an, China
wangqianzhou@mail.nwpu.edu.cn

Jinjian Wu
Northwestern Polytechnical
University
Xi'an, China
wujinjian@mail.nwpu.edu.cn

Botong Geng
Northwestern Polytechnical
University
Xi'an, China
2021300094@mail.nwpu.edu.cn

Jianmin Chen
Northwestern Polytechnical
University
Xi'an, China
chenjianmin@mail.nwpu.edu.cn

Yuyang Xia
Northwestern Polytechnical
University
Xi'an, China
2021302800@mail.nwpu.edu.cn

Lei Zhang
Northwestern Polytechnical
University
Xi'an, China
nwpuzhanglei@nwpu.edu.cn

Abstract

Current visual tokenizers in Multimodal Large Language Models (MLLMs) predominantly rely on patch-based partitioning, which causes severe semantic mixture and object fragmentation in remote sensing imagery due to the irregular contours of geo-objects. Moreover, existing adaptive methods struggle to extract precise object-level tokens and lack dedicated geometric positional encodings for irregular regions. In this paper, we propose HeatTok, a semantic-aware tokenizer driven by thermodiffusion aggregation. Inspired by the physical principles of heat conduction, HeatTok adaptively merges adjacent homogeneous regions to generate semantically independent, object-aligned irregular tokens. To enable MLLMs to perceive these irregular shapes, we design the Gaussian Multimodal Rotary Positional Embedding (G-MRoPE), which models token spatial distributions via 2D Gaussians and explicitly injects center, scale, and orientation cues. Extensive evaluations on the VRSBench and EarthVQA datasets demonstrate that HeatTok effectively preserves object-level semantic integrity and achieves state-of-the-art performance under a reasonable token budget. The code is available: <https://github.com/YingyingYan1/HeatTok>.

Keywords

Irregular Visual Tokenization, Thermodiffusion Aggregation, Multimodal Large Language Models

1 Introduction

Multimodal Large Language Models (MLLMs) [3, 19, 22, 33, 41] have demonstrated significant potential in remote sensing image analysis and have been widely applied to downstream tasks such as complex scene understanding [11, 14, 17, 31, 40, 42, 43], urban planning [10, 20, 23, 32], and visual reasoning [29, 30, 38]. As a




Figure 1: Motivation and paradigm comparison of visual tokenizers. Patch-based fragment irregular geo-objects, harming Semantic Integrity. Dynamic Merging groups tokens but remains grid-confined, yielding blocky outlines. HeatTok leverages thermodiffusion to generate object-level tokens that adhere to true boundaries.

core component of MLLMs, the visual tokenizer is responsible for identifying basic visual elements from images and transforming

*The first two authors contributed equally.

[✉]Corresponding author: Wei Wei.

them into model-processable token sequences. Its quality directly impacts the visual comprehension of the model.

Current MLLMs predominantly adopt patch-based visual tokenization [9], where images are uniformly partitioned into fixed-size square patches. However, this content-agnostic partitioning mechanism severely misaligns with the irregular geo-object boundaries, multi-scale targets, and complex backgrounds prevalent in remote sensing images. Regular grids fail to align with the true contours of geo-objects such as buildings and roads. This results in a mixture of multiple semantic classes within a single token, or the fragmentation of a single object across multiple tokens, as shown in Fig. 1(a), thereby hindering the capability of the model to comprehend complete object structures.

To mitigate the aforementioned issues, existing studies have attempted to introduce adaptive tokenization methods, such as dynamically grouping, merging, or reallocating tokens to reduce redundancy [5, 15, 25] (Fig. 1(b)), replacing fixed patch partitioning with adaptive sampling of positions and scales [7, 39, 45], or leveraging superpixels [1, 2, 18] to generate content-aligned regions. Although these strategies enhance semantic alignment to a certain extent, they encounter two primary challenges within the context of MLLMs: First, the generated tokens predominantly remain as rectangular blocks or fragmented superpixels, failing to form irregular regions that precisely conform to complete object boundaries. Second, they lack positional encoding mechanisms specifically designed for irregular tokens in MLLMs, preventing MLLMs from effectively perceiving their geometric shapes and spatial relationships, thus limiting the practical integration of these methods.

In this paper, we propose **HeatTok**, a semantic-aware tokenization method driven by thermodiffusion, as illustrated in Fig. 1(c). **HeatTok** first utilizes the Fast Segment Anything (FastSAM) [46] to generate fine-grained region proposals that tightly adhere to the boundaries of remote sensing geo-objects. To avoid the computational overhead associated with directly using these proposals, we draw inspiration from physical heat conduction principles [37] and propose a novel **thermodiffusion aggregation** method. This method adaptively merges similar fine-grained regions on a region graph, elevating tokens from the “pixel-level” to the “object-level.” Consequently, it generates irregular tokens that are semantically independent, compactly shaped, and aligned with individual geo-objects. Furthermore, to resolve the geometric representation challenge of irregular tokens within MLLMs, we design a **Gaussian Multimodal Rotary Positional Embedding (G-MRoPE)**. This strategy models the spatial distribution of irregular regions via 2D Gaussian distributions [44], compactly approximating the actual contours of geo-objects with elliptical shapes. By embedding the fitted Gaussian center coordinates, scale parameters, and orientation information into the Multimodal Rotary Positional Embedding (M-RoPE) [35], this approach not only provides a more robust positional representation than traditional centroids or rectangular centers but also endows the MLLM with the capability to perceive the actual coverage and geometric scale of the tokens.

To validate the effectiveness of **HeatTok**, we integrate it into the Qwen2.5-VL [4] model and construct a unified evaluation framework to conduct a fair comparison with existing tokenization methods. Experimental results on VRSBench [21] and EarthVQA [34]

datasets, demonstrate that **HeatTok** superiorly preserves object-level semantic integrity under a reasonable token budget. Our main contributions are summarized as follows:

- We propose **HeatTok**, a semantic-aligned tokenizer that utilizes a thermodiffusion mechanism to adaptively aggregate fine-grained regions. By merging adjacent homogeneous areas, it generates boundary-adherent tokens, substantially reducing semantic mixture and fragmentation.
- We design G-MRoPE, which injects the Gaussian center, scale, and orientation parameters of irregular tokens into M-RoPE. This endows MLLMs with robust positional representations and precise perception of scale and orientation.
- We establish a unified evaluation benchmark on VRSBench [21] and EarthVQA [34]. Extensive experiments demonstrate superior effectiveness of **HeatTok**, achieving an accuracy of 76.37% on VRSBench and 78.88% on EarthVQA.

2 Related Work

Patch-based visual tokenization [9] divides the image into square patches of fixed size. This leads to semantic fragmentation, semantic mixture within a single token, and computational redundancy. To address these issues, existing studies have begun to explore adaptive visual tokenization methods, which can be primarily categorized into three classes [1].

Dynamic Grouping and Merging. These methods reduce redundancy by dynamically grouping, merging, or reallocating tokens from the original patch grid. Representative methods include ToMe [5], ALGM [24], Chat-UniVi [16], STViT [15], Quadtree [25], HOOK [26], and MSViT [12]. They primarily operate on the encoded grid tokens, focusing on compressing computation or adjusting the token budget based on existing patch representations, rather than redefining the visual tokenization units from the input side. Essentially, they still rely on regular patch primitives.

Deformable Sampling. Compared with directly merging grid tokens, this line of work replaces fixed patch partitioning with learned adaptive sampling of positions and scales. DPT [7] and DAT [39] introduce deformable patch embedding and deformable attention, respectively, enabling tokens to adjust their sampling regions in a data-dependent manner. GPSToken [45] further utilizes 2D Gaussians to parameterize each token, explicitly modeling the position and shape of the regions, thereby achieving spatially adaptive tokenization beyond uniform grids. However, the fundamental representation units of these methods remain tied to rectangular patches or the patch level. Consequently, they struggle to naturally conform to the complex boundaries of geo-objects prevalent in remote sensing imagery, such as curved rivers or tilted roads.

Subobject and Superpixel Tokenizers. To enhance object-level perception, researchers explore tokenization over irregular regions to align tokens with semantically consistent visual entities. Subobject methods, such as EPOC [6], form adaptive regions via boundary-aware segmentation. Superpixel tokenizers, e.g., SuiT [18], ∂ HT [1], MSOM [8], and SPiT [2], further replace square patches with superpixel based tokens, thereby better preserving semantic integrity. However, these methods typically rely on near-pixel-level grouping strategies, thus still potentially incurring significant tokenization overhead. Furthermore, most of




Figure 2: The overall framework of our method. Global branch extracts regular tokens with grid positions $BPos(P_1)$. Semantic branch uses thermodiffusion to generate object-aligned irregular tokens. Their positions $BPos(P_2)$ are parameterized into 2D Gaussians—center (P_c), scale (P_e), and orientation (ρ)—and explicitly injected via G-MRoPE before token concatenation.

them employ implicit positional aggregation or simple centroid representations, lacking explicit geometric parameterization and positional encoding mechanisms tailored for irregular tokens in MLLMs.

Despite attempts to transcend rigid grids, existing adaptive tokenization strategies remain constrained by rectangular primitives or lack adequate geometric representations. Consequently, remote sensing MLLMs struggle to simultaneously preserve the semantic integrity of irregular regions [18] and accurately convey their geometric morphology [6, 45]. To bridge this gap, we propose **HeatTok**. By generating semantically aligned irregular tokens via thermodiffusion aggregation and integrating Gaussian parameters into M-RoPE, **HeatTok** equips MLLMs to explicitly perceive the geometric attributes of these tokens.

3 Methodology

Given a remote sensing image $I \in \mathbb{R}^{H \times W \times 3}$, our objective is to generate semantically complete and geometrically rich irregular visual tokens to enhance the remote sensing image understanding of MLLMs. This problem involves two key challenges: transforming over-segmented regions into object-aligned tokens, and providing accurate geometric representations for these tokens so that MLLMs can effectively perceive their spatial extent, orientation, and relationships.

Overall. As illustrated in Fig. 2, the complete pipeline of **HeatTok** consists of two complementary branches. In the semantic branch, we first utilize thermodiffusion-guided region merging to aggregate the fine-grained proposals generated by the lightweight FastSAM [46] into semantically complete irregular regions, and subsequently inject their explicit geometric information into the visual tokens via G-MRoPE. Although this branch is highly effective at preserving object integrity and boundary alignment, its object-centric and spatially non-uniform sampling motivates us to retain a parallel

global context branch. In this branch, the input image is downsampled by a factor of 8 to provide complementary scene-level layout and long-range spatial topology for multi-scale remote sensing imagery using only a small number of coarse-grained tokens. Finally, the tokens from both the global and semantic branches are directly concatenated to form a unified visual context for subsequent multi-modal reasoning.

3.1 Thermodiffusion-Guided Token Merging

Preliminary. Thermodiffusion, also known as heat conduction, is a fundamental process in physics describing the spontaneous transfer of thermal energy from high-temperature regions to low-temperature regions. Within a two-dimensional spatial region $D \in \mathbb{R}^2$, the classic Heat Equation [37] is formulated as a partial differential equation:

$$\frac{\partial u}{\partial t} = k \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} \right) = k \nabla^2 u \quad (1)$$

where $u(x, y, t)$ denotes temperature distribution at point (x, y) at time t , ∇^2 is the Laplacian operator, and k denotes the thermal diffusivity, measuring the rate of heat transfer in a material.

Recently, this physical principle was introduced to computer vision via the vHeat architecture [36], which models semantic propagation as adaptive thermal diffusion from patch "heat sources." Its frequency selectivity—where high-frequency components decay faster while low-frequency structures remain stable—naturally fits irregular contours of remote sensing geo-objects, addressing the semantic fragmentation caused by patch-based tokenization.

Problem Formulation and Graph Construction. Given a remote sensing image $I \in \mathbb{R}^{H \times W \times 3}$, we first utilize lightweight FastSAM [46] to generate initial set of fine-grained region proposals $\mathcal{S} = \{S_1, S_2, \dots, S_N\}$. As illustrated in Fig. 3, regions generated by FastSAM typically exhibit an over-segmented state, where a single semantic object is fragmented into multiple disjoint regions.




Figure 3: Thermodiffusion-guided token merging. (a) Initial over-segmented regions act as graph nodes. (b) Heat diffuses via semantic consistency to merge correlated subgraphs. (c) Yields semantically complete, object-aligned regions.

We construct a region adjacency graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where vertex set $\mathcal{V} = \{v_1, v_2, \dots, v_N\}$ corresponds to FastSAM regions, and edge set $\mathcal{E}$ contains spatially adjacent region pairs (v_i, v_j) . Two regions S_i and S_j are adjacent iff they share a common boundary or their spatial distance is less than a predefined threshold δ . Analogous to thermodynamics, each vertex v_i is assigned a temperature T_i , characterizing the intensity of semantic consistency within that region; each edge (v_i, v_j) is assigned a thermal diffusivity κ_{ij} , which controls the rate of heat transfer between adjacent regions.

Calculation of Thermodynamic Parameters. The construction of the initial temperature field $T^{(0)} = \{T_1^{(0)}, T_2^{(0)}, \dots, T_N^{(0)}\}$ is grounded in the semantic similarity between regions. For each region S_i , we compute its mean feature vector $c_i \in \mathbb{R}^3$ in the LAB color space, and then define the initial temperature as

$$T_i^{(0)} = \frac{1}{|N(i)|} \sum_{j \in N(i)} \exp\left(-\frac{\|c_i - c_j\|}{\sigma_T}\right) \quad (2)$$

where $N(i) = \{j \mid (v_i, v_j) \in \mathcal{E}\}$ denotes the neighbors of vertex v_i , and σ_T is the temperature scale. This definition ensures that vertices within homogeneous regions (i.e., those similar in color to their neighbors) acquire a higher initial temperature $T_i^{(0)} \approx 1$, acting as **Heat Sources**; vertices located at semantic boundaries (exhibiting significant color differences from their neighbors) possess temperatures approaching zero, acting as **Cold Sinks**.

The thermal diffusivity matrix $\mathbf{K} = \{\kappa_{ij}\}_{(v_i, v_j) \in \mathcal{E}}$ controls the heat transfer rate and is jointly determined by inter-region color similarity and region complexity:

$$\kappa_{ij} = \kappa_0 \cdot \exp\left(-\frac{\|c_i - c_j\|_2^2}{2\sigma_c^2}\right) \cdot (1 + \alpha \cdot \min(C_i, C_j)) \quad (3)$$




Figure 4: (a) M-RoPE: Assigns discrete 2D integer coordinates to uniform grids, ignoring object boundaries. (b) G-MRoPE: Uses 2D Gaussian fitting to explicitly encode the continuous centers (x, y) , scales (w, h) , and orientations ρ of irregular regions, enabling precise perception of complex geo-objects.

where κ_0 is the base diffusivity and σ_c controls color sensitivity. The complexity $C_i = \frac{1}{|S_i|} \sum_{(x,y) \in S_i} \|\nabla I(x, y)\|$ measures average gradient over pixel set S_i . $\alpha \geq 0$ modulates the influence of complexity on diffusivity. This design ensures that heat diffuses faster in texture-complex regions (high C_i), facilitating the rapid absorption of heat source by cold sinks at boundaries, while maintaining slower diffusion in smooth regions to preserve internal stability.

Discrete Heat Conduction Equation. The heat conduction process in the continuous domain is governed by the partial differential equation in Eq. (1). On the discrete graph structure, we employ the Graph Laplacian operator [27] to approximate the continuous Laplacian term, yielding the iterative update formula:

$$T_i^{(t+1)} = T_i^{(t)} + \Delta t \sum_{j \in N(i)} \kappa_{ij} (T_j^{(t)} - T_i^{(t)}) \quad (4)$$

where Δt denotes the discrete time step, satisfying the stability condition $\Delta t < \frac{1}{\max_i \sum_{j \in N(i)} \kappa_{ij}}$. The iteration process proceeds until the system reaches an equilibrium state: $\max_{i \in \{1, \dots, N\}} |T_i^{(t+1)} - T_i^{(t)}| < \epsilon$, where ϵ represents a predefined convergence threshold.

Region Merging Criteria. Upon thermodiffusion convergence, we merge regions based on the final temperature field $T^{(\text{final})}$. Specifically, for each edge $(v_i, v_j) \in \mathcal{E}$, if the semantic consistency condition $|T_i^{(\text{final})} - T_j^{(\text{final})}| < \tau_m$ holds, regions S_i and S_j are merged into a single semantic unit. The threshold τ_m governs aggregation granularity. Following this operation, we obtain semantically complete regions $\mathcal{R} = \{R_1, R_2, \dots, R_M\}$ ($M \ll N$). Each merged region R_k inherits the geometric union of its constituent regions, forming irregular shapes that tightly conform to geo-object boundaries.

3.2 Gaussian Multimodal Rotary Positional Embedding

Gaussian Parameterized Modeling. To provide geometric representations for irregular regions $R_k \in \mathcal{R}$, traditional solutions based on bounding box centers or geometric centroids are inadequate. They exhibit spatial deviations and fail to capture scale and shape attributes, particularly for slender, curved, or non-convex geo-objects. To obtain a comprehensive geometric representation, we model




Figure 5: Visual comparison of semantic integrity across different tokenization methods. HeatTok preserves crisp object boundaries and avoids over-segmentation.

each semantic region R_k with a 2D Gaussian distribution $\mathcal{G}_k$. This formulation encapsulates the spatial distribution of irregular tokens into a compact five-parameter vector, characterizing their absolute centers, extents, and orientations:

$$\mathcal{G}_k = (\mu_{xk}, \mu_{yk}, \sigma_{xk}, \sigma_{yk}, \rho_k) \quad (5)$$

where $\mu_{xk}, \mu_{yk} \in \mathbb{R}$ define the spatial center of the distribution, $\sigma_{xk}, \sigma_{yk} > 0$ represent the standard deviations along the horizontal and vertical axes, and the correlation coefficient $\rho_k \in [-1, 1]$ governs the orientation of the Gaussian ellipse.

Specifically, we extract the principal-axis angle from Gaussian parameters as $\varphi_k = \frac{1}{2} \text{atan2}(2\rho_k\sigma_{xk}\sigma_{yk}, \sigma_{xk}^2 - \sigma_{yk}^2)$. Here, $\varphi_k \in [-\pi/2, \pi/2]$ denotes the rotation angle of the principal axis of region R_k relative to the coordinate axes. For isotropic regions ($\sigma_{xk} = \sigma_{yk}$), the orientation angle degenerates to $\varphi_k = 0$.

Integration of G-MRoPE. To inject Gaussian geometric information into the MLLM, we extend the M-RoPE framework of Qwen2.5-VL [4] by designing a joint position-scale encoding strategy, named Gaussian multimodal rotational positional encoding (G-MRoPE), as compared in Fig. 4. Let D denote the visual token feature dimension. Standard RoPE [28] defines inverse frequencies $\{\omega_m\}_{m=0}^{D/2-1}$ with $\omega_m = \theta^{-2m/D}$. For each frequency ω_m and region orientation angle φ_k , we define their respective 2D rotation matrices:

$$\mathbf{R}(\omega_m) = \begin{pmatrix} \cos \omega_m & -\sin \omega_m \\ \sin \omega_m & \cos \omega_m \end{pmatrix}, \quad \mathbf{R}(\varphi_k) = \begin{pmatrix} \cos \varphi_k & -\sin \varphi_k \\ \sin \varphi_k & \cos \varphi_k \end{pmatrix} \quad (6)$$

To effectively incorporate the orientation prior along with the spatial context, we apply a joint rotational transformation to both the center vector $\boldsymbol{\mu}_k = (\mu_{xk}, \mu_{yk})^\top$ and the scale vector $\boldsymbol{\sigma}_k =$

$(\sigma_{xk}, \sigma_{yk})^\top$:

$$\mathbf{P}_{km}^{(c)} = \mathbf{R}(\omega_m) \mathbf{R}(\varphi_k) \boldsymbol{\mu}_k, \quad \mathbf{P}_{km}^{(e)} = \mathbf{R}(\omega_m) \mathbf{R}(\varphi_k) \boldsymbol{\sigma}_k \quad (7)$$

where $\mathbf{R}(\varphi_k)$ rotates the center and scale vectors into the principal axis frame of region R_k , and $\mathbf{R}(\omega_m)$ then applies frequency-dependent rotational encoding. This sequential mechanism decouples the intrinsic orientation of the irregular region from multi-frequency spatial encoding. Specifically, $\mathbf{R}(\varphi_k)$ aligns the coordinate vectors with the principal axis frame of the geo-object, reducing orientation-induced geometric variance, while $\mathbf{R}(\omega_m)$ projects the aligned coordinates into the frequency domain.

Through this joint transformation, the resulting vectors $\mathbf{P}_{km}^{(c)} \in \mathbb{R}^2$ and $\mathbf{P}_{km}^{(e)} \in \mathbb{R}^2$ comprehensively encode the absolute spatial coordinates and the region coverage extent, respectively. To balance the contributions of position and scale information across the limited feature dimensions, we design frequency-dependent weight coefficients defined as $\alpha_m = 1 - \frac{m}{D/2-1}$ and $\beta_m = 1 - \alpha_m$. Low-frequency components (small m) emphasize absolute position, while high-frequency components (large m) prioritize fine-grained scale, since lower frequencies smoothly capture stable, global geometric attributes, whereas higher frequencies are more sensitive to local spatial variations. The final MRoPE embedding is obtained through weighted combination:

$$\begin{aligned} E_{k,m}^{\cos} &= \alpha_m \cos(\mathbf{P}_{km}^{(c)}) + \beta_m \cos(\mathbf{P}_{km}^{(e)}) \\ E_{k,m}^{\sin} &= \alpha_m \sin(\mathbf{P}_{km}^{(c)}) + \beta_m \sin(\mathbf{P}_{km}^{(e)}) \end{aligned} \quad (8)$$

This encoding is integrated with the attention mechanism of the Large Language Model backbone in Qwen2.5-VL. For the m -th

Table 1: Performance comparison of different tokenization methods across various dimensions on VRSBench. *Tokens* denotes average number of visual tokens per image, and *Throughput* denotes number of images processed per second (images/s). Red indicates the best performance, while blue denotes the second best.

Visual Tokenizer	Tokens	Throughput	Category	Presence	Quantity	Color	Shape	Size	Position	Direction	Scene	Reasoning	All
Patch Embed [9]	324	24.6	83.86	90.94	57.25	72.06	75.12	63.60	65.56	51.99	81.82	72.95	75.03
Dynamic Grouping and Merging													
ToMe [5]	164	25.43	82.13	91.92	50.39	72.14	75.26	63.60	60.57	50.52	83.45	73.17	73.24
Chat-UniVi [16]	112	27.99	85.38	91.50	55.15	74.79	75.83	63.49	67.57	53.02	83.61	74.15	75.87
Quadtree [25]	144	29.97	56.12	88.01	50.30	61.52	76.77	60.87	54.77	49.01	63.26	72.07	64.16
HOOK [26]	128	35.33	70.69	79.33	60.65	74.85	73.12	58.73	59.60	51.17	79.10	68.41	69.95
STViT [15]	144	29.99	56.74	78.21	47.91	62.11	74.05	63.73	57.55	51.59	54.33	69.51	61.13
Deformable Sampling													
DPT [7]	144	27.00	54.25	71.80	46.47	61.25	72.41	60.06	55.23	52.35	59.68	69.30	59.25
GPSToken [45]	128	28.46	56.43	88.26	52.06	56.28	71.48	59.96	54.22	51.96	56.16	69.85	62.86
Subobject and Superpixel Tokenizers													
SuiT [18]	196	18.77	67.55	90.91	50.09	69.15	75.05	62.65	56.71	51.64	67.36	73.29	67.97
SPiT [2]	196	18.6	68.44	91.16	51.59	65.49	75.19	63.52	58.31	52.64	71.33	72.40	68.82
EPOC [6]	≈ 140	24.64	64.60	90.67	49.15	61.29	74.06	63.82	51.77	49.38	70.69	72.29	66.17
∂HT [1]	≈ 150	27.50	64.12	89.14	49.61	67.01	75.12	63.91	56.03	50.64	68.75	72.18	66.88
HeatTok	≈ 120	30.84	84.45	91.41	56.36	77.32	78.07	64.20	67.96	55.35	83.75	74.28	76.37

Table 2: Performance comparison on the EarthVQA.

Visual Tokenizer	BasJu	RelJu	BasCo	RelCo	ObjAn	ComAn	All
Patch Embed [9]	80.44	84.56	76.56	79.15	66.66	58.15	77.86
Dynamic Grouping and Merging							
ToMe [5]	73.64	80.21	76.88	78.85	52.5	54.39	73.67
Chat-UniVi [16]	82.74	80.83	73.68	77.65	62.09	55.51	75.72
Quadtree [25]	60.23	78.81	72.06	78.43	53.81	49.40	68.82
HOOK [26]	81.96	82.00	54.19	56.87	43.42	48.87	69.62
STViT [15]	58.80	79.26	74.07	79.43	50.27	51.22	69.17
Deformable Sampling							
DPT [7]	62.67	76.35	70.45	79.43	50.27	51.76	68.16
GPSToken [45]	64.81	75.8	71.91	78.43	58.11	50.70	68.94
Subobject and Superpixel Tokenizers							
SuiT [18]	80.69	82.12	73.83	80.85	56.72	57.18	75.82
SPiT [2]	82.16	79.34	73.19	79.43	55.07	58.82	74.98
EPOC [6]	64.11	79.65	73.65	78.43	53.77	52.96	70.69
∂HT [1]	74.88	80.32	74.08	78.43	50.27	53.84	73.18
HeatTok	82.60	85.94	75.06	81.67	68.87	59.49	78.88

feature slice of the query (or key) vector $\mathbf{q}_{k,m}$ associated with token k , position awareness is achieved via the rotary operation:

$$\tilde{\mathbf{q}}_{k,m} = \mathbf{q}_{k,m} \odot E_{k,m}^{\cos} + \mathbf{q}_{k,m}^{\perp} \odot E_{k,m}^{\sin} \quad (9)$$

where $\mathbf{q}_{k,m}^{\perp}$ denotes adjacent-dimension swapping with sign negation of $\mathbf{q}_{k,m}$. This allows the model to preserve original geometric information when processing normalized patches, enhancing its ability to understand and localize irregular geo-objects.

4 Experiments



4.1 Experimental Settings

Benchmarks and Metric. We evaluate on VRSBench [21] and EarthVQA [34], comprehensive benchmarks designed for remote sensing visual question answering. Both datasets feature diverse question types covering multiple semantic levels, ranging from basic object attributes and counting to complex scene understanding and reasoning. We use overall answer accuracy as the primary evaluation metric, and additionally report the number of visual tokens and throughput to provide a concise assessment of efficiency.

Implementation details. HeatTok is built upon Qwen2.5-VL-7B [4]. We use LoRA [13] with a rank of 64 to fine-tune all compared methods on the VRSBench and EarthVQA datasets under the same supervised setting. Training uses a global batch size of 32, the AdamW optimizer, an initial learning rate of 1×10^{-4} with cosine decay, and a 10% linear warmup. For the Thermomdiffusion module, hyperparameters are empirically set as follows: base diffusivity $\kappa_0 = 1.0$, complexity factor $\alpha = 0.5$, temperature scale $\sigma_T = 5.0$, color sensitivity scale $\sigma_C = 5.0$, and merging threshold $\tau_m = 0.03$. The diffusion iteration terminates when the maximum temperature change falls below 1×10^{-5} .

Baselines. To ensure fair comparison, we establish a unified evaluation framework based on Qwen2.5-VL [4] by integrating compared tokenization methods into the same MLLM backbone. Specifically, we replace the Patch Embed tokenizer of Qwen2.5-VL with each baseline tokenizer while keeping the backbone and training protocol unchanged. For methods with explicit positional or geometric encodings (e.g., EPOC [6], GPSToken [45]), we incorporate their position-related information together with the M-RoPE interface of Qwen2.5-VL. For irregular-region tokenizers without explicit positional designs, we use the geometric centroid of each

Table 3: Case study on remote sensing visual question answering. We show the visual question answering results of a specific scenario along with the tokenization visualizations for different methods. Red indicates hallucinations or incorrect perceptions; Green indicates accurate alignment with the ground truth.

Remote Sensing Image & Tokenization Visualization:					
					
Prompt: What are the water situations around the agricultural land? What are the needs for the renovation of villages?					
Ground Truth: There are polluted waters near the agriculture land. The roads need to be improved , and waters need to be cleaned up .					
Patch Embed: There are no water area. The roads need to be improved . Analysis: Uniform grid partitioning rigidly fragments the continuous polluted water body and agricultural land. This disruption of semantic integrity causes the model to fail entirely in recognizing the presence of the water body.					
Dynamic Grouping and Merging					
ToMe: There are clean waters near the agriculture land. Waters need to be cleaned up . Chat-UniVi: A small pond can be seen in the center of the road loop and there is a larger body of water to the upper right. The narrow dirt roads between the fields need to be improved , and the murky ponds in the upper right need to be cleaned up . Quadtree: The area seems to lack prominent water features near the fields. Infrastructure improvements, housing upgrades, and agricultural enhancements. HOOK: Farmland is completely devoid of nearby water resources. There are no needs . STViT: Two distinct clean water bodies are present adjacent to the fields. Roadways need to be improved and the nearby water bodies need cleaning up . Analysis: Although these methods group adjacent tokens, the Chat-UniVi visualization reveals that they remain constrained by rectangular primitives . This blocky grouping mixes the boundaries of the polluted water with the surrounding land, leading the model to hallucinate incorrect attributes .					
Deformable Sampling					
DPT: There is absolutely no water nor any agricultural fields visible. There are no needs for the renovation of villages in this image. GPSToken: I cannot detect any water area around the agricultural land. The agricultural land needs to be expanded . Analysis: The GPSToken visualization shows that deformable sampling generates dense, spatially non-uniform cells that capture local textures but disregard the macroscopic semantic structure . Consequently, the MLLM loses the holistic concept of the "polluted water," resulting in severe hallucinations and failure to recognize the renovation needs.					
Subobject and Superpixel Tokenizers					
SuiT: There are water bodies adjacent to the farm plots. There is a need to improve the dirt roads . SPiT: I see clean waters around the agricultural land. The roads need improvement and housing needs upgrading . EPOC: I see no water bodies in the area. The roads need to be improved . ∂HT: Yes, water resources are located nearby. The roads need to be improved . Analysis: Superpixel methods like SPiT rely on low-level pixel features, leading to severe over-segmentation . The polluted water body is shattered into disjointed, jagged fragments . This fragmentation makes it difficult for the model to perceive the pollution status correctly, causing it to incorrectly guess "clean waters" or miss the water cleanup requirement.					
HeatTok: I observe that polluted waters are indeed found near the agriculture land. Waters need to be cleaned up , and the roads need to be improved . Analysis: By leveraging thermodiffusion aggregation, HeatTok more accurately outlines the continuous, irregular boundaries of the dark water body and the agricultural plots. Preserving this object-level semantic integrity helps the MLLM better ground the visual features, allowing it to identify the "polluted" status and provide more reliable renovation needs with fewer hallucinations .					

token region as its position to establish spatial awareness. All methods are configured to produce a comparable number of visual tokens for fair evaluation. We benchmark **HeatTok** against representative visual tokenization methods across three paradigms: (i) Dynamic

Grouping and Merging (ToMe [5], Chat-UniVi [16], Quadtree [25], HOOK [26], STViT [15]); (ii) Deformable Sampling (DPT [7], GPSToken [45]); and (iii) Subobject and Superpixel Tokenizers (SuiT [18], SPiT [2], EPOC [6], ∂HT [1]).

Table 4: Ablation on core components of HeatTok. $P^{(c)}$, $P^{(e)}$, and ρ denote the Gaussian center, scale, and orientation encodings.

Thermodiffusion	GMrope			Category	Presence	Quantity	Color	Shape	Size	Position	Direction	Scene	Reasoning	All
	$P^{(c)}$	$P^{(e)}$	ρ											
×	×	×	×	83.86	90.94	57.25	72.06	75.12	63.6	65.56	51.99	81.82	72.95	75.03
✓	×	×	×	83.47	90.65	56.41	77.17	75.98	60.94	65.38	52.06	82.45	68.18	75.15
✓	✓	×	×	83.82	91.14	55.96	76.92	76.15	61.72	67.34	52.94	82.81	73.63	75.72
✓	✓	✓	×	84.26	91.20	56.27	77.28	76.54	63.34	67.86	53.24	83.62	74.26	76.14
✓	✓	✓	✓	84.45	91.41	56.36	77.32	78.07	64.20	67.96	55.35	83.75	74.28	76.37

4.2 Main results

Semantic Integrity of HeatTok. Fig. 5 visualizes tokenization results to demonstrate semantic integrity of **HeatTok** against three paradigms. Dynamic grouping methods (e.g., ToMe, Chat-UniVi) remain constrained by rigid rectangular grids, producing jagged contours that miss object boundaries. Deformable sampling (e.g., GPSToken) generates localized cells that often disregard semantic structures. Furthermore, subobject and superpixel tokenizers (e.g., SuiT, SPiT, ∂ HT) rely on low-level pixel grouping, leading to over-segmentation and shattered entities. In contrast, **HeatTok** leverages thermodiffusion to **aggregate** homogeneous regions. It merges over-segmented parts into compact, semantically coherent tokens that adhere to crisp boundaries. This enables **HeatTok** to achieve a superior **object-level** representation, accurately capturing the semantic structures of complex geo-objects.

Comparison with Other Tokenization Methods. Tables 1 and 2 report performance on VRSBench and EarthVQA. **HeatTok** achieves the best overall performance on both datasets, reaching 76.37% on VRSBench and 78.88% on EarthVQA, while maintaining a competitive token budget and favorable throughput. In contrast, other semantic tokenization methods (e.g., DPT, GPSToken, and EPOC) perform worse on VRSBench. This suggests that these tokenizers are less suitable for remote sensing understanding, as they struggle to preserve complete object-level semantics of irregular geo-objects. Moreover, without positional encodings designed for irregular regions and compatible with M-RoPE, models may lose critical geometric details, hindering accurate visual-linguistic alignment in MLLMs. Analysis shows that **HeatTok** is particularly effective on **Shape**, **Size**, **Position**, and **Direction**, suggesting that G-MRoPE helps the model better capture the spatial extent, morphology, and orientation of irregular regions.

Case Study. To demonstrate **HeatTok**'s superiority in remote sensing visual question answering, Table 3 compares tokenization methods on a scene involving agricultural land, polluted water, and village renovation needs. Existing methods exhibit recognition errors and hallucinations. Patch Embed fails to recognize the water body, predicting "no water". Dynamic grouping and merging methods, such as ToMe and STViT, misclassify polluted water as "clean waters", while HOOK outputs "no needs". Deformable sampling methods, including DPT and GPSToken, hallucinate "no water", "no needs", and "expanded" agricultural land. Superpixel-based methods fragment the polluted water body, weakening pollution and cleanup recognition. In contrast, **HeatTok** captures spatial relations among the irregular water body, farmland, and roads, correctly identifying *polluted waters* and renovation needs.

4.3 Ablation Study

To verify the effectiveness of core components in **HeatTok**, we conducted ablation studies on VRSBench. As shown in Table 4, using Qwen2.5-VL Patch Embed as baseline (Row 1), we incorporate thermodiffusion aggregation, Gaussian center encoding ($P^{(c)}$), Gaussian scale encoding ($P^{(e)}$), and Gaussian orientation encoding (ρ).

Effectiveness of Thermodiffusion Aggregation. Introducing thermodiffusion alone (Row 2) improves semantic metrics like Color (72.06% $\rightarrow$ 77.17%) and Shape (75.12% $\rightarrow$ 75.98%), validating that forming semantically coherent regions preserves object contours. However, because irregular tokens disrupt grid-based positional structures, spatial-reliant metrics (e.g., Size, Position) slightly decline, underscoring the necessity of geometric parameterization.

Contribution of Geometric Information in G-MRoPE. Building upon thermodiffusion, the incremental integration of G-MRoPE restores geometric contexts. First, embedding Gaussian center coordinates ($P^{(c)}$) resolves the spatial disorder introduced by irregular tokens. By providing a spatial anchor, this component endows the model with localization capabilities, significantly boosting **Position** accuracy from 65.38% to 67.34%. Subsequently, we introduce Gaussian scale encoding ($P^{(e)}$). Since irregular tokens exhibit varying spatial extents, standard point-based coordinates fail to convey object dimensions. Explicit scale parameterization equips the model with precise size perception, yielding a gain in the **Size** metric from 61.72% to 63.34%. Finally, incorporating the Gaussian orientation parameter (ρ) completes the representation. This prior captures the rotational properties of geo-objects—a crucial attribute for interpreting tilted buildings or winding roads—advancing **Direction** accuracy from 53.24% to 55.35%. Collectively, G-MRoPE ensures MLLMs fully comprehend the complex spatial layouts and morphologies of irregular tokens.

5 Conclusion

In this study, we proposed **HeatTok** to address the critical issue of semantic fragmentation caused by Patch-based tokenization in remote sensing MLLMs. By leveraging a novel thermodiffusion aggregation mechanism, our method successfully generates irregular, object-aligned tokens that preserve the semantic integrity of complex geo-objects. Furthermore, we introduced G-MRoPE to explicitly inject Gaussian geometric priors, enabling the model to accurately perceive the precise spatial extent and location of these irregular tokens. Extensive experiments on the VRSBench and EarthVQA datasets demonstrate that **HeatTok** better preserves object-level semantic integrity than existing methods under a reasonable token budget, achieving state-of-the-art performance.

References

- [1] Marius Aasan, Martine Hjelkrem Tan, Nico Catalano, Changkyu Choi, and Adin Ramirez Rivera. 2026. Differentiable hierarchical visual tokenization. *Advances in Neural Information Processing Systems* 38 (2026), 87605–87634.
- [2] Marius Aasan, Odd Kolbjørnsen, Anne Schistad Solberg, and Adin Ramirez Rivera. 2024. A spitting image: Modular superpixel tokenization in vision transformers. In *European Conference on Computer Vision*. Springer, 124–142.
- [3] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altmerschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774* (2023).
- [4] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibao Song, Kai Dang, Peng Wang, Shijie Wang, and Jun Tang. 2025. Qwen2.5-VL Technical Report. (2025).
- [5] Daniel Bolya, Cheng-Yang Fu, Xiaoliang Dai, Peizhao Zhang, Christoph Feichtenhofer, and Judy Hoffman. 2022. Token merging: Your vit but faster. *arXiv preprint arXiv:2210.09461* (2022).
- [6] Delong Chen, Samuel Cahyawijaya, Jianfeng Liu, Baoyuan Wang, and Pascale Fung. 2024. Subobject-level image tokenization. *arXiv preprint arXiv:2402.14327* (2024).
- [7] Zhiyang Chen, Yousong Zhu, Chaoyang Zhao, Guosheng Hu, Wei Zeng, Jinqiao Wang, and Ming Tang. 2021. Dpt: Deformable patch-based transformer for visual recognition. In *Proceedings of the 29th ACM international conference on multimedia*. 2899–2907.
- [8] Zack Dawis, Yimin Zhu, Zhengsen Xu, Mabel Heffring, Saeid Taleghanidooz-doozan, Kaylee Xiao, Motasem Alkayid, and Lincoln Linlin Xu. 2026. Multitask GLocal OBIA-Mamba for Sentinel-2 Landcover Mapping. *IEEE Geoscience and Remote Sensing Letters* (2026).
- [9] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xi-aohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. 2020. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929* (2020).
- [10] Jie Feng, Shengyuan Wang, Tianhui Liu, Yanxin Xi, and Yong Li. 2025. Urbanllava: A multi-modal large language model for urban intelligence. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*. IEEE, 6209–6219.
- [11] Xin Guo, Jiangwei Lao, Bo Dang, Yingying Zhang, Lei Yu, Lixiang Ru, Lihong Zhong, Ziyuan Huang, Kang Wu, Dingxiang Hu, Huimei He, Jian Wang, Jingdong Chen, Ming Yang, Yongjun Zhang, and Yansheng Li. 2024. SkySense: A Multi-Modal Remote Sensing Foundation Model Towards Universal Interpretation for Earth Observation Imagery. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 27662–27673. doi:10.1109/CVPR52733.2024.02613
- [12] Jakob Drachmann Havtorn, Amélie Royer, Tijmen Blankevoort, and Babak Ehteshami Bejnordi. 2023. Msvit: Dynamic mixed-scale tokenization for vision transformers. In *2023 IEEE/CVF International Conference on Computer Vision Workshops (ICCVW)*. IEEE, 838–848.
- [13] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, et al. 2022. Lora: Low-rank adaptation of large language models. *ICLR*, 1, 2 (2022), 3.
- [14] Yuan Hu, Jianlong Yuan, Congcong Wen, Xiaonan Lu, Yu Liu, and Xiang Li. 2025. Rsqpt: A remote sensing vision language model and benchmark. *ISPRS Journal of Photogrammetry and Remote Sensing* 224 (2025), 272–286.
- [15] Huaibo Huang, Xiaoqiang Zhou, Jie Cao, Ran He, and Tieniu Tan. 2022. Vision transformer with super token sampling. *arXiv preprint arXiv:2211.11167* (2022).
- [16] Peng Jin, Ryuichi Takanobu, Wancai Zhang, Xiaochun Cao, and Li Yuan. 2024. Chat-univi: Unified visual representation empowers large language models with image and video understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 13700–13710.
- [17] Kartik Kuckreja, Muhammad Sohail Danish, Muzammal Naseer, Abhijit Das, Salman Khan, and Fahad Shabbaz Khan. 2024. GeoChat: Grounded large vision-language model for remote sensing. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. IEEE, 27831–27840.
- [18] Jaihyun Lew, Soohyuk Jang, Jaehoon Lee, Seungryong Yoo, Eunji Kim, Saehyung Lee, Jisoo Mok, Siwon Kim, and Sungroh Yoon. 2024. Superpixel tokenization for vision transformers: Preserving semantic integrity in visual tokens. *arXiv preprint arXiv:2412.04680* (2024).
- [19] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. 2023. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*. PMLR, 19730–19742.
- [20] Kaiyu Li, Zepeng Xin, Li Pang, Chao Pang, Yupeng Deng, Jing Yao, Guisong Xia, Deyu Meng, Zhi Wang, and Xiangyong Cao. 2025. Segearth-r1: Geospatial pixel reasoning via large language model. *arXiv preprint arXiv:2504.09644* (2025).
- [21] Xiang Li, Jian Ding, and Mohamed Elhoseiny. 2024. Vrsbench: A versatile vision-language benchmark dataset for remote sensing image understanding. *Advances in Neural Information Processing Systems* 37 (2024), 3229–3242.
- [22] Yanwei Li, Yuechen Zhang, Chengyao Wang, Zhisheng Zhong, Yixin Chen, Ruihang Chu, Shaoteng Liu, and Jiaya Jia. 2025. Mini-gemini: Mining the potential of multi-modality vision language models. *IEEE Transactions on Pattern Analysis and Machine Intelligence* (2025).
- [23] Zhonghang Li, Lianhao Xia, Jiabin Tang, Yong Xu, Lei Shi, Long Xia, Dawei Yin, and Chao Huang. 2024. Urbangpt: Spatio-temporal large language models. In *Proceedings of the 30th ACM SIGKDD conference on knowledge discovery and data mining*. 5351–5362.
- [24] Narges Norouzi, Svetlana Orlova, Daan De Geus, and Gijs Dubbelman. 2024. Algm: Adaptive local-then-global token merging for efficient semantic segmentation with plain vision transformers. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. IEEE, 15773–15782.
- [25] Tomer Ronen, Omer Levy, and Avram Golbert. 2023. Vision transformers with mixed-resolution tokenization. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*. IEEE, 4613–4622.
- [26] Run Shao, Zhaoyang Zhang, Chao Tao, Yunsheng Zhang, Chengli Peng, and Haifeng Li. 2024. Homogeneous tokenizer matters: Homogeneous visual tokenizer for remote sensing image understanding. *ISPRS Journal of Photogrammetry and Remote Sensing* 218 (2024), 294–310.
- [27] Olga Sorkine, Daniel Cohen-Or, Yaron Lipman, Marc Alexa, Christian Rössl, and H-P Seidel. 2004. Laplacian surface editing. In *Proceedings of the 2004 Eurographics/ACM SIGGRAPH symposium on Geometry processing*. 175–184.
- [28] Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. 2024. Reformer: Enhanced transformer with rotary position embedding. *Neurocomputing* 568 (2024), 127063.
- [29] Jiaqi Tang, Jianmin Chen, Wei Wei, Xiaogang Xu, Runtao Liu, Xiangyu Wu, Qipeng Xie, Jiafei Wu, Lei Zhang, and Qifeng Chen. 2026. Robust-r1: Degradation-aware reasoning for robust visual understanding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 40. 9421–9429.
- [30] Jiaqi Tang, Jianmin Chen, Youyang Zhai, Wei Wei, Runtao Liu, Mengjie Zhao, Xiangyu Wu, Qingfa Xiao, and Qifeng Chen. 2026. Robust-U1: Can MLLMs Self-Recover Corrupted Visual Content for Robust Understanding?. In *Forty-third International Conference on Machine Learning*.
- [31] Jiaqi Tang, Hao Lu, Ruizheng Wu, Xiaogang Xu, Ke Ma, Cheng Fang, Bin Guo, Jiangbo Lu, Qifeng Chen, and Ying-Cong Chen. 2024. Hawk: Learning to understand open-world video anomalies. *Advances in Neural Information Processing Systems* 37 (2024), 139751–139785.
- [32] Jiaqi Tang, Yingying Yan, Qianzhou Wang, Yuyang Xia, Botong Geng, Jianmin Chen, Ke Ma, Youyang Zhai, Qingfeng He, Weigeng Shao, Yunjin Sun, Junwei Dai, Chuxi Chen, Xiaogang Xu, Kelu Yao, Lei Zhang, Wei Wei, Qifeng Chen, Antonio Plaza, and Yanning Zhang. 2026. Intelligent Remote Sensing Agents: A Survey. doi:10.13140/RG.2.2.24924.35205
- [33] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971* (2023).
- [34] Junjue Wang, Zhuo Zheng, Zihang Chen, Ailong Ma, and Yanfei Zhong. 2024. Earthvqa: Towards queryable earth via relational reasoning-based remote sensing visual question answering. In *Proceedings of the AAAI conference on artificial intelligence*, Vol. 38. 5481–5489.
- [35] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. 2024. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv preprint arXiv:2409.12191* (2024).
- [36] Zhaozhi Wang, Yue Liu, Yunjie Tian, Yunfan Liu, Yaowei Wang, and Qixiang Ye. 2025. Building vision models upon heat conduction. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. IEEE, 9707–9717.
- [37] David Vernon Widder. 1976. *The heat equation*. Vol. 67. Academic Press.
- [38] Jinjian Wu, Jiaqi Tang, Wei Wei, Yingying Yan, Jianmin Chen, Botong Geng, Lei Zhang, and Qifeng Chen. 2026. IQA-T1: Tool-based Visual Evidence Reasoning for Image Quality Assessment. *arXiv preprint arXiv:2607.12375* (2026).
- [39] Zhuofan Xia, Xuran Pan, Shiji Song, Li Erran Li, and Gao Huang. 2022. Vision transformer with deformable attention. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. IEEE, 4784–4793.
- [40] Yingying Yan, Runking Xi, Weijie Wang, and Kehao Zhu. 2025. SAL-BSNet: Structure-Aware and Bilateral Network for Real-Time Unstructured Road Segmentation. In *Chinese Conference on Pattern Recognition and Computer Vision (PRCV)*. Springer, 46–61.
- [41] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388* (2025).
- [42] Yang Zhan, Zhitong Xiong, and Yuan Yuan. 2025. Skyegypt: Unifying remote sensing vision-language tasks via instruction tuning with large language model. *ISPRS Journal of Photogrammetry and Remote Sensing* 221 (2025), 64–77.
- [43] Wei Zhang, Miao Xin Cai, Tong Zhang, Yin Zhuang, and Xuerui Mao. 2024. EarthGPT: A universal multimodal large language model for multisensor image comprehension in remote sensing domain. *IEEE Transactions on Geoscience and Remote Sensing* 62 (2024), 1–20.
- [44] Xinjie Zhang, Xingtong Ge, Tongda Xu, Dailan He, Yan Wang, Hongwei Qin, Guo Lu, Jing Geng, and Jun Zhang. 2024. Gaussianimage: 1000 fps image representation and compression by 2d gaussian splatting. In *European Conference on Computer Vision*. Springer, 327–345.

- [45] Zhengqiang Zhang, Rongyuan Wu, Lingchen Sun, and Lei Zhang. 2026. Gpstoken: Gaussian parameterized spatially-adaptive tokenization for image representation and generation. *Advances in Neural Information Processing Systems* 38 (2026), 11218–11249.
- [46] Xu Zhao, Wenchao Ding, Yongqi An, Yinglong Du, Tao Yu, Min Li, Ming Tang, and Jinqiao Wang. 2023. Fast segment anything. *arXiv preprint arXiv:2306.12156* (2023).

A Methodological Details

This section details the mathematical derivation of our thermodiffusion-guided token merging mechanism. We generalize the classical physical heat diffusion process from a continuous domain to irregular graph structures constructed by FastSAM [20], thereby facilitating semantic-aware feature smoothing and aggregation.

Theoretical Foundation: Classical Heat Equation. Our merging methodology is physically inspired by the classical Heat Equation [18]. In a two-dimensional continuous space $\Omega \subset \mathbb{R}^2$, assuming an isotropic homogeneous medium, the evolution of the temperature field $u(x, y, t)$ over time t is described by the following Partial Differential Equation (PDE):

$$\frac{\partial u}{\partial t} = k \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} \right) = k \nabla^2 u \quad (10)$$

where:

- $\frac{\partial u}{\partial t}$ denotes the rate of change of temperature u with respect to time.
- k represents the thermal diffusivity, which governs the ease of feature propagation. In classical isotropic media, k is a constant.
- $\nabla^2 u = \nabla \cdot \nabla u$ is the Laplacian operator, describing the net heat flux (diffusion) from higher temperature regions to lower temperature regions.

Graph Construction and Discretization. In our context, the visual input is not processed as a regular grid but as an **irregular graph** $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ initialized by FastSAM. To achieve semantic-aware merging, we generalize the isotropic diffusion into an anisotropic process on the graph.

- **Vertices $\mathcal{V}$:** Each node $v_i \in \mathcal{V}$ corresponds to a fine-grained semantic region S_i generated by FastSAM. We define the semantic state of node v_i as its **temperature** T_i .
- **Edges $\mathcal{E}$:** An edge $(v_i, v_j) \in \mathcal{E}$ exists if regions S_i and S_j are spatially adjacent. The constant diffusivity k is generalized into an edge-specific weight κ_{ij} , representing the semantic affinity (thermal conductivity) between different regions.

To apply Eq. (10) to this graph structure, we perform discretization in both temporal and spatial dimensions.

Temporal Discretization: We employ Forward Euler method [8] to approximate the time derivative with a discrete time step Δt :

$$\frac{\partial T_i}{\partial t} \approx \frac{T_i^{(t+1)} - T_i^{(t)}}{\Delta t} \quad (11)$$

where $T_i^{(t)}$ denotes the temperature (feature representation) of node i at iteration t .

Spatial Discretization (Graph Laplacian): On the discrete graph, the continuous Laplacian operator $k \nabla^2 u$ is replaced by the Graph Laplacian [16]. The net heat flux received by node i is the aggregate of fluxes from all its spatial neighbors $j \in N(i)$. According to the diffusion principle, the flux from neighbor j to i is proportional to their temperature difference $(T_j^{(t)} - T_i^{(t)})$, dynamically weighted by the inter-region diffusivity κ_{ij} . Thus, the spatial term is discretized as:

$$k \nabla^2 u \Big|_i \approx \sum_{j \in N(i)} \kappa_{ij} \cdot (T_j^{(t)} - T_i^{(t)}) \quad (12)$$

Algorithm 1 Thermodiffusion-Guided Token Merging

Require: Input Image $I \in \mathbb{R}^{H \times W \times 3}$

Require: FastSAM model for generating initial region proposals

Require: Thermodynamic params: $\kappa_0, \sigma_C, \sigma_T, \alpha$

Require: Integration params: Time step Δt , tolerance ϵ

Require: Merging threshold τ_m

// Step 1. Graph Construction and Initialization

- 1: $\mathcal{S} \leftarrow$ Generate fine-grained region proposals $\{S_1, \dots, S_N\}$ via FastSAM
- 2: $\mathcal{G}(\mathcal{V}, \mathcal{E}) \leftarrow$ Construct region adjacency graph where edges $\mathcal{E}$ represent spatial adjacency
- 3: **for** each region $S_i \in \mathcal{S}$ **do**
- 4: $c_i, C_i \leftarrow$ Calculate LAB color mean and texture complexity
- 5: $T_i^{(0)} \leftarrow$ Initialize temperature using σ_T via Eq. (2)
- 6: **end for**
- 7: **for** each edge $(v_i, v_j) \in \mathcal{E}$ **do**
- 8: $\kappa_{ij} \leftarrow$ Calculate thermal diffusivity using $(\kappa_0, \sigma_C, \alpha)$ via Eq. (3)
- 9: **end for**

// Step 2. Thermodiffusion Process

- 10: $t \leftarrow 0$
- 11: $\Delta T_{max} \leftarrow \infty$
- 12: **while** $\Delta T_{max} \geq \epsilon$ **do**
- 13: **for** each region $v_i \in \mathcal{V}$ **do**
- 14: $T_i^{(t+1)} \leftarrow T_i^{(t)} + \Delta t \sum_{j \in N(i)} \kappa_{ij} (T_j^{(t)} - T_i^{(t)})$
- 15: **end for**
- 16: $\Delta T_{max} \leftarrow \max_i |T_i^{(t+1)} - T_i^{(t)}|$
- 17: $t \leftarrow t + 1$
- 18: **end while**

// Step 3. Region Merging

- 19: $\mathcal{R} \leftarrow$ Merge adjacent regions (S_i, S_j) into a single semantic unit if $|T_i^{(\text{final})} - T_j^{(\text{final})}| < \tau_m$
 - 20: **Return** Final semantically complete region set $\mathcal{R} = \{R_1, \dots, R_M\}$
-

Final Iterative Update Rule. Substituting Eq. (11) and Eq. (12) back into Eq. (10), we obtain the heat conduction equation on the graph:

$$\frac{T_i^{(t+1)} - T_i^{(t)}}{\Delta t} = \sum_{j \in N(i)} \kappa_{ij} \cdot (T_j^{(t)} - T_i^{(t)}) \quad (13)$$

By rearranging the terms, we derive the final iterative update formula used in our Thermodiffusion-Guided Token Merging algorithm:

$$T_i^{(t+1)} = T_i^{(t)} + \Delta t \sum_{j \in N(i)} \kappa_{ij} (T_j^{(t)} - T_i^{(t)}) \quad (14)$$

This equation mathematically demonstrates that in each step, the temperature (semantic feature) of a region is updated by absorbing information from its neighbors, weighted by their semantic affinity κ_{ij} , effectively simulating the physical process of thermal equilibrium to achieve boundary-preserving homogenization.

To provide a clear understanding of our implementation details, we summarize the complete workflow of the Thermodiffusion-Guided Token Merging algorithm in Algorithm 1.

Table 5: List of hyperparameters for the Thermodiffusion-Guided Token Merging algorithm, including their symbols, optimal values, and physical interpretations.

Parameter	Symbol	Value	Physical Interpretation & Impact
Base Diffusivity	κ_0	1.0	Controls the global baseline speed of heat exchange between all adjacent regions.
Color Sensitivity Scale	σ_C	5.0	Controls sensitivity to color differences during diffusion. A larger value makes diffusion less sensitive to color variations, allowing heat to flow across minor spectral differences.
Temperature Scale	σ_T	5.0	Controls color sensitivity for initial temperature assignment ($T^{(0)}$). A smaller value requires high neighbor similarity to form a "Heat Source".
Complexity Factor	α	0.5	Modulates the influence of texture complexity (C_i). A larger value accelerates heat exchange in high-frequency/complex regions.
Merging Threshold	τ_m	0.03	The threshold for temperature difference. A larger value leads to more aggressive merging and coarser tokens.

Table 6: Hyperparameter settings for different experimental ablation sets.

Experiment Set	κ_0 (Diffusivity)	σ_C (Color Sens.)	σ_T (Temp. Scale)	α (Complexity)	τ_m (Threshold)
Optimal (Ours)	1.0	5.0	5.0	0.5	0.03
Set A	2.0	10.0	10.0	0.5	0.03
Set B	1.0	5.0	5.0	0.0	0.03
Set C	4.0	5.0	5.0	0.5	0.03

B Hyperparameter Sensitivity Analysis

To validate the robustness of our proposed method and determine the optimal configuration for the thermodynamic parameters, we conducted a comprehensive hyperparameter sensitivity analysis. The Thermodiffusion-Guided Token Merging process is governed by five key parameters: base diffusivity (κ_0), color sensitivity (σ_C), temperature initialization scale (σ_T), complexity factor (α), and merging threshold (τ_m).

B.1 Hyperparameter Definitions

In this section, we provide a detailed analysis of the five hyperparameters involved in the Thermodiffusion-Guided Token Merging module. These parameters govern the initialization of the temperature field, the rate of semantic diffusion, and the final merging granularity. Table 5 summarizes the optimal values identified through empirical validation on the VRSBench and EarthVQA datasets.

Initialization Parameter (σ_T). The parameter σ_T determines the "activation" of Heat Sources.

- **Impact:** A smaller σ_T implies strict conditions for high initial temperatures; a region must be highly similar to its neighbors to be considered a core semantic object. Conversely, a larger σ_T results in a broader distribution of high-temperature initial regions, leading to larger merged areas. We set $\sigma_T = 5.0$ to balance selectivity and coverage.

Diffusion Dynamics Parameters ($\kappa_0, \sigma_C, \alpha$). These parameters define the thermal diffusivity κ_{ij} , regulating how semantic information propagates.

- **Base Diffusivity (κ_0):** Acts as a global scaling factor. A larger κ_0 accelerates the overall convergence speed but may lead to instability if the discrete time step Δt is not adjusted accordingly.
- **Color Sensitivity (σ_C):** This parameter is critical for boundary preservation. A larger σ_C (e.g., 5.0) indicates a higher tolerance (i.e., lower sensitivity) to color differences, allowing heat to flow rapidly even between regions with slight spectral discrepancies. This is essential for merging heterogeneous parts of a single object (e.g., a roof with shadows).
- **Complexity Factor (α):** This parameter incorporates texture information. A higher α amplifies diffusivity in high-frequency regions (high gradient C_i), ensuring that complex textures are homogenized quickly, while smooth regions diffuse at a standard rate.

Merging Parameter (τ_m). The final token generation is controlled by the merging threshold.

- **Merging Threshold (τ_m):** This is the decision boundary for the final aggregation. A larger τ_m allows regions with larger temperature gradients to merge, resulting in fewer tokens. We set $\tau_m = 0.03$ to achieve object-level representation.

B.2 Ablation Study on Thermodynamic Parameters

To demonstrate the impact of each hyperparameter, we designed several comparative experimental sets by ablating the optimal parameters individually. The detailed settings are listed in Table 6.



Figure 6: Visual comparison of tokenization results under different hyperparameter configurations.

Experimental Setup. We established three comparative groups (Set A, B, C) alongside our final Optimal configuration.

- **Optimal (Ours):** The balanced configuration ($\kappa_0 = 1.0$, $\sigma_C = 5.0$, $\sigma_T = 5.0$, $\alpha = 0.5$, $\tau_m = 0.03$) used in our main experiments.
- **Set A:** We simultaneously increased the base diffusivity ($\kappa_0 = 2.0$), color sensitivity ($\sigma_C = 10.0$), and temperature scale ($\sigma_T = 10.0$). This tests the model’s behavior under conditions that favor broader initial heat activation and more aggressive region aggregation.
- **Set B:** We set the complexity factor to $\alpha = 0.0$, effectively disabling the texture-aware diffusivity modulation.
- **Set C:** We significantly increased the base diffusivity to $\kappa_0 = 4.0$ to evaluate the stability of the heat equation solver under extreme high-speed diffusion.

Qualitative Analysis. The visual comparison of tokenization results under these settings is presented in Figure 6.

- **Under-segmentation in Set A:** When the parameters for diffusion, color tolerance, and temperature activation are excessively high, as in Set A, the algorithm leads to severe under-segmentation. Small but semantically distinct objects (e.g., small buildings surrounding the stadium) are incorrectly merged into the background, causing the MLLM to lose fine-grained details.
- **Boundary Noise in Set B:** By removing the texture complexity constraint ($\alpha = 0.0$), Set B fails to accurately delineate boundaries in texture-rich areas. The generated tokens become irregular and fail to align with inherent high-frequency texture transitions, confirming that texture-guided diffusion is crucial for handling the complex heterogeneity of remote sensing imagery.
- **Over-smoothing in Set C:** The extremely high base diffusivity ($\kappa_0 = 4.0$) in Set C causes semantic heat to propagate too rapidly, eroding fine-grained details before stable equilibrium boundaries can be established. Consequently, this

leads to severe boundary degradation and a significant loss of morphological fidelity in the generated tokens.

- **Superiority of Optimal Settings:** In contrast, our Optimal configuration achieves the best balance. It successfully preserves the semantic integrity of large objects while accurately separating adjacent distinct regions. The generated tokens exhibit high boundary adherence and appropriate granularity, providing a solid foundation for the subsequent MLLM visual understanding.

C Ablation on Region Proposal Dependency

To demonstrate that the performance gains of **HeatTok** stem primarily from our proposed thermodiffusion aggregation rather than a heavy reliance on a specific region proposal model, we substitute FastSAM with alternative proposal generators: SLIC [3] and SAM-H [11]. For a strictly fair comparison, the 24.0M parameter overhead of the thermodiffusion module is explicitly added to the frontend parameters for all relevant configurations. The ablation results across the sub-categories of VRSBench and EarthVQA are detailed in Table 7 and Table 8, respectively.

When using raw proposals generated by FastSAM without the thermodiffusion module (w/o Thermo.), the overall performance drops drastically (e.g., to 69.84% on VRSBench and 70.60% on EarthVQA). This confirms that relying solely on fine-grained segmentation outputs leads to semantic fragmentation and fails to provide coherent object-level tokens for the MLLM. Applying thermodiffusion aggregation yields significant accuracy improvements across all proposal generators, demonstrating that the primary performance gain is driven by the thermodiffusion aggregation module.

Notably, substituting FastSAM with the heavy-weight SAM-H yields highly competitive performance, slightly outperforming our method on specific fine-grained subsets due to its massive zero-shot priors. However, **HeatTok** reclaims the lead in the overall sample-weighted accuracy on both datasets (76.37% vs. 76.28% on VRSBench; 78.88% vs. 78.39% on EarthVQA). More importantly, the grid-prompting mechanism of SAM-H in "Everything mode" incurs a catastrophic frontend latency (1468.4 ms) and a bloated parameter overhead (624.0M), completely bottlenecking the pipeline’s efficiency. Conversely, while SLIC offers a lightweight alternative, it suffers in boundary precision and CPU-bound latency (45.2 ms), leading to a performance drop. These results comprehensively prove that **HeatTok** is fundamentally agnostic to the initial proposal generator, and FastSAM combined with thermodiffusion offers the absolute optimal trade-off among frontend latency (15.3 ms), parameter efficiency (92.0M), and downstream reasoning accuracy.

D Generalization to Fundamental Vision Tasks

To further validate the generalization capability of **HeatTok** beyond VQA tasks, we extend our evaluation to fundamental vision tasks including visual grounding and semantic segmentation.

D.1 Visual Grounding

Figure 7 presents qualitative visual grounding results on VRSBench. Compared to the standard Patch Embed tokenization, **HeatTok** produces more accurate bounding box predictions that are better aligned with object boundaries. This demonstrates that our

Table 7: Ablation on region proposal dependency on VRSBench [13]. *w/o Thermo* indicates using raw proposals without our aggregation module. *Frontend Params* strictly includes the 24.0M parameters of the thermodiffusion module where applicable. *All* represents the sample-weighted average accuracy. **Red indicates the best performance, while **blue** denotes the second best.**

Proposal Generator	Frontend Latency (ms)	Frontend Params (M)	Category	Presence	Quantity	Color	Shape	Size	Position	Direction	Scene	Reasoning	All
FastSAM (w/o Thermo)	12.1	68.0	76.53	85.27	51.56	68.78	71.82	58.55	59.88	50.52	78.59	68.74	69.84
SLIC + Thermo	45.2	24.0	82.52	90.13	55.21	75.84	76.56	62.48	65.47	53.44	82.37	72.84	74.77
SAM-H + Thermo	1468.4	624.0	84.23	91.61	56.12	77.49	78.15	64.53	67.52	55.03	83.54	74.57	76.28
FastSAM + Thermo (Ours)	15.3	92.0	84.45	91.41	56.36	77.32	78.07	64.20	67.96	55.35	83.75	74.28	76.37

Table 8: Ablation on region proposal dependency on EarthVQA [17], showing that gains stem from thermodiffusion rather than a specific frontend.

Proposal Generator	Frontend Latency (ms)	Frontend Params (M)	BasJu	RelJu	BasCo	RelCo	ObjAn	ComAn	All
FastSAM (w/o Thermo)	12.1	68.0	75.13	77.28	68.32	74.56	55.09	50.43	70.60
SLIC + Thermo	45.2	24.0	81.12	83.96	73.25	79.83	65.17	56.48	76.84
SAM-H + Thermo	1468.4	624.0	82.83	85.19	74.30	82.04	67.81	59.06	78.39
FastSAM + Thermo (Ours)	15.3	92.0	82.60	85.94	75.06	81.67	68.87	59.49	78.88

thermodiffusion-based tokenization effectively preserves the geometric integrity of objects, enabling more precise spatial localization.

D.2 Semantic Segmentation

Figure 8 visualizes the segmentation results on EarthVQA. **HeatTok** produces more accurate boundaries and better preserves the integrity of land-cover regions, demonstrating that our thermodiffusion-based tokenization extends effectively to dense prediction tasks.

E Additional Qualitative Results

E.1 Tokenization Visualization

To further validate the robustness and generalization ability of our proposed method, we provide additional visualization comparisons on randomly selected samples from the evaluation set. As shown in Fig. 10, we comprehensively compare **HeatTok** against other representative tokenization paradigms. These visualizations intuitively demonstrate that our thermodiffusion-based approach can adaptively group semantically consistent regions, preserving the structural integrity of diverse geographical objects while avoiding the severe over-segmentation and rigid geometric cuts seen in previous methods.

E.2 Case Study

In this section, we present additional remote sensing visual question answering (VQA) case studies to qualitatively evaluate the direct impact of different tokenization strategies on the reasoning capabilities of the Multimodal Large Language Model (MLLM).

Table 9 and Table 10 detail the visual question answering results alongside the corresponding tokenization visualizations for two distinct geographical scenarios (i.e., curved park layouts and meandering rivers). These cases further corroborate that the object-level

semantic integrity preserved by **HeatTok** is crucial for accurate multi-modal grounding and robust reasoning.

F Limitations and Future Work

While **HeatTok** achieves consistent improvements across diverse RS benchmarks, we acknowledge two main limitations regarding its broader applicability.

F.1 Generalization to Natural Images

Our framework is fundamentally motivated by the unique properties of RS imagery, which features extensive homogeneous regions and multi-scale, irregular geometric structures. The thermodiffusion mechanism explicitly addresses these characteristics by aggregating irregular geometries into coherent, well-bounded region-level units. While the formulation is inherently task- and domain-agnostic, standard natural images exhibit distinct object-centric characteristics. We do not presume uniform performance gains across general natural image benchmarks; extending this framework to high-resolution natural imagery remains a direction for future research.

F.2 Robustness and Failure Cases

Our ablation studies confirm that performance gains stem from the thermodiffusion-based aggregation mechanism rather than any specific region proposal method. As shown in Figure 9, thermodiffusion corrects over-segmentation and erroneous boundaries by merging fragmented proposals into coherent regions, demonstrating robustness to initial segmentation errors in complex RS scenes. However, under extremely degraded imaging conditions (e.g., severe haze or heavy fog), performance is constrained by frontend visual priors—compromised region proposals may limit overall system performance. Future work will explore domain-adaptive perception mechanisms tailored for such extreme scenarios.




Figure 7: Visual grounding comparison between Patch Embed and HeatTok on Qwen2.5-VL, highlighting improved object-boundary alignment and more precise spatial localization.




Figure 8: Qualitative segmentation results on EarthVQA, showing more accurate boundaries and better preserved land-cover integrity.




Figure 9: Robustness analysis. HeatTok corrects over-segmentation by merging fragmented proposals into coherent regions (left), but performance degrades under severe haze (right).





Figure 10: Visual comparisons of tokenization results across different paradigms. Compared to baseline methods, HeatTok successfully preserves crisp object boundaries, maintains geometric continuity, and effectively avoids over-segmentation.

Table 9: Case study on remote sensing visual question answering. We show the visual question answering results of a specific scenario along with the tokenization visualizations for different methods. **Red** indicates hallucinations or incorrect perceptions; **Green** indicates accurate alignment with the ground truth.

Remote Sensing Image & Tokenization Visualization:



Prompt: What are the land use types in this scene? What is the situation of barren land?

Ground Truth: There are **park, and agricultural areas**. There is no barren land.

Patch Embed: I can observe that there are **park, and agricultural areas** within the scene. However, it seems the **barren land is scattered** across multiple small patches.

Analysis: The uniform grid **rigidly cuts across the curved boundaries** of the park and fields. This **destruction of geometric continuity** causes the model to misinterpret local texture variations (like winding paths or dry grass) as scattered barren land.

Dynamic Grouping and Merging

ToMe: I can identify **industrial zones** alongside **agricultural areas**. The **barren land appears to be distributed** unevenly.

Chat-UniVi: Based on the image, there are **park, residential, and agricultural areas**. Fortunately, **there is no barren land** visible in this specific environment.

Quadtree: The land use types predominantly include **residential and agricultural areas**. Additionally, the **barren land is concentrated** in the lower section of the region.

HOOK: The scene is mostly **residential and commercial**. A large patch of **barren land dominates** the upper left corner.

STViT: There are **park** areas mixed with **dense residential buildings**. Some **scattered barren land** is present near the edges.

Analysis: Although these methods attempt to group adjacent tokens, the Chat-UniVi visualization reveals that they remain **inherently constrained by rigid rectangular primitives**. This inflexible spatial quantization is inadequate for delineating the continuous curved contours of the park, ultimately misleading the MLLM to **hallucinate artificial residential structures** and non-existent barren regions.

Deformable Sampling

DPT: The area is entirely a **dense urban residential zone**. A vast stretch of **barren land covers the majority** of the visible space.

GPSToken: The land use types are primarily **commercial and agricultural**. Furthermore, the **barren land is clearly located in the center** of the complex.

Analysis: The GPSToken visualization demonstrates that deformable points focus heavily on local high-frequency details but **severely distort the macro-level layout**. Because the MLLM **loses the global topological shape** of the fields, it confidently hallucinates "commercial" areas and a centralized barren patch.

Subobject and Superpixel Tokenizers

SuiT: There are **parks** and **industrial facilities**. The **barren land is adjacent** to the main roads.

SPiT: The land use types in this image include **park, residential, and agricultural areas**. Moreover, the **barren land is scattered** randomly throughout the site.

EPOC: I observe **agricultural fields** and **commercial buildings**. Small pockets of **barren land are scattered** widely.

oHT: There are **park** areas and **residential blocks**. **There is no barren land** present here.


Analysis: Superpixel algorithms like SPiT **excessively fragment** the continuous grassy regions into erratic, jagged pieces. This **over-segmentation noise** breaks the visual consistency of the park's landscaping, tricking the model into identifying these irregular fragments as scattered barren land and residential zones.

HeatTok (Ours): The dominant land use types are clearly well-maintained **park, and agricultural areas**. **There is no barren land** anywhere in the image.

Analysis: By utilizing thermodiffusion aggregation, **HeatTok elegantly preserves the continuous, sweeping curves** of the park layout and the intact agricultural fields. Maintaining this **precise geometric and semantic integrity** allows the MLLM to easily recognize the correct land use categories and firmly conclude the absence of barren land **without any hallucinations**.

Table 10: Case study on remote sensing visual question answering. We show the visual question answering results of a specific scenario along with the tokenization visualizations for different methods. Red indicates hallucinations or incorrect perceptions; Green indicates accurate alignment with the ground truth.

Remote Sensing Image & Tokenization Visualization:



Prompt: What are the water situations around the agricultural land? What are the needs for the renovation of villages?

Ground Truth: There is **clean water** near the agriculture land. The **roads** need to be **improved**.

Patch Embed: Based on the scene, I can see **dried-up water channels** near the agriculture land. The **roads** need to be **improved**, and **new residential buildings should be constructed**.

Analysis: The uniform grid partitioning **rigidly bisects the meandering river** and adjacent fields. This **spatial fragmentation** disrupts the clear water textures, causing the model to misinterpret the disjointed river segments as "dried-up channels" and hallucinate unrelated construction needs.

Dynamic Grouping and Merging

ToMe: There are **polluted streams** near the agriculture land. The **roads** need to be **improved** and **residential areas expanded**.

Chat-UniVi: There appear to be **scattered muddy pools** near the fields. The narrow dirt **roads** need to be **improved**.

Quadtree: The area seems to **lack prominent water features** near the fields. **Infrastructure** improvements and **housing** upgrades are critically needed.

HOOK: The farmland is completely **devoid of nearby water resources**. There are **no specific needs** for village renovation visible in this particular area.

STViT: Some **stagnant water** is visible. The **roadways** need to be **improved**.

Analysis: Chat-UniVi's visualization shows these methods remain **constrained by rigid rectangular primitives**. This **inflexible block-wise quantization** fails to delineate the river's continuous meandering trajectory. Consequently, the fragmented semantics mislead the MLLM into misclassifying the water as "muddy pools," triggering cascaded hallucinations of unwarranted housing upgrades.

Deformable Sampling

DPT: The area is **completely dry** without any rivers. The village needs a **completely new water supply system** due to the arid environment.

GPSToken: I **cannot detect any water** area around the agricultural land. The agricultural land needs to be **restructured** and the **buildings upgraded**.

Analysis: The GPSToken visualization illustrates that deformable sampling produces **dense but spatially fragmented focal points** that latch onto arbitrary local textures. By **discarding the macro-level topological continuity** of the river, the model completely fails to perceive the water body, hallucinating a dry environment and inventing the need for water supply systems.

Subobject and Superpixel Tokenizers

SuiT: There are **highly polluted** water bodies adjacent to the farm plots. There is a need to **improve** the dirt **roads** and **build bridges**.

SPiT: I observe **fragmented muddy water** around the agricultural land. The **roads** need **improvement**.

EPOC: I see only **dry riverbeds** in the area. The **roads** need to be **improved** for better rural access.

oHT: Yes, **contaminated ponds** are located nearby. The **roads** need to be **improved**.

Analysis: Superpixel algorithms like SPiT rely heavily on low-level pixel variations, leading to **excessive over-segmentation** of the river surface. Breaking the homogeneous water area into **fractured, jagged fragments** introduces visual noise, tricking the model into classifying it as "fragmented muddy water" and fabricating extra renovation tasks.

HeatTok (Ours): I can clearly observe that **clean water** are flowing near the agriculture land. For the renovation of the village, the dirt **roads** need to be **improved** to facilitate better transportation.

Analysis: By leveraging thermodiffusion aggregation, **HeatTok** **precisely delineates the continuous, winding geometry** of the river and the road networks. Maintaining this **object-level semantic integrity** enables the MLLM to correctly assess the "clean" state of the water and accurately pinpoint the road improvement needs **without any hallucinations**.

References

- [1] Marius Aasan, Martine Hjelkrem Tan, Nico Catalano, Changkyu Choi, and Adin Ramirez Rivera. 2026. Differentiable hierarchical visual tokenization. *Advances in Neural Information Processing Systems* 38 (2026), 87605–87634.
- [2] Marius Aasan, Odd Kolbjørnsen, Anne Schistad Solberg, and Adin Ramirez Rivera. 2024. A spitting image: Modular superpixel tokenization in vision transformers. In *European Conference on Computer Vision*. Springer, 124–142.
- [3] Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurelien Lucchi, Pascal Fua, and Sabine Süsstrunk. 2012. SLIC superpixels compared to state-of-the-art superpixel methods. *IEEE transactions on pattern analysis and machine intelligence* 34, 11 (2012), 2274–2282.
- [4] Daniel Bolya, Cheng-Yang Fu, Xiaoliang Dai, Peizhao Zhang, Christoph Feichtenhofer, and Judy Hoffman. 2022. Token merging: Your vit but faster. *arXiv preprint arXiv:2210.09461* (2022).
- [5] Delong Chen, Samuel Cahyawijaya, Jianfeng Liu, Baoyuan Wang, and Pascale Fung. 2024. Subobject-level image tokenization. *arXiv preprint arXiv:2402.14327* (2024).
- [6] Zhiyang Chen, Yousong Zhu, Chaoyang Zhao, Guosheng Hu, Wei Zeng, Jinqiao Wang, and Ming Tang. 2021. Dpt: Deformable patch-based transformer for visual recognition. In *Proceedings of the 29th ACM international conference on multimedia*. 2899–2907.
- [7] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xi-aohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. 2020. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929* (2020).
- [8] Leonhard Euler. 1845. *Institutionum calculi integralis*. Vol. 4. impensis Academiae imperialis scientiarum.
- [9] H Huang, X Zhou, J Cao, R He, and T Tan. [n. d.]. Vision transformer with super token sampling. *arXiv 2022. arXiv preprint arXiv:2211.11167* ([n. d.]).
- [10] Peng Jin, Ryuichi Takanobu, Wancai Zhang, Xiaochun Cao, and Li Yuan. 2024. Chat-univi: Unified visual representation empowers large language models with image and video understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 13700–13710.
- [11] Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. 2023. Segment anything. In *2023 IEEE/CVF international conference on computer vision (ICCV)*. IEEE, 3992–4003.
- [12] Jaihyun Lew, Soohyuk Jang, Jaehoon Lee, Seungryong Yoo, Eunji Kim, Saehyung Lee, Jisoo Mok, Siwon Kim, and Sungroh Yoon. 2024. Superpixel tokenization for vision transformers: Preserving semantic integrity in visual tokens. *arXiv preprint arXiv:2412.04680* (2024).
- [13] Xiang Li, Jian Ding, and Mohamed Elhoseiny. 2024. Vrsbench: A versatile vision-language benchmark dataset for remote sensing image understanding. *Advances in Neural Information Processing Systems* 37 (2024), 3229–3242.
- [14] Tomer Ronen, Omer Levy, and Avram Golbert. 2023. Vision transformers with mixed-resolution tokenization. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*. IEEE, 4613–4622.
- [15] Run Shao, Zhaoyang Zhang, Chao Tao, Yunsheng Zhang, Chengli Peng, and Haifeng Li. 2024. Homogeneous tokenizer matters: Homogeneous visual tokenizer for remote sensing image understanding. *ISPRS Journal of Photogrammetry and Remote Sensing* 218 (2024), 294–310.
- [16] Olga Sorkine, Daniel Cohen-Or, Yaron Lipman, Marc Alexa, Christian Rössl, and H-P Seidel. 2004. Laplacian surface editing. In *Proceedings of the 2004 Eurographics/ACM SIGGRAPH symposium on Geometry processing*. 175–184.
- [17] Junjue Wang, Zhuo Zheng, Zihang Chen, Ailong Ma, and Yanfei Zhong. 2024. Earthvqa: Towards queryable earth via relational reasoning-based remote sensing visual question answering. In *Proceedings of the AAAI conference on artificial intelligence*, Vol. 38. 5481–5489.
- [18] David Vernon Widder. 1976. *The heat equation*. Vol. 67. Academic Press.
- [19] Zhengqiang Zhang, Rongyuan Wu, Lingchen Sun, and Lei Zhang. 2026. Gpstocken: Gaussian parameterized spatially-adaptive tokenization for image representation and generation. *Advances in Neural Information Processing Systems* 38 (2026), 11218–11249.
- [20] Xu Zhao, Wenchao Ding, Yongqi An, Yinglong Du, Tao Yu, Min Li, Ming Tang, and Jinqiao Wang. 2023. Fast segment anything. *arXiv preprint arXiv:2306.12156* (2023).