


Prac 8

UML



Description

In Sort class:

`swap(int* x, int*y) : swap two values of two inputs;`

In Bubble Sort class:

`Void bubblesort(int arr[], int array Length):` take two inputs in, give out sorted array using bubble sort.

In quicksort class:

`Int partition(int arr[], int low, int high):` take three inputs, it is the first step of quicksort: partition. Basically, leave all the number which are smaller than the pivot to left side, and leave all the number which are greater than pivot to right side.

`Void quicksort(arr[], int low, int high):` take three inputs, it is the second step of quicksort. Recursively call itself until all the elements are sorted.

In recursivelybinarySearch class:

`Int binarySearch(int arr[], int l, int r, int x):` take four inputs. Using binary search to find the position of x is.

Main

Call all the functions, print out whether 1 is in the input or not. Then print out sorted array using quicksort.

Tests

Input: 1 345 765865 324 52 7 65 2

Expected output: True 1 2 7 52 65 324 345 765865

Input: 1 1 1 1 1 1 1 1 1 1 1 1 1

Expected output: True 1 1 1 1 1 1 1 1 1 1 1 1 1

Input: 0 0 0 0 0 0 0 0 0 0

Expected output: False 0 0 0 0 0 0 0 0 0 0

Input: -5 -2 -4 -1 0 -3 2

Expected output: False -5 -4 -3 -2 -1 0 2

Input: 123 321 12345 54321 1

Expected output: true 1 123 321 12345 54321

Input: 3 93 54872 82173 4

Expected output: false 3 4 93 54872 82173