

Fall Semester 2015

Line following robot

Group 2

2. Semester IT-Technology

Group members: Benjamin Nielsen - Henrik Jensen - Martin Nonboe - Nikolaj Bilgrau

Supervisor: Jesper Kristensen - Steffen Vutborg

Title:

Line following robot

Project Period:

2. Semester | Spring semester 2016

Projectgroup:

Group 2

Medvirkende:

Benjamin Nielsen

Henrik Jensen

Martin Nonboe

Nikolaj Bilgrau

Supervisor:

Jesper Kristensen

Steffen Vutborg

Pages: TBD

Appendices: TBD

Completed TBD

Introduction

This project was written by group 2, for the second semester on the IT-electronics education at university college Nordjylland, Sofiendalsvej 60. The project goal is to make a line following robot.

Benjamin Nielsen

Henrik Jensen

Martin Nonboe

Nikolaj Bilgrau

Table of Contents

1	Requirements specification	1
2	Hardware section	2
2.1	Description of the hardware structure and functionality	2
2.2	Hardware diagram	2
2.3	Selection of sensor	2
2.4	Analog-to-digital converter (ADC)	4
2.5	The Arduino Uno32 board	4
2.6	The motor shield - PKA03	5
2.7	The blue-tooth transmitter - BlueSMIRF Silver	5
3	Software section	6
3.1	Description of the software structure and functionality	6
3.2	Description of the PID controller	6
3.3	Description of the Pulse width modulator - PWM	10
3.4	Future development?	11
3.5	The GUI	11
4	Test	12
4.1	Testing round 1	12
5	Conclusion	13
6	Appendices	14
6.1	Group collaboration agreement	14
7	List of references	18
	List of Figures	19
	List of Tables	20

Glossary

ADC Analog-digital conversion

PID Proportional-integral-derivative controller

THT Through-hole-technology

3Dprint Printing something in 3 dimensions

PWM Pulse-width modulation

MCU Micro controller unit

Requirements specification

1

The following section will describe the specific requirements that have been decided to fulfil to the general requirements as shown in the project description.

- Project must include light sensors
- Implement motor control
- Should make use of the Pic32 MCU
- Software will be written in MPLABX
- Autonomous operation
- The product must make use of feedback concept e.g. a PID algorithm
- A function & performance test is to be conducted

Hardware section 2

2.0.1 Hardware diagram

2.1 Description of the hardware structure and functionality

In the following section, the hardware parts and functions will be introduced and described. The following part consists of sensor selection, ADC, pic uno32 board & motor-shield.

2.2 Hardware diagram

The micro-controller is connected to the motor-shield and the motor-shield is then powering both motor 1 and motor 2. The sensor-array is sending the collected data to the micro-controller every 25 ms, the micro-controller then sends it further to the bluetooth unit. The bluetooth unit then writes the data to the terminal.




Figure 2.1: Block diagram showing the hardware.

2.3 Selection of sensor

The table shows a comparison of the two sensors that were taken into consideration for the project, that is to show the price difference and the utility from sensor to sensor. (*fig 2.1*)


Table 2.1: Table showing the sensors in consideration

Name	QRE1113 Board	OPB704
Max sensor distance	3mm	3.8mm
Forward current	50mA	40mA
Mounting	On print	In casing
Price	19.43DKK	42.55DKK


2.3.1 The OPB704

The selected sensor for the line following robot will not be the OPB704 after all. It was supposed to be. But because of interface and coding problems it is no longer the sensor that will be used.

The sensor was chosen from a range of criteria, most important being the optimal sensor distance and the easier mounting method. This method makes it more efficient to add several sensors in an array, which will be done with a 3D-printed mount.




(a) The sensor OPB 704




(b) 3D printed sensor array module

2.3.2 The QRE1113 board(Analog)

The new sensor now used is the QRE1113, the way the sensor works is an LED will shoot out an infra-red beam that then should be reflected back into the sensitive photo transistor. When the photo transistor is receiving an infra-red beam the output will begin to lower. This sensor is easy to mount and will be done so to a 3D printed mount. The sensor is commonly used within the line following robot business which is a good indicator that it's reliable.



(a) QRE1113 Sensor with own mount



(b) 3D printed sensor array module with the QRE1113

2.4 Analog-to-digital converter (ADC)

The purpose of the ADC is to convert the analog data from the sensors to digital data that can be managed by a computer - this allows data received from the blue-tooth transmitter on the product to be processed into readable data more easily, which is great for showing how the sensors are reacting. The sensors themselves cannot discern what they actually need to read, the sensors just read anything they can see and send that signal.

Analog signals can have a significant amount of noise - since any received noise is interpreted as part of the signal, a digital signal is not only more easy to work with, it will also provide more precise data. This will make for more accurate readings on the tachometer on the robot, which allows even more finely tuned monitoring of the robot and its working processes.

ADC diagram

TBD? Er det relevant?

This products usage of ADC

Hvordan har vi gjort det i vores tilfælde? «««< HEAD TBD

2.5 The Arduino Uno32 board

Our main computing core is at the Arduino Uno32 board. The board was selected both because of previous experiences, and because it met the set requirements perfectly - most importantly it has twelve analog inputs to handle our array of seven sensors. This board utilizes the PIC32MX320F128 microcontroller, which features a 32-bit processing core running at 80Mhz with 128K of flash program memory and

16K SRAM data memory. This board allowed the most important aspects of the project to become reality; namely a GUI showing both the ADC readings as well as visualizing the sensor inputs, plenty of analog inputs to allow for the sensor array, and Bluetooth transmission of data from the robot unto a computer.

The board is compatible for use with MPLAB IDE and the PICKit3 debugger.

2.6 The motor shield - PKA03

The motor shield was chosen because it is compatible with the Uno32 board, and fits perfectly within the scope of the project. It controls both motors and receives power from the 7.2 V lithium-ion battery pack mounted on the chassis itself. The motor shield is instrumental in providing motor controls to the product. To do this, it utilizes a specific electric circuit, called an H bridge.

2.6.1 The H bridge

An H bridge is a circuit that allows a voltage to be applied across a load in either direction. The purpose of this in the case of this project is to enable controls of the two motors in a way so that they can function individually, and both drive forwards and backwards.

At first, there were experiments with custom prints and a purpose-built h bridge on the first iteration of the motor shield. However after testing, it proved faulty and was changed to accommodate time constraints. ===== TBD samarbejd med personen bag det »»»»> origin/master

2.7 The blue-tooth transmitter - BlueSMIRF Silver

The robot utilizes the BlueSMIRF Silver blue-tooth transmitter made by Sparkfun. Its function is to send data from the ADC and pulse width modulator (see the software section) to a C# GUI run on a computer. This way, it is possible to monitor both the inputs the robot is receiving, as well as the logic behind the steering. It allows for any stream between 2400 to 115200 bps.

Software section 3

3.0.1 Software diagram

TBD Software diagram

3.1 Description of the software structure and functionality

The following section will introduce the software segment, based on the required specifications. The design will shown in the form of a flowchart. The section consists of the PID controller & the Pulse width modulator. TBD Softwarebeskrivelse og underafsnit

3.2 Description of the PID controller

A PID controller continuously calculates an error value as the difference to a reference point and a measured process variable.

PID is an abbreviation for a proportional-integral-derivative controller, it is a control loop feedback mechanism. The controllers job is to minimize the error value for the given devices running time. In the case of this project the reference point is the line to follow and the PID will allow the MCU to adjust the power to the engines, to steer accordingly to said reference point.

$$F(t) = K_p e(t) + K_i \int_0^t e(\tau) d\tau + K_d \frac{de(t)}{dt}$$




Figure 3.1: Block diagram, showing the idea of PID controller.

(a) Credits: www.wikipedia.org/wiki/PID_controller

3.2.1 Proportional control(P)

The proportional part creates an output value that is proportionally related to the current error value, this value can be tuned by multiplying the error by a constant K_p . A high proportional gain results in a large change in the output for a given change in the error.

$$P_{\text{out}} = K_p e(t)$$

If the proportional gain is too high, the system can become unstable. Contrarily, a small gain will result in the device adjusting too slowly, which decreases overall efficiency and in the case of this project, it will end up being detrimental to the steering accuracy.




Figure 3.3: K_p with 3 values. (K_i , K_d held constant)

(a) Credits: www.wikipedia.org/wiki/PID_controller

3.2.2 Steady-state error

When looking at figure 3.2 the reference point is the blue line and the feedback line is the green, the two lines merge up and the steady-state is achieved. When the lines don't merge, but the feedback line is slightly above or under the reference point. This steady-state error can be minimized by adjusting the proportional and integral term.

3.2.3 Integral control(I)

The integral controller is contributing proportionally to both the magnitude of the error and the duration of the error.

The integral in a PID controller is the sum of the instantaneous error over time and gives the accumulated offset that should have been corrected previously.

The controller output equals the accumulated error multiplied by the integral gain(K_i)

$$I_{\text{out}} = K_i \int_0^t e(\tau) d\tau$$

The integral part accelerates the movement of the process towards the reference point. Since the integral term correlates to accumulated errors from the past, it can cause the present value to overshoot the reference value.

3.2.4 Derivative control(D)

The derivative of the process error is calculated by determining the slope of the error over time and multiplying this rate of change by the derivative gain K_d . The magnitude of the contribution of the derivative term to the overall control action is termed the derivative gain, K_d .




Figure 3.5: K_i shown with 3 values.

(a) Credits: www.wikipedia.org/wiki/PID_controller

The derivative term is given by:

$$D_{\text{out}} = K_d \frac{de(t)}{dt}$$

The derivative action predicts system behaviour and utilizes this to improve the settling time and stability of the system. An ideal derivative is not causal, so that implementations of PID controllers include an additional low pass filtering for the derivative term, to limit the high frequency gain and noise.

3.2.5 Loop tuning

Tuning the loop is the term used to describe the adjustments of the PID's control parameters (proportional band/gain, integral gain/reset, derivative gain/rate) to the optimal values for the given control scheme.

Stability is the first requirement; however systems can differ greatly, and different applications may have different requirements and these may even conflict with each other. For example, high speed and high accuracy often cancel each other out, because high speed may cause overshooting, while high accuracy is slow.

The ideal realistic behaviour is both as fast as possible, while also having minimum overshoot and oscillation.




Figure 3.7: K_d shown with 3 values.

(a) Credits: www.wikipedia.org/wiki/PID_controller

Even though the process seems simple, with only three variables, it can be challenging to achieve, because it must satisfy the criteria despite being within the limitations of PID control. While adjusting the PID can seem conceptually intuitive, and while most PIDs may perform acceptably with default controls, they may very well also have an unsatisfactory performance.

This can generally be fixed through optimisation and tuning, either through computer simulations or manual testing. In this case, there was used manual tuning of the numbers.

3.2.6 Stability

If the parameters of the PID controller are set incorrectly the process input can become unstable. This means the controllers output becomes divergent, which can be limited by saturation and mechanical breaking.

3.2.7 Manual tuning

When a system must be online at all times a method for tuning is to first set K_i and K_d values to zero. Increase K_p until the loop output oscillates, setting K_p at approximately half the value for a "quarter amplitude decay" type response.

Then increase K_i until any set off is corrected in sufficient time for the process. Adding too much K_i will however cause an instability. Finally, increase K_d , if required at all, until the loop is acceptably quick to reach its reference after a load disturbance.

A fast PID loop tuning process usually overshoots slightly to reach the reference point faster.

In the case of systems that can't accept overshoot, an over-damped closed-loop system is best suited, which requires K_p setting significantly less than half that of the K_p setting that was causing the oscillation.

TBD (Vores fremgangsmåde med PID alt efter om "THE D - giggedy" skal bruges)

Table 3.1: Manual tuning

Parameter	Rise time	Overshoot	Settling time	Steady-state error	Stability
K_p	Decrease	Increase	Small change	Decrease	Degrade
K_i	Decrease	Increase	Increase	Eliminate	Degrade
K_d	Minor change	Decrease	Decrease	No effect in theory	Improves if K_d is small

Table 3.1 explained

Table 3.1 gives an informative overview of what the different parameters does when tuned manually.

- To minimize the rise time, decrease K_p
- To eliminate the steady-state error, increase K_i
- To reduce the overshoot and settling time, decrease K_d

3.3 Description of the Pulse width modulator - PWM

A pulse width modulation technique used to encode a message into a pulsing signal. Its primary use is to control the power supply of electronic devices - the case of this project; this means the motors. The average voltage and amplitude output to the motors is altered by rapidly switching between an 'on' and 'off' state. This way, the average output is easily altered by changing the proportions between the on and off state. The longer the switch is set to on compared to off, the higher the average supply will be. Pulse-width modulation utilizes a rectangular pulse where the width of the pulse is modulated to get the variation in the average value of the waveform. Given the pulse waveform $f(t)$ over the period T , low value y_{\min} and high value y_{\max} and duty cycle D , the average waveform is given by:

$$\bar{y} = \frac{1}{T} \int_0^T f(t) dt$$

This expression can be simplified where $y_{\min} = 0$ as $\bar{y} = D \cdot y_{\max}$. From this it can be observed that the average value of the signal (\bar{y}) has a direct correlation with the duty cycle D .

$$\begin{aligned}
\bar{y} &= \frac{1}{T} \left(\int_0^{DT} y_{\max} dt + \int_{DT}^T y_{\min} dt \right) \\
&= \frac{1}{T} (D \cdot T \cdot y_{\max} + T(1 - D)y_{\min}) \\
&= D \cdot y_{\max} + (1 - D) y_{\min}
\end{aligned}$$

This expression can be simplified where $y_{\min} = 0$ as $\bar{y} = D \cdot y_{\max}$. From this it can be observed that the average value of the signal (\bar{y}) has a direct correlation with the duty cycle D .

3.3.1 Duty cycles

The duty cycle describes the proportion of 'on' compared to any given period of runtime for the device. The duty cycle is described as a percentage, where 100% means that it's turned on the entire time, where 10% would be a tenth of the time. TBD Vores duty cycle

3.4 Future development?

TBD er det nødvendigt?
evt, chassis, LCD osv.

3.5 The GUI

The project utilizes a GUI written in C# , it shows a graphical representation of the sensor load, as well as which motor is running in accordance to the PID. The GUI has controls to set the COM-port as well as the baud rate, and a button prompt to connect and disconnect the robots blue-tooth transmission. It also features a decision history on the right (TBD - er det der stadig?) and a terminal in the bottom, showing all the data sent from the ADC on the robot.




Figure 3.9: Screenshot of the C# GUI used to monitor the sensor readings.

4.1 Testing round 1

4.1.1 Test description

To make sure the product as a whole is working according to plan, testing must be done. First the components must be tested, this is done individually for each component to make sure there are no errors or fails when the product is built. The purpose of integration testing is to detect any inconsistencies between the software units that are integrated together. Testing is also done to watch the behavior of the product and tweak it.

4.1.2 Board Testing

TBD virker boardet?

4.1.3 Unit Testing

TBD testing af individuelle dele

4.1.4 Integration Testing

TBD testing af interfacet og evt samarbejde mellem enkelte dele

4.1.5 System Testing

TBD testing af systemet som helhed

4.1.6 Acceptance Testing

TBD testing af systemet som helhed. Acceptabel ydeevne?

Conclusion 5

TBD Konklusion

Appendices 6

6.1 Group collaboration agreement

6.1.1 Contact Information

Table 6.1: Contacts

Benjamin Nielsen	Tlf: 30427645	@: yipiyuk5@gmail.com
Henrik Jensen	Tlf: 28568934	@: henrik_kort@hotmail.com
Martin Nonboe	Tlf: 23827566	@: nonsens_4@hotmail.com
Nikolaj Bilgrau	Tlf: 29802715	@: nikolajbilgrau@gmail.com

6.1.2 Workflow

- Every friday after 12:00 is expected work consisting of three hours.
- If you aren't able of attending for scheduled study day. - Notice must be given to the project team.

6.1.3 Deadline

- Hand in June 7th.

6.1.4 Milestones and goals

In may there is listed a workshop from the 17-23 May. This was postponed and used for project days instead.

April 2016

MONDAY	TUESDAY	WEDNESDAY	THURSDAY	FRIDAY	SATURDAY	SUNDAY
28	29	30	31	1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20 Project day - Tidsplan, rapportstruktur	21	22	23	24
25	26 Project day - Argumentation for komponenter	27	28 Project day -	29 Project day Shield	30 Finish	1
2	3	NOTES				

Figure 6.1: 4 Work days in April

May 2016

MONDAY	TUESDAY	WEDNESDAY	THURSDAY	FRIDAY	SATURDAY	SUNDAY
25	26	27	28	29	30	1
2	3	4	5	6 Project day(Halv helligdag) - Hardware done, software start	7	8
9	10	11	12	13 Project day - Start testing(motor)	14	15
16	17 WORKSHOP	18 WORKSHOP	19 WORKSHOP	20 WORKSHOP	21	22
23 WORKSHOP	24	25 Project day - Software done	26	27 Project day -	28	29
30 Project day	31 Project day - Testing done	NOTES				

Figure 6.2: 6 Work days in May

June 2016

MONDAY	TUESDAY	WEDNESDAY	THURSDAY	FRIDAY	SATURDAY	SUNDAY
30	31	1	2	3	4	5
		Project day - Rapport	Project day - Rapport	Project day - Rapport		
6	7	8	9	10	11	12
Project day - Rapport	<u>!!!Aflevering!!!</u> <u>Kl 12.00!</u>					
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30	1	2	3
4	5	NOTES				

Figure 6.3: 4 Work days in June

List of references 7

TBD list of references

PID:

https://en.wikipedia.org/wiki/PID_controller#/media/File:PID_en_updated_feedback.svg

https://en.wikipedia.org/wiki/PID_controller#Proportional_term

<http://saba.kntu.ac.ir/eecd/pcl/download/PIDtutorial.pdf>

<http://blog.opticontrols.com/archives/1066>

https://en.wikipedia.org/wiki/PID_controller#Steady-state_error

https://en.wikipedia.org/wiki/PID_controller#Integral_term

https://en.wikipedia.org/wiki/PID_controller#Derivative_term

https://en.wikipedia.org/wiki/PID_controller#Manual_tuning

https://en.wikipedia.org/wiki/PID_controller#Control_loop_basics

<http://blog.opticontrols.com/archives/1066>

PWM:

https://en.wikipedia.org/wiki/Pulse-width_modulation

List of Figures

2.1	Block diagram showing the hardware.	2
3.1	Block diagram, showing the idea of PID controller.	6
3.3	K_p with 3 values. (K_i , K_d held constant)	7
3.5	K_i shown with 3 values.	8
3.7	K_d shown with 3 values.	9
3.9	Screenshot of the C# GUI used to monitor the sensor readings.	11
6.1	4 Work days in April	15
6.2	6 Work days in May	16
6.3	4 Work days in June	17

Page

List of Tables

2.1	Table showing the sensors in consideration	3
3.1	Manual tuning	10
6.1	Contacts	14
		Page