

Category: Facilities Management & Safety (Internal)

Document ID: doc_19_evacuation_protocol

Effective Date: January 1, 2026

Revision: 2.1

VoltVibe Corporate Emergency Preparedness & Evacuation Protocol

1. Emergency Response and Building Scope

This internal document details the evacuation routes, assembly zones, and coordinator duties for VoltVibe's primary corporate offices and logistics centers. All personnel must familiarize themselves with this protocol. Given the presence of hazardous chemical materials in the battery testing zones, emergency evacuations must be conducted promptly, prioritizing human safety and orderly exit routing over equipment protection.

2. Emergency Evacuation Routing

In the event of a fire, toxic gas warning, or physical building damage, the building alarm system will sound. All personnel must exit using the nearest emergency exit stairs. Elevators are automatically disabled. Standard exit routing zones are outlined in the table below:

Office Zone / Floor	Primary Stairwell Route	Emergency Assembly Area
Floor 1 & 2 (Office)	East Exit Stairwell	Assembly Area A (North Lot)
Floor 3 (Engineering)	West Exit Stairwell	Assembly Area A (North Lot)
Bay 4 (Warehouse)	Loading Dock Exit Gates	Assembly Area B (South Lot)
Bay 4-C (HAZMAT Vault)	South Fire Escape Door	Assembly Area B (South Lot)

2.1 Heavy Machinery Shutdown Guidelines

Before exiting, forklift operators and heavy machinery users must safely park their vehicles. Forklifts must be parked in their designated charging bays with the forks lowered completely to the floor and the parking brake engaged. This prevents the vehicle from blocking emergency fire doors or hindering emergency vehicle access to the loading docks (in accordance with doc_11_forklift_safety.pdf). Operators must leave their ignition keys in the dashboard in case emergency responders need to move the machinery.

2.2 Assembly Areas and Headcount Controls

Once outside, employees must report to their assigned assembly area. Fire Wardens will utilize the digital badge access log to perform headcounts. Employees must remain in their assembly area until the Incident Commander issues an official 'all-clear' notification. Do not re-enter the building to retrieve personal belongings under any circumstances.

2.3 The Emergency Alarm Conflict (Safety Discrepancy)

THE SAFETY CONFLICT: Section 2.3 of this document states that in the event of any localized smoke detection or battery casing heat spike inside the Bay 4 warehouse facility, fire wardens must immediately pull the manual fire alarm and initiate a full building evacuation. This directive directly conflicts with Section 4.2 of [doc_23_warehouse_safety_protocol.pdf](file:///E:/agy/router/AI-support-routing-system/data/documents/doc_23_warehouse_safety_protocol.pdf), which permits holding the evacuation if the thermal event is entirely contained inside the Class 9 HAZMAT isolation vault (Bay 4-C) and temperature rise is documented as under 3°C per minute. To resolve this discrepancy during drills, fire wardens must wait for the supervisor's directive before pulling the fire pull station, provided the vault door is fully sealed.