UNF
COPY (barcode, book_callno, book_title, (author_name,) (subject_name,) book_discription, publisher_name, publisher_country, publisher_state, publisher_city, book_pubDate, book_edtion, book_pages, book_language, book_notes, isbn_no, isbn_type, branchNo, branchName, copy_status)

1NF
COPY (barcode, book_callno, book_title, book_discription, publisher_name, publisher_country, publisher_state, publisher_city, book_pubDate, book_edtion, book_pages, book_language, book_notes, isbn_no, isbn_type, branchNo, branchName, copy_status)

barcode -> book_callno, book_title, book_discription, publisher_name, book_pubDate, book_edtion, book_pages, book_language, book_notes, isbn_no, branchNo, copy_status FULL
isbn_no -> isbn_type TRANSITIVE
branchNo -> branchName TRANSITIVE
publisher_name -> publisher_country, publisher_state, publisher_city TRANSITIVE

WRITE (*barcode*, author_name)

COPYSUBJECT (*barcode*, subject_name)

2NF
No partial dependency

3NF
COPY (barcode, book_callno, book_title, book_discription, publisher_name, book_pubDate, book_edtion, book_pages, book_language, book_notes, isbn_no, branchNo, copy_status)
barcode -> book_callno, book_title, book_discription, publisher_name, book_pubDate, book_edtion, book_pages, book_language, book_notes, isbn_no, branchNo, copy_status FULL

PUBLISHER (publisher_name, publisher_country, publisher_state, publisher_city)
publisher_name -> publisher_country, publisher_state, publisher_city FULL

ISBN (isbn_no, isbn_type)
isbn_no -> isbn_type FULL

BRANCH (branchNo, branchName)
branchNo -> branchName FULL

WRITE (*barcode*, author_name)

COPYSUBJECT (*barcode*, subject_name)