

生物信息学

天津医科大学
生物医学工程与技术学院

2015-2016 学年上学期 (秋)
2014 级生信班

第五章 基因组功能注释分析

伊现富 (Yi Xianfu)

天津医科大学 (TJMU)
生物医学工程与技术学院

2015 年 10 月



章节内容概览

5.1,5.2 基因组功能注释分析基础

- ① 基础知识：组装版本，坐标系统，常用格式，逻辑运算模式
- ② 准备工作：坐标转换，格式转换，逻辑运算
- ③ 扩展知识：文本文件与文本编辑器

5.3 基因组功能的高级注释

- ① 高级注释：变异位点注释，富集分析，序列标识
- ② 扩展知识：box plot，解析图表

5.3 Galaxy 分析平台

- ① Galaxy 分析平台：简介，使用
- ② 扩展知识：数据处理三段论

教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析

- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题

教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20

复习思考题



基因组注释 (genome annotation)

从原始的基因组核酸序列中挖掘有用的生物学信息并阐释其生物学含义，包括基因组结构注释和基因组功能注释两大部分。

基因组结构注释 (structural annotation)

在基因组序列中寻找基因等功能元件并明确其基本结构。

基因组功能注释 (functional annotation)

在结构注释的基础上，将进化保守性 (evolutionary conservation) 和基因本体论 (gene ontology) 等元数据 (meta-data) 与功能元件对应起来，找到其生物学功能。



基因组注释 (genome annotation)

从原始的基因组核酸序列中挖掘有用的生物学信息并阐释其生物学含义，包括基因组结构注释和基因组功能注释两大部分。

基因组结构注释 (structural annotation)

在基因组序列中寻找基因等功能元件并明确其基本结构。

基因组功能注释 (functional annotation)

在结构注释的基础上，将进化保守性 (evolutionary conservation) 和基因本体论 (gene ontology) 等元数据 (meta-data) 与功能元件对应起来，找到其生物学功能。



基因组注释 (genome annotation)

从原始的基因组核酸序列中挖掘有用的生物学信息并阐释其生物学含义，包括基因组结构注释和基因组功能注释两大部分。

基因组结构注释 (structural annotation)

在基因组序列中寻找基因等功能元件并明确其基本结构。

基因组功能注释 (functional annotation)

在结构注释的基础上，将进化保守性 (evolutionary conservation) 和基因本体论 (gene ontology) 等元数据 (meta-data) 与功能元件对应起来，找到其生物学功能。



基因组注释


- 结构注释 ← 实验手段，单个基因
 - 限制性酶切位点分析、开放阅读框分析、启动子分析、CpG 岛识别
 - 重复序列分析、基因识别
 - mRNA 选择性剪接分析
- 功能注释 ← 组学时代，复杂疾病
 - 变异位点的注释
 - 基因集富集分析
 - 生物学通路分析
 - 相互作用网络分析
 - 分子进化分析



- 基因组组装版本
- 基因组坐标系统
- 注释常用格式
- 文本编辑器
- 坐标的逻辑运算



Sequence to Variation Workflow



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20


复习思考题



- These sequences were mapped to human and mouse genomes sequences ([hg18 and mm9](#), respectively) using BLASTN.
- We used DNA sequences from the human and mouse genome assemblies [hg18 and mm9](#).
- Currently there are 25,000 genes annotated in the human ([hg18](#)) and mouse ([mm9](#)) genome, which comprise less than 3% of the genome (UCSC genome browser; <http://genome.ucsc.edu/>).
- The [GRCh37/hg19](#) and [GRCm38/mm10](#) assemblies at the UCSC genome browser (<http://genome.ucsc.edu/>) were used for mapping the chromosomal defect and gene annotations.
- The genome assemblies from which the sequences obtained were Dec 2011 ([GRCm38/mm10](#)), Feb 2009 ([GRCh37/hg19](#)) and Nov 2004 ([Baylor3.4/rn4](#)) for mouse, human and rat respectively.



组装版本 | XP vs. Win7



基因组序列不是确定的吗？也需要版本升级？

SPECIES	UCSC	DATE	NCBI
Human	hg19	Feb. 2009	Genome Reference Consortium GRCh37
	hg18	Mar. 2006	NCBI Build 36.1
	hg17	May 2004	NCBI Build 35
	hg16	Jul. 2003	NCBI Build 34
Mouse	mm10	Dec. 2011	Genome Reference Consortium GRCm38
	mm9	Jul. 2007	NCBI Build 37
	mm8	Feb. 2006	NCBI Build 36
	mm7	Aug. 2005	NCBI Build 35

human: *Homo sapiens*; mouse: *Mus musculus*

hg: human genome; GRC: Genome Reference Consortium



基因组序列不是确定的吗？也需要版本升级？

SPECIES	UCSC	DATE	NCBI
Human	hg19	Feb. 2009	Genome Reference Consortium GRCh37
	hg18	Mar. 2006	NCBI Build 36.1
	hg17	May 2004	NCBI Build 35
	hg16	Jul. 2003	NCBI Build 34
Mouse	mm10	Dec. 2011	Genome Reference Consortium GRCm38
	mm9	Jul. 2007	NCBI Build 37
	mm8	Feb. 2006	NCBI Build 36
	mm7	Aug. 2005	NCBI Build 35

human: *Homo sapiens*; mouse: *Mus musculus*

hg: human genome; GRC: Genome Reference Consortium

基因组序列不是确定的吗？也需要版本升级？

SPECIES	UCSC	DATE	NCBI
Human	hg19	Feb. 2009	Genome Reference Consortium GRCh37
	hg18	Mar. 2006	NCBI Build 36.1
	hg17	May 2004	NCBI Build 35
	hg16	Jul. 2003	NCBI Build 34
Mouse	mm10	Dec. 2011	Genome Reference Consortium GRCm38
	mm9	Jul. 2007	NCBI Build 37
	mm8	Feb. 2006	NCBI Build 36
	mm7	Aug. 2005	NCBI Build 35

human: *Homo sapiens*; mouse: *Mus musculus*

hg: human genome; GRC: Genome Reference Consortium



- UCSC liftOver tool：支持 BED 和 “chrN:start-end” 格式的输入
- Galaxy（基于 UCSC liftOver tool）：支持 BED、GFF 和 GTF 格式的输入
- CrossMap：支持 SAM/BAM、Wiggle/BigWig、BED、GFF/GTF 和 VCF 格式的输入，输出对应格式
- NCBI Remap：支持 BED、GFF、GTF 和 VCF 等格式的输入
- Ensembl assembly converter (2015 年退休, CrossMap 继位)：支持 BED、GFF、GTF 和 PSL 格式的输入，但输出都是 GFF 格式的
- pyliftover：仅支持点坐标 (point coordinates) 的转换，无法对区段 (ranges) 坐标进行转换



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19


总结与答疑

20



复习思考题





坐标系统 | 坐标轴




坐标系统 | 坐标轴



坐标系统 | 坐标轴



坐标系统 | 坐标轴



hg19

- SNP, rs1800468: "chr19 41860587"; "chr19:41860587"
- gene, *SAMD11*: "chr1 861121 879961"; "chr1:861121-879961"

坐标系统 | 两大系统

序列

0-based index	0	1	2	3	4	5	6	7
Sequence	A	A	T	T	G	G	C	C
1-based index	1	2	3	4	5	6	7	8

TG 的坐标

- 0-based, half-open: [3,5)
- 1-based, fully-closed: [4,5]

实例

- 0-based: BED、BAM、PSL、dbSNP、Table Browser
- 1-based: GFF、VCF、SAM、Wiggle、DAS、Genome Browser

坐标系统 | 两大系统

序列

0-based index	0	1	2	3	4	5	6	7
Sequence	A	A	T	T	G	G	C	C
1-based index	1	2	3	4	5	6	7	8

TG 的坐标

- 0-based, half-open: [3,5)
- 1-based, fully-closed: [4,5]

实例

- 0-based: BED、BAM、PSL、dbSNP、Table Browser
- 1-based: GFF、VCF、SAM、Wiggle、DAS、Genome Browser

坐标系统 | 两大系统

序列

0-based index	0	1	2	3	4	5	6	7
Sequence	A	A	T	T	G	G	C	C
1-based index	1	2	3	4	5	6	7	8

TG 的坐标


- 0-based, half-open: [3,5)
- 1-based, fully-closed: [4,5]

实例

- 0-based: BED、BAM、PSL、dbSNP、Table Browser
- 1-based: GFF、VCF、SAM、Wiggle、DAS、Genome Browser


坐标系统 | 类比

first floor




坐标系统 | 类比

first floor



数组



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20

复习思考题



格式 | 文件格式



EPS



FLA



HTML



GIF



IND



PHP



PPT



PDF



XLS



DOC



MOV



CSS



WAV



JPG



ZIP



MP3

格式 | FASTA


```
>gi|183121|gb|M29645.1|HUMGFI Human insulin-like growth factor II mRNA, complete cds  
CAGGGGCCAAGAGTCACCAACCGAGCTGTGTGGAGGAGGTGGATTCCAGCCCCAGCCCCAGGGCTCT  
GAATCGCTGCCAGCTCAGCCCCCTGCCAGCCTGCCACAGCCTGAGCCCCAGCAGGCCAGAGAGCCA  
GTCCTGAGGTGAGCTGCTGTGGCTGTGGCCAGGGCACCCAGCGCTCCAGAACGTGAGGCTGGCAGCCA  
GCCCCAGCCTCAGCCCCAACTGCGAGGCAGAGAGACACCAATGGGAATGCAATGGGAAGTCGATGCTG  
GTGCTTCTCACCTTCTGGCTTCGCCTCGTGCATTGCTGCTTACCGCCCCAGTGAGACCCGTGCG  
GCGGGGAGCTGGGGACACCCCTCCAGTTCTGTGTGGGGACCGCGCTCTACTTCAGCAGGCCGCAAG  
CCGTGTGAGCCGTCGCAGCGTGGCATCGTGAGGAGTGCTGTTCCGCACTGTGACCTGGCCCTCTG  
GAGACGTACTGTGCTACCCCGCCAAGTCCGAGAGGGACGTGTCGACCCCTCCGACCGTGCTCCGGACA  
ACTTCCCCAGATAACCCGTGGCAAGTTCTCAATATGACACCTGGAAGCAGTCCACCCAGCGCCTGCG  
CAGGGGCCTGCCTGCCCTCTGCGTGCCGCCGGGTACGTGCTGCCAAGGAGCTGAGGCCTTCAGG  
GAGGCCAAACGTACCGTCCCTGATTGCTTACCCACCCAAAGACCCGCCACGGGGCGCCCCCCCAG  
AGATGGCCAGCAATCGGAAGT GAGCAAACACTGCCAAGTCTGAGCCGGCGCCACCATCCTGAGCCT  
CCTCTGACCACGGACGTTCCATCAGGTTCCATCCGAAATCTCTCGGTTCCACGTCCCCCTGGGCTT  
CTCCTGACCCAGTCCCCGTGCCCGCCTCCCCGAAACAGGCTACTCTCCTCGGCCCCCTCCATGGGCTG  
AGGAAGCACAGCAGCATCTCAAACATGTACAAATGATTGGCTTAAACACCTTCACATACCT
```



- 每一行最好不要超过 80 个字符
- 序列中的换行符不会影响序列的连续性
- 使用标准的 IUB/IUPAC 核酸代码和氨基酸代码
- 允许小写字母的存在，但会转换成大写
- 单个 “-” 代表不明长度的空位
- 在氨基酸序列中允许出现 “U” 和 “*”
- 任何数字都应该被去掉或转换成字母
- 不明核酸和氨基酸分别用 “N” 和 “X” 表示



格式 | FASTA | IUB/IUPAC 核酸



格式 | FASTA | IUB/IUPAC 核酸

Code	Meaning	Code	Meaning
A	Adenine	Y	Pyrimidine (C, T, or U)
C	Cytosine	K	T, U, or G (keto)
G	Guanine	W	T, U, or A (weak)
T	Thymine	B	C, T, U, or G (not A)
U	Uracil	D	A, T, U, or G (not C)
R	Purine (A or G)	H	A, T, U, or C (not G)
S	C or G (strong)	V	A, C, or G (not T, not U)
M	C or A (amino)	N	Any base (A, C, G, T, or U)
X	masked	-	gap of indeterminate length



格式 | FASTA | IUB/IUPAC 氨基酸

1	3	Meaning	1	3	Meaning
A	Ala	Alanine	B	Asx	Aspartic acid or Asparagine
C	Cys	Cysteine	D	Asp	Aspartic acid
E	Glu	Glutamic acid	F	Phe	Phenylalanine
G	Gly	Glycine	H	His	Histidin
I	Ile	Isoleucine	K	Lys	Lysine
L	Leu	Leucine	M	Met	Methionine
N	Asn	Asparagine	P	Pro	Proline
Q	Gln	Glutamine	R	Arg	Arginine
S	Ser	Serine	T	Thr	Threonine
U	Sec	Selenocysteine	V	Val	Valine
W	Trp	Tryptophan	X	Xaa	Any amino acid
Y	Tyr	Tyrosine	Z	Glx	Glutamine or Glutamic acid
*		translation stop	-		gap of indeterminate length
O	Pyl	Pyrrolysine			



格式 | FASTA | FASTA vs. Sequence

FASTA

```
>gi|183121|gb|M29645.1|HUMGFI Human insulin-like growth factor II mRNA, complete cds  
CAGGGGCCAAGAGTCACCACCGAGCTGTGAGGGAGGTGATTCCAGCCCCCAGCCCCAGGGCTCT  
GAATCGCTGCCAGCTCAGCCCCCTGCCAGCCTGCCACAGCCTGAGCCCAGCAGGCCAGAGAGCCCA  
GTCCTGAGGTGAGCTGCTGTGGCTGTGGCCAGGGCACCCAGCCTCCAGAACGTAGGGCTGGCAGCCA  
GCCCCAGCCTCAGCCCCAACACTGCAGGGCAGAGAGACACCAATGGGAATGCCAATGGGAAGTCGATGCTG  
GTGCTTCTCACCTTCTTGGCTTCGCCCTCGTGTGCATTGCTGCTTACGCCAGTGAGACCCCTGTGCG  
GCGGGGAGCTGGGGACACCCCTCAGTTGTCTGTGGGGACCCGGCTTACTTCAGCAGGCCAGAAG  
CCGTGTAGCCGTCGAGCCGTGGCATCGTGTGAGGAGTGTGTTCCGAGCTGTGACCTGGCCCTCG  
GAGACGTACTGTGCTACCCCCGCCAAGTCCAGAGAGGGACGTGTCACCCCTCGACCGTGCTTCCGGACA  
ACTTCCCCAGATAACCCGTGGCAAGTTCTCAATATGACACCTGGAAGCAGTCCACCCAGCGCCTGCG  
CAGGGGCTGCCCTCTCGTGTGCCGCCGGGTCACGTGTGCTGCCAAGGAGCTGAGGGCTTCAGG  
GAGGCCAAACGTACCGTCCCCCTGATTGCTCTACCCACCCAAGACCCGCCACGGGGCGCCCCCAG  
AGATGGCCAGCAATCGGAAGTGTGAGCAAACACTGCCAAGTCTGAGCCGGCGCCACCATCCTGAGCCT  
CCTCTGACCACGGACGTTCCATCAGGTTCCATCCGAAATCTCTGGTTCCACGTCCCCCTGGGCTT  
CTCCTGACCCAGTCCCCGTCCCCGCCCTCCCCGAAACAGGCTACTCTCTCGGCCCCCTCATGGGCTG  
AGGAAGCACAGCAGCATTTCAAACATGTACAAAATGATTGGCTTAAACACCTTACATACCT
```

Sequence

- GTACGACGGAGTGTATAAGATGGAAATCGGATACCAGATGAAATTGTGGATCAG
- MWTALPLLCAGAWLLSAGATAELTVNAIEKFHFTSWMKQHQKTYSSREYSHRLQVFAN

格式 | BED (Browser Extensible Data)

chr7	127471196	127472363	Pos1	0	+	127471196	127472363	255,0,0
chr7	127472363	127473530	Pos2	0	+	127472363	127473530	255,0,0
chr7	127473530	127474697	Pos3	0	+	127473530	127474697	255,0,0
chr7	127474697	127475864	Pos4	0	+	127474697	127475864	255,0,0
chr7	127475864	127477031	Neg1	0	-	127475864	127477031	0,0,255
chr7	127477031	127478198	Neg2	0	-	127477031	127478198	0,0,255
chr7	127478198	127479365	Neg3	0	-	127478198	127479365	0,0,255
chr7	127479365	127480532	Pos5	0	+	127479365	127480532	255,0,0
chr7	127480532	127481699	Neg4	0	-	127480532	127481699	0,0,255



BED#

BED12 包含全部 12 列

BED6 chrom, start, end, name, score, and strand

BED5 chrom, start, end, name, and score

BED4 chrom, start, end, and name

BED3 chrom, start, and end

例子

chr1	11873	14409	uc001aaa.3	0	+	11873	11873	0
3	354,109,1189,	0,739,1347,						



BED#

BED12 包含全部 12 列

BED6 chrom, start, end, name, score, and strand

BED5 chrom, start, end, name, and score

BED4 chrom, start, end, and name

BED3 chrom, start, and end

例子

chr1 11873 14409 uc001aaa.3 0 +



BED#

BED12 包含全部 12 列

BED6 chrom, start, end, name, score, and strand

BED5 chrom, start, end, name, and score

BED4 chrom, start, end, and name

BED3 chrom, start, and end

例子

chr1 11873 14409 uc001aaa.3 0



BED#

BED12 包含全部 12 列

BED6 chrom, start, end, name, score, and strand

BED5 chrom, start, end, name, and score

BED4 chrom, start, end, and name

BED3 chrom, start, and end

例子

chr1 11873 14409 uc001aaa.3



BED#

BED12 包含全部 12 列

BED6 chrom, start, end, name, score, and strand

BED5 chrom, start, end, name, and score

BED4 chrom, start, end, and name

BED3 chrom, start, and end

例子

chr1 11873 14409



格式 | GFF (General Feature Format)

```
##gff-version 3
ctg123 . operon      1300 15000  .  +  .  ID=operon001;Name=superOperon
ctg123 . mRNA        1300 9000   .  +  .  ID=mrna0001;Parent=operon001;Name=sonichedgehog
ctg123 . exon         1300 1500   .  +  .  Parent=mrna0001
ctg123 . exon         1050 1500   .  +  .  Parent=mrna0001
ctg123 . exon         3000 3902   .  +  .  Parent=mrna0001
ctg123 . exon         5000 5500   .  +  .  Parent=mrna0001
ctg123 . exon         7000 9000   .  +  .  Parent=mrna0001
ctg123 . mRNA        10000 15000  .  +  .  ID=mrna0002;Parent=operon001;Name=subsonicsquirrel
ctg123 . exon         10000 12000  .  +  .  Parent=mrna0002
ctg123 . exon         14000 15000  .  +  .  Parent=mrna0002
```



格式 | VCF (Variant Call Format)

```
##fileformat=VCFv4.0
##fileDate=20110705
##reference=1000GenomesPilot-NCBI37
##phasing=partial
##INFO=<ID=NS,Number=1,Type=Integer,Description="Number of Samples With Data">
##INFO=<ID=DP,Number=1,Type=Integer,Description="Total Depth">
##INFO=<ID=AF,Number=.,Type=Float,Description="Allele Frequency">
##INFO=<ID=AA,Number=1,Type=String,Description="Ancestral Allele">
##INFO=<ID=DB,Number=0,Type=Flag,Description="dbSNP membership, build 129">
##INFO=<ID=H2,Number=0,Type=Flag,Description="HapMap2 membership">
##FILTER=<ID=q10,Description="Quality below 10">
##FILTER=<ID=s50,Description="Less than 50% of samples have data">
##FORMAT=<ID=GQ,Number=1,Type=Integer,Description="Genotype Quality">
##FORMAT=<ID=GT,Number=1,Type=String,Description="Genotype">
##FORMAT=<ID=DP,Number=1,Type=Integer,Description="Read Depth">
##FORMAT=<ID=HQ,Number=2,Type=Integer,Description="Haplotype Quality">
#CHROM POS ID REF ALT QUAL FILTER INFO
2 4370 rs6057 G A 29 . NS=2;DP=13;AF=0.5;DB;H2
2 7330 . T A 3 q10 NS=5;DP=12;AF=0.017
2 110696 rs6055 A G,T 67 PASS NS=2;DP=10;AF=0.333,0.667;AA=T;DB
2 130237 . T . 47 . NS=2;DP=16;AA=T
2 134567 microsat1 GTCT G,GTACT 50 PASS NS=2;DP=9;AA=G
```

	FORMAT	Sample1	Sample2	Sample3
2 4370 rs6057 G A 29 . NS=2;DP=13;AF=0.5;DB;H2	GT:GQ:DP:HQ	0 0:48:1:52,51 1 0:48:8:51,51	1/1:43:5:,,	
2 7330 . T A 3 q10 NS=5;DP=12;AF=0.017	GT:GQ:DP:HQ	0 0:46:3:58,50 0 1:3:5:65,3	0/0:41:3	
2 110696 rs6055 A G,T 67 PASS NS=2;DP=10;AF=0.333,0.667;AA=T;DB	GT:GQ:DP:HQ	1 2:21:6:23,27 2 1:2:0:18,2	2/2:35:4	
2 130237 . T . 47 . NS=2;DP=16;AA=T	GT:GQ:DP:HQ	0 0:54:7:56,60 0 0:48:4:56,51	0/0:61:2	
2 134567 microsat1 GTCT G,GTACT 50 PASS NS=2;DP=9;AA=G	GT:GQ:DP	0 1:35:4	0/2:17:2	1/1:40:3



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20

复习思考题



文本 | 纯文本 vs. 格式化文本

P8_Ain_Pro - 记事本
文件(F) 编辑(E) 格式(O) 查看(V) 帮助(H)
CLUSTAL X (1.83) multiple sequence alignment

RGDV_ABC75537 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
RGDV_AAY14576 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
RGDV_BAA02676 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
RGDV_AAY14579 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
RGDV_AAY14580 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
RGDV_AAO04253 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
RGDV_AAY14577 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
RGDV_AAY14578 HSRQWIEITSALIECISEVGTCKCSFDTFQGLTINDISTLSNLHNQISUASUGFLNDPRTP
WTU_P17380 HSRQHWEETSALIECISEVYURCNGDTFSGLTTGDFNALSNNHTQLSUSSAGYUSDPRUP
RDVS_Q85451 HSRQHMLDTSALLEAISEYVURCNGDTFSGLTTGDFNALSNNHTQLSUSSAGYUSDPRUP
RDVS_P17379 HSRQHMLDTSALLEAISEYVURCNGDTFSGLTTGDFNALSNNHTQLSUSSAGYUSDPRUP
RDVA_Q85449 HSRQHMLDTSALLEAISEYVURCNGDTFSGLTTGDFNALSNNHTQLSUSSAGYUSDPRUP
RDUF_Q85439 **** *:***** * ***** .. *** *** *.*.*****:*****..*:***.*.*

RGDV_ABC75537 LQAHSCFUFNSTADRHHYLQKNMFDSDUAPNUTDNFIATYIKPRFSRTUSDULRQU
RGDV_AAY14576 LQAHSCFUFNSTADRHHYLQKNMFDSDUAPNUTDNFIATYIKPRFSRTUSDULRQU
RGDV_BAA02676 LQAHSCFUFNSTADRHHYLQKNMFDSDUAPNUTDNFIATYIKPRFSRTUSDULRQU
RGDV_AAY14579 LQAHSCFUFNSTADRHHYLQKNMFDSDUAPNUTDNFIATYIKPRFSRTUSDULRQU
RGDV_AAY14580 LQAHSCFUFNSTADRHHYLQKNMFDSDUAPNUTDNFIATYIKPRFSRTUSDULRQU
RGDV_AAO04253 LQAHSCFUFNSTADRHHYLQKNMFDSDUAPNUTDNFIATYIKPRFSRTUSDULRQU
RGDV_AAY14577 PQAHSCFUFNSTADRHHYLQKNMFDSDUAPNUTDNFIATYIKPRFSRTUSDULRQU

Ln 1, Col 1

File Home Insert Page Layout References Mailings Review View Picture Tools Format
Clipboard Font Paragraph Styles
collaborate. Today, I'm thrilled to announce that we are taking a step towards improving collaboration – by bringing simultaneous editing to Word Web App in addition to Microsoft Word 2010, Microsoft Word for Mac 2011. (Word now joins Excel and OneNote on the web with simultaneous editing.)
It's no secret that we love Word around here. It's used to author all the specifications we write for our products, as well as all the blog posts we publish on this blog. These are professional documents that we produce all the time and there are countless millions of people that have been using Word to express and communicate thoughts and ideas.
Word has a long history of innovation. I remember when the red squiggle line arrived and I no longer had to manually spell check all the school papers I wrote. I also remember when Word introduced auto-correct and many common mistakes were corrected for me (still get corrected to this day). I remember when Outlook started to use Word as its default mail editor and all the power of Word arrived in the place that I write the most. In short, I have grown up with Word, first on the Mac, and now on the PC and am happy we can offer yet another feature to enable you to be more productive.
In fact, this post was written using Word 2010 on my ThinkPad, while my colleague Harrison has been making changes to this post such as inserting screen shots to demonstrate certain word features. And we even made a video of us doing this. It doesn't get more meta than this!
<insert video>
Here are some of the features that showcase how Word communicates to you about changes collaborators are making
Notifications of other collaborators
Word on Word docs at the same time with others using SkyDrive

Word 488 100% LiveShare

三大类

- Windows: \r\n (CR+LF, 回车 + 换行) , 文件尾部直接 EOF (文件结束标志)
- Unix: \n (LF, 仅有换行) , 文件最后一行也会增加该字符, 然后才是 EOF
- Mac: \r (CR, 仅有回车)

识别与转换

- Windows: 文本编辑器, 如 Notepad++
- Unix: file 识别, fromdos & todos 转换




三大类

- Windows: \r\n (CR+LF, 回车 + 换行) , 文件尾部直接 EOF (文件结束标志)
- Unix: \n (LF, 仅有换行) , 文件最后一行也会增加该字符, 然后才是 EOF
- Mac: \r (CR, 仅有回车)

识别与转换

- Windows: 文本编辑器, 如 Notepad++
- Unix: file 识别, fromdos & todos 转换





文本 | 编辑器 | Notepad++

*C:\mediawiki\includes\Article.php - Notepad++

File Edit Search View Encoding Language Settings Macro Run Plugins Window ? X

Article.php

```
2580 $modified = $current != '' && $pro...  
2581  
2582 if ( $protect ) {  
2583     $comment_type = $modified ? 'm...  
2584 } else {  
2585     $comment_type = 'unprotectedar...  
2586 }  
2587  
2588 $comment = $wgContLang->ucfirst( w...  
2589  
2590 # Only restrictions with the 'prot...  
2591 # Otherwise, people who cannot nor...  
2592 $editrestriction = isset( $limit['...  
2593  
2594 # The schema allows multiple restr...  
2595 if ( !in [ 'protect', $editrestrict...  
2596     $...  
2597 }  
2598 $casc...  
2599  
2600  
2601 if ( ...  
2602     $cascade_description = ...  
2603  
2604  
2605  
2606  
2607  
2608  
2609  
2610  
2611  
2612  
2613  
2614  
2615  
2616  
2617  
2618  
2619  
2620  
2621  
2622  
2623  
2624  
2625  
2626  
2627  
2628  
2629  
2630  
2631  
2632  
2633  
2634  
2635  
2636  
2637  
2638  
2639  
2640  
2641  
2642  
2643  
2644  
2645  
2646  
2647  
2648  
2649  
2650  
2651  
2652  
2653  
2654  
2655  
2656  
2657  
2658  
2659  
2660  
2661  
2662  
2663  
2664  
2665  
2666  
2667  
2668  
2669  
2670  
2671  
2672  
2673  
2674  
2675  
2676  
2677  
2678  
2679  
2680  
2681  
2682  
2683  
2684  
2685  
2686  
2687  
2688  
2689  
2690  
2691  
2692  
2693  
2694  
2695  
2696  
2697  
2698  
2699  
2700  
2701  
2702  
2703  
2704  
2705  
2706  
2707  
2708  
2709  
2710  
2711  
2712  
2713  
2714  
2715  
2716  
2717  
2718  
2719  
2720  
2721  
2722  
2723  
2724  
2725  
2726  
2727  
2728  
2729  
2730  
2731  
2732  
2733  
2734  
2735  
2736  
2737  
2738  
2739  
2740  
2741  
2742  
2743  
2744  
2745  
2746  
2747  
2748  
2749  
2750  
2751  
2752  
2753  
2754  
2755  
2756  
2757  
2758  
2759  
2760  
2761  
2762  
2763  
2764  
2765  
2766  
2767  
2768  
2769  
2770  
2771  
2772  
2773  
2774  
2775  
2776  
2777  
2778  
2779  
2780  
2781  
2782  
2783  
2784  
2785  
2786  
2787  
2788  
2789  
2790  
2791  
2792  
2793  
2794  
2795  
2796  
2797  
2798  
2799  
2800  
2801  
2802  
2803  
2804  
2805  
2806  
2807  
2808  
2809  
2810  
2811  
2812  
2813  
2814  
2815  
2816  
2817  
2818  
2819  
2820  
2821  
2822  
2823  
2824  
2825  
2826  
2827  
2828  
2829  
2830  
2831  
2832  
2833  
2834  
2835  
2836  
2837  
2838  
2839  
2840  
2841  
2842  
2843  
2844  
2845  
2846  
2847  
2848  
2849  
2850  
2851  
2852  
2853  
2854  
2855  
2856  
2857  
2858  
2859  
2860  
2861  
2862  
2863  
2864  
2865  
2866  
2867  
2868  
2869  
2870  
2871  
2872  
2873  
2874  
2875  
2876  
2877  
2878  
2879  
2880  
2881  
2882  
2883  
2884  
2885  
2886  
2887  
2888  
2889  
2890  
2891  
2892  
2893  
2894  
2895  
2896  
2897  
2898  
2899  
2900  
2901  
2902  
2903  
2904  
2905  
2906  
2907  
2908  
2909  
2910  
2911  
2912  
2913  
2914  
2915  
2916  
2917  
2918  
2919  
2920  
2921  
2922  
2923  
2924  
2925  
2926  
2927  
2928  
2929  
2930  
2931  
2932  
2933  
2934  
2935  
2936  
2937  
2938  
2939  
2940  
2941  
2942  
2943  
2944  
2945  
2946  
2947  
2948  
2949  
2950  
2951  
2952  
2953  
2954  
2955  
2956  
2957  
2958  
2959  
2960  
2961  
2962  
2963  
2964  
2965  
2966  
2967  
2968  
2969  
2970  
2971  
2972  
2973  
2974  
2975  
2976  
2977  
2978  
2979  
2980  
2981  
2982  
2983  
2984  
2985  
2986  
2987  
2988  
2989  
2990  
2991  
2992  
2993  
2994  
2995  
2996  
2997  
2998  
2999  
2999  
3000  
3000
```


load.php index.php

exit;
}
}
if(\$wgUseFileCache && isset(\$wgProfileIn('main-try-filecache'))) {
// Raw pages should handle cache.
// even when using file cache.
if(\$action != 'raw' && HTMLF...
/* Try low-level file cache */
\$cache = new HTMLFileCache;
if(\$cache->isFileCacheGood()) {
/* Check incoming header */
if(!\$wgOut->checkLastModified()) {
\$cache->loadFromFile();
}
Do any stats incrementing.
\$wgArticle = MediaWiki...
\$wgArticle->viewUpdate();
Tell \$wgOut that out...
wfProfileOut('main-try-fil...
\$mediaWiki->restInPage();
exit;

PHP Hy length: 139209 lines: 4673 Ln: 2595 Col: 26 Sel: 0 UNIX ANSI as UTF-8 INS



文本 | 编辑器 | Vim



[No file] - GVIM

File Edit Tools Syntax Buffers Window Help

VIM - Vi IMproved

version 6.0.152
by Bram Moolenaar et al.
Vim is open source and freely distributable

Help poor children in Uganda!
type :help icccf<Enter> for information


type :q<Enter> to exit
type :help<Enter> or <F1> for on-line help
type :help version6<Enter> for version info

0,0-1 All

This screenshot shows the GVIM interface with the Vim startup screen displayed. The title bar reads '[No file] - GVIM'. The menu bar includes File, Edit, Tools, Syntax, Buffers, Window, and Help. The toolbar below the menu bar contains various icons for file operations like Open, Save, Find, and Cut/Copy/Paste. The main editor area displays the Vim startup message, which includes the version number (6.0.152), author (Bram Moolenaar et al.), and the fact that Vim is open source and freely distributable. It also provides instructions for getting help, such as using ':help icccf' to help poor children in Uganda and ':q' to exit. The status bar at the bottom shows the current position (0,0-1) and the search term (All).



文本 | 编辑器 | Emacs



文本 | 编辑器 | Sublime Text

Soda Light.sublime-theme — Theme – Soda

OPEN FILES

- Soda Light.sublime-theme
- Soda Dark.sublime-theme

FOLDERS

- ▼ Theme – Soda
 - Soda Dark
 - Soda Light
- README.md
- Soda Dark.sublime-theme
- Soda Light.sublime-theme

Soda Light.sublime-theme

1 soda light

2

3 658 Soda Light.sublime-theme

4 Soda Light.sublime-theme

5 532 Widget – Soda Light.stTheme

6 Soda Light/Widget – Soda Light.stTheme

7

8 532 Widget – Soda Light.sublime-settings

9 Soda Light/Widget – Soda Light.sublime-settings

10 "layer0.texture": "Theme – Soda/Soda Light/tabsheet-
background.png",

11 "layer0.inner_margin": [1, 7],

12 "layer0.opacity": 1.0,

13 "content_margin": [-4, 0, -4, 3],

14 "tab_overlap": 5,

15 "tab_width": 180,

16 "tab_min_width": 45,

17 "tab_height": 25,

18 "mouse_wheel_switch": false

19 },

20 {

Find What: dark

Replace With: light

Find Replace All

Line 15, Column 1

Spaces: 4

JSON



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20

复习思考题



逻辑运算 | 常见问题

数据

gene1	chr1	10	20	+
gene2	chr1	40	60	+
gene3	chr1	50	100	+
snp1	chr1	15		+
snp2	chr1	55		-
exon3.1	chr1	50	60	+
exon3.2	chr1	90	100	+

问题

- ① 找到 gene1 和 gene2 之间的基因间区域。
- ② snp1 在 gene1 上吗? snp2 在 gene1 上吗 (, 在 gene2 上吗) ?
- ③ 找到与 gene3 重叠和不重叠的基因?
- ④ 找到 gene3 的内含子区域。

逻辑运算 | 常见问题


数据

gene1	chr1	10	20	+
gene2	chr1	40	60	+
gene3	chr1	50	100	+
snp1	chr1	15		+
snp2	chr1	55		-
exon3.1	chr1	50	60	+
exon3.2	chr1	90	100	+


问题

- ① 找到 gene1 和 gene2 之间的基因间区域。
- ② snp1 在 gene1 上吗? snp2 在 gene1 上吗 (, 在 gene2 上吗) ?
- ③ 找到与 gene3 重叠和不重叠的基因?
- ④ 找到 gene3 的内含子区域。


逻辑运算 | 集合运算




求同
交集




求异



相加
并集



相减 $A-B$




差集



相减 $B-A$


补集

逻辑运算 | 集合 \Rightarrow 基因组




逻辑运算 | 运算模式

A Intersect




B Subtract



C Merge




D Concatenate




E Complement



F Cluster



逻辑运算 | intersect




逻辑运算 | intersect

Chromosome ======


BED/BAM A ====== ======

BED File B ======


Result ======




逻辑运算 | subtract




逻辑运算 | subtract




逻辑运算 | merge



逻辑运算 | merge




逻辑运算 | concatenate



逻辑运算 | complement




逻辑运算 | complement



逻辑运算 | cluster



逻辑运算 | cluster



逻辑运算 | join

Input						
Query 1:						
chr1 10 100 Query1.1						
chr1 500 1000 Query1.2						
chr1 1100 1250 Query1.3						
Query 2:						
chr1 20 80 Query2.1						
chr1 2000 2204 Query2.2						
chr1 2500 3000 Query2.3						
Output						
(Return only records that are joined)						
chr1 10 100 Query1.1 chr1 20 80 Query2.1						
Return only records that are joined (INNER JOIN) Return all records of first query (fill null with ".") Return all records of second query (fill null with ".") Return all records of both queries (fill nulls with ".")						



逻辑运算 | join

Input																											
Query 1:	<table><tbody><tr><td>chr1</td><td>10</td><td>100</td><td>Query1..1</td><td></td><td></td><td></td></tr><tr><td>chr1</td><td>500</td><td>1000</td><td>Query1..2</td><td></td><td></td><td></td></tr><tr><td>chr1</td><td>1100</td><td>1250</td><td>Query1..3</td><td></td><td></td><td></td></tr></tbody></table>						chr1	10	100	Query1..1				chr1	500	1000	Query1..2				chr1	1100	1250	Query1..3			
chr1	10	100	Query1..1																								
chr1	500	1000	Query1..2																								
chr1	1100	1250	Query1..3																								
Query 2:	<table><tbody><tr><td></td><td></td><td></td><td>chr1</td><td>20</td><td>80</td><td>Query2..1</td></tr><tr><td></td><td></td><td></td><td>chr1</td><td>2000</td><td>2204</td><td>Query2..2</td></tr><tr><td></td><td></td><td></td><td>chr1</td><td>2500</td><td>3000</td><td>Query2..3</td></tr></tbody></table>									chr1	20	80	Query2..1				chr1	2000	2204	Query2..2				chr1	2500	3000	Query2..3
			chr1	20	80	Query2..1																					
			chr1	2000	2204	Query2..2																					
			chr1	2500	3000	Query2..3																					
(Return all records of first query)	<table><tbody><tr><td>chr1</td><td>10</td><td>100</td><td>Query1..1</td><td>chr1</td><td>20</td><td>80</td></tr><tr><td>chr1</td><td>500</td><td>1000</td><td>Query1..2</td><td>.</td><td>.</td><td>.</td></tr><tr><td>chr1</td><td>1100</td><td>1250</td><td>Query1..3</td><td>.</td><td>.</td><td>.</td></tr></tbody></table>						chr1	10	100	Query1..1	chr1	20	80	chr1	500	1000	Query1..2	.	.	.	chr1	1100	1250	Query1..3	.	.	.
chr1	10	100	Query1..1	chr1	20	80																					
chr1	500	1000	Query1..2	.	.	.																					
chr1	1100	1250	Query1..3	.	.	.																					
	<p>Return only records that are joined (INNER JOIN) Return all records of first query (fill null with ".") Return all records of second query (fill null with ".") Return all records of both queries (fill nulls with ".")</p>																										



逻辑运算 | join

Input																														
Query 1:	<table><tbody><tr><td>chr1</td><td>10</td><td>100</td><td>Query1.1</td><td></td><td></td><td></td></tr><tr><td>chr1</td><td>500</td><td>1000</td><td>Query1.2</td><td></td><td></td><td></td></tr><tr><td>chr1</td><td>1100</td><td>1250</td><td>Query1.3</td><td></td><td></td><td></td></tr></tbody></table>						chr1	10	100	Query1.1				chr1	500	1000	Query1.2				chr1	1100	1250	Query1.3						
chr1	10	100	Query1.1																											
chr1	500	1000	Query1.2																											
chr1	1100	1250	Query1.3																											
Query 2:	<table><tbody><tr><td></td><td></td><td></td><td>chr1</td><td>20</td><td>80</td><td>Query2.1</td></tr><tr><td></td><td></td><td></td><td>chr1</td><td>2000</td><td>2204</td><td>Query2.2</td></tr><tr><td></td><td></td><td></td><td>chr1</td><td>2500</td><td>3000</td><td>Query2.3</td></tr></tbody></table>									chr1	20	80	Query2.1				chr1	2000	2204	Query2.2				chr1	2500	3000	Query2.3			
			chr1	20	80	Query2.1																								
			chr1	2000	2204	Query2.2																								
			chr1	2500	3000	Query2.3																								
(Return all records of second query)	<table><tbody><tr><td>chr1</td><td>10</td><td>100</td><td>Query1.1</td><td>chr1</td><td>20</td><td>80</td><td>Query2.1</td></tr><tr><td>.</td><td>.</td><td>.</td><td>.</td><td>chr1</td><td>2000</td><td>2204</td><td>Query2.2</td></tr><tr><td>.</td><td>.</td><td>.</td><td>.</td><td>chr1</td><td>500</td><td>3000</td><td>Query2.3</td></tr></tbody></table>						chr1	10	100	Query1.1	chr1	20	80	Query2.1	chr1	2000	2204	Query2.2	chr1	500	3000	Query2.3
chr1	10	100	Query1.1	chr1	20	80	Query2.1																							
.	.	.	.	chr1	2000	2204	Query2.2																							
.	.	.	.	chr1	500	3000	Query2.3																							
	<p>Return only records that are joined (INNER JOIN) Return all records of first query (fill null with ".") Return all records of second query (fill null with ".") Return all records of both queries (fill nulls with ".")</p>																													



逻辑运算 | join

Input						
Query 1:						
chr1 10 100 Query1..1						
chr1 500 1000 Query1..2						
chr1 1100 1250 Query1..3						
Query 2:						
chr1 20 80 Query2..1						
chr1 2000 2204 Query2..2						
chr1 2500 3000 Query2..3						
(Return all records of both queries)						
chr1 10 100 Query1..1	chr1 20 80 Query2..1	Return only records that are joined (INNER JOIN)				
chr1 500 1000 Query1..2	chr1 . . .	Return all records of first query (fill null with ".")				
chr1 1100 1250 Query1..3	chr1 2000 2200 Query2..2	Return all records of second query (fill null with ".")				
.	chr1 2500 3000 Query2..3	Return all records of both queries (fill nulls with ".")				



- coverage** Finds the number of bases each interval in the first dataset covers of the second dataset.
- flank** Finds the upstream and/or downstream flanking region(s).
- closest** Find the closest, potentially non-overlapping upstream and/or downstream features.
- slop** Adjust the size of intervals.
- window** Find overlapping intervals within a window around an interval.



逻辑运算 | 实例

Dataset 1

chr1	10	49	Feature1.1
chr1	70	119	Feature1.2
chr1	170	209	Feature1.3
chr1	180	229	Feature1.4

Dataset 2

chr1	80	109	Feature2.1
chr1	150	199	Feature2.2
chr1	250	289	Feature2.3
chr1	270	309	Feature2.4



逻辑运算 | 实例

Dataset 1

chr1	10	49	Feature1.1
chr1	70	119	Feature1.2
chr1	170	209	Feature1.3
chr1	180	229	Feature1.4

Dataset 2

chr1	80	109	Feature2.1
chr1	150	199	Feature2.2
chr1	250	289	Feature2.3
chr1	270	309	Feature2.4

intersect

chr1	80	109	Feature3.1
chr1	170	199	Feature3.2
chr1	180	199	Feature3.3



逻辑运算 | 实例

Dataset 1

chr1	10	49	Feature1.1
chr1	70	119	Feature1.2
chr1	170	209	Feature1.3
chr1	180	229	Feature1.4

Dataset 2

chr1	80	109	Feature2.1
chr1	150	199	Feature2.2
chr1	250	289	Feature2.3
chr1	270	309	Feature2.4

subtract (1-2)

chr1	10	49	Feature4.1
chr1	70	80	Feature4.2
chr1	109	119	Feature4.3
chr1	199	209	Feature4.4
chr1	199	229	Feature4.5

subtract (2-1)

chr1	150	170	Feature5.1
chr1	250	289	Feature5.2
chr1	270	309	Feature5.3



逻辑运算 | 实例

Dataset 1

chr1	10	49	Feature1.1
chr1	70	119	Feature1.2
chr1	170	209	Feature1.3
chr1	180	229	Feature1.4

Dataset 2

chr1	80	109	Feature2.1
chr1	150	199	Feature2.2
chr1	250	289	Feature2.3
chr1	270	309	Feature2.4

join

chr1	70	119	Feature1.2	chr1	80	109	Feature2.1
chr1	170	209	Feature1.3	chr1	150	199	Feature2.2
chr1	180	229	Feature1.4	chr1	150	199	Feature2.2



实际问题

- ① Find genes that overlap LINEs.
- ② Remove introns from gene features. Exons will (should) be reported.
- ③ Merge overlapping repetitive elements into a single entry.
- ④ Report all intervals in the human genome that are not covered by repetitive elements.

解决策略

- ① intersect
- ② subtract
- ③ merge
- ④ complement

实际问题

- ① Find genes that overlap LINEs.
- ② Remove introns from gene features. Exons will (should) be reported.
- ③ Merge overlapping repetitive elements into a single entry.
- ④ Report all intervals in the human genome that are not covered by repetitive elements.

解决策略

- ① intersect
- ② subtract
- ③ merge
- ④ complement

- Galaxy 中的 “Operate on Genomic Intervals” 工具集
- bedtools: a powerful toolset for genome arithmetic
- BEDOPS: the fast, highly scalable and easily-parallelizable genome analysis toolkit



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20

复习思考题



知识点——基因组注释基础

- 基因组组装版本——对应关系
- 两种坐标系统——0-based 和 1-based
- 四种常用格式——FASTA, BED, GFF, VCF
- 坐标逻辑运算——常见模式及其适用范围
- 坐标转换、格式转换、逻辑运算的工具

技能——纯文本与文本编辑器

- 纯文本与格式化文本
- 不同操作系统中的换行符
- 文本编辑器——Notepad++, Vim, Emacs



教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析

- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题



前期准备工作

- 组装版本
- 坐标系统
- 常用格式
- 逻辑运算

后续功能注释

- 变异位点的注释
- 基因集富集分析
- 制作序列标识
- ...



前期准备工作

- 组装版本
- 坐标系统
- 常用格式
- 逻辑运算

后续功能注释

- 变异位点的注释
- 基因集富集分析
- 制作序列标识
- ...



教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析


- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题



变异位点的注释 | SNP

ID	Chromosome	Position	Reference	Mutation	TotalHit
SNP00000001	15	20833654	C	A	38
SNP00000002	15	23501058	C	A	31
SNP00000003	15	45564496	C	A	20
SNP00000004	15	45564498	A	T	20
SNP00000005	15	45564501	G	T	20
SNP00000006	15	45564504	C	A	20
SNP00000007	15	45564505	C	T	20
SNP00000008	15	45564506	T	C	20
SNP00000009	15	45564508	A	T	20
SNP00000010	15	50212324	G	C	21
SNP00000011	15	50212325	A	T	21
SNP00000012	15	50212326	A	C	21
SNP00000013	15	50212328	G	A	21
SNP00000014	15	50212329	A	G	21
SNP00000015	15	50212330	G	A	21
SNP00000016	15	50212342	G	T	21
SNP00000017	15	52098626	A	G	20
SNP00000018	15	52098627	G	A	20

变异位点的注释 | SNP 注释



Pos	Alt SNP	Ref SNP	Alt SNP Codon	Ref SNP Codon	Alt SNP AA	Ref SNP AA	Anno Type
3	G	A	--	--	--	--	5'UTR
5	A	C	CAT	CCT	His	Pro	Non_Synonymous
13	G	T	CCG	CCT	Pro	Pro	Synonymous
25	C	A	TAC	TAA	Tyr	Stop	Stop Loss
43	A	C	--	--	--	--	Splice Site
44	G	T	--	--	--	--	Intronic
50	C	A	--	--	--	--	Essential Splice Site
53	A	C	ACC	CCC	Thr	Pro	Non_Synonymous
66	C	T	--	--	--	--	3'UTR
72	A	C	--	--	--	--	Downstream

- SNVs 的注释：SeattleSeq Annotation、variant tools、SnpEff
- 非同义多态性的功能注释：SIFT、PolyPhen-2、SNPs3D
- indels 的功能注释：PROVEAN



变异位点的注释 | 结果解析 | SeattleSeq Annotation

File:
/data/jboss-as-
7.1.1.Final/gvsBatchOutput/SeattleSeqAnnotation137.1.individual.294000040650.txt

Title:
1individual

Counts:
HapMapFreqType HapMapFreqMinor
polyPhenType polyPhenScore

Count missense SNPs = 8
Count stop SNPs = 0
Count SNP's in splice sites = 0
Count SNP's in coding synonymous = 8
Count SNP's in coding (not mod 3) = 0
Count SNP's in a UTR = 0
Count SNP's near a gene = 0
Count SNP's in introns = 0
Count intergenic SNPs = 0

number SNPs in microRNAs = 0

number accessions coding-synonymous NCBI = 19
number accessions missense NCBI = 15
number accessions stop NCBI = 0
number accessions splice-site NCBI = 0
number SNPs in dbSNP = 16
number SNPs not in dbSNP = 0
number SNPs total = 16

Add or Remove Columns:

- Sample Alleles
- Alleles in dbSNP
- GVS Function
- dbSNP Function
- Chimp Allele
- Copy Number Variations
- HapMap Rare-Allele Frequencies
- dbSNP Validation
- RepeatMasker
- Tandem Repeats
- microRNAs
- Grantham Score
- cDNA Position
- PolyPhen Prediction
- Clinical Association
- Distance to Nearest Splice Site
- NHLBI ESP Allele Counts

Sort by Column Value:

- Original Order
- dbSNP Function
- GVS Function
- Conservation Score phastCons
- Conservation Score GERP
- In dbSNP

Sort Direction:

- Forward
- Reverse

Filter:

- Only missense, nonsense, splice, frameshift (GVS)
- Only synonymous SNP's or coding (not frameshift) indels (GVS)
- Only intron (GVS)
- Only variations not in dbSNP
- Only variations with clinical association

Table 

reset 

16 SNP locations 36 accession lines page 1 of 1

inDBSNPOrNot	chromosome	position	referenceBase	sampleGenotype	sampleAlleles	allelesDBSNP	accession	functionGVS	functionDBSNP	rsID	aminoAcids	proteinPosition
dbSNP_130	10	1126383	A	R	A/G	A/G	NM_014023.3	coding-synonymous	synonymous-codon	73578536	none	121/495
dbSNP_86	10	3150973	C	Y	C/T	C/T	NM_001242339.1	coding-synonymous	synonymous-codon	1132173	none	309/777
dbSNP_86	10	3150973	C	Y	C/T	C/T	NM_002627.4	coding-synonymous	synonymous-codon	1132173	none	317/785



变异位点的注释 | 结果解析 | SeattleSeq Annotation

inDBSNPOrNot	chromosome	position	referenceBase	sampleGenotype	sampleAlleles	allelesDBSNP
dbSNP_130	10	1126383	A	R	A/G	A/G
dbSNP_86	10	3150973	C	Y	C/T	C/T
dbSNP_86	10	3150973	C	Y	C/T	C/T
accession	functionGVS	functionDBSNP	rsID	aminoAcids	proteinPosition	aaChange
NM_014023.3	coding-synonymous	synonymous-codon	73578536	none	121/495	
NM_001242339.1	coding-synonymous	synonymous-codon	1132173	none	309/777	
NM_002627.4	coding-synonymous	synonymous-codon	1132173	none	317/785	

变异位点的注释 | 结果解析 | SIFT

Transcript ID	Protein ID	Substitution	Region	dbSNP ID	SNP Type	Prediction	SIFT Score
ENST00000294724	ENSP00000294724	R1487G	EXON CDS	rs12118058:G	Nonsynonymous	TOLERATED	0.46
ENST00000294724	ENSP00000294724	E1405G	EXON CDS	rs28730708:G	Nonsynonymous	DAMAGING	0.01
ENST00000294724	ENSP00000294724	R1487R	EXON CDS	rs12118058:G	Synonymous	TOLERATED	0.64
ENST00000330029	ENSP00000332887	E49A	EXON CDS	novel	Nonsynonymous	DAMAGING	0.02
ENST00000371564	ENSP00000360619	T612N	EXON CDS	rs6067785:T	Nonsynonymous	DAMAGING	0
ENST00000283943	ENSP00000283943	Q1910*	EXON CDS	rs1803846:A	Nonsynonymous	N/A	N/A
ENST00000341772	ENSP00000345229	P433L	EXON CDS	rs17853365:A	Nonsynonymous	DAMAGING	0.02



教学提纲

1 引言
2 基因组组装版本
3 基因组坐标系统
4 基因组注释常用格式
5 文本文件与文本编辑器
6 基因组坐标的逻辑运算
7 总结与答疑
8 引言
9 变异位点的注释
10 基因集富集分析

11 序列标识
12 box plot
13 解析图表
14 总结与答疑
15 引言
16 Galaxy 分析平台
17 Galaxy 使用演示
18 数据处理三段论
19 总结与答疑
20 复习思考题



富集分析 | 基因集

Table 7 The minimum gene set selected in PRI dataset (gene scores rank from high to low)

Probe ID	Gene symbol	Gene name	Chromosomal regions
219868_s_at	ANKFY1	Ankyrin repeat and FYVE domain containing1	17p13.3
213613_s_at	NADK	NAD kinase	1p36.33-p36.21
208002_s_at	ACOT7	Acyl-coa thioesterase 7	1p36
222133_s_at	PHF20L1	PHD finger protein 20-like 1	8q24.22
203858_s_at	COX10	COX10 homolog, cytochrome c oxidase assembly protein, heme A: farnesyltransferase (yeast)	17p12
204051_s_at	SFRP4	Secreted frizzled-related protein 4	7p14.1
207567_at	SLC13A2	Solute carrier family 13 (sodium-dependent dicarboxylate transporter), member 2	17p13.2
225803_at	FBXO32	F-box protein 32	8q24.13
205527_s_at	GEMIN4	Gem (nuclear organelle) associated protein 4	17p13
207017_at	RAB27B	RAB27B, member RAS oncogene family	18q21.2
206746_at	BFSP1	Beaded filament structural protein 1, filensin	20p12.1
217099_s_at	GEMIN4	Gem (nuclear organelle) associated protein 4	17p13
233638_s_at	POMGNT1	Protein O-linked mannose beta1,2-N-acetylglucosaminyltransferase	1p34.1
217381_s_at	TRGV5	T cell receptor gamma variable 5	7p14



数据库

GO Gene Ontology

KEGG Kyoto Encyclopedia of Genes and Genomes

分析工具

DAVID Database for Annotation, Visualization and Integrated Discovery



数据库

GO Gene Ontology

KEGG Kyoto Encyclopedia of Genes and Genomes

分析工具

DAVID Database for Annotation, Visualization and Integrated Discovery



三个方面

- biological process, BP, 生物学过程
- molecular function, MF, 分子功能
- cellular component, CC, 细胞组份

两大关系

- is_a: for simple, hierarchical connections between terms
- part_of: for describing how the components of a living system fit together



三个方面


- biological process, BP, 生物学过程
- molecular function, MF, 分子功能
- cellular component, CC, 细胞组份


两大关系

- is_a: for simple, hierarchical connections between terms
- part_of: for describing how the components of a living system fit together




富集分析 | GO






富集分析 | GO


B




Relationships	Nodes
-P→ part_of	ontology term
-i→ is_a	root node
-d→ develops_from	
-→ inferred	
— annotation	gene name




富集分析 | GO



富集分析 | KEGG



富集分析 | KEGG



- Gene Name Batch Viewer
 - Gene ID Conversion Tool
 - Gene Functional Classification Tool
 - Functional Annotation Tool
 - Functional Annotation Clustering
 - **Functional Annotation Chart:** 富集分析
 - Functional Annotation Table



富集分析 | DAVID | 结果解析

Functional Annotation Chart

[Help and Manual](#)**Current Gene List: demolist1****Current Background: Homo sapiens****155 DAVID IDs** Options[Rerun Using Options](#)[Create Sublist](#)**105 chart records** [Download File](#) [1, 2, 3, 4, 5, 6](#)

Category	Term	RT	Genes	Count	%	P-Value	Benjamini
GOTERM_CC_FAT	extracellular_region	RT		40	25.8	6.9E-6	1.5E-3
GOTERM_CC_FAT	extracellular_region_part	RT		24	15.5	3.8E-5	4.0E-3
GOTERM_MF_FAT	oxygen_binding	RT		6	3.9	3.8E-5	1.4E-2
GOTERM_CC_FAT	extracellular_space	RT		19	12.3	9.4E-5	6.5E-3
GOTERM_MF_FAT	heme_binding	RT		8	5.2	1.0E-4	1.9E-2
GOTERM_BP_FAT	defense_response	RT		18	11.6	1.3E-4	1.7E-1
GOTERM_BP_FAT	response_to_bacterium	RT		10	6.5	1.4E-4	9.1E-2
GOTERM_MF_FAT	tetrapyrrole_binding	RT		8	5.2	1.5E-4	1.9E-2
GOTERM_MF_FAT	iron_ion_binding	RT		11	7.1	4.3E-4	3.9E-2
GOTERM_BP_FAT	defense_response_to_bacterium	RT		7	4.5	8.9E-4	3.4E-1
GOTERM_BP_FAT	response_to_drug	RT		9	5.8	1.5E-3	4.0E-1
GOTERM_BP_FAT	regulation_of_response_to_external_stimulus	RT		7	4.5	5.2E-3	7.7E-1
GOTERM_BP_FAT	taxis	RT		7	4.5	5.4E-3	7.2E-1
GOTERM_BP_FAT	chemotaxis	RT		7	4.5	5.4E-3	7.2E-1
GOTERM_CC_FAT	hemoglobin_complex	RT		3	1.9	5.7E-3	2.6E-1
GOTERM_MF_FAT	oxygen_transporter_activity	RT		3	1.9	5.8E-3	3.5E-1

富集分析 | DAVID | 工具选择

- Highly recommended
- Recommended

	Gene ID conversion tool	Gene name batch viewer	Gene functional classification	Functional annotation chart	Functional annotation clustering	Functional annotation table
Convert gene IDs from one type to another	■					
Diagnose and fix problems of gene IDs		■				■
Explore gene names in batch		■	■			■
Discover enriched functionally related gene groups			■	■		
Display relationship of many-genes-to-many-terms on 2D view.				■	■	■
Initial glance of major biological functions associated with gene list	■		■	■		
Identify enriched (overrepresented) annotation terms				■	■	
Visualize genes on BioCarta and KEGG pathway maps				■		
Link gene–disease associations				■		
Highlight protein functional domains and motifs			■			
Redirect to related literatures				■		■
List interacting proteins				■	■	■
Cluster redundant and heterozygous annotation terms					■	
Search other functionally similar genes in genome, but not in list	■	■		1	1	
Search other annotations functionally similar to one of my interests			■			
Read all annotation contents associated with a gene						■

Gene ID conversion tool
Gene name batch viewer
Gene functional classification
Functional annotation chart
Functional annotation clustering
Functional annotation table



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19


总结与答疑

20

复习思考题




序列标识



序列标识 (sequence logo)

- 数据：多序列比对信息
- 横轴：序列坐标位置
- 纵轴：比特，计量单位
- 总高度：保守性
- 相对高度：相对频率
- 制作工具：WebLogo, enoLOGOS, Skylign


序列标识



序列标识 (sequence logo)


- 数据：多序列比对信息
- 横轴：序列坐标位置
- 纵轴：比特，计量单位
- 总高度：保守性
- 相对高度：相对频率
- 制作工具：WebLogo, enoLOGOS, Skylign

序列标识 | 剪接




序列标识 | 实例

Exon-Intron (Donor) Sites



Intron-Exon (Acceptor) Sites



序列标识 | 实例 | 真实数据

Donor Sites(%)		Acceptor Site(%)	
GT	98.797	AG	99.714
GC	0.920	AC	0.120
AT	0.143	TG	0.032
GA	0.028	AT	0.024
GG	0.025	GG	0.022
CT	0.018	AA	0.019
TT	0.016	CG	0.010
CC	0.011	CC	0.010
TG	0.007	TT	0.009
AG	0.007	CT	0.008
TA	0.006	CA	0.008
AC	0.006	GC	0.007
CA	0.006	TA	0.006
TC	0.004	TC	0.004
AA	0.004	GT	0.004
CG	0.002	GA	0.003


教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析

- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题



box plot | 实例



box plot | 简介

历史

- box plot, boxplot, Box-whisker Plot
- 箱线图、箱须图、盒须图、盒式图、盒状图，因形状如箱子而得名
- 1977 年由美国著名统计学家约翰·图基（John Tukey）发明

简介

- 显示一组数据分散情况的统计图
- 显示最大值、最小值、中位数、下四分位数和上四分位数

优缺点

- 可以粗略地看出数据是否具有对称性、分布的离散程度
- 适合用于几个样本的比较
- 不能提供关于数据分布偏态和尾重程度的精确度量

box plot | 简介

历史

- box plot, boxplot, Box-whisker Plot
- 箱线图、箱须图、盒须图、盒式图、盒状图，因形状如箱子而得名
- 1977 年由美国著名统计学家约翰·图基（John Tukey）发明

简介

- 显示一组数据分散情况的统计图
- 显示最大值、最小值、中位数、下四分位数和上四分位数

优缺点

- 可以粗略地看出数据是否具有对称性、分布的离散程度
- 适合用于几个样本的比较
- 不能提供关于数据分布偏态和尾重程度的精确度量

box plot | 简介

历史

- box plot, boxplot, Box-whisker Plot
- 箱线图、箱须图、盒须图、盒式图、盒状图，因形状如箱子而得名
- 1977 年由美国著名统计学家约翰·图基（John Tukey）发明

简介

- 显示一组数据分散情况的统计图
- 显示最大值、最小值、中位数、下四分位数和上四分位数

优缺点

- 可以粗略地看出数据是否具有对称性、分布的离散程度
- 适合用于几个样本的比较
- 不能提供关于数据分布偏态和尾重程度的精确度量

- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5IQR, Q1 - 1.5IQR$
- 外限: $Q3 + 3IQR, Q1 - 3IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5IQR, Q1 - 1.5IQR$
- 外限: $Q3 + 3IQR, Q1 - 3IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



box plot | 相关概念

- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5IQR, Q1 - 1.5IQR$
- 外限: $Q3 + 3IQR, Q1 - 3IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5IQR, Q1 - 1.5IQR$
- 外限: $Q3 + 3IQR, Q1 - 3IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5IQR, Q1 - 1.5IQR$
- 外限: $Q3 + 3IQR, Q1 - 3IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5IQR$, $Q1 - 1.5IQR$
- 外限: $Q3 + 3IQR$, $Q1 - 3IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5/IQR$, $Q1 - 1.5/IQR$
- 外限: $Q3 + 3/IQR$, $Q1 - 3/IQR$
- 异常值 (outliers) : 处于内限以外的数据
 - 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
 - 极端的异常值 (extreme outliers) : 在外限以外的异常值



- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5/IQR$, $Q1 - 1.5/IQR$
- 外限: $Q3 + 3/IQR$, $Q1 - 3/IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



- 最小值 min, 最大值 max
- 中位数 median
- 下四分位数 Q1, 上四分位数 Q3
- 四分位数差 IQR (interquartile range) , $IQR = Q3 - Q1$
- 内限: $Q3 + 1.5/IQR$, $Q1 - 1.5/IQR$
- 外限: $Q3 + 3/IQR$, $Q1 - 3/IQR$
- 异常值 (outliers) : 处于内限以外的数据
- 温和的异常值 (mild outliers) : 在内限与外限之间的异常值
- 极端的异常值 (extreme outliers) : 在外限以外的异常值



box plot | 绘图步骤

● 绘制数轴。

- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- 计算四分位数差 (IQR) 。
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5 \times IQR$ 和 $Q1 - 1.5 \times IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3 \times IQR$ 和 $Q1 - 3 \times IQR$ 处画两条线段, 称为外限。(注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- 从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须), 表示该批数据正常值的分布区间。
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用 *) 表示。



box plot | 绘图步骤

- 绘制数轴。
- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- 计算四分位数差 (IQR) 。
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5/IQR$ 和 $Q1 - 1.5/IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3/IQR$ 和 $Q1 - 3/IQR$ 处画两条线段, 称为外限。 (注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- 从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须), 表示该批数据正常值的分布区间。
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用 *) 表示。



- 绘制数轴。
- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- **计算四分位数差 (IQR) 。**
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5/IQR$ 和 $Q1 - 1.5/IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3/IQR$ 和 $Q1 - 3/IQR$ 处画两条线段, 称为外限。**(注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)**
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- 从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须), 表示该批数据正常值的分布区间。
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用星号 *) 表示。



- 绘制数轴。
- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- 计算四分位数差 (IQR) 。
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5/IQR$ 和 $Q1 - 1.5/IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3/IQR$ 和 $Q1 - 3/IQR$ 处画两条线段, 称为外限。**(注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)**
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- 从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须), 表示该批数据正常值的分布区间。
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用星号 *) 表示。



- 绘制数轴。
- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- 计算四分位数差 (IQR) 。
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5/IQR$ 和 $Q1 - 1.5/IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3/IQR$ 和 $Q1 - 3/IQR$ 处画两条线段, 称为外限。 (注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- 从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须), 表示该批数据正常值的分布区间。
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用星 *) 表示。



- 绘制数轴。
- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- 计算四分位数差 (IQR) 。
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5/IQR$ 和 $Q1 - 1.5/IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3/IQR$ 和 $Q1 - 3/IQR$ 处画两条线段, 称为外限。**(注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)**
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- 从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须), 表示该批数据正常值的分布区间。
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用星 *) 表示。




- 绘制数轴。
- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- 计算四分位数差 (IQR) 。
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5/IQR$ 和 $Q1 - 1.5/IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3/IQR$ 和 $Q1 - 3/IQR$ 处画两条线段, 称为外限。**(注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)**
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- **从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须) , 表示该批数据正常值的分布区间。**
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用星*) 表示。



- 绘制数轴。
- 计算上四分位数 (Q3) , 中位数, 下四分位数 (Q1) 。
- 计算四分位数差 (IQR) 。
- 绘制箱线图的矩形, 上限为 Q3, 下限为 Q1。在矩形内部中位数的位置画一条横线 (中位线) 。
- 在 $Q3 + 1.5/IQR$ 和 $Q1 - 1.5/IQR$ 处画两条与中位线一样的线段, 这两条线段为异常值截断点, 称为内限; 在 $Q3 + 3/IQR$ 和 $Q1 - 3/IQR$ 处画两条线段, 称为外限。**(注意: 统计软件绘制的箱线图一般都没有标出内限和外限。)**
- 在非异常值的数据中, 最靠近上边缘和下边缘 (即内限) 的两个数值处画横线, 作为箱线图的触须。
- 从矩形的两端向外各画一条线段直到不是异常值的最远点 (即上一步的触须), 表示该批数据正常值的分布区间。
- 温和的异常值用空心圆表示; 极端的异常值用实心点 (一说用星号*) 表示。





box plot | 图解




最小值 (min) =0.5; 下四分位数 (Q1) =7; 中位数 (Med) =8.5;
上四分位数 (Q3) =9; 最大值 (max) =10; 平均值 =8;
四分位数差 (interquartile range, 四分位间距) =Q3-Q1=2。



box plot | 图解



box plot | 图解



Sample, $n = 20$ ○ ●○○ ●○○○ ○○○○ ○○○○

$1.5 \times IQF$

IQR

$$1.5 \times IQR$$

Q

四

Q


whiskers

Outliers




box plot | 变体


Traditional Box Plot




Notched Box Plot





Variable Width Box Plot



Variable Width Notched Box Plot



box plot | 变体



- BoxPlotR
- Plotly
- ECplot
- Galaxy (“Graph/Display Data” 工具集中的 Boxplot)
- R
- ...



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20

复习思考题



表格

- 行、列的含义
- 缩写的含义
- 数值的含义

图片

- 生成图片的数据
- 横、纵轴的含义
- 图片包含的元素
- 图片元素属性的含义



表格

- 行、列的含义
- 缩写的含义
- 数值的含义

图片

- 生成图片的数据
- 横、纵轴的含义
- 图片包含的元素
- 图片元素属性的含义




解析图表 | 图形的语法


- 数据 (data) : 我们想要可视化的对象。
- 几何对象 (geom) : 用以呈现数据、在图中实际看到的图形元素 (点、线、条形、多边形等)。
- 图形属性 (aes) : 几何对象的视觉属性 (位置、颜色、形状、大小和线条类型)。
- 映射 (mapping) : 从数据中的变量对应到图形属性。
- 统计变换 (stats) : 对数据进行的某种汇总 (将数据分组计数以创建直方图)。
- 标度 (scale) : 控制着数据空间的值到图形属性空间的值的映射 (用颜色、大小或形状来表示不同的取值)。
- 坐标系 (coord) : 描述了数据是如何映射到图形所在的平面的，它同时提供了看图所需的坐标轴和网格线。
- 引导元素 (guide) : 向看图者展示了如何将视觉属性映射回数据空间 (坐标轴上的刻度线和标签、图例)。
- 分面 (facet) : 描述了如何将数据分解为各个子集，以及如何对子集作图并联合进行展示。分面也叫做条件作图或网格作图。
- 位置调整：控制着图形对象的重叠。



解析图表 | 图形的语法 | ggplot2



解析图表 | 其他



教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析

- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题



知识点——基因组功能的高级注释

- 变异位点的注释——用途，注释内容，注释工具
- 基因集富集分析——功能，分析工具
- 序列标识——含义，制作工具
- box plot——理解，绘制

技能——解析图表

- 表——行列，缩写，数值
- 图——数据，横纵轴，图元素，元素属性



教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析

- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题



基础知识

- 组装版本和坐标系统
- 常用格式
- 坐标的逻辑运算

高级注释

- 变异位点的注释
- 基因集富集分析
- 制作序列标识

分析平台

- Galaxy
- GenePattern

基础知识

- 组装版本和坐标系统
- 常用格式
- 坐标的逻辑运算

高级注释

- 变异位点的注释
- 基因集富集分析
- 制作序列标识

分析平台

- Galaxy
- GenePattern

基础知识

- 组装版本和坐标系统
- 常用格式
- 坐标的逻辑运算

高级注释

- 变异位点的注释
- 基因集富集分析
- 制作序列标识

分析平台

- Galaxy
- GenePattern

教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析

- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题



- Get Data
- Text Manipulation
- Convert Formats
- Operate on Genomic Intervals
- Phenotype Association
- Statistics
- Graph/Display Data
- NGS Toolbox
- ...



The screenshot shows the Galaxy web interface with the following components:

- Header:** Galaxy | 界面
- Top Navigation:** Analyze Data, Workflow, Shared Data, Visualization, Cloud, Help, User, and a grid icon.
- Left Sidebar (Tools):** A search bar labeled "search tools" with a clear button, followed by a list of links:
 - Get Data
 - Lift-Over
 - Text Manipulation
 - Convert Formats
 - FASTA manipulation
 - Filter and Sort
 - Join, Subtract and Group
 - Extract Features
 - Fetch Sequences
 - Fetch Alignments
 - Get Genomic Scores
 - Operate on Genomic Intervals
 - Statistics
 - Graph/Display Data
 - Regional Variation
 - Multiple regression
 - Multivariate Analysis
- Main Content Area:** A large central panel titled "Galaxy 101" with the subtitle "Start small" and the text "The very first tutorial you need". Below the text is a horizontal navigation bar with several circular icons.
- Right Sidebar (History):** A panel titled "历史" (History) showing "Unnamed history" (1.5 MB). It contains a message: "历史已空，请单击左边窗格中'获取数据'" (History is empty, please click on the left panel to 'Get Data').
- Bottom Navigation:** A series of small navigation icons including arrows, a magnifying glass, and a refresh symbol.
- Page Footer:** Includes the text "Yixf (TJMU)" and "基因组功能注释分析" (Genome Function Annotation Analysis), the date "2015年10月" (October 2015), and the page number "115 / 137".

教学提纲

- 1 引言
- 2 基因组组装版本
- 3 基因组坐标系统
- 4 基因组注释常用格式
- 5 文本文件与文本编辑器
- 6 基因组坐标的逻辑运算
- 7 总结与答疑
- 8 引言
- 9 变异位点的注释
- 10 基因集富集分析

- 11 序列标识
- 12 box plot
- 13 解析图表
- 14 总结与答疑
- 15 引言
- 16 Galaxy 分析平台
- 17 Galaxy 使用演示
- 18 数据处理三段论
- 19 总结与答疑
- 20 复习思考题



- UCSC liftOver tool：支持 BED 和 “chrN:start-end” 格式的输入
- Galaxy (基于 UCSC liftOver tool)：支持 BED、GFF 和 GTF 格式的输入
- CrossMap：支持 SAM/BAM、Wiggle/BigWig、BED、GFF/GTF 和 VCF 格式的输入，输出对应格式
- NCBI Remap：支持 BED、GFF、GTF 和 VCF 等格式的输入
- Ensembl assembly converter (2015 年退休, CrossMap 继位)：支持 BED、GFF、GTF 和 PSL 格式的输入，但输出都是 GFF 格式的
- pyliftover：仅支持点坐标 (point coordinates) 的转换，无法对区段 (ranges) 坐标进行转换



Galaxy 演示 | 坐标转换 | liftOver

hg19 ⇒ hg18

获取输入

输出文件



hg19 ⇒ hg18

① 获取输入

- 输入文件：hg19 坐标

② 数据处理

- 使用 Galaxy 中的“坐标转换”工具

③ 保存输出



hg19 ⇒ hg18

① 获取输入

- 输入文件：hg19 坐标

② 数据处理

→ 通过工具 hg19 ⇒ hg18

③ 保存输出



hg19 \Rightarrow hg18

① 获取输入

- 输入文件：hg19 坐标

② 数据处理

- 设置参数：hg19 \Rightarrow hg18

③ 保存输出



hg19 \Rightarrow hg18

① 获取输入

- 输入文件：hg19 坐标

② 数据处理

- 设置参数：hg19 \Rightarrow hg18

③ 保存输出

正在处理... MAPPED



hg19 \Rightarrow hg18

- ① 获取输入
 - 输入文件：hg19 坐标
- ② 数据处理
 - 设置参数：hg19 \Rightarrow hg18
- ③ 保存输出
 - 过滤结果：MAPPED VS. UNMAPPED



hg19 \Rightarrow hg18

- ① 获取输入
 - 输入文件：hg19 坐标
- ② 数据处理
 - 设置参数：hg19 \Rightarrow hg18
- ③ 保存输出
 - 过滤结果：MAPPED VS. UNMAPPED



BED ⇌ GFF

① 获取输入

选择文件



BED ⇌ GFF

① 获取输入

- 输入文件：BED

② 数据处理

③ 保存输出



BED ⇌ GFF

① 获取输入

- 输入文件：BED

② 数据处理

BED → GFF

GFF → BED

③ 保存输出



BED ⇌ GFF

① 获取输入

- 输入文件：BED

② 数据处理

- ① BED ⇒ GFF
- ② GFF ⇒ BED

③ 保存输出



BED ⇌ GFF

① 获取输入

- 输入文件：BED

② 数据处理

① BED ⇒ GFF

② GFF ⇒ BED

③ 保存输出



BED ⇌ GFF

① 获取输入

- 输入文件：BED

② 数据处理

- ① BED ⇒ GFF
- ② GFF ⇒ BED

③ 保存输出

- 运行结果：互相比较



BED ⇌ GFF

① 获取输入

- 输入文件：BED

② 数据处理

- ① BED ⇒ GFF
- ② GFF ⇒ BED

③ 保存输出

- 查看结果：互相对比



BED ⇌ GFF

① 获取输入

- 输入文件：BED

② 数据处理

- ① BED ⇒ GFF
- ② GFF ⇒ BED

③ 保存输出

- 查看结果：互相比较



- Galaxy 中的 “Operate on Genomic Intervals” 工具集
- BEDTools: a powerful toolset for genome arithmetic
- BEDOPS: the fast, highly scalable and easily-parallelizable genome analysis toolkit



外显子 vs. SNP

① 获取输入



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

③ 保存输出



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

③ 保存输出



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

- subtract
- join

③ 保存输出



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

- subtract
- join

③ 保存输出



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

- **subtract**
- join

③ 保存输出



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

- subtract
- join

③ 保存输出

→ 分析结果



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

- subtract
- join

③ 保存输出

- 解析结果



外显子 vs. SNP

① 获取输入

- exon
- SNP

② 数据处理

- subtract
- join

③ 保存输出

- 解析结果



问题

- 找到含有至少 N (2) 个 SNP 的外显子。

输入

- 外显子数据 (BED 格式)
- SNP 数据 (BED 格式)

输出

- 满足要求的外显子信息 (BED 格式)



问题

- 找到含有至少 N (2) 个 SNP 的外显子。

输入

- 外显子数据 (BED 格式)
- SNP 数据 (BED 格式)

输出

- 满足要求的外显子信息 (BED 格式)



问题

- 找到含有至少 N (2) 个 SNP 的外显子。

输入

- 外显子数据 (BED 格式)
- SNP 数据 (BED 格式)

输出

- 满足要求的外显子信息 (BED 格式)



外显子数据

①	chr1	10	20	exon1	0	+
②	chr1	30	40	exon2	0	+
③	chr1	50	60	exon3	0	-
④	chr1	65	75	exon4	0	+
⑤	chr1	85	95	exon5	0	-



SNP 数据

①	chr1	11	12	snp1	0	+
②	chr1	15	16	snp2	0	+
③	chr1	17	18	snp3	0	+
④	chr1	24	25	snp4	0	+
⑤	chr1	33	34	snp5	0	+
⑥	chr1	37	38	snp6	0	+
⑦	chr1	44	45	snp7	0	+
⑧	chr1	54	55	snp8	0	+
⑨	chr1	57	58	snp9	0	-



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- Input: Get exons, SNPs; UCSC Table Browser
- Join[Operate on Genomic Intervals]: Join exons with SNPs
- Group: Count the number of SNPs per exon
- Filter: Filter exons that have ten or more SNPs
- Compare two Datasets: Recover exon information
- Sort: Sort the start and end coordinates
- Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter SNPs with count >= 10
- ⑤ Sort: Sort by count (descending)



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Compare two Datasets: Recover exon information
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Compare two Datasets: Recover exon information
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Compare two Datasets: Recover exon information
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Compare two Datasets: Recover exon information
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Compare two Datasets: Recover exon information
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Compare two Datasets: Recover exon information
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Group-Filter-Compare-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Compare two Datasets: Recover exon information
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- Input: Get exons, SNPs; UCSC Table Browser
- Join[Operate on Genomic Intervals]: Join exons with SNPs
- Count: Count the number of SNPs per exon
- Filter: Filter exons that have ten or more SNPs
- Cut: Cut columns to recover BED format
- Sort: Sort the start and end coordinates
- Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Count: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Cut: Cut columns to recover BED format
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Count: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Cut: Cut columns to recover BED format
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Count: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Cut: Cut columns to recover BED format
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Count: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Cut: Cut columns to recover BED format
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Count: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Cut: Cut columns to recover BED format
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Count: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Cut: Cut columns to recover BED format
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding exons with the highest number (≥ 10) of SNPs

Join-Count-Filter-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Count: Count the number of SNPs per exon
- ④ Filter: Filter exons that have ten or more SNPs
- ⑤ Cut: Cut columns to recover BED format
- ⑥ Sort: Sort the start and end coordinates
- ⑦ Visualize: Display data in genome browser



Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- Input: Get exons, SNPs; UCSC Table Browser
- Join[Operate on Genomic Intervals]: Join exons with SNPs
- Group: Count the number of SNPs per exon
- Sort: Sort exons by SNPs count
- Select first: Select top ten
- Join[Join two Datasets]: Recover exon information
- Cut: Cut columns to recover BED format
- Sort: Sort the start and end coordinates
- Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon

④ Sort[Sort by column]: Sort by the count of SNPs in descending order

⑤ SelectFirst[Select first N rows]: Select the top 10 rows

⑥ Join[Operate on Genomic Intervals]: Join exons with SNPs

⑦ Cut[Cut by column]: Cut the first 10 columns

⑧ Sort[Sort by column]: Sort by the count of SNPs in descending order

⑨ SelectFirst[Select first N rows]: Select the top 10 rows

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding 10 exons with the highest number of SNPs

Join-Group-Sort-SelectFirst-Join-Cut-Sort

- ① Input: Get exons, SNPs; UCSC Table Browser
- ② Join[Operate on Genomic Intervals]: Join exons with SNPs
- ③ Group: Count the number of SNPs per exon
- ④ Sort: Sort exons by SNPs count
- ⑤ Select first: Select top ten
- ⑥ Join[Join two Datasets]: Recover exon information
- ⑦ Cut: Cut columns to recover BED format
- ⑧ Sort: Sort the start and end coordinates
- ⑨ Visualize: Display data in genome browser

Finding exons with the highest number (≥ 10) of SNPs

BEDTools-shell-BEDTools

考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c -s |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

不考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

Finding exons with the highest number (≥ 10) of SNPs

BEDTools-shell-BEDTools

考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c -s |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

不考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

Finding exons with the highest number (≥ 10) of SNPs

BEDTools-shell-BEDTools

考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c -s |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

不考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

Finding exons with the highest number (≥ 10) of SNPs

BEDTools-shell-BEDTools

考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c -s |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

不考虑链性

```
bedtools intersect -a exon.bed -b snp.bed -c |  
awk '{if($7>=10) print;}' | cut -f1-6 |  
bedtools sort -i stdin
```

Workflow: create, modify, rerun, share

Save: Rename the history as "Exons and SNPs"

Workflow: Extract workflow from history

Workflow: Create a new workflow from the extracted one



Workflow: create, modify, rerun, share

- ① Save: Rename the history as “Exons and SNPs”
- ② Workflow: Extract workflow from history
- ③ Modify: Open workflow editor and modify the parameter
- ④ Rerun: Run workflow on whole genome data
- ⑤ Share: Share or publish workflow
- ⑥ Create: Create workflows from scratch (e.g. Find the 50 longest exons)



Workflow: create, modify, rerun, share

- ① Save: Rename the history as “Exons and SNPs”
- ② Workflow: Extract workflow from history
- ③ Modify: Open workflow editor and modify the parameter
- ④ Rerun: Run workflow on whole genome data
- ⑤ Share: Share or publish workflow
- ⑥ Create: Create workflows from scratch (e.g. Find the 50 longest exons)



Workflow: create, modify, rerun, share

- ① Save: Rename the history as “Exons and SNPs”
- ② Workflow: Extract workflow from history
- ③ **Modify: Open workflow editor and modify the parameter**
- ④ Rerun: Run workflow on whole genome data
- ⑤ Share: Share or publish workflow
- ⑥ Create: Create workflows from scratch (e.g. Find the 50 longest exons)



Workflow: create, modify, rerun, share

- ① Save: Rename the history as “Exons and SNPs”
- ② Workflow: Extract workflow from history
- ③ Modify: Open workflow editor and modify the parameter
- ④ **Rerun: Run workflow on whole genome data**
- ⑤ Share: Share or publish workflow
- ⑥ Create: Create workflows from scratch (e.g. Find the 50 longest exons)



Workflow: create, modify, rerun, share

- ① Save: Rename the history as “Exons and SNPs”
- ② Workflow: Extract workflow from history
- ③ Modify: Open workflow editor and modify the parameter
- ④ Rerun: Run workflow on whole genome data
- ⑤ Share: Share or publish workflow
- ⑥ Create: Create workflows from scratch (e.g. Find the 50 longest exons)



Workflow: create, modify, rerun, share

- ① Save: Rename the history as “Exons and SNPs”
- ② Workflow: Extract workflow from history
- ③ Modify: Open workflow editor and modify the parameter
- ④ Rerun: Run workflow on whole genome data
- ⑤ Share: Share or publish workflow
- ⑥ Create: Create workflows from scratch (e.g. Find the 50 longest exons)



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19



总结与答疑

20


复习思考题



三段论：“输入-加工-输出”



三段论：“输入-加工-输出”



教学提纲

1

引言

2

基因组组装版本

3

基因组坐标系统

4

基因组注释常用格式

5

文本文件与文本编辑器

6

基因组坐标的逻辑运算

7

总结与答疑

8

引言

9

变异位点的注释

10

基因集富集分析

11

序列标识

12

box plot

13

解析图表

14

总结与答疑

15

引言

16

Galaxy 分析平台

17

Galaxy 使用演示

18

数据处理三段论

19

总结与答疑

20

复习思考题



知识点——Galaxy 分析平台

- Galaxy——界面、学习、使用

技能——“输入-加工-输出”三段论

- 获取输入——格式、来源、过滤
- 数据处理——工具、版本、参数
- 解析输出——格式、注释、解析



教学提纲

- 11 序列标识
 - 12 box plot
 - 13 解析图表
 - 14 总结与答疑
 - 15 引言
 - 16 Galaxy 分析平台
 - 17 Galaxy 使用演示
 - 18 数据处理三段论
 - 19 总结与答疑
 - 20 复习思考题



复习思考题

知识点

- ① hg19 和 mm10 分别代表什么含义？hg19 是和 GRCh37 相对应，还是和 GRCm38 相对应？
- ② 常见的基因组坐标系统是哪两种，举例进行说明。
- ③ 简述 BED 格式前 6 列的含义，能解释实际的 BED 记录。
- ④ 基于基因组坐标的常见逻辑运算模式有哪些，画图进行解释。
- ⑤ 简述序列标识的含义，能解释实际的序列标识图。

技能

- ① 不同操作系统的换行符有何区别？
- ② 以 SNP 的注释结果为例，论述如何解析一张表。
- ③ 以 box plot 为例，论述如何解析一张图。
- ④ 以坐标转换为例，论述“输入-加工-输出”的工作流程。

Powered by



T_EX L^AT_EX X_ET_EX Beamer