

Commercial Battery Storage & Inverter Handbook

Sales & Aftersales Reference — Australia | Document OPS-SAL-2026-03, Revision C, effective 1 July 2026

1. Document Control

Field	Value
Document number	OPS-SAL-2026-03
Revision	C (supersedes Revision B of 1 January 2026)
Owner	Commercial Operations, Australia
Audience	Direct sales representatives, channel account managers, aftersales engineers
Review cycle	Every 6 months, or on any change to warranty or discount policy

2. Scope

This handbook is the single source of truth for statements made to customers about warranty periods, channel discounts, certification status and delivery lead times for the HC series battery cabinets, the INV series inverters and the in-house EMS platform. Where a customer quotation contradicts this handbook, this handbook prevails until a written exception is issued by Commercial Operations.

3. Product Line Summary

Model	Category	Usable capacity	Rated power	Chemistry / topology	Typical application
HC-215	Battery cabinet	215 kWh	100 kW	LFP, liquid cooled	Single-factory peak shaving
HC-430	Battery cabinet	430 kWh	200 kW	LFP, liquid cooled	Industrial park, two-cabinet cluster
HC-860	Battery cabinet	860 kWh	400 kW	LFP, liquid cooled	Commercial complex, four-cabinet cluster
INV-50	PV inverter	—	50 kW	Three-phase string	Rooftop commercial PV
INV-100	PV inverter	—	100 kW	Three-phase string	Large rooftop and ground mount
EMS-Pro	Energy management	—	—	Software, on-premise gateway	Site controller for HC clusters

4. Warranty Policy

4.1 Standard warranty periods

Product	Standard warranty	Extended option	Throughput limit	End-of-warranty capacity retention
HC-215	10 years	up to 15 years	6,000 cycles	70% of rated usable capacity
HC-430	10 years	up to 15 years	6,000 cycles	70% of rated usable capacity
HC-860	10 years	up to 20 years	8,000 cycles	70% of rated usable capacity
INV-50	5 years	up to 10 years	not applicable	not applicable
INV-100	5 years	up to 10 years	not applicable	not applicable
EMS-Pro gateway	3 years	not offered	not applicable	not applicable

The warranty period starts on the earlier of the commissioning date recorded in the EMS platform or 6 months after despatch from the company warehouse. Whichever limit is reached first — the calendar period or the throughput limit — ends the warranty.

4.2 Extended warranty pricing

Extension	HC-215	HC-430	HC-860
+5 years	AUD 6,400	AUD 11,900	AUD 22,500
+10 years	not offered	not offered	AUD 41,000

Extended warranty must be purchased before the end of the second year of the standard warranty. After that point no extension can be sold for that unit.

4.3 Exclusions

1. Damage caused by installation that does not follow the official installation manual, including inadequate clearance or unsealed cable entries.
2. Operation outside the specified ambient range of -20°C to $+50^{\circ}\text{C}$.
3. Any repair or firmware modification performed by a party that is not an accredited service partner.
4. Consumables: air filters, door seals and the coolant charge, all of which are treated as scheduled maintenance items.
5. Sites where the EMS platform has been disconnected from the internet for more than 90 consecutive days, because degradation data cannot be verified.

Response commitment: for a warranty claim raised through the partner portal, the company responds within 2 business days and attends site within 5 business days in a metropolitan area, or 10 business days in a regional area.

5. Channel Commercial Policy

5.1 Discount tiers

Tier	Annual committed volume	Discount off list price	Payment terms	Demo stock
Registered reseller	below AUD 500k	12%	Prepayment	not eligible
Authorised partner	AUD 500k – 2m	18%	30 days net	1 unit HC-215
Premier partner	above AUD 2m	25%	45 days net	1 unit HC-430

The maximum discount any sales representative may offer without approval is 25% off list price. A discount above 25% and up to 30% requires written approval from the National Sales Manager, and nothing beyond 30% is approved under any circumstance. Project-specific pricing is not stackable with tier discount: the larger of the two applies, never both.

5.2 Delivery lead times

State	HC series, stock available	HC series, made to order	INV series
NSW	3 weeks	12 weeks	2 weeks
VIC	3 weeks	12 weeks	2 weeks
QLD	4 weeks	13 weeks	2 weeks
SA	4 weeks	13 weeks	3 weeks
WA	6 weeks	15 weeks	4 weeks

Lead time is counted from receipt of a signed order and the deposit, not from the date of quotation. Freight to a metropolitan delivery address is included for orders above AUD 150,000; below that threshold freight is quoted per site.

5.3 Cancellation and return

- An order may be cancelled without charge until manufacturing release, which is 10 business days after order confirmation.
- After manufacturing release a cancellation fee of 15% of order value applies.
- Commissioned units cannot be returned; the warranty replacement process applies instead.

6. Certification and Compliance

Product	Grid connection standard	Safety standard	CEC listed	Certificate reference
HC-215 / HC-430 / HC-860	AS/NZS 4777.2:2020	AS/NZS 5139:2019	Yes	CEC-BAT-2025-0418
INV-50 / INV-100	AS/NZS 4777.2:2020	IEC 62109-1 / -2	Yes	CEC-INV-2025-1177
EMS-Pro	not applicable	IEC 62443-4-1 aligned	not applicable	—

All HC series cabinets carry an IP54 enclosure rating and are rated for outdoor installation. Fire safety documentation is issued per project and references AS 2419.1 for hydrant provision; the company does not certify the site fire system itself.

7. Approved Customer-Facing Statements

The wording below is pre-approved and may be used verbatim in customer correspondence. Any variation must be reviewed by Commercial Operations before it is sent.

- On warranty: “The HC series carries a 10 year standard warranty with a guaranteed 70% capacity retention at end of term, extendable to 15 years for HC-215 and HC-430 and to 20 years for HC-860.”
- On availability: “Stocked HC units are delivered within 3 to 6 weeks depending on state; made-to-order configurations are 12 to 15 weeks from order confirmation.”
- On compliance: “All battery cabinets and inverters sold in Australia are Clean Energy Council listed and certified to AS/NZS 4777.2:2020.”

Anything not covered by this handbook — bespoke availability guarantees, liquidated damages, uptime percentages — must not be committed to in writing without Commercial Operations sign-off.