ETH ROBOTICS SUMMER SCHOOL LINUX & ROS CHEAT SHEET

AUTHOR: YIZE WANG LAST UPDATED: MAY 5, 2020

File Commands

\$ 1s	list contents of files and directories	
\$ ls -a	list hidden files and directories	
cd \$DIR	change working directory to \$DIR	
\$ cd	change working directory to home	
mkdir \$DIR	create a directory named \$DIR	
\$ pwd	print working directory	
rm \$FILE	remove \$FILE	
rm -r \$DIR	remove \$DIR	
\$ rm -f \$FILE	force remove \$FILE	
rm -rf \$DIR	force remove \$DIR	
cp \$FILE1 \$FILE2	copy \$FILE1 to \$FILE2	
cp -r \$DIR1 \$DIR2	copy \$DIR1 to \$DIR2	
mv \$FILE1 \$FILE2	move \$FILE1 to \$FILE2	
ln -s \$FILE \$LINK	create symbolic link \$LINK to \$FILE	
touch \$FILE	create \$FILE	
cat \$FILE	view content of \$FILE	
\$ cat > \$FILE	write input into \$FILE	
\$ more \$FILE	print contents of \$FILE	
head \$FILE	print the first 10 lines of \$FILE	
\$ tail \$FILE	print the last 10 lines of \$FILE	

System Info

print environment variables	
print system date and time	
print current month calendar	
print system uptime	
print online users	
print current user	
print information about \$USER	
print kernel information	
print cpu information	
print memory information	
print user manual of \$COMMAND	
print disk usage	
print directory space usage	
print memory and swap usage	
print locations of \$APP	
print print executable file of \$APP	

Compression

\$ tar cf \$FILE.tar \$FILES	convert \$FILES into \$FILE.tar	
\$ tar xf \$FILE.tar	extract files from \$FILE.tar	
\$ tar czf \$FILE.tar.gz \$FILES	compress \$FILES into \$FILE.tar.gz using Gzip	
\$ tar xfz \$FILE.tar.gz	extract files from \$FILE.tar.gz using Gzip	
\$ gzip \$FILE	compress \$FILE and rename it as \$FILE.gz	
\$ gzip -d \$FILE.gz	decompress \$FILE.gz back to \$FILE	

Network

\$ ip address	print all internet protocol addresses	
\$ ping \$HOST	ping \$HOST and print results	
\$ whois \$DOMAIN	print information about \$DOMAIN	
\$ dig \$DOMAIN	print DNS of \$DOMAIN	
\$ dig -x \$HOST	reverse lookup \$HOST	
\$ wget \$FILE	download \$FILE	

Terminator

\$ Ctrl+Alt+T	launch a new terminal
\$ Ctrl+C	kill the current process
\$ Ctrl+Z	suspend the current process
\$ fg	resume the suspended process in foreground
\$ bg	resume the suspended process in background
\$ Ctrl+D	log out of the current session
\$ Ctrl+W	erase one word in the current line
\$ Ctrl+U	erase the whole current line
\$ Ctrl+R	reverse search in the previous commands
\$!!	execute the last command
\$ exit	log out of the current session
\$ Ctrl+Shift+E	split the window vertically vertically
\$ Ctrl+Shift+O	split the window horizontally

Package

\$ apt-get update	synchronize package index files from sources	
\$ apt-get upgrade	de install latest versions of installed packages	
\$ apt-get install \$PACKAGE	install \$PACKAGE	
\$ dpkg -i \$PACKAGE.deb	install a Debian package \$PACKAGE.deb	
\$./configure	configure building settings	
\$ make	build the program from source code	
\$ make install	install the program	

Secure Shell (SSH)

\$ ssh \$USER @ \$HOST	connect to \$HOST as \$USER
\$ ssh \$IP_ADDRESS	connect to \$IP_ADDRESS
\$ ssh -p \$PORT \$USER @ \$HOST	connect to \$HOST on \$PORT as \$USER
\$ ssh-copy-id \$USER @ \$HOST	add the key to \$HOST as \$USER

Searching

\$ grep \$PATTERN \$FILE	search for \$PATTERN in \$FILE
\$ grep -r \$PATTERN \$DIR	recursively search for \$PATTERN in \$DIR
\$ \$CMD grep \$PATTERN	search for \$PATTERN in \$CMD's output
\$ locate \$FILENAME	find all files whose name contain \$FILENAME

Git

OIL		
\$ git clone \$URL	clone the repository from \$URL	
\$ git status	print current branch status \$BRANCH	
\$ git branch \$BRANCH	create a new branch named \$BRANCH	
\$ git checkout \$BRANCH	switch to the branch named \$BRANCH	
\$ git merge \$BRANCH	combine \$BRANCH into the current one	
\$ git fetch	download all history from GitHub	
\$ git merge	combine remote branches into local branch	
\$ git push	upload all local branch commits to GitHub	
\$ git pull	update local branch from GitHub	
\$ git log	list version history for current branch	
\$ git log -follow \$FILE	list version history for \$FILE	
\$ git show \$COMMIT	output content changes of \$COMMIT	
\$ git add \$FILE	stage \$FILE	
\$ git commit -m "\$MESSAGE"	commit staged file with \$MESSAGE	
\$ git reset \$FILE	reset \$FILE	
\$ git reset –hard	reset all uncommitted changes	
\$ git clean -fd	recursively force remove unstaged files	

.bashrc

\$	
\$	
\$	
\$	
\$	
\$	
\$ 	

ROS Run

\$ roscore	invoke the core of ros
\$ rosrun \$PACKAGE \$EXECUTABLE	run \$EXECUTABLE in \$PACKAGE
\$ roslaunch \$PACKAGE \$LAUNCHFILE	launch \$LAUNCHFILE in \$PACKAGE

ROS Node

\$ rosnode ping \$NODE	test connectivity to \$NODE
\$ rosnode list	list active nodes
\$ rosnode info \$NODE	print information about \$NODE
\$ rosnode machine	list nodes running on the machine
\$ rosnode kill \$NODE	kill a running node

ROS Topic

\$ rostopic list	print information about active topics
\$ rostopic bw \$TOPIC	display bandwidth used by \$TOPIC
\$ rostopic echo \$TOPIC	print messages from \$TOPIC
\$ rostopic find \$TYPE	find topics with \$TYPE
\$ rostopic hz \$TOPIC	display publishing rate of \$TOPIC
\$ rostopic info \$TOPIC	print information about \$TOPIC
\$ rostopic pub \$TOPIC	publish data to \$TOPIC
\$ rostopic type \$TOPIC	print type of \$TOPIC

ROS Packge Structure

package.xml	manifest, dependencies and plugins
CMakeLists.txt	description of compilation procedure
src/	C and C++ source codes
include/	C and C++ header files
scripts/	Python and bash scripts
config/	ymal configuration files
cfg/	dynamics reconfigure scripts
launch/	launch files

sudo sudo means super user do, elevated right granted

ROS Service

\$ rosservice list	list active services
\$ rosservice call \$SERVICE \$ARGS	call \$SERVICE with \$ARGS
\$ rosservice find \$TYPE	find services with \$TYPE
\$ rosservice info \$SERVICE	print information about \$SERVICE
\$ rosservice type \$SERVICE	print type of \$SERVICE
\$ rosservice uri \$SERVICE	print uri of \$SERVICE

ROS Visualization Tools

\$ rviz	3D visualization of data and models
\$ gzclient	Gazebo GUI
\$ rqt	powerful GUI tool
\$ rqt_plot	simple and lightweight plotting
\$ rqt_bag	visualize content of a bag
\$ rqt_image_view	visualize camera images

ROS Parameter

\$ rosparam list	list all parameter names
\$ rosparam set \$PARAM \$VAL	set \$PARAM to \$VAL
\$ rosparam get \$PARAM	print value of \$PARAM
\$ rosparam load \$YAML	load parameters from \$YAML
\$ rosparam dump \$YAML	dump parameters to \$YAML
\$ rosparam delete \$PARAM	delete \$PARAM

ROS Visualization

\$
\$
\$
\$
\$
\$
\$
\$
\$
\$
\$
\$
\$
\$
\$

ROS Bag

\$ rosbag record \$TOPIC	record \$TOPIC into bag
\$ rosbag info \$BAG	print content summary of \$BAG
\$ rosbag play \$BAG	play back content of \$BAG
\$ rosbag check \$BAG	check play-ability of \$BAG in current system
\$ rosbag compress \$BAG	compress \$BAG using BZ2
\$ rosbag decompress \$BAG	decompress \$BAG using BZ2

TODO

1020	
ubuntu mono font for commands	
tab auto-completion	
tar explanation	
is git reset unstage or reset?	
simtime true	
copyright	
rosnode machine	
column split	
Cmakelist	
ros launchfile	

ROS Catkin Workspace

\$ mkdir -p ~/catkin_ws/src	create a new catkin workspace	
\$ cd ~/catkin_ws		
\$ catkin_make		
\$ catkin build	build the whole workspace	
\$ catkin build \$PACKAGE	build \$PACKAGE	
\$ catkin clean	clean the whole workspace	
\$ catkin clean \$PACKAGE	clear \$PACKAGE	

remember to source ~/catkin_ws/devel/setup.bash

Variable Declaration VARIABLE stands for a variable whose name is VARIABLE. For example, FILE means a file named FILE.