Multi-Channel Hebbian Plasticity in Multilayer BDH: A Learned Partition of Working Memory on a Synthetic Binding Task with Local Cues

A window gate, slow memory and a channel split aimed at the task's key positions find an eight-way partition of the grouped layout without stream labels or restarts, on two machines with disjoint seeds, and 17/20 in a replication from the text alone

A technical report • Revision 11 (final)

Project repository: `Ynkling/clankers`

Abstract

BDH's Hebbian working memory is split into k channels, and a per-token gate distributes each token's write over the channels and blends its read from them. On a synthetic task, S streams bind the same keys to different values, cued by a stream token; one channel cannot hold the conflicting bindings at four or eight streams, and a hand-set gate, one channel per stream, can. The question is whether a gate trained only on the task loss finds that partition. Revision 8 answered it for the task's grouped layout, where the cue is within three tokens of every write: a *window gate* (a width-3 causal convolution of the embeddings), slow memory for the first 2400 updates and a plateau-triggered *channel split* that copies the busiest channel's gate row onto the idlest bind eight streams, the streams on disjoint sets of channels, in 38/40 runs of a pre-registered test on two machines with disjoint seeds, against 0/40 for the recurrent-gate recipe (38 vs 0 discordant pairs) and 15/40 without the split (23 vs 0). The recipe uses no stream labels, no restarts and no hinge; the split reads the task's key positions.

This revision reports what has been done to that result since. An independent referee session recomputed the numbers of the report's tables from the records (140 of 156 reproduce; the seven that disagreed were statements, corrected in Revision 8.1), audited the pre-registration of every claim (none edited after a run), compiled the project's claim registry (53 pre-registered tests per machine, of which the headline survives any multiplicity correction), and found statements in Revision 8 that were wrong when committed; they are corrected and listed. A clean-room replication, from the report alone for its first twenty seeds, by a session that had not seen the code when it ran them, bound eight streams 17/20 against 7/20 without the split (10 vs 0), and 18/20 on twenty further seeds after taking the split's probe and key positions from our code (35/40 against 12/40 pooled, 23 vs 0): the model it built agrees with ours to 7×10^{-9} in the gates and 7×10^{-8} in the logits, the 44 details it logged (34 of them guesses) are stated in an appendix, and one of them exposed a sampling weakness in the split's own probe. On the main line, the second claim of Revision 8 is now a pre-registered result on two machines with disjoint seeds: the copy with its reset binds eight streams 18/20 against the reset alone 6/20 (12 vs 0), the reset alone is within the bound of no trigger (6/20 against 8/20, 0 vs 2), and one delta-rule channel binds 0/20 where the recipe binds 18/20 (18 vs 0); the pre-fixed readings "the copy, not the reset" and "the partition is necessary at eight streams against a single delta channel" both apply. Exploratory screens, which are not claims, answered three questions the earlier revision left open, each on ten to twenty paired seeds. The delta-rule write, with its write strength fixed rather than learned, is not shown worse than the Hebbian write at two, four and eight streams (10/10, 10/10 and 9/10 against 10/10) and binds sooner at two and eight, and its pre-registered test is now complete on both machines: pooled over 40 pairs with disjoint seeds, the delta recipe binds eight streams 35/40 against the Hebbian recipe's 35/40 ($d = 0$; the pre-fixed label "delta not shown worse by more than 2 pairs"), it needs no split to do so (without a trigger 38/40; the split's claim on delta NOT SHOWN, with no room), and the Hebbian write needs the split

(35/40 against 17/40, 19 vs 1, $p = 2 \times 10^{-5}$); the readings "delta: no room; Hebbian: helps" apply, and delta binds sooner on 24 of the 30 seeds both bind. The headline arms also ran on a third machine class, a GPU with CUDA arithmetic, on fresh seeds: the recipe 19/20, without the split 6/20, the recurrent gate 0/20; and the replication session reproduced `test_split_copy`'s three counts on fresh seeds (18/20, 9/20, 0/20), each inside the main line's interval, its delta arm from the specification alone. On Hebbian memory the layer whose routing matters is the first: perfect gates at the later layers alone bind 0/10, and a register that overwrites at the context token, read by a gate at all three layers, carries a cue up to six tokens away 20/20 when nudged by labels, is found label-free on 4/20 seeds, fourteen of the sixteen failures on each memory being key splits, formed in the records before any write at the cue, and is found 20/20 on fresh seeds when a hinge on the gate's key-dependence holds the key split off for the first 2400 updates, a training-time prior that reads the task's key positions and identities, as the split reads key positions. Under a dense next-token loss on two interleaved sources a single channel learns to carry the source by itself; at four sources, on a GPU screen that its own validity rule leaves untested (the perfect gate ended at 0.880 and 0.892 against a bar of 0.9), neither one channel nor either learned gate did, on ten seeds each. Two-stream key splits resist repair and are prevented by the hinge's key term on a screen (20/20 against 15/20), as the register's are; a replication's probe can be wrong about a plateau; the title is scoped to what was shown.

Two further rounds of screens (19–23 October), the last of the project, took away what the recipe reads. With each sequence's four keys drawn from 32 types, a Hebbian channel with its routing given does not bind them (0/2 on each of two tasks at 24,000 and at 48,000 updates, routing perfect throughout) and a delta channel binds at 2400–3600; the short convolution restores the Hebbian channel (2/2 and 2/2). A hinge that reads only which token types repeat within the sequence, no labels and no corpus table, matches the labelled key hinge within one pair where the keys are pooled, the committed rule's "replaces the key hinge" (20/20 against 20/20 on delta memory, where the register alone already binds 16/20; 19/20 against 18/20 on Hebbian memory with the convolution, where the register alone binds 9/20 and the hinge is needed, 9–10 vs 0), and falls short of it on the original task (17/20 against 20/20, 3 vs 0). When the context tokens themselves are drawn from a pool, one delta channel binds two documents without any gate (10/10) and no learned gate routes them, with two channels, where any fixed type→channel map is capped at 0.533 of sequences, or with sixteen, where a handed channel per type routes every sequence (0/20 and 0/10 in every arm on either memory, against 2/2 for the handed index and the handed type map): at sixteen channels a learning negative at the budget and not a capacity limit, the referee's reading, and the frontier at which the work stops. On the eight-stream grouped layout both perfect gates are reliable to eight key types, the delta one is the limit from sixteen, and at eight the delta recipe with the split carries 10/10 where the Hebbian recipe binds 6/10 and, at 32 key types with a reliable oracle, 1/10. The author concluded the project on 1 November 2026. This final revision records those rounds, every report of which but one the referee checked against its records; the revision itself was checked by a checking agent run from the author's session, not by the referee. Two tests were left specified and not run: the register test, whose specification the referee passed for adoption after ten text fixes, and the dense-loss follow-up at four sources, prepared on both GPUs through its pre-run note.

Revision 8 (7–10 October 2026). Revision 8 added Phase VI: two pre-registered tests on two machines with disjoint seeds, an audit of the project's records (`docs/audit_2026-10.md`), five exploratory batches on the side branch, three exploratory sessions on their own branches and a reading of twelve papers (`docs/reading/`). Its first draft was reviewed by an independent referee session, which found statements that were wrong when committed; Revision 8.1 corrected them and nothing else (the list is in Section 15).

Revision 9 (10–13 October 2026). Revision 9 added, on the main line, a third pre-registered test (`test_split_copy`, complete on both machines) and a fourth (`test_delta_recipe`), speci-

fied, reviewed by the referee, amended once before any run and written, its test file checked against the amended spec before any arm's run (the check preceded the runs by two and a half hours; X's verification took three), and complete on X (a second amendment, to the report's rules only, was committed during X's run with a statement of what had been seen; L's half was not yet recorded); the referee's report, recomputation and claim registry, merged into the repository (`docs/review_2026-10/`); an independent clean-room replication of the main result (branch `claude/replicate-R`); the exploratory sessions' second and third rounds (F's S68–S81, G's S55–S83, H's S61–S86, I's S74, its GPU package and S75 at four sources on the user's GPU); and L's result files for Phases III–IV, which were missing from the repository. Two machines ran every main-line test: **X**, a cloud container on Intel Xeon hosts at 2.10 and 2.80 GHz, and **L**, an Intel i7-12650H. From the Muon-recipe test on, X and L run disjoint seeds and the pooled claim is primary. The exploratory sessions are **E** (branch `claude/outside-ideas`, batches 1–19, complete), **F**, **G**, **H** and **I** (branches `claude/explore-F/G/H/I`), the replication **R** (`claude/replicate-R`) and the referee **V** (`claude/review-V`); F, G, H, I and V ran on 2.10 GHz Xeons (R's records carry no CPU model), E's batches mostly on 2.10 GHz hosts with 60 of batch 16's 165 runs and batch 19 on 2.80 GHz. Every verdict was fixed before its run and printed mechanically; the referee's recomputation (Section 15) re-derived every pre-registered reading of the sessions' later reports from their records and checked that the earlier ones were committed before their first run. The referee also checked Revision 9's first draft against the records, and the statements it found wrong are corrected and listed in Section 15. Revision 9 was checked against the records in seven passes by the referee session before it was merged. The title has been scoped to what was shown.

Revision 10 (19 October 2026). This revision records `test_delta_recipe`'s L half and its pooled result, which is primary (Section 11); a run of `test_window_gate`'s eight-stream arms on a third machine class, a consumer GPU, on fresh seeds (session I; Section 5); the replication session's fifth phase, `test_split_copy` on fresh seeds, its delta arm from the specification alone (Section 14); the exploratory sessions' fifth round (F's S88, G's S87, H's S87, I's last S75 arm) and E's batches 20 and 21, which ran beside it; the referee's checks of the first three of these before the draft (`docs/review_2026-10/round6_A3.md`) and, after the merge, of the whole revision and of the fifth round's screens (`rev10/referee_pass.md`; the draft itself had been checked in two passes by a separate checking agent run from the author's own session, whose files git cannot order before the third version and which recomputed `test_delta_recipe`, the GPU run and H's screens and read the other screens' reports, `rev10/first_pass.md`, `second_pass.md`) and its reviews of three of the four specifications the sessions drafted (three main-line tests and one exploratory screen), none of which is ready to run as written (Section 15). No claim of Revision 9 changes. The GPU was a GTX 1660 SUPER on the user's server, which left the project on 19 October; the remaining GPU is the laptop's RTX 3070. Everything remains one small model on synthetic tasks.

Revisions 10.1 and 10.2 (19–20 October 2026). Revision 10 was merged after two passes by a separate checking agent; the referee session then checked it against the records (`docs/review_2026-10/rev10/referee_pass.md`) and found every number of every pre-registered claim to reproduce and nine statements, in sixteen places, false against the records or git: an account of who had checked what, a run count and a sentence made stale by the fifth round's screens, two descriptions of screens, four provenance rows that stopped before the fifth round, and an index row. Revision 10.1 corrected them and most of the looser statements the pass listed, and was itself merged before the referee read it; its check (`rev10/revision_10_1_check.md`) found the nine corrected in all sixteen places and about a dozen small residues, which Revision 10.2 takes, with

nothing else changed; the list is in Section 15. Revision 10.2 is the first revision since 9 to be passed by the referee before its merge.

Revision 11 (final, 1 November 2026). The author concluded the project on 1 November 2026, by choice, and this revision is its last. It adds the exploratory sessions' sixth and seventh rounds (19–23 October), which removed the task's marked keys and then its fixed context identities: session F's pool and context-pool task families and what one channel holds on them (Section 11); session G's label-free hinges on pooled keys, its screens of contexts without fixed identity at $k = 2$ and $k = 16$, and the register specification's second revision (Section 12); session H's recipe and oracles at key pools of 4 to 32 on the eight-stream grouped layout (Section 10); and session I's preparation of the dense-loss follow-up S75b on both GPUs, through its pre-run note and up to, not including, its pilot (Section 19; the GTX 1660 SUPER returned to the project on 22 October). Every one of the sessions' reports but the last, H's report 12, was checked by the referee against its records (`docs/review_2026-10/check_*`, `screen_review_*`; Section 15; F's report 10 in its first version, its two addenda coming after the check); the referee's last file is dated 23 October. No main-line test ran after `test_delta_recipe` (13 October), and no claim of Revisions 9 and 10 changes. This revision was checked against the records by a separate checking agent run from the author's session, whose independence git cannot show, and not by the referee: it is the first revision since 10.1 to be merged without the referee's pass, and the report says so where it matters. The repository's state at the conclusion is `STATUS.md`: the final state of every branch, what was left ready (the register test, S75b) and what was left open, and how to resume; `specs/drafts/` holds the register specification's revision 2, marked as not adopted. Everything remains one small model on synthetic tasks.

test, batch or session	question	verdict	§
`muon_recipe` (X, L, pooled)	the early hinge window under Muon; Muon's speed at four streams and eight keys	M1 SHOWN pooled; M2, M3 NOT SHOWN pooled; reading not met	7
`window_gate` (X, L, pooled)	the window gate with slow memory, no hinge, at 2, 4 and 8 streams; the split at 8	G1, G2, G4 SHOWN pooled; G3 HOLDS; "eight streams bind without labels or restarts"	5
`split_copy` (X, L, pooled)	the copy against the reset; one delta channel at eight streams	C1, C3 SHOWN and C2 HOLDS pooled and on each machine; "the copy, not the reset"; "the partition is necessary at eight streams against a single delta channel"	6, 11
`delta_recipe` (X, L, pooled)	the delta write against the Hebbian write at eight streams, and the split on each	D1 $d = 0$ (35/40 against 35/40), "delta not shown worse by more than 2 pairs"; D2 NOT SHOWN, no room (delta without a trigger 38/40); D4 SHOWN 19 vs 1; D3 delta sooner on 24 of 30; "delta: no room; Hebbian: helps"	11
batches 15–18 (E)	the recurrent gate's cap; the window gate; the split; the reset control; key splits	as in Revision 8	4, 6
batch 19 (E)	width and depth at four streams; eight streams at the larger sizes; the key load	scale-free to $N = 1024$, $D = 128$, 4 layers at four streams; carries to $D = 128$ and 2 layers at eight (one-pair rule); the oracle (2 seeds) binds 16 keys at $N = 256$, the learned recipe 0/10	10
batches 20–21 (E)	sixteen keys: slow or stuck; the $D = 128$ oracle as a validity check	stuck (0/12 by 86,400); the oracle 4/10 and 0/10 at 40,800: the drafted key-load test has no validity check	10
session F	delta-rule channels; the premise test; forget gates; the lite task; the probe; the delta recipe; the write strength; the horizon	one delta channel 2/10, 0/10 at four and eight streams; the delta recipe with fixed β keeps 2, 4 and 8 streams; on delta the flat-start guard lost two seeds, the evaluation trigger none; a learned β collapses and binds 7/10 against 10/10 (no reading applies); the forget gate's horizon screen untested	11

test, batch or session	question	verdict	§
session F, rounds 6–7	the lite task without marked keys (`-pool`, `-allpool`) and without fixed contexts (`-ctxpool`, `-docs`); what one channel holds	with its routing given, a Hebbian channel binds four keys drawn from 32 types 0/2 at 24,000 and at 48,000, where a delta channel binds at 2400–3600 (both pool tasks "untested" for Hebbian memory); the convolution restores it (2/2; `-allpool` at 48,000); one delta channel with no gate binds two documents with pooled contexts 10/10 and three or four 0/10, a Hebbian channel with the convolution 0/10 at an accuracy of $1/D$; a fixed type→channel map separates every sequence only with a channel per type (its cap 0.533 at $k = D = 2$), where the type-level perfect gate binds 4/4	11
session G	the cue in the stack; the register; which layers must be routed	the cue is absent; layer 1 is the block on Hebbian memory; the register carries the cue 20/20 nudged, 4/20 label-free, 20/20 with the key hinge; the register and the identity term are both needed; a label-free frequency hinge 17/20, two pairs short of replacing the key hinge	12
session G, rounds 6–7	hinges that read no labels where the keys are not frequent; contexts without fixed identity; the register specification	a hinge on the types repeated within the sequence matches the key hinge within one pair on pooled keys ("replaces the key hinge": 20/20 against 20/20 on delta, where the register alone binds 16/20; 19/20 against 18/20 on Hebbian memory with the convolution, where it binds 9/20 and the hinge is needed, 9–10 vs 0) and falls short on lite (17/20 against 20/20, 3 vs 0); with pooled contexts every learned arm is 0/20 at $k = 2$ (confounded with the 0.533 cap on a fixed type map) and 0/10 at $k = 16$ on both memories while the perfect gates bind 2/2 (at $k = 16$ a learning negative, the referee's reading); a comparing gate and a novelty signal 0/10; the register specification's revision 2 "ready for X's adoption after the fixes at the end" (ten, all text), not adopted	12
session H	anti-collapse devices; the copy without reset; the split's constants; two streams	neither device carried to eight streams replaces the split; the copy alone suffices (a one-pair bound); the cap matters; the flat-start guard moves the splits to higher probe accuracies without changing the count; a trigger reading all positions keeps binding within one pair on twenty new seeds (16/20 against 17/20; 24/30 against 26/30 over two screens); no main-line firing had a one-to-one map before it; the key term's constants are robust on a ceiling screen; two-stream key splits resist the copy and are prevented by the key hinge, not by a slow gate	6, 9
session H, rounds 6–7	the recipe and its trigger on pooled keys at eight streams; the oracles at key pools of 4 to 32	at 32 key types the main line's recipe binds 1/10 with a reliable oracle (the all-position trigger 3/10, no trigger 0/10, printed); a later first check 1/10 and a cap of six 2/10 against a rerun's 2/10; the delta oracle binds one of two seeds; both oracles are reliable to pool 8, the delta one the limit at 16 and 32 ($P^* = 8$); at pool 8 the delta recipe with the split 10/10 ("carries"), the Hebbian recipe 6/10 and the delta recipe without a trigger 7/10 (no reading applies)	10, 6

test, batch or session	question	verdict	§
session I	a dense next-token loss on interleaved sources; the GPU package; the headline on a GPU	at two sources one channel learns to carry the source; at four, on the GPU (untested by its rule: the perfect gate at 0.880 and 0.892 against 0.9), the window gate with and without the split and the register gate route 0/10 each; `window_gate`'s eight-stream arms on a GPU, fresh seeds: 19/20, 6/20, 0/20 (descriptions)	19, 5
session I, round 7	S75b's preparation	the specification's Appendix C takes the referee's review item by item; both cards' CUDA CHECKs and benchmarks pass on the final driver; the pre-run note is committed; the pilot was never run	19
session R	a clean-room replication of `window_gate`'s eight-stream result	17/20 against 7/20 (10 vs 0) from the text alone; 18/20 with the split's probe and key positions as the main line specifies them; 35/40 against 12/40 pooled (23 vs 0), "consistent with the report"; `split_copy` on fresh seeds (the delta arm from the specification alone): 18/20, 9/20, 0/20, each "consistent"	14
session V	referee: recomputation, pre-registration audit, claim registry, literature, spec and draft reviews	140 of 156 numbers reproduce, the rest statements; 53 tests per machine; Revisions 8's and 9's errors; the probe's imbalance; `delta_recipe` pooled, R's Phase 5 and I's GPU run reproduce; the three specifications it reviewed are not ready; after the merge, Revision 10 itself: the numbers right, nine statements false (10.1); rounds 6–7: every report of F, G and H but H's last checked against its records (every count and reading right; a dozen descriptive numbers wrong in G's reports; five readings whose names outrun their content; one budget defect; reviews the queues did not wait for), S92's oracle phase, and the register specification's revision 2 (ready after ten text fixes); Revision 11 not checked	15

Table 1: Phase VI. Main-line tests are files `test_<name>.py` whose docstring records the pre-registered design and, after the run, the result on each machine and pooled; from `test_window_gate` on, the specification is committed to `specs/` before the test is written, and from `test_delta_recipe` on it is reviewed by the referee session before any run. Exploratory batches and sessions write only new files on their own branches and label every output "exploratory, not a result". Appendix A lists the commits.

1 Background

BDH [1] stores working memory in synaptic state updated by a Hebbian rule. In its GPU form the operation is linear attention: the score between a query position t and a past position s is a content match $x_t \cdot x_s$ between sparse positive neuron activations, weighted by a positional operator (scalar decay or RoPE). The public implementation, `bdh.py`, ties queries to keys ($Q = K$), shares one layer's weights across depth, and LayerNorms the attention output. Its state update, in the paper's notation, is $\rho_t = \rho_{t-1} + \mathrm{LN}(Ey_t)\, x_t^\top U$: a pure additive write.

The extension gives every synapse k channels and every token a gate $g_t \in \Delta^{k-1}$ that distributes its write over the channels and blends its read from them. With one distribution for both, the effective score becomes

$$\underbrace{(x_t \cdot x_s)}_{\text{content match}} \times \underbrace{(g_t \cdot g_s)}_{\text{context-gate match}} \times \text{decay}^{\,t-s}, \tag{1}$$

strictly causal ($s < t$), so tokens sharing a context can read each other's memory while tokens in different contexts are isolated. The score has the three-factor form that Triadic Linear Attention [3] describes (cited for its form; the paper is not among the twelve read in full), with g as the second key; there the second key is a learned projection of the token, here it is a routing distribution inferred from context, and the subject is its label-free discovery. With $k = 1$ the model is single-channel BDH. One gate g_t is computed per token from the raw token embedding v_t (not LayerNormed, not convolved, not the residual stream) and applied at every layer. The hand-set *perfect gate* sends every token of stream s to channel s; it is used only as a validity ceiling.

Two learned gates. The *recurrent gate* of Phases II–V,

$$h_t = \tanh\big(W_{\text{in}}\, v_t + W_h\, h_{t-1}\big), \qquad g_t = \text{softmax}(W_g\, h_t), \tag{2}$$

with 32 units in h_t and $W_{\text{in}}, W_h, W_g \sim \mathcal{N}(0, 0.1^2)$ (so that $\rho(W_h) \approx 0.6$ and $\sigma_{\max}(W_h) \approx 1.08$ at initialization). The *window gate* of this revision,

$$h_t = \tanh\Big(W_{\text{in}} \sum_{j<3} w_j \odot v_{t-j}\Big), \qquad g_t = \text{softmax}(W_g\, h_t), \tag{3}$$

a depthwise causal convolution of width 3 over the embeddings (weights drawn uniformly in $\pm 1/\sqrt{3}$, no bias), with no recurrence. It sees the current token and the two before it, which in the grouped layout is enough to see each key's stream token at the key, the value and the query. It cannot see anything further back, and it has no notion of position.

The uniform gate is a stationary point. Writing each gate as a deviation from uniform, $g_t = \frac{1}{k}\mathbf{1} + \delta_t$, gives $g_t \cdot g_s = \frac{1}{k} + \delta_t \cdot \delta_s$. The constant is cancelled by the LayerNorm after attention, so routing enters only through products of deviations, and at the uniform gate the task loss exerts no first-order pull toward any routing. This is why discovery is a race between the gate's first commitment and whatever the memory learns first, and why the recipes below act in the first few thousand updates.

A short causal convolution. Most arms include the short convolution that Mamba and most linear-attention models place before their token mixer [4]: a depthwise causal filter of width 4 at every layer, initialized to the identity, feeding the queries and the values. Without it, the perfect gate of this model ($N = 256$) binds the two-stream configuration on every seed recorded (4/4 in the main line's CEIL_A, 14/14 in session F). The first draft attributed four failures to the missing convolution; those runs used a smaller model (`test_multilayer_binding`'s $N = 64$ ceiling, 7,552 parameters against 25,984), as the referee's recount found. Whether the convolution carries part of the binding is open.

2 Earlier phases in brief

Phases I–IV (Revisions 1–6). A gate that was a function of token identity could not express the routing (Phase I); a recurrent gate could (Phase II). On the binding task of Section 3, two channels with the perfect gate bind two streams where no single-channel model binds, and a label-free learned gate finds the routing on about half its runs (Phase III). A restart rule made two streams reliable; four streams with four channels mostly failed by merging streams into a shared channel, and spare channels removed most merges (Phase IV).

Phase V (Revision 7). An early-training recipe replaced restarts at two streams and at four with sixteen channels: for the first 2400 updates the memory trains at a tenth of the gate's rate (**SLOW**), and a hinge penalizes the gate when its channel choice at key positions is explained by position (**HINGE**; **WINDOW** switches the hinge off after update 2400). Eight streams failed in every arm (none of more than 100 runs), and screens located the failure in the recurrent gate: its state carries the stream at initialization and loses it within the first 600–1200 updates, as its recurrent term grows and, in seven of ten runs, the spectral radius of W_h rises above one. Revision 7 ended with a cap on that recurrence being screened.

3 The tasks, the outcomes and the recipes

The binding task. There are S streams, each with a context token CTX_s. For each of P keys, S distinct values are drawn from 16 value tokens, so every key is bound to a different value in every stream. In the *grouped* layout the body is SP triples $[\mathrm{CTX}_s, \mathrm{KEY}_i, \mathrm{VAL}_{i,s}]$, grouped by key, keys in random order and stream order random within each key's group. One query $[\mathrm{CTX}_q, \mathrm{KEY}_q, ?]$ ends the sequence; the model predicts the value from the query's KEY position, where CTX_q is one token back. The write that must carry the stream is at the VAL position, where CTX is two tokens back. Chance among values is 1/16; a model that binds keys to values but cannot tell streams apart scores $1/S$. The *header* layout gives each stream one block $[\mathrm{CTX}_s, \mathrm{KEY}, \mathrm{VAL}, \mathrm{KEY}, \mathrm{VAL}, \ldots]$ with the stream token once at the start, so most writes are far from their cue; at a fixed block length, position can route it. The *randomised header layout* ("RandHeaderTask-lite", session F's S70; the distant-cue task of Sections 12 and 14) has $S = 2$ streams of $P = 4$ keys, each stream's keys in two blocks whose lengths are a uniformly drawn composition of 4 into parts of 1–3 pairs, the four blocks in uniformly random order, one CTX token at the start of each block, every (stream, key) once, and one query; $L = 23$, and a token is one to six tokens from its block's cue, the write at a value position two to six. Both perfect gates bind it by update 1200 on five of six seeds. The model has three layers with weights shared across depth, decay 0.95 (half-life about 14 tokens), $N = 256$, embedding width 32 and one head, and trains at batch 32 for a budget set per test (24,000, 28,800 or 43,200 updates; 48,000 in some of session F's screens), with evaluation every 1200 updates on 2048 held-out queries; a run stops early after three consecutive evaluations at or above 0.95. Session I's dense-loss task is defined in Section 19.

Outcomes.

- **Bound:** an evaluation reaches 0.95 and every later one stays there; the *transition* is the first such step. A run that reaches its budget counts as bound on a single final evaluation; this has happened in 14 of 1869 bound runs in `results/` at Revision 8's commit (the referee's recount).
- **Discovered** ($k = S = 2$): bound, with the streams' read gates separated at value positions (final VAL cosine below 0.5).
- **Bound routed** ($k \geq S > 2$): bound, every stream has its own channel (a one-to-one *stream-to-channel map*, measured at value positions, where the writes are), and every stream's accuracy is at least 0.9. The map takes each stream's largest-mass channel, from a 256-sequence probe, ties resolved on unrounded values; in the 38 headline runs the streams' channel sets are disjoint (largest pairwise overlap 0.047) while in 18 of them some stream's largest channel holds under 0.9 of its gate mass. On the randomised header layout session F's **ROUTED*@end** (routing margin ≥ 0.9 and η^2 by stream at key positions > 0.9 at the end) is used, and

the readings of session G's S72, S73 and S82 (Section 12) are on **ROUTED-BOUND**, bound and ROUTED*@end, while S71's and S56's are on bound and on G's own bound routed; the name DISCOVERED is reserved for the outcome above, since one screen's reading named "discovered" was fixed on ROUTED-BOUND and would have come out differently on DISCOVERED (Section 12).

- **Failure classes:** POSITION or KEY when the gate's channel choice at key positions is explained ($\eta^2 \geq 0.5$) by position or by key identity; STREAM-PARTIAL; OTHER. For $S > 2$: MERGED (j share) when j streams share a channel, non-stream when the gate does not split by stream, *collapsed* when final accuracy is below 0.15. The classifier of record (v1) applies the margin rule before the key rule and labelled one batch-18 run at $\eta^2 = 0.500004$ by key STREAM-PARTIAL (two more sit at 0.49986 and 0.499985 and keep that label under both); `fail_class_v2` (commit `ba8901a`) applies the key rule first and is used by every test from `test_split_copy` on; recorded verdicts keep the rule they were read under, and the two classifiers disagree only where η^2 by key ≥ 0.5 and the margin rule fired (six of 29 recorded unbound two-stream runs of three earlier screens, four of S78's seventeen, and none at eight streams in S79).

Recipes.

- **SLOW:** one Adam optimizer with two groups. The gate's parameters train at 10^{-3} throughout; every other parameter, embedding and convolution included, at 10^{-4} for updates 1–2400 and 10^{-3} after. The perfect gate (the validity arm) trains at a single rate, 10^{-3}, without SLOW.
- **HINGE, WINDOW:** Revision 7's position hinge, on the recurrent gate; kept here only as the comparison.
- **SPLIT (KEYMASS):** at checks every 2400 updates from 4800, if the probe's accuracy is below 0.95 and rose by less than 0.02 since the previous check (the probe is also read at 2400 as the first reference; the last check is at the budget minus 2400), copy the gate row $W_g[c^*]$ of the channel with the largest mean read-gate mass at the body's key positions onto the row $W_g[c_0]$ of the channel with the smallest; at most three splits per run, at least 4800 updates apart. `test_window_gate`'s form adds noise of 0.1 times the row's standard deviation to both rows and zeroes W_g's Adam state, step counter included; session H's *exact copy* does neither, and is the form of the screens of Sections 6 and 11 and of the next main-line test. The probe is one fixed set of 64 sequences, the same for every seed and arm (`Generator(12345)`), scored on its queries only; its queries fall 5, 5, 6, 8, 10, 12, 5 and 13 on streams 0–7, so it is unbalanced in the same way for every run (Section 14). The split uses no stream labels; it needs to know where the key positions are.
- **MUON:** Muon at learning rate 0.005 on every 2-D weight (momentum 0.95, Nesterov), with Adam on the rest, and SLOW's schedule.
- **The delta write (session F):** each channel's state follows Gated DeltaNet's rule, $S_t^c = S_{t-1}^c\big(\alpha_t^c(I - g_t^c\beta_t\hat{x}_t\hat{x}_t^\top)\big) + g_t^c\beta_t v_t\hat{x}_t^\top$, with unit keys $\hat{x}_t$, the decay fixed at 0.95, and the write strength β *fixed at 1*; at $\beta = 0$ its logits agree with the Hebbian model's to 2×10^{-7}, and with the new path disabled it reproduces a recorded run bit for bit through 2400 updates. A learned β collapsed toward "do not write" at value positions in two screens and rose above its initial 0.5 in two others (Section 11).
- **The register gate (session G):**a 16-dimensional register $R_t = R_{t-1}(1 - \beta_t^R) + \beta_t^R W_R v_t$, $\beta_t^R = \sigma(w_R \cdot v_t + b_R)$ with b_R initialised to logit 0.1, written by every token and

read causally (the gate at t reads R_{t-1}); one gate shared by all three layers, $g_t^{(\ell)} = \mathrm{softmax}(W_g \tanh(A\,[\mathrm{LN}(r_t^{(\ell)});\, u_t;\, R_{t-1}]))$ over the layer's residual input, the window gate's input u_t and the register, with A initialised so that the gate equals the window gate at step 0 up to a $\mathcal{N}(0, 0.01^2)$ perturbation of its register and residual blocks, and a stop-gradient from the gate into the stack. "REG3" is this gate at all three layers; session G's first design (S56) had a register gate at layers 2–3 only, reading the raw embedding rather than the window, with the window gate at layer 1.

Statistics. Paired comparisons in the main-line tests use exact one-sided McNemar tests on the discordant pairs ("b vs c"), unpaired ones Fisher's exact test; E's exploratory batches report two-sided McNemar p-values and sessions F, G and H one-sided ones, as marked where quoted; bands are RELIABLE at $\geq 90\%$ and MAJORITY at $\geq 50\%$ of runs, with Wilson 95% intervals. From the Muon-recipe test on, X and L run disjoint seeds (X 400–599, L 1400–1599), the pooled claim over both machines' pairs is primary and each machine's is secondary. The referee's claim registry (`docs/review_2026-10/claims_registry.md`) counts 53 pre-registered hypothesis tests per machine over Phases III–VI (52 one-sided; 25 Fisher, 25 McNemar, 2 Mann–Whitney, 1 sign test), plus six pooled tests in Phase VI, besides 3 bounds without a p-value, 41 bands, 29 validity gates and 37 readings; every test was run at $\alpha = 0.05$ with no adjustment, which controls the per-comparison rate only, so about 2.7 false positives per machine are expected if every null were true. The conclusions are assessed under Benjamini–Hochberg at 0.05 after the fact: 19 of X's 23 positive verdicts and 27 of L's 32 survive, and the four on X (`stream_recipe` R3, `recipe_scope` Q2, `slow_start` S0, `muon_recipe` M2) and five on L (`short_conv` K2, `stream_channels` MG, `slow_start` HA, H0S and S0) that depend on the unadjusted level carry no conclusion below; the main result (G2, G4; the pooled G1 and M1) survives Holm on X, on L and pooled. The conclusions that matter are those replicated on both machines or pooled over disjoint seeds.

4 The window gate

History. The window gate was the first screen of the first exploratory batch (S1, batch 1): on seeds 160–179 with plain Adam and no recipe it discovered 15/20 against the recurrent gate's 7/20 (12 vs 4, two-sided $p = 0.077$: "promising" by the screen's rule) and bound sooner on average (mean transition 2720 against 3429; equal medians); its five failures were three key splits and two stream-partial runs under the main-line classifier, four key splits under the key-first rule (it cannot position-split, having no position). Batch 2 ran it on the header layout, where it bound 2/10, both by key splits, and it was dropped: a gate that cannot see a cue three tokens back seemed the wrong direction for a language model. It was never combined with slow memory and never run at four or eight streams. The October audit of the project's records (`docs/audit_2026-10.md`, Section 3.1) noticed that every obstacle of Phase V was a property of the recurrent parameterization: position splits are the recurrence counting triples, and the eight-stream loss of the stream is the recurrence becoming expansive. A window gate can do neither. The audit fixed a prediction before any run: with slow memory, at two streams $\geq 36/40$ with key failures gone; at eight streams, binding on some seeds where every recurrent arm bound none.

Batch 16 (E). The window gate with SLOW and no hinge (LOCAL3_SLOW): at two streams 31/40 on seeds 160–199 (STREAM-PARTIAL 5, KEY 4, no POSITION), inconclusive against the hinge recipe's 34/40 (5 vs 8). At four streams with sixteen channels, 20/20 bound routed against X's recorded HINGE4k16 15/20 (5 vs 0, two-sided $p = 0.0625$). At eight streams, 3/10 under Adam

and 3/10 under Muon, where every recurrent arm in batches 13–16 had bound 0/10; the seven unbound Adam runs ended with two or three streams sharing a channel at accuracy 0.73–0.88. The window gate's state decodes the stream at both key and value positions (1.00 at four streams at update 4800, the two runs still training at 9600 reading 0.70–0.72; at eight, 0.93–1.00 under Muon and, under Adam, 0.55–0.67 at updates 2400–4800 recovering to 0.87–0.88 by 9600), where the recurrent gate's reads 0.14–0.28. So the audit's first prediction was partly met (no position failures; key failures reduced, not gone, and 31/40 short of 36), and its second was met.

Batch 17 (E). The failures at eight streams were merges, so batch 17 added the targeted split of Section 3 (S37's KEYMASS rule, at most three splits). W_SPLIT bound routed 9/10 against 3/10 for the same seeds without it (6 vs 0, two-sided $p = 0.031$); every one of its 19 splits was on target by the labels (the busy channel held two to five streams, the idle one none), and in six of nine bound runs the transition came at the evaluation right after the last split. Decay 0.98 alone bound 1/10 (it settled the merges early) and a longer budget alone 4/10: the splits, not the decay or the time, do the work. The screen handed W_SPLIT back for a pre-registered test.

5 The main result: `test_window_gate`

The test's specification was committed before the test was written (`specs/test_window_gate.md`) and amended, before any Part D run, to add the split. Both machines ran it on their own seeds (X 500–559, L 1500–1559). Part A ($S = 2$, $P = 4$, $k = 2$, no convolution, 24,000 updates, 40 seeds per machine): the window gate with one learning rate (WIN3), with slow memory (WIN3_SLOW), and the recurrent-gate recipe (HINGE0). Part B ($S = 4$, $P = 4$, $k = 16$, convolution, 28,800, 20 seeds): WIN3_SLOW16 against WIN16_A, the recurrent gate under Adam with the early hinge window. Parts C and D ($S = 8$, $P = 4$, $k = 16$, convolution, 43,200, 20 seeds): WIN3_SLOW_D8, HINGE_D8 (the recurrent recipe) and WIN3_SPLIT_D8 (the window gate with the split), with a reset-only control (WIN3_RESET_D8: the Adam-state reset at the same trigger, no copy) on five seeds per machine, printed and not claimed. The perfect gate on two seeds per part was the validity arm, and bound on every one (Part C at 4800 and 3600–6000). Every CHECK passed on X, including bit-for-bit reproductions of batch 1's window gate, batch 16's LOCAL3_SLOW and batch 17's W_SPLIT (its split at 4800 included); L's file carries the metadata the test writes only after its verification passes. Nothing was cut; X ran its 225 learned-gate records in 30.9 h of training (its six perfect-gate records came from an earlier start that a container restart ended), L its 231 records in one start (projected 17.3 h).

part	arm	X	L	pooled
A: S=2, P=4, k=2, discovered	WIN3	33/40	32/40	65/80
	WIN3_SLOW	33/40	36/40	69/80
	HINGE0 (recurrent, Rev. 7's recipe)	33/40	34/40	67/80
B: S=4, k=16, bound routed	WIN3_SLOW16	19/20	19/20	38/40
	WIN16_A (recurrent, early window)	15/20	12/20	27/40
C, D: S=8, k=16, bound routed	WIN3_SPLIT_D8 (the recipe)	18/20	20/20	**38/40**
	WIN3_SLOW_D8 (no split)	6/20	9/20	15/40
	HINGE_D8 (recurrent, Rev. 7's recipe)	0/20	0/20	0/40
	WIN3_RESET_D8 (control, of 5)	0/5	3/5	3/10
	perfect gate (of 2)	2/2	2/2	4/4

Table 2: `test_window_gate`. Pooled claims (primary, exact one-sided McNemar over both machines' pairs): G1, WIN3_SLOW16 beats WIN16_A: 13 vs 2 (X 5 vs 1, L 8 vs 1), $p = 0.0037$, SHOWN. G2, WIN3_SPLIT_D8 beats HINGE_D8: 38 vs 0, $p = 3.6 \times 10^{-12}$, SHOWN. G3, WIN3_SLOW not worse than HINGE0 by more than two discordant pairs: HINGE0 only 9, WIN3_SLOW only 11, $d = -2$, HOLDS (a bound, no p-value). G4, WIN3_SPLIT_D8 beats WIN3_SLOW_D8: 23 vs 0 (X 12 vs 0, L 11 vs 0), $p = 1.2 \times 10^{-7}$, SHOWN. Per machine every claim is SHOWN or HOLDS on both, except G1 on X (5 vs 1, $p = 0.11$; on L 8 vs 1, $p = 0.020$). Bands, pooled: WIN3_SPLIT_D8 RELIABLE, Wilson $[0.835, 0.986]$; WIN3_SLOW16 RELIABLE $[0.835, 0.986]$; WIN3_SLOW MAJORITY $[0.770, 0.921]$; WIN3_SLOW_D8 MINORITY $[0.242, 0.530]$; HINGE_D8 NEVER $[0, 0.088]$. The pre-registered reading, "eight streams bind without labels or restarts" (WIN3_SPLIT_D8 RELIABLE pooled and G2, G4 SHOWN), applies.

What the runs show (diagnostics, not claims). The recurrent-gate recipe bound none of 40 eight-stream runs (15 collapsed, 17 non-stream, 8 merged). The window gate alone bound 15/40, and every one of its 25 failures was a merge of two, three or four streams on one channel. The split raised that to 38/40: the trigger fired 85 splits in 40 runs (none to three per run), every target labelled on target, and brought the median time to bind forward (X: 21,600 against 27,600; L: 18,600 against 32,400; medians over bound runs). The two failures (X's seeds 555 and 556) ended with two streams sharing a channel. The reset-only control matched the window gate without the split seed for seed on L (3/5 and 3/5, 0 vs 0 discordant) and bound 0/5 against 1/5 on X: on these seeds the row copy, not the Adam reset, made the difference (Section 6). At four streams, WIN3_SLOW16's two failures were one unrouted bind (X) and one merge (L); WIN16_A's thirteen were four position splits, three merges, four unrouted binds and two others. At two streams no arm failed by position; WIN3's failures were key splits (12 of 15), WIN3_SLOW's key splits and partial streams (6 and 5 of 11), and HINGE0's key splits (10 of 13), with two OTHER and one partial. Slow memory on the window gate at two streams is printed, not claimed: 69/80 against 65/80 (7 vs 3, $p = 0.17$).

What is and is not established. The result is a pre-registered, two-machine, disjoint-seed test of a recipe that uses no stream labels, no restarts and no hinge, and that finds an eight-way partition of the memory, the streams on disjoint channel sets with one channel per stream by largest mass, in 38 of 40 runs where the previous recipe found none. The split needs to know where the key positions are (as the hinge did); the window gate needs the cue within two tokens; and the task is the grouped layout, where it is. Neither limitation is new. The audit's over-prediction for two streams ("$\geq$ 36/40 with KEY failures gone") was not met on X (33/40) and KEY failures were reduced, not removed; what was claimed, G3, holds.

Routing by overlap, intervals, and what a replication should expect. The referee's recount (Section 15) scored the headline runs a second way, by the overlap of the streams' channel sets rather than by each stream's largest channel: in all 38 bound runs the sets are disjoint (largest pairwise overlap 0.047), and under that criterion G4 is unchanged and G1 strengthens to 16 vs 2. The paired differences carry their uncertainty: G1's four-stream difference is 13 vs 2 ($p = 0.0037$), which is secondary, is not shown on X alone (5 vs 1), and would not survive a family-wise correction over the project's 53 claims (Bonferroni 0.20), though it survives Holm within the pooled family of six; G3's two-stream difference of two pairs in the window recipe's favour is $+0.025$ with a 95% interval of $[-0.079, +0.121]$, so "equal at two streams" means within eight points either way, not equal. The eight-stream rate, 38/40, has Wilson interval $[0.835, 0.986]$; a 20-seed replication of a recipe that truly binds 95% of the time reaches ≥ 18 with probability 0.92 and ≥ 17 with 0.98, and one of a recipe that binds 90% reaches ≥ 18 with only 0.68. Section 14 reports a replication at 17/20.

The headline on a GPU (session I, report 3). The three eight-stream arms ran on a third machine class, a GTX 1660 SUPER with CUDA arithmetic, on twenty fresh seeds (2540–2559; a note fixing the seeds, the arms and the rule that nothing would be read as a claim was committed before any run, and every record carries the code hash that first exists at that commit). The test code is the main line's own, byte for byte over 29 modules, run through a thin device wrapper that builds on the CPU and moves to the card; curves are not bit-equivalent to the CPU's and the report compares outcomes only. The perfect gate bound 2/2. Bound routed: the recipe **19/20**, without the split 6/20, the recurrent-gate recipe 0/20; paired, 19 vs 0, 13 vs 0 and 6 vs 0 (the referee's exact one-sided p: 1.9×10^{-6}, 1.2×10^{-4} and 0.016; the report prints none, as its note fixed). These are descriptions, not pre-registered claims, and the pooled main-line result stands at 38/40 on its own: report 3 states that the GPU run is never pooled with it. The referee recomputed every number of the report from the records (64 of 65 rows match; the one that is not record-checkable is a statement about X's commit; `docs/review_2026-10/check_I_report3.md`). The card belonged to the user's server, which left the project after this run and S75b's CUDA CHECKs.

6 The split: the copy, the reset and the trigger

The split bundles two actions, a row copy and an optimizer-state reset, and Revision 7's screens had no reset-only control. Revision 8 reported three looks (Table 3, first three rows), each comparing the copy with its reset against the reset alone; they showed that the reset alone is not enough, and the first draft said more than that. Two further looks settle it, one of them pre-registered on two machines.

where	configuration	copy + reset	copy only	reset only	none	paired
batch 18, S50 (E)	S=8, k=16, 260–269; the reset replayed at the recorded split updates	9/10	—	2/10	3/10	8 vs 1, two-sided $p = 0.039$
session H, S58b	S=8, k=16, 460–469; live trigger	10/10	—	2/10	—	8 vs 0, one-sided $p = 0.0039$
`window_gate` control	S=8, k=16, 540–544, 1540–1544; live trigger	—	—	3/10	4/10	0 vs 1
session H, S61	S=8, k=16, 480–489; live trigger	9/10	9/10; with noise 9/10	4/10	3/10	copy only vs reset only 5 vs 0, $p = 0.031$ (ours, not pre-fixed); vs copy + reset 0 vs 0
`split_copy`, X	S=8, k=16, 560–569; live trigger; pre-registered	**10/10**	—	**3/10**	5/10	C1 7 vs 0, $p = 0.0078$ SHOWN; C2 reset vs none 0 vs 2, HOLDS
`split_copy`, L	S=8, k=16, 1560–1569; live trigger; pre-registered	**8/10**	—	**3/10**	3/10	C1 5 vs 0, $p = 0.031$ SHOWN; C2 0 vs 0, HOLDS
`split_copy`, pooled (primary)	20 pairs, disjoint seeds	**18/20**	—	**6/20**	8/20	C1 12 vs 0, $p = 0.00024$ SHOWN; C2 0 vs 2, HOLDS; "the copy, not the reset"

Table 3: The split's two actions, bound routed. In every look the reset-only arm fired under the live rule or at the recorded split updates, on labelled targets where labelling was recorded; it bound no more often than the arm with no trigger in `test_split_copy` and the `window_gate` control, and more often in S61 (4/10 against 3/10, 2 vs 1). S61's pre-fixed readings "the copy alone suffices" and "the reset adds nothing" are one-pair bounds on the copy *with* noise against the full split (0 vs 0), and both held; the exact copy (no noise, no reset) enters only the reading "the noise matters" (≥ 4 vs 0), which did not apply (0 vs 0), and the exact copy against the full split (0 vs 0) was not a reading. `test_split_copy`'s pooled claims are primary and its readings are read pooled only.

The pre-registered look (`test_split_copy`). Specified (`specs/test_split_copy.md`) before it was written, with three claims pooled primary and per machine secondary. On X (seeds 560–569, 54 runs; every CHECK passed except two whose records another CPU wrote, printed rather than asserted, one of them (130) differing; 14.7 h from the test's commit to the result's, the runs about 12 h on four workers): C1, the split beats the reset alone, SHOWN, 10/10 against 3/10, 7 vs 0, $p = 0.0078$; C2, the reset alone is not better than no trigger by more than two pairs, HOLDS, 3/10 against 5/10, 0 vs 2 (every seed the reset bound also bound without it); C3 is Section 11's. All 22 splits and all 27 resets were on labelled targets (printed, not claimed); the reset never uses its target, so what the copy adds, on our reading, is the row and not the aim. The validity arms bound 2/2 (the Hebbian perfect gate at 4800 and 3600; the delta perfect gate at 1200 and 1200). On L (seeds 1560–1569, 54 runs; every CHECK asserted that could be, the cross-CPU comparisons printed and unequal, as the specification provides; 536 min of runs on six workers): C1 SHOWN, 8/10 against 3/10 (5 vs 0, $p = 0.031$); C2 HOLDS, 3/10 against 3/10 (0 vs 0); the two split failures are merges of two streams after three splits; all 19 splits and 26 resets on labelled targets; both perfect gates 2/2. Pooled over the 20 pairs (primary): C1 SHOWN, 18/20 against 6/20, 12 vs 0, $p = 0.00024$; C2 HOLDS, 6/20 against 8/20, 0 vs 2 ($d = -2$); the pre-fixed reading "the copy, not the reset" applies. The reset alone bound the same seeds as no trigger on L and a subset of them on X.

The copy alone (session H, S61). With the exact copy as its own arm, the three forms of the split bound the same nine seeds and missed the same one (483, two streams sharing): the copy with noise and reset 9/10, the copy with noise 9/10, the exact copy 9/10; the reset alone 4/10, no trigger 3/10. All 83 firings across the four trigger arms were on labelled targets, a channel holding at least two streams and an empty one; the 57 in the three copying arms copied the row, the 26 resets did not. That two identical rows, their symmetry broken only by their Adam moments and the data, separate merged streams as well as two noisy ones is what 0 vs 0 on ten seeds is consistent with, not a shown equality. The exact copy is therefore the split's form in every later screen and in `test_delta_recipe`; the pre-registered test of the copy alone against the full split was never run.

The constants (session H, S79). The split's constants had never been varied. With the exact copy as the base (9/10, 21 firings, all on target) and one change at a time on ten seeds: a cap of one split, 5/10 (BASE only 4, CAP1 only 0; "sensitive"); checks every 1200 from 2400, 7/10 (2 vs 0; "inconclusive"); a cap of six, 9/10; a 16-sequence probe, 10/10; a rise threshold of 0.05, 10/10 (all "robust"). The pre-fixed reading "the extra splits are harmless" did not apply, because one of the cap-of-six arm's seven extra firings was not on a labelled target (the run bound anyway). Descriptively, and not pre-registered: four of CAP1's five failures spent their single split at updates 4800–12,000 while the probe read 0.09–0.50 (per-stream accuracy is recorded only at 4800 and 9600; the seed that fired at 12,000 had two streams above 0.99 at 9600), and the fast-check arm's three failures had used all three splits by 7200–10,800. The plateau rule fires during the flat start, and a split spent there is one fewer for the merge that comes later; the fast check binds sooner when it binds (median 14,400 against 24,000) and fails that way when it fails. Our recommendation from this, not a reading: a replication should state the cap and the check schedule (the fast-check arm moved the interval, the first check and the gap together, so the three are not separated), and can state the probe size and the rise threshold loosely. Two trigger variants that follow from this were screened on ten fresh seeds (session H's S84, seeds 2300–2309; the oracle 2/2). A guard that forbids splits while the probe is below 0.5 binds 9/10 against the base's 9/10 (0 vs 0); it fires its 17 splits at probe accuracies of 0.50–0.91, where the base fired 7 of its 24 at 0.06–0.16, and it locks out the one seed whose probe never reaches 0.5, which ends MERGED in every guarded arm. Checks every 1200 with the guard bind 9/10 (S79's unguarded fast check, on other seeds, bound 7/10) with a median transition 1200 earlier than the base's, not the 2400 the pre-fixed reading "faster without the cost" required. A trigger that reads the 2048-query held-out evaluation instead of the probe binds 10/10 (1 vs 0; the reading "the evaluation is the better probe" applies by its rule, on a single discordant seed, where the probe read 0.000 then 0.047 and the evaluation 0.066 then 0.068, so, on our reading, the probe's noise decided whether the first check fired); the guard with fast checks and the evaluation together bind 9/10 (0 vs 0), and no arm read "costs binding". These seeds hardly tested the flat start, since, on our reading, the base kept enough splits for its merges after spending some; the guard changes when the splits fire and, on these seeds, not whether the run binds. Session F's S81 is the same screen on delta channels (seeds 2020–2029; the delta perfect gate 2/2): there the guard reads the other way, 7/10 against the base's 9/10 (0 vs 2; neither "aims" nor "costs binding" applies by F's rules), on session F's post-hoc account because on delta channels the base's flat-start splits precede runs that bind (all eight runs that split in the flat start bound, though only 10 of the base's 19 firings were on labelled targets), and the guard removes exactly those; the evaluation as the probe binds 10/10 against 9/10 (1 vs 0), "the evaluation is the better probe" not applying under F's stricter rule because 5 of its 13 firings came where the probe would have decided otherwise, and applying under H's rule. The seed-914 mode appeared in one guarded run where it could block the rule (and at four checks of that seed's evaluation-read guarded run, which fired,

and at two of the base's) (the probe at 0.95–0.98 against the evaluation's 0.87–0.92 at five checks; MERGED at 0.93). Over the three screens of the evaluation as the trigger's probe (S84, S86, S81) it is 29/30 against 27/30, 2 vs 0, descriptive; it has not cost a run. Session H then screened what the trigger reads (S86, seeds 2330–2339; the oracle 2/2): a trigger whose target pair is chosen by the mean read-gate mass over every input position, which reads no task structure, binds routed 8/10 against the key-position rule's 9/10 (0 vs 1; "keeps it"), with 20 of its 21 firings on labelled targets ("aims"); the one discordant seed is the one mistarget, at a check where the two rules chose different pairs and the all-position pair copied a channel that held no stream onto another that held none, leaving the shared channel as it was, after which the run merged while the key-position rule's run bound. The two rules chose the same pair at only 8 of about 20 firings per arm, and both pairs were labelled targets at most of them, as in the main line's records (Section 18). The evaluation as the trigger's probe binds 9/10 against 9/10 here (0 vs 0), and 19/20 against 18/20 pooled with S84 (1 vs 0, descriptive).

The probe can be wrong about a plateau. The replication of Section 14 lost one of its three failures to the probe: on its seed 914 the 64-query probe read 0.953–1.000 at every check from 16,800 on while the 2048-query evaluation sat at 0.871–0.887 with two streams merged, so the rule never fired again. A 64-query probe near 0.9 has a standard error of about 0.04. The referee then found that the main line's own fixed probe is unbalanced across streams (5, 5, 6, 8, 10, 12, 5 and 13 queries for streams 0–7) and identical for every seed, so that a merge of two under-sampled streams costs the probe about 0.08 where the balanced evaluation loses 0.125: the direction that blocks a split, and a systematic bias rather than noise. The main line's records store the probe's reading at every check beside the evaluation's curve, and the referee read them against each other: 6 of the 353 checks in the split arm's 40 runs read the probe at or above 0.95 with the evaluation at 0.865–0.88, in 2 of those the probe alone blocked a split, and both fired at the next check and bound routed; the reset arm had none. Session R's Phase 4 counted the same thing across its runs: with the fixed probe the mode occurred at 3 of 263 checks and never decided a run, with one probe drawn per seed at 13 of 282 and, on R's inference, it decided one run (Section 14). The next main-line test prints every check's probe reading beside the held-out accuracy, and the trigger arms above are the remedy under test.

What does not replace it (session H). Two devices the literature uses against router collapse were run beside the split and the reset at four streams, $k = 16$ (40 paired seeds), where every arm but one sat at the ceiling (NONE 38/40); two of its three readings did not apply and the third, "the split is the reset", held by its rule (0 vs 0) and was printed uninformative by its own qualifier. A rule fixed beforehand then carried the two best-scoring devices, the reset and write-gate noise (it ranked the four devices only; the no-device arm's 38/40 outscored write-gate noise's 37/40), to eight streams (10 seeds). Gumbel$(0, 1)$ noise on the gate's logits during training, Raven's device for a router whose reads are dense [13]: on both the read and write gates it collapsed routing even at four streams (33 of 40 runs merged); on the write gate alone it bound 37/40 at four streams with a later transition (median 6000 against 3600) and a lower margin, and at eight streams it bound 0/10, with up to six streams sharing a channel (10 vs 0 against the split; the screen had no no-device arm there). A Switch-style balance loss, as Mixture-of-Memories uses [12, 17]: 36/40 at four streams, routed by stream, but in 34 of those 36 runs the streams were mapped to different channels at key positions than at value positions and the routing margin fell from 0.87 to 0.46; on our reading it changed the routing's shape, not its count, and it was not carried to eight streams. In the other arms with a full set of runs the query's read gate follows the write map (session H's S62,

descriptive: in 32–37 of the 38–40 bound runs per arm at four streams, and 12/12 at eight). At two streams ($k = 2$, no convolution, ten seeds), a learned gate temperature with a floor ran to the floor in every run, and a stable-max softmax read "no change at $n = 10$" by its rule (7/10 against 8/10). Slope annealing of the gate (S63) and a hard, one-hot write gate from update 2400 both read "does not help" (9/10 against 10/10; 0/10, 0 vs 10, KEY 3, MERGED 4, OTHER 3). With the write one-hot the gate gets gradient only through the read, by construction; that the writes' stream labelling therefore never forms is the session's description, and four of the ten runs did form a partial one (MERGED needs a margin of 0.25). Session H's fifth round, on fresh seeds, closed three small questions about the split as a description: a trigger that reads the gate's mass at every body position rather than at the key positions bound 16/20 against the key-position rule's 17/20 (S87a, seeds 2600–2619; 1 vs 2), 24/30 against 26/30 pooled with S86, all 42 of its firings on a target the key-position labels name and 40 on one the all-position labels name; its readings "keeps it" and "aims" apply, "costs binding" does not (printed "no cost by the rule"), and the key-position rule stays. A guard that would stop the split from firing on a map that is already one-to-one, proposed after S75 (Section 19), would have changed nothing on the main line: none of the 126 firings in the 60 recorded split-arm runs of `test_window_gate` and `test_split_copy` had a one-to-one map before it. And the key term's constants (its weight at 0.3, 1 and 3, its window at 1200 or 2400 updates) all discovered 10/10 at two streams (S87c; "robust", and the drafted constants stand; the drafted arm was at the ceiling, so the screen could only have shown a worse variant, and a variant at a true rate of 0.8 still reads "robust" 38% of the time).

The split needs an idle channel. With no spare channel (batch 18, S51, $S = k = 4$), the trigger once fired on a correctly routed map, found no empty channel, overwrote a live one and merged the run. Session H's S78 then ran the exact copy at $k = S = 2$ (Section 9): the copy resets the gate to uniform and, on the eight firings of the seeds that ended in a key split, the same split is back by the next check (two of the eight are read from the end of the run); one seed had no key split when the copy came and discovered. That the copy works at eight streams because the channel it copies onto is empty, and has nothing to offer where every channel is busy, is our reading of these screens. Spare channels remain the default, and, our recommendation, the trigger should not fire when its target already carries key mass.

Pooled keys (session H, rounds 6–7). With each sequence's four keys drawn from 32 types on the eight-stream grouped layout, the recipe's failures look like the split's again, on session H's description: the trigger fires first at 4800 in every run, in the flat start, all three splits are spent by 14,400–36,000, and the late merges find none left, the aim being right (27–28 of 30 firings on labelled targets); neither schedule change reached 4/10 (a later first check 1/10, a cap of six 2/10, against 2/10), which by the rule's operating characteristics excludes only a gain of about +0.2 or more. At eight key types the delta recipe with the exact copy binds 10/10 where the Hebbian recipe binds 6/10 and the delta recipe without a trigger 7/10; on delta channels only 7 of its 22 firings were on labelled targets and nine fired on maps already one-to-one, every such run binding. Section 10.

7 Muon is not an ingredient

Revision 7 reported, from one machine, that under Muon the recipe "binds four streams sooner". The Muon-recipe test (`test_muon_recipe`, the first on disjoint seeds) asked three questions. M1, the early hinge window under Muon at two streams: WIN_M 79/80 against SLOW_M 69/80 pooled, 10 vs 0, $p = 0.001$, SHOWN (on L 6 vs 0, SHOWN; on X 4 vs 0, $p = 0.0625$). M2, Muon binds

four streams by update 4800 more often than Adam: 12 vs 8 pooled, $p = 0.25$, NOT SHOWN; per machine it was shown on X (7 vs 1, $p = 0.035$) and reversed on L (5 vs 7). Revision 7's result had come from L (7 vs 0 on its seeds; X's cut arm gave 5 vs 1), so on fresh seeds it was confirmed on the other machine and reversed on its own; the machines disagree, by seed block or by CPU (the design cannot separate them), and pooled it is not shown. M3, the same at eight keys: 7 vs 5 over 30 pairs (X's time rule cut its Adam arm to ten seeds), $p = 0.39$, NOT SHOWN. The test's reading, "the Muon recipe is reliable at the working configurations", was not met: WIN16_M was MAJORITY pooled (33/40). Batch 18 then ran the window recipe with the split under Muon at eight streams: 9/10, the same as under Adam (1 vs 1), and 9/10 against a fresh Muon reference without the split at 2/10 (7 vs 0, two-sided $p = 0.016$). The eight-stream result is the recipe's, not the optimizer's. Muon's bf16 Newton–Schulz step does not reproduce across processors, which cost the project paired comparisons; nothing in the main line now needs it.

8 The recurrent gate's eight-stream failure, closed

Revision 7's reading was that the recurrent gate's state stops carrying the stream when its recurrence becomes expansive, and it left a cap on that recurrence being screened. Batch 15 (S41) ran the cap at 0.5 on the spectral norm of W_h under Muon, alone, with a previous-token input, and with the previous-token input and no recurrence, and the capped previous-token input under Adam: the three Muon arms bound 0/10 and the Adam arm 0/5. With the look-back the capped gate's state kept the stream at key positions throughout (decodability 0.93–1.00) and still ended with the eight streams on three to seven channels; final accuracy rose in every pair (median 0.61 against 0.36) but no run bound. Batch 16 added a frozen reservoir recurrence (0/10), decay 0.98, a tenth of the rate on W_h, and a higher learning rate: none bound (the perfect gate binds at decay 0.98, so the decay is valid). The window gate then bound where all of these had not. Two corrections to Revision 7 follow: the gate's state must carry the stream at the *write* position, where CTX is two tokens back, not only at the read, where it is one back, so the sentence "the gate needs only one token of memory" was wrong (the audit noted it; batch 16's S47 measured the write positions, which S38–S41 had not); and S41's no-recurrence arm, whose input is (v_t, v_{t-1}), cannot by construction see the stream token at value positions, so its ten key splits were a property of that window and not evidence about recurrence (audit, Section 2.3). The cap, as specified, also acted from update 1 ($\sigma_{\max}(W_h) \approx 1.08$ at initialization), not only after the crossing. The diagnosis stands as a description of the recurrent gate; the remedy was to remove the recurrence.

9 Two-stream key splits

At two streams with two channels and no convolution, the window gate fails by routing on key identity: its key splits form within the first 600 updates, while the memory is still at 10^{-4} (batch 17, S49). Slow memory reduces them (WIN3 KEY 12 of 15 failures pooled; WIN3_SLOW KEY 6 of 11), and batch 18 screened two further devices on seeds 160–199: two spare channels ($k = 4$: 36/40 bound routed, with four key splits still formed by update 325) and the hinge's key term on updates 1–2400 (36/40 discovered, one KEY failure, but three "STREAM-PARTIAL" failures with η^2 by key within 10^{-3} of 0.5, the signature of a hard two-of-four key pattern; the key-first classifier relabels the one at 0.500004 KEY and leaves the two just below). The configuration is the project's hardest relative to its size and the one with the least headroom (65–69/80 for every arm); it is also the only one where the window recipe's margin over the hinge recipe is small (two pairs pooled, $[-0.079, +0.121]$) and where the hinge recipe won a screen (batch 16: 34/40 against 31/40 on seeds 160–199).

The split does not repair a key split (session H, S78). Session H ran the exact copy at $k = S = 2$ on 20 seeds (1300–1319), with the main line's noisy form and the two-spare-channel recipe beside it: the baseline discovered 15/20, the exact copy 16/20, the copy with noise and reset 17/20, four channels 15/20; no arm beats the baseline (best 2 vs 0, $p = 0.25$), and the pre-fixed reading is "neither device". The firing records say why. After $W_g[c_0] := W_g[c^*]$ the two rows are equal and the gate is uniform, every η^2 at 0.00; the same key split had re-formed exactly (KEY/stream η^2 1.00/0.00) after all eight firings on the three seeds that ended KEY under the classifier of record (six read at the next check, 2400 updates later; two, fired at the last check, read from the end of the run), and the half-key pattern after all three on a fourth. The one rescue was a seed whose gate was not yet a key split when the copy came. With noise and the Adam reset the key split re-formed only partly on two seeds and fully on one. Our reading: at eight streams the copy creates a near-tie between a crowded channel and an empty one; at $k = S$ it only resets the gate to where the gradient takes it again. Session H's reading of the mechanism, that W_g's untouched Adam moments still point along the old split, was not measured and is not a reading.

Prevention, not repair (session H, S85). Two devices against the key split were screened on 20 fresh seeds (2310–2329; the oracle 2/2 at 1200), under the key-first classifier: a gate held at 10^{-4} for the first 1200 updates, and the hinge's key term on updates 1–2400 (batch 18's device, Section 9 above). The key term discovers **20/20** against the baseline's 15/20 (5 vs 0, one-sided $p = 0.031$) with no key failure (the baseline has four), and its pre-fixed reading "prevention works" applies; the slow gate discovers 14/20 (0 vs 1) with four key failures of its own, three on the baseline's seeds, reading "prevention not shown; the key split only moves"; the two together discover 19/20 (5 vs 1, $p = 0.109$), "not shown", the one failure (seed 2317) a run that each device alone discovered: under both together the gate was still unrouted at 2400 and the split formed after the window (η^2 by key 0.30 at 3600, 0.77 at 4800) without recovering, which session H reads as the slow gate pushing the gate's learning past the hinge's window, though its hold ends at 1200 and the record shows only the combination failing. Descriptively, from the gate's η^2 by key every 25 updates to 1200 and every 100 to 2400: the baseline's onsets after update 0 lie at updates 25–125 (seven seeds) and the slow gate's at 275–575 (three seeds, two of them seeds the baseline also split and one it discovered), so, on our reading, the gate's learning rate is not what lets them form; under the key term η^2 by key stays below the term's threshold of 0.2 at every measurement from update 25 to 2400 (maximum 0.195 over the 20 runs; the term fired on 1–11 batches per run), a split can start after the window (0.21–0.88 at 3600 on seven seeds) and every such run recovers, routing by stream appearing at 4800 or 6000, after the rise; the price is a later transition (median 4800 against 2400). At initialisation the near-uniform gate's small variations are organised by key on five of the twenty seeds (η^2 up to 0.84 at update 0), the audit's near-uniform case, which the baseline's discovering runs shed by update 600. This is the result of session G's S82 at the other place the key split forms (Section 12): the key term, which reads key positions and key identities during the slow phase, prevents the split that the copy did not repair (S78). Session H proposes the pre-registered test, the window recipe with and without the key term at two streams on disjoint seeds under the key-first classifier. Four of S78's seventeen unbound runs are STREAM-PARTIAL under the classifier of record and KEY under `fail_class_v2`, and one of S85's; no reading changes.

10 Scale

Batch 19 (E) asked whether the recipe's constants are tuned to $N = 256$, $D = 32$, three layers. At four streams with sixteen channels (seeds 270–289, the oracle binding at every size and depth),

with every constant unchanged: $N = 512$ and 1024 at $D = 32$, and $D = 64$ and 128 at $N = 256$, bound routed 10/10 each against the reference's 9/10, all with median transition 3600; 2, 4 and 6 applications of the shared layer bound routed 10/10, 10/10 and 9/10 against 10/10 for three, with six layers slower (median 4800). Both readings were "scale-free" by their pre-fixed rule (every $d \geq -1$), at four streams only; with ten seeds the screen rules out a large drop, not a small one. Eight streams and larger key loads at the larger widths follow.

Eight streams and larger key loads (S66, S67). The batch completed after Revision 9's first draft (186 of 186 runs). At eight streams ($k = 16$, the convolution, 43,200 updates, seeds 290–299, paired with the $N = 256$, three-layer reference at 8/10), the recipe with every constant unchanged binds routed 8/10 at $D = 128$ (2 vs 2; "carries", $d = 0$) and 10/10 with two applications of the layer (2 vs 0, $p = 0.5$; "carries", $d = +2$; two layers was S65's "best depth" through a tie with four that the arms' order broke, a step outside the pre-registered rule, which session E discloses), both with an earlier median transition (15,600 against 21,600) and a higher probe accuracy at the first check; every failure in the three arms had spent its three splits and ended merged. The rule, "carries" at $d \geq -1$ on ten seeds against a reference at 8/10, reads "carries" about 40% of the time when the larger model's true rate is 0.6 against 0.8, so the screen rules out a large drop and not a moderate one. At four streams with eight and sixteen keys per stream (S67, seeds 270–279): the perfect gate binds $P = 16$ at $N = 256$ on both of its seeds, late (24,000 and 27,600), and at $D = 128$ on one of two, so the reading "not capacity-bound at $N = 256$", which is about the oracle, applies and the oracle gives no capacity reason for the wider model's learned advantage; the learned recipe binds $P = 8$ at both widths (9/10, 10/10; median 7200) and $P = 16$ on 0/10 at $N = 256$ against 4/10 at $D = 128$ (4 vs 0, $p = 0.125$; printed, no reading), with most of the failures at both widths ending one-to-one and unbound, which the screen cannot tell from slow. Session E hands back $P = 16$ at $D = 128$ against $D = 32$ as its clearest lead, weak, with the advice that a main-line test fix a longer budget beforehand and pre-register how a one-to-one unbound run counts; and it notes, as a description, that no run in S66 had its transition at or before the first check or the learning-rate switch, so the trigger's absolute schedule can stand at these sizes. Batch 20 then asked whether the sixteen-key runs that had not bound were slow or stuck: every unbound learned run of S67 at $P = 16$ (six one-to-one at $D = 128$; six one-to-one and four merged at $N = 256$) was regenerated from update 0, reproduced its record at 43,200 bit for bit, and continued to 86,400 updates; none bound (the one-to-one groups 0/6 and 0/6, on which the pre-fixed readings "stuck" at both widths and "neither" jointly are read; the merged four 0/4, descriptive), the $D = 128$ one-to-one runs creeping by 0.02–0.10 over the second 43,200 updates and the $N = 256$ ones moving by -0.01 to $+0.41$ without binding, and the $D = 128$ perfect gate on the seed it had failed (270) was still unbound at 86,400. The rule for a main-line budget fixed beforehand gave 40,800 (the latest transition of any bound sixteen-key run, 38,400, plus 2400), and printed beside it "86,400 is not enough". Session E's drafted key-load test (`explore_out/spec_draft_keyload.md`: sixteen keys at $D = 128$ against $D = 32$, 20 seeds per machine, the $D = 128$ perfect gate on two seeds as the validity check) therefore rested on an oracle that had bound one of its two seeds (three runs, the failed seed having been continued), and batch 21 screened that first (E's S69, not F's; seeds 270–279, 40,800 updates, readings fixed before any run): the $D = 128$ perfect gate with sixteen keys binds 4/10 under the recorded single-Adam recipe (three more seeds ended at 0.91–0.92, under the 0.95 bar, and three stuck near 0.30) and 0/10 under SLOW (every seed at 0.33–0.36; with the routing given and no gate to protect, the slow start hurt: no SLOW run bound and SLOW ended lower on every seed that bound or came close under the other recipe). The pre-registered reading is "no $D = 128$ validity check at 40,800": two validity seeds drawn from these ten would

both bind with probability about 0.13 (two fresh seeds on one machine about 0.16 at that rate, on both machines 0.03), and the draft does not go to the referee as written. Session E's status note lists five ways forward, none screened and none adopted (a longer budget for the oracle alone; the eight-key oracle as the validity check, which validates the model and not the capacity; one validity seed; claims conditional on the learned arms alone; or no $D = 128$ arm until a configuration has a reliable oracle). Session E's own verdict on the lead batch 19 handed back, 4/10 against 0/10 ($p = 0.125$), is "inconclusive, weaker than handed back", and the wider model's advantage at sixteen keys has no test it can be put to yet.

Pooled key types at eight streams (session H, S89, S89c, S89b, S92). The main line's keys are four fixed types at fixed positions. Session H drew each sequence's four keys from a pool of 32 types on the eight-stream grouped layout ($k = 16$, the convolution, 43,200 updates; H's own pool draw on the main line's task, equal to the main line's batches at a pool of four), which makes every key type rare across the corpus (0.0105 per type against 0.084) and moves no key: the keys stay at positions $3j + 1$, are the most repeated types within a sequence and sit beside their stream's context token, which the window gate reads; so these screens are about rare key types on a layout with positional keys, not about unmarked key positions, a caveat the referee asked to be printed with every reading. With the Hebbian perfect gate (with the convolution) binding 2/2 as validity, late (16,800 and 10,800 against 2400 and 8400 at four fixed keys in S87a; medians 13,800 against 5400), the main line's recipe binds routed **1/10** (seeds 2902–2911): the pre-fixed reading "the labelled recipe itself fails here" applies and no other is read. Printed beside it: a trigger on all positions 3/10 and no trigger 0/10, and a trigger on the types repeated within the sequence, which on this layout selects 96% of the positions and reproduced the all-position trigger's record on eight of ten seeds, printed as the referee asked and not as a second finding. The nine failures were level or still rising slowly when the budget ended (four at their maximum at the last evaluation, five within 0.009 of it; held-out accuracy first reaching 0.5 at 14,400–26,400, against the oracle's 0.5 by 4800, and ending at 0.60–0.85 with two or three streams sharing a channel): the trigger fires first at 4800 in every run, in the flat start, 17 of each arm's 30 firings came at a probe accuracy below 0.2, every run had spent its three splits by 14,400–36,000, and the late merges found none left, which session H describes as S79's cap failure at a cap of three (a cap of six did not change the count, below); the aim was not the problem (each arm's own pair a labelled target at 27–28 of 30 firings). S89c put the schedule to a paired screen on fresh seeds (2924–2933): the first eligible check moved to 12,000 binds 1/10 and a cap of six splits 2/10, against a rerun of the recipe at 2/10, no pair favouring a new arm; the pre-fixed reading is "the channel is the limit", which by its own operating characteristics reads a schedule effect below about +0.2 in the rate, and whose name, the referee noted, asserts a cause the screen did not test (the 12,000 was itself chosen from S89's curves). On delta memory (S89b) the delta perfect gate bound one of two seeds within 43,200 (at 24,000; the other at 0.875, one-to-one, at its maximum and level over the last evaluation), so by its rule no learned arm ran: what is slow on delta memory at 32 key types is recall within a stream's own channel, not routing, on session H's reading (the perfect gate routes by construction, so no arm tests this). S92 then screened the oracles before any learned arm, four seeds per cell (3020–3023) at 86,400 updates with early stopping, at pools of 4, 8, 16 and 32. The Hebbian perfect gate with the convolution is "reliable" at every pool (4/4 by 43,200; transitions 2400–4800, 8400–10,800, 9600–14,400 and 14,400–19,200); the delta perfect gate is reliable at 4 (all four at 1200) and 8 (7200–22,800) and "the oracle is the limit" at 16 (2/4; the two unbound seeds flat near 0.83 to 86,400) and at 32 (3/4; the unbound seed at 0.70); so $P^* = 8$, with a budget of 43,200 for both memories, which the referee recomputed from the records cell by cell. At pool 8 (seeds 3024–3033, paired) the main line's Hebbian recipe binds routed 6/10

("no reading applies"; its four failures spent their three splits by 19,200–26,400 and ended merged, S89's pattern), the delta recipe with the exact-copy split **10/10** ("the recipe carries to P^*"), and the delta recipe without a trigger 7/10 (3 vs 0, $p = 0.125$; "no reading applies", so on delta the split is neither shown needed nor shown unneeded here; its three failures ended one-to-one with recall short of the bar, the shape of the delta oracle's failures at 16 and 32, and the same seeds bound with the split at 24,000–40,800); the delta against the Hebbian recipe, 10/10 against 6/10 (4 vs 0, $p = 0.0625$), is printed and not read. Only 7 of the delta recipe's 22 firings were on labelled targets and nine fired on maps that were already one-to-one, late and at probe accuracies mostly above 0.77, the case S75b's guard stops; every such run bound. So on this layout both memories' oracles bind reliably to eight key types; from sixteen the delta perfect gate is unreliable at 86,400 updates where the Hebbian one with the convolution is not, which on session H's reading puts the limit in the delta memory's recall within a channel rather than in its routing; the Hebbian recipe falls well before its oracle does (6/10 at eight key types, 1–2/10 at 32 with a reliable oracle) and the delta recipe carries to eight. Reports 10 and 11 and S92's oracle phase were checked by the referee against the records, every count, pair and reading correct; report 12 (62 runs, 88.9 CPU-hours) is the one exploratory report of rounds 5 to 7 the referee did not check, and the review's fixes to S92 were applied after its second phase's first record, which the report discloses (Section 17).

11 The memory rule

What the literature holds. Twelve papers on routing, memory and context were read in full (`docs/reading/`): the test-time-regression framework [5], Gated DeltaNet [6], the Tiny Recursive Model and recurrent-depth language models [7, 8], Flesch et al.'s Hebbian context gating [9], Active Dendrites [10], Context-Gated Associative Retrieval [11], Mixture-of-Memories [12], Raven [13], a study of content-based routing [14], the Hierarchical Multiscale RNN [15] and Nested Learning [16]. None of the twelve carries an inferred context cue across distance without labels under a sparse end-of-sequence loss (the Hierarchical Multiscale RNN infers its boundaries from a dense likelihood, as our note records): each hands the context over (a task identifier, a prototype readable off every input, a clamped context layer), carries it with softmax attention, or routes by token type. The study of content-based routing is the sharpest statement of why our header-layout runs failed: a router over a frozen state-space model's summaries reaches about 29% of the right positions even with the route supervised, over Fourier-mixed representations 0.9%, and 98–99.7% once an upstream, jointly trained attention or mixing layer has written the context into each token's representation. Flesch et al. fit a leaky integrator of the context cue to human learners and show that slow integration of interleaved contexts merges them, and that inside a block the loss exerts no pressure to use a constant cue. Our window gate reads three raw embeddings; our fading-memory gates pooled everything; our fixed header layout is positionally solvable. Those are the failures the papers' analyses, read as analogies, predict.

BDH-CQ. Pathway's follow-up [2] describes its memory as "linear correction rules on S" with linear attention as the special case $S_t = S_{t-1} + U_\theta(D_t)$, and its reasoning as $H_{r+1} = F_\theta(H_r, S_K)$ over a frozen memory; "dimensions, exact update rules, and implementation details remain proprietary". Our reading (`docs/reading/`, an inference from the sentences quoted above, not a finding, and one reading among several, since the quoted sentence counts plain linear attention, which does not read S, among such rules): in the taxonomy of [5] and [16], the rules that are affine in S and read S before writing are the delta-rule family (DeltaNet, Longhorn, Gated DeltaNet, DeltaProduct), and the loop matches the recursive-refinement models [7, 8]; the recurrent-depth model re-injects

its input embedding at every step to keep the recurrence stable, and the frozen memory S_K in BDH-CQ's loop would be the analogue, which is our analogy and not theirs. Neither is a distant-cue mechanism. The 97.4% Sudoku figure sometimes attached to BDH is from Pathway's blog, on internal data with an unstated protocol, and is not comparable to the Sudoku-Extreme numbers of [7].

The premise: one channel cannot. One Hebbian channel binds the two-stream grouped layout 0/60 without the convolution and a minority with it at a higher learning rate (18/40, 10/20), and four streams 0/20 (Phase IV). Session F's delta-rule channel (Section 3) was the stronger single memory the project lacked: at a fixed decay it binds the two-stream *header* layout 8/10 (S53, $P = 4$) and the grouped two-stream layout 4/10. The premise test then ran it where the partition's claim lives (S68, seeds 300–309, 43,200 updates): one delta channel binds the grouped layout 2/10 at four streams and 0/10 at eight, while both delta perfect gates bind at 1200 and the gated Hebbian recipe binds 19/20 and 9/10 on other seeds; the pre-fixed readings "context-tagged keys scale" ($\geq 7/10$ at eight) and "the partition's advantage is in the number of streams" ($\geq 7/10$ at four and $\leq 3/10$ at eight) both read "neither". The main line's pre-registered version, `test_split_copy`'s C3, is SHOWN pooled over both machines: the recipe 18/20 against one delta channel 0/20 (18 vs 0, $p = 3.8 \times 10^{-6}$; X 10 vs 0, L 8 vs 0; the channel's final accuracy 0.08–0.76), one Hebbian channel 0/20 (printed, not claimed) and the delta perfect gate 4/4 at 1200 on both machines; the pre-fixed reading "the partition is necessary at eight streams against a single delta channel" applies, which is what makes the channel's failure the missing partition rather than the delta rule.

The forget gate needs the delta rule. On the fixed eight-key header layout a single delta channel with a learned forget gate (Raven's routed decay, or Gated DeltaNet's) bound 9/10 and 8/10 against 3/10 at the fixed decay (S59), and, post hoc, had learned to partly clear its memory at the context token (median α of 0.18–0.26 at CTX in the first layer, 0.72–0.74 in the third, 1.00 at keys and values). The same decays on a single *Hebbian* channel, same seeds and batches, bound 0/10, 0/10 and 0/10 (S69): the Hebbian channel does not learn the clearing (median α at CTX 0.975 and 0.988 in the first layer), and its final accuracy was lower with the learned decay (0.17 against 0.22; a description of ten runs).

The delta recipe keeps eight streams (session F, S76). Revision 8 reported that the window-gate recipe on delta channels stalled at eight streams (3/10 against 9/10, S54(c)) with a perfect gate that itself took 22,800–28,800 updates, and concluded that the Hebbian write stays on the main line. S76 repeated the comparison with the write strength fixed at $\beta = 1$ and the exact-copy split. Its first phase ran the perfect gate on four seeds: with L2-normalised keys the delta oracle binds all four at the first evaluation (1200) at $\beta = 1$ and at 2400 at $\beta = 0.25$, at $\beta = 1$ sooner than the Hebbian oracle on every seed (2400–6000; at $\beta = 0.25$ it ties the Hebbian oracle on two of the four); with raw keys at $\beta = 1$ one seed diverged and one bound late (16,800), and at $\beta = 0.25$ all four bound, one of them at 7200. The pre-fixed readings for the slowness (the overwrite; the key normalisation) both read "neither", because no L2 arm was slow. Its second phase ran the recipe, paired, on ten seeds: on delta channels 9/10 bound routed against 10/10 on Hebbian channels (1 vs 0), sooner on eight of the nine seeds both bind (median 14,400 against 24,000); the reading "the delta recipe keeps eight streams" applies. Six of the twelve splits on delta channels were not on labelled targets: at each the map had already merged; in five of the six the split copied a channel that held no stream or one, and at the sixth (seed 1314, update 9600) it copied a merged channel onto an occupied one; mostly single splits in runs that then bound. That the plateau rule's target

selection is tuned to the Hebbian trajectory is our reading of this. S54(c) differed from S76 in the learned β, the noisy split with a reset, and the seeds; the oracle comparison holds the routing fixed, which makes the learned β the likely cause of the earlier stall, consistent with its collapse toward zero in S53 and S54(d), but the screen did not separate the two and that attribution is post hoc.

. . . and two and four streams (S80). The same recipe on delta channels, paired with Hebbian on ten seeds each: at two streams ($k = 2$, no convolution) 10/10 against 10/10, delta at the first evaluation on every seed against 2400–6000; at four streams ($k = 16$, with the convolution) 10/10 against 10/10, both at 3600 on every seed, no split firing in either arm. Both readings are "keeps it". Both arms sit at the ceiling, so ten seeds can only detect a large loss: at the main line's rates (0.86 and 0.95) a Hebbian arm loses about 1.4 and 0.5 runs in ten, and "keeps it" means that no seed failed on delta, not equivalence at the main line's power.

What the delta stack carries. Session F's one-seed observation in Revision 8, keys at the third layer tagged by stream, did not generalise. Reruns of 30 recorded single-channel runs with a linear probe at the end (S77; every curve bit for bit) found the stream linearly readable from the residual at layer 3 in one of sixteen bound delta runs on the fixed header layouts (medians at key positions 0.57–0.67), and the two S53 runs that did carry it at value positions (0.92–1.00) were the two that failed to bind; the Hebbian channel's medians are 0.50–0.53 at key positions (single runs up to 0.60). Our reading: keys can be near-orthogonal in the 256-dimensional code without a stream direction in the residual. On the grouped two-stream layout (S80) the delta stack does carry the stream at *key* positions, from layer 2 on (0.98–1.00 at layer 3, median 1.00; Hebbian 0.57), and not at value positions (0.54–0.65), in the perfect-gate arm as well; session F reads this, post hoc, as adjacency to the context token that precedes each key rather than a tag carried to the write. On the randomised header layout (Section 12) the in-run probe finds the stream at key positions in most of the delta solutions that bind without routing and in no routed one.

What this changes. "The Hebbian write stays on the main line" is withdrawn. With the write strength fixed, the delta write is not shown worse than the Hebbian write at two, four and eight streams on screens of ten paired seeds ("keeps it": 10/10, 10/10 and 9/10 against 10/10 each, one-sided bounds at the ceiling and not parity), binds sooner at two and eight, binds the randomised header layout 14/20 against 1/20 for the window baseline (Section 12), tolerates an unrouted first layer (S71), and as a single channel binds 2/10 and 0/10 at four and eight streams (S68, whose reading of that name did not apply; the pre-registered support for the partition is C3, pooled and on each machine). The question is a main-line one again, and `test_delta_recipe` puts it (specified in `specs/`, reviewed by the referee before any run, amended once on its review and written, with the test file checked against the amended spec before any arm's run; run on X, where a second amendment confined to the report's rules, taking the referee's fixes for the test file, was committed during the run with a statement of the 24 run lines that had been read, none of them a claim, a reading or a Hebbian learned-gate run; two were the Hebbian perfect gate's): the exact-copy recipe and the recipe without a trigger on delta and on Hebbian channels (four arms), 20 seeds per machine. D1 is the pooled discordant difference between the two split arms, labelled "delta not shown worse; ahead by ≥ 3 pairs (untested)" ($d \leq -3$; Amendment 2's wording, the first draft of the label having read "delta binds more often"), "delta not shown worse by more than 2 pairs" or "delta not shown non-inferior" ($d \geq 3$), printed beside a paired rate difference with a 95% interval and the bound's operating characteristics (a ten-point deficit passes it 22–29% of the time at 40 pairs); D2 and D4 test the split against no trigger on each write (exact one-sided McNemar) and

read "helps", "not shown" or, when the no-trigger arm binds $\geq 36/40$, "no room"; D3, secondary, is that delta binds sooner. The referee's review, which found the first draft's readings "interchangeable" and "Hebbian-specific" each readable two ways, is in `docs/review_2026-10/`. Both halves are complete: X (seeds 580–599, 84 runs, 29.2 h, Intel Xeon at 2.10 GHz) and L (seeds 1580–1599, 84 runs, about 18.4 h of runs on five workers of the i7-12650H, PyTorch 2.14.1 against X's 2.14.0; a first start on 12 October was lost before any run to a reboot during the projection's timing, which the author attributes to a GPU job running beside it, and the second found no cached record); every perfect gate bound 2/2 on each machine, every CHECK passed, and CHECK 174 dropped no pair on either. Bound routed: on X, DELTA_SPLIT 19/20, DELTA_SLOW 19/20 (the same outcome on every seed, both failing only on one, a merge), HEBB_SPLIT 16/20, HEBB_SLOW 7/20; on L, DELTA_SPLIT 16/20 (three merges and one bound but not routed), DELTA_SLOW 19/20, HEBB_SPLIT 19/20, HEBB_SLOW 10/20. **Pooled, primary**, b and c summed over the 40 pairs: D1, DELTA_SPLIT 35/40 against HEBB_SPLIT 35/40, delta alone on 5 seeds and Hebbian alone on 5 (X 4 vs 1, L 1 vs 4), $d = 0$, rate difference $+0.000$ with 95% interval $[-0.162, +0.162]$; the label is "delta not shown worse by more than 2 pairs", a one-sided bound that passes a true ten-point deficit 22–29% of the time at this size (printed beside it) and so does not state parity. D2, DELTA_SPLIT 35/40 against DELTA_SLOW 38/40, 0 vs 3, $p = 1$, NOT SHOWN, and the no-trigger arm is at $\geq 36/40$: "no room". D4, HEBB_SPLIT 35/40 against HEBB_SLOW 17/40, 19 vs 1, $p = 2.0 \times 10^{-5}$, SHOWN. D3, secondary: on the 30 seeds both split arms bind, delta's transition is earlier on 24, later on 5 and tied on 1 (medians 13,200 against 18,600; sign test $p = 0.00027$). Bands: DELTA_SLOW RELIABLE $[0.835, 0.986]$; DELTA_SPLIT and HEBB_SPLIT MAJORITY $[0.739, 0.945]$; HEBB_SLOW MINORITY $[0.285, 0.578]$. The readings, fixed by the specification and its two amendments, are "delta not shown worse by more than 2 pairs" for the memory rule and "delta: no room; Hebbian: helps" for the split, and no combined name is given when either write reads "no room". The two machines mirrored each other on D1 (X $d = -3$, L $d = +3$), which is what a pooled primary claim with disjoint seeds is for. Printed: every Hebbian firing on a labelled target (80 of 80 over both machines), the delta firings on 26 of 63; the probe alone blocked 5 Hebbian and 14 delta checks. Two descriptions, not claims. On delta channels the split did not help on any seed and cost three (L's 1581, 1582 and 1591 bound routed without a trigger and not with one: two merges and one bound but unrouted; two-sided $p = 0.25$): the no-trigger arm binds routed 38/40 where its Hebbian counterpart binds 17/40, so on this layout the delta write does by itself what the Hebbian write needs the split for, and the pre-registered label "no room" is the right name for a difference the test was not built to show. And the exact-copy split on Hebbian channels binds 35/40 here (0.875), against the noisy copy's 38/40 of `test_window_gate` and 18/20 of `test_split_copy` on other seeds; X's half alone had suggested a wider gap (16/20), which L's (19/20) did not show, and the two copies have not been compared on the same seeds. Raw keys are excluded by their numerical fragility ($\beta\|x\|^2 > 2$ makes $I - \beta xx^\top$ expanding, which is session F's post hoc reading of the one divergence in eight raw-key oracle runs), and the trigger on delta channels is the subject of F's S81. The referee recomputed every count, pair, p-value, interval, band, CHECK and label of L's half and the pooled block from the records, with the test's own functions and independently, and found all of them to reproduce (`docs/review_2026-10/check_delta_recipe_L.md`); one sentence of L's RESULT block was false (the first start had printed only its projection's heading) and is corrected.

The write strength, learned (session F, S88a). Revision 8's stall at eight streams had been attributed, post hoc, to a learned write strength. S88a put that to a paired screen on the delta recipe with the exact-copy split (eight streams, $k = 16$, seeds 2400–2409; readings fixed before any

run): β fixed at 1 against a learned per-token β in the gate's learning-rate group and the same in the slow group. Bound routed: fixed **10/10**; learned 7/10 (0 vs 3, $p = 0.125$); learned and slow 3/10 (0 vs 7, $p = 0.0078$). Neither pre-fixed reading applies: "keeps the partition" needed the better learned arm within one pair of the fixed one (it is three behind), "costs it" needed both learned arms four or more behind with none ahead (the slow one is, the other is not). What the records show, as a description: in every learned run β falls from 1 to below 0.1 in every layer's median, by 3600 in the first arm (whose rate is 10^{-3} from the start) and 1200–6000 updates after the switch in the slow one (which holds it at 0.6–1.0 while its rate is 10^{-4}); at the end it does not diverge by stream in any run, and where it stays of order 1 it is mostly at value positions (the first layer's in 13 of 20 runs, a later layer's in 8 run-layers, and the context position in one); with the tied write, a β near zero both erases and writes almost nothing, and the learned-β perfect gate bound at 21,600 and 30,000 where $\beta = 1$ binds at 1200. Every learned-arm failure is a one-to-one map stuck at 0.31–0.78 or one merge. The earlier screens in which a learned β rose (Section 15) were on other layouts and schedules; the collapse here is this configuration's, and the attribution of Revision 8's stall to it remains post hoc. The fixed write strength stays on the main line.

The horizon (S88b). S59's learned forget gate had raised one delta channel's binding on the eight-key header layout; S88b asked whether it extends the memory's horizon, on the lite randomised header task of S70 at the original cue-to-key distances (1, 3 and 5 tokens) and at twice them (2, 6 and 10, with filler tokens; the same draws, bindings and queries), the fixed decay against Raven's routed decay initialised to equal it, paired, ten seeds at each length (2420–2429), the perfect gate 2/2 at 1200 at both lengths. Bound: at the original distance fixed 9/10, routed 6/10 (0 vs 3); at twice it 4/10 against 5/10 (3 vs 2). The pre-fixed rule requires both arms at $\geq 8/10$ at the shorter distance before any reading on the longer, so the screen is *untested*; had it been tested, neither "the forget gate extends the horizon" (it needed 4 vs 0 at the longer distance) nor "the horizon is the decay's" (the two arms' drops across lengths, 5 and 1, differ by more than one) would have applied. Every failure at either length is a stream confusion at 0.5, flat across the queried key's distance to its cue, so what fails on this task is the stream's identity rather than the memory's reach. The two screens closed S88 (report 8); session F's rounds 6 and 7 follow.

What one channel holds when the keys are not fixed types (session F, S89-F, S90-F). Round 6 removed the task's marked keys. Session F's `RandHeaderTask-pool` is the lite randomised header task with each sequence's four keys drawn from 32 types, and `-allpool` draws its two context tokens from 16 types as well, every other token lite's (each batch is lite's batch with the identities renamed, CHECKed), so that a frequency table no longer selects the keys: on `-pool` the largest-ratio cut selects the two context types only, on `-allpool` the sixteen value types, and a model that sees ten tokens and has no memory reaches about 0.4 on all three tasks, lite included. The validity pilots (the perfect gate, $k = 2$, SLOW, seeds 2800–2801) found the memory rule dividing where the main line had found it even: with its routing given, a *Hebbian channel does not bind four keys drawn from 32 types*, 0/2 on each task at 24,000 and at 48,000 updates with the routing perfect throughout (end margin 1.00), so the failure is inside the channel; the delta channel binds both tasks at 2400–3600 on the same seeds. Both tasks read "untested" for Hebbian memory by the rule fixed before the runs, and no baseline ran. A post-hoc diagnostic of two seeds per cell, committed after the readings and descriptive by its own docstring, found that under S70's single Adam the Hebbian perfect gate also stays at 0.29–0.34 on both pool tasks while under SLOW it binds lite at 2400, which session F reads post hoc as the pool and not the recipe. The short causal convolution on the memory's input, the main line's, restores it (a hypothesis stated before the runs, from session H's

Hebbian oracle binding the eight-stream pooled layout, which has the convolution): the Hebbian perfect gate with the convolution binds `-pool` 2/2 at 24,000 (4800, 13,200) and `-allpool` 1/2 at 24,000 and 2/2 at 48,000 (6000, 28,800), the readings "partly" and "needs the longer budget"; why the convolution helps is not separated, session F's post-hoc candidate being the short-convolution account of associative recall, the write at a value position carrying its key one token back in the same layer. Round 7 removed the contexts' fixed identity while keeping lite's keys: `-ctxpool` draws the two context tokens from 16 types, and `-docs` is the same at $D = 3$ and 4 documents with $S = D$ streams, the stream index by first appearance; every perfect gate handed the per-sequence index binds 2/2 on both memories at 24,000 (seeds 3060–3061), so all six task–memory pairs are valid. On these, without any gate, *one delta channel binds the two-document task* **10/10** (seeds 3062–3071; transitions 7200–15,600; the pre-fixed reading "one channel binds without a context identity") and three or four documents 0/10 (one run at 0.81 and still rising), while one Hebbian channel with the convolution binds 0/10 at every D with its accuracy at $1/D$ (0.48–0.51, 0.32–0.35, 0.24–0.26): it retrieves one of the key's D values without telling the documents apart, and without preferring the last write. A fixed type→channel map, which is what any gate that reads a context's identity can express, separates all D documents of a sequence in at most 0.533, 0.268 and 0.141 of sequences at $k = D$ (0.800, 0.664 and 0.615 at $k = 2D$), exact over every partition of the sixteen types and checked by the referee, and in every sequence at $k = 16$, one channel per type: the cap is a property of $k = D$, not of the task, and at $k = 16$ the type-level perfect gate is the per-sequence gate (one model, CHECKed) and binds 4/4 on `-ctxpool` and `-allpool` on both memories (2400 and 1200; 7200 and 3600). On delta memory a type-level gate at $k = D$ binds all three tasks at a fraction of the cap (final accuracy 0.96–1.00 while separating 0.53, 0.32 and 0.14 of sequences), which session F reads post hoc as a delta channel holding two documents; on Hebbian memory with the convolution the same gate ends at 0.72–0.81 unbound. The referee checked both reports against the records (every number holds, every reading mechanical); it found the sentence comparing `-ctxpool`'s 10/10 with lite's 8/10 to cross recipes (the lite references ran under a single Adam, S90 under SLOW), which session F withdrew as a comparison, and the single-channel screen to have run past the referee's hold, the queue having had no stop (Section 17). Where this leaves the memory rule: on two seeds per cell, a Hebbian channel with its routing given binds pooled keys only with the convolution and a delta channel without it; one delta channel binds the two-document task with no routing and no context identity and a Hebbian one does not (a capacity of two documents against one is session F's post-hoc account of it); and at eight streams on the grouped layout the delta perfect gate is unreliable from sixteen key types where the Hebbian one with the convolution is not (Section 10). Neither write rule dominates.

12 Distant cues

The window gate sees three tokens, so on the header layout it cannot see the cue from the third pair of a block on. Revision 8 left the distant-cue problem open with three proposals from the audit: probe where the cue is in the residual stream, add a register that overwrites on the cue and holds otherwise, and let a per-layer gate read the residual stream. Session G ran all three, in two rounds, and the second round changed the answer.

The cue is not in the stack (S55). A logistic-regression probe from the residual stream entering each layer to the stream, at key and value positions, on the trained window-gate stacks of the eight-key header layout: 0.55–0.58 at layers 2 and 3 and at the output, from about 0.70 at initialisation (where, on our reading, the decayed sum of the block still carries the header). Training

removes the cue (our reading: the gate reads only the window, so nothing asks the stack to keep it), and the perfect gate's stack carries nothing either (0.53–0.56 over the three sites). The pre-fixed reading "absent" applied; that a gate over the residual stream therefore had nothing to read, as the routing study would predict [14], is our reading of it.

The register at layers 2–3 fails on Hebbian memory, and the reason was layer 1 (S56, S57, S71). With the register gate at layers 2 and 3 and the window gate at layer 1, on the fixed eight-key header layout, every Hebbian arm bound 0/10: the baseline, the residual gate alone, the register with and without a stop-gradient, and the register with a 5% labelled nudge. The nudged arm is the informative failure: its register writes a clean latch in eight of the ten runs (medians: β^R 0.96 at the context token against 0.02 and 0.05 at keys and values), its gates route one-to-one with margin 1.00 at layers 2 and 3 in the same eight, and its accuracy plateaus at 0.20–0.44 (the lower of the two runs without a clean latch) with the two streams within 0.03 of each other in most runs, no better than the unrouted baseline (0.28–0.42); the reading "architecture insufficient" applied. A perfect gate at layers 2–3 alone bound 0/3 where the full perfect gate bound one of two seeds, one paired seed of evidence. On delta channels the same architecture binds: the nudged register 8/10, routed 7/10, transitions 3600–6000; the unnudged register 6/10 bound against the baseline's 2/10, which met the screen's own rule for "discovered" on delta (6 against 2 with no unbound key failure; 4 vs 0 by McNemar, which was not its rule), but only two of its six routed, three binding through key splits. The Hebbian perfect gate itself is marginal on this layout at 24,000 updates (3 of 6 seeds over the three screens), so those zeros are weak. Session G then put the layer question on ten paired seeds of the randomised header layout, whose perfect gates bind at 1200 (S71): on Hebbian memory the perfect gate at all three layers binds 10/10 (median 1200, range 1200–4800), at layers 2–3 alone 0/10, the runs' accuracies 0.31–0.54 in two clusters near 0.32 and 0.53 and the per-cell medians over runs 0.46–0.51 in every (stream, block, pair) cell, with layers 2–3 routed perfectly, and at layer 1 alone 9/10, slowly (median 16,800); on delta memory the perfect gate at layers 2–3 alone binds 10/10. The pre-fixed readings "layer 1 is the block" (10 vs 0, $p = 0.00098$), "layer 1 alone suffices" and "delta tolerates an unrouted layer 1" all apply. The interpretation, which is ours and not a reading, is that an unrouted Hebbian memory at the first layer mixes the streams before the routed layers read it; the first design kept layer 1 on the window gate, and that choice is what sank its Hebbian register; the interpretation crosses two tasks (S56's fixed eight-key layout; S71's randomised one) and two gate inputs (S56's register gate read the raw embedding, REG3's reads the window).

The register at all three layers carries the cue; discovery is the gap (S72, S73). One register gate shared by all three layers (REG3, Section 3), on the randomised header layout, 20 seeds, readings on ROUTED-BOUND. With the 5% labelled nudge it carries the cue every time: **20/20** on Hebbian memory (transitions 2400–8400) and **10/10** on delta (all at 1200), one-to-one with margin 1.00 at every layer. Without the nudge it finds the solution on 4/20 seeds on each memory, against 0/20 for either baseline, each discovering run routed perfectly; both screens are one discordant pair short of their $p < 0.05$ rule (4 vs 0, $p = 0.0625$), so S72's pre-fixed reading is "not discovered" and S73's "discovered (register)" does not apply, and 8 vs 0 over the 40 pairs is a description, not a test, since the two screens share seeds but not models. Two other readings of S73 did not apply either, "the delta stack carries the cue" (the baseline 7/20) and "the gate is not needed" (one channel 7/10). The S73 reading was fixed on ROUTED-BOUND; on the outcome named DISCOVERED the same arm is 5 vs 0 ($p = 0.031$), one run binding and separating its values with a margin of 0.66, which is why Section 3 fixes the names. Descriptively: in every routed unnudged run β^R at the context token rose above its value at keys and values (Hebbian 0.32–0.64

against 0.16–0.24; delta 0.36–0.58 against about 0.2), and in the runs that failed the gate had locked into a key split (14 of the 16 runs that did not route on each memory; on delta two of the 14 bound) with β^R at the context token not separated above keys and values in 27 of the 28 such runs. The unbound Hebbian runs sit near chance between the streams (per-cell medians 0.46–0.55; flat across cells by the screen's rule in about half of them). The other devices of the screen: the residual gate alone routes 0/10 on delta (5/10 bound, three by key splits); the HM-RNN latch with slope annealing holds an exact latch when nudged (9/10 routed, $z = 1$ at the context token and 0 elsewhere) and, unnudged, goes to $z = 1$ at every role by update 1200 in eight of ten runs and key-splits in nine of its nine unbound runs (on the fixed layout, S57, it had gone to $z = 1$ in every run and key-split 3/10); one delta channel binds the layout 7/10 with no gate. The in-run probe finds the stream in the residual of no routed run; among the 31 non-routing delta solutions it finds it at key positions in 18 and at both key and value positions in 13 (the single channel's bound runs at 0.93–1.00 at keys; the half-routed baseline's at 0.86–1.00, also at keys): on delta memory the stack can learn stream-tagged keys, and when it does the gate does not need to route, which is a description of a 2×2 the screen fixed as descriptive.

Holding the key split off lets the write appear (S82). Most of the runs that fail to discover end in a key split (28 of 32 in S72 and S73), formed in the records before any write at the cue (Section 9), so session G screened three devices against the key split on 20 fresh seeds (2100–2119), Hebbian memory, with the baseline, REG3 and a nudged pair for validity (2/2, with the perfect gate 2/2). The hinge's key term of batch 18, a penalty on the shared gate's dependence on key identity at key positions during updates 1–2400 (REG3_KEYHINGE), binds routed **20/20** against the baseline's 0/20 and REG3's 2/20 on these seeds (20 vs 0 and 18 vs 0; the readings "discovered" and "helps" both apply, and the arm has no key failures and β^R at the cue above keys and values in every run); on delta memory, descriptive by the screen's docstring, the same arm binds routed 10/10 against 0/10 and 2/10 (bound: 2/10 and 4/10). A gate held slow for the first 1200 updates binds 0/20 (0 vs 0 against the baseline; "hurts" did not apply, 0 vs 2 against the plain register): the records show the key split delayed (η^2 by key above 0.5 at 1200 in 2 of 20 runs against 16 of 20) but formed (KEY 18 of 20) and the write at the cue separating in only 1 of 20, which we read as the slow gate delaying the write along with the split; a gate without the raw window input binds 5/20, "discovered" exactly at its threshold (5 vs 0), with a register that writes at nearly every token. What the firing records show, as a description: the near-uniform gate's small variations are organised by key from initialisation (η^2 by key 0.89 at update 1), the hinge holds that at 0.05 from update 300, the register's write at the cue separates from its write at keys and values during the hinged phase (0.12 at every role at 1200; 0.48 against 0.20 at the end), 18 of the 20 bind at 3600, the first evaluation after the hinge stops, and the key split does not return in the 2400 updates each run is observed after its transition. The hinge reads the task's key positions and key identities, as the split reads key positions: it is a training-time prior over the first 2400 updates and not an architecture, and in a language model key identity would be token identity, which a gate must in general be allowed to use.

What this changes. On a screen of twenty seeds, the distant-cue task has a solution without stream labels: a register that overwrites at the cue, a gate over the register, the window and the residual at all three layers, and a hinge that keeps the gate off key identity while the memory is slow. Its capacity was never the limit (the nudged register, 20/20); its discovery is 20/20 with the hinge and 2–4/20 without. Session G then screened, on S82's seeds and against its records (S83; each S82 reference arm reproduced bit for bit through 2400 at one seed first), the control the main-line test

needs and what the hinge must read. The key term on the window gate without the register binds routed 0/20 (the register beats it 20 vs 0; "the register is needed"): on our reading of G's traces, the hinge has nothing to release there, since the window gate's key-structured variation is already small and nothing carries the stream. A term that reads key positions but not identities (the gate's KL from uniform at key positions, updates 1–2400) binds 1/20 ("the identity term is needed", 19 vs 0), and the same term at every body position 0/20: both held the gate at uniform from update 300 through 1200 (its KL from uniform at most 1.4×10^{-5} in every run; the flat term's through 2400) and the register's write stays at its initial value through 1200, moving only afterwards, where, on session G's account, the ratio term removes only the share of the gate's variation organised by key and leaves it free to commit by stream. The key term for updates 1–1200 only binds 18/20 (18 vs 0 against the baseline; one pair short of "the short window suffices"). So the device that works reads key positions and key identities, and the one form tried of each device that reads less fails, by clamping the gate, which S83's specification had allowed in advance as a weakness of the form rather than of reading less (though it expected the term too weak near uniform, not too strong); the main-line test session G has drafted (`explore_out/G/spec_draft_register.md`) puts the hinged register against the baseline, against the register without the hinge and against the hinge without the register, 20 seeds per machine on seeds no branch has used, with a rate claim of $\geq 18/20$ on each; it is the register test proposed to follow `test_delta_recipe`; the referee's review of the draft is in Section 15. Session G's last screen (S87, seeds 2700–2719 Hebbian and 2720–2729 delta, with the S82 baseline and key hinge rerun as controls, 0/20 and 20/20 again) asked what a hinge must read: a hinge on a *frequency table* of token ids, computed once before training from a sample of 4096 training sequences with no labels of any kind, in which the largest ratio cut happens to select the six frequent types (the two context tokens at 0.114 each, the four keys at 0.102; the values are rare at 0.023) and so covers the key term's eight positions and, beyond them, the query's key and the five context positions, discovered **17/20** (17 vs 0 against the baseline, $p = 8 \times 10^{-6}$; on delta memory 10/10 against 0/10, descriptive), two pairs short of the pre-fixed rule for "replaces the key hinge" (the key hinge alone on 3 seeds, the frequency hinge alone on none) and with the key term not shown needed over it (3 vs 0, $p = 0.125$); a penalty on each position's gate's distance from the sequence's own mean gate, which reads nothing, bound 0/20 and clamped the gate (its commitment 0.0001 against the baseline's 0.873 at 2400, the pre-fixed "clamps"), and a raised gate temperature for the slow phase 3/20. So a prior that reads the task's token statistics rather than its labels does most of the key hinge's work on this task, on one screen, and the three failures of the frequency hinge are key splits: what the hinge covers that the key term does not, the context positions, groups them by stream and penalises the gate's dependence on the stream token there, which on session G's account is why it lags. The audit's per-layer gate over the residual stream, run alone, bound 0/10 on the fixed Hebbian layout (S56, every run a key split, with nothing in the stack to read) and routed 0/10 on delta (S73; 5/10 bound, eight key splits); no reading of either screen applied to it, and it is not pursued.

A hinge that reads what repeats (session G, S89, S89H, S90). Round 6 put S87's hinges on session F's pooled tasks with the register gate at all three layers (REG3; $k = 2$, SLOW, 24,000 updates; seeds 2842–2861, paired across arms, tasks and memories, with the perfect gate 2/2 as validity on each task and memory) on delta memory, which the pilots had made the valid one (S89), and on Hebbian memory with the convolution (S89H), and added a hinge that reads neither labels nor a corpus table: a penalty on the gate's dependence on token identity at the positions whose token type *repeats within the sequence*, which on these tasks selects the context, key and about 2.6 value positions, the key term's eight positions among them. On `-pool`, where no frequency

cut reaches the keys, the repeat hinge binds routed **20/20** against the key hinge's 20/20 on delta memory and **19/20** against 18/20 on Hebbian memory with the convolution, the same binding seeds as the key hinge on delta (0 vs 0; the transitions equal on half the seeds) and one seed more on Hebbian memory (0 vs 1), in each case the committed rule's "replaces the key hinge"; the frequency hinge, on this task a hinge on the two context types, that is on the stream token itself, binds 7/20 on delta, worse than no hinge (10 vs 1, $p = 0.006$), and 18/20 on Hebbian memory. What the register alone does differs by memory, and the referee's reading of it is the one that matters: on delta memory REG3 without a hinge binds 16/20 (against 0/10 on lite), neither hinge is shown needed over it (4 vs 0, $p = 0.0625$) and "replaces" replaces a hinge whose own contribution is not established; on Hebbian memory REG3 alone binds 9/20, its register shutting (β^R decaying to 0.03), and both hinges beat it by nine or ten pairs ($p = 0.001$–0.002), so there the hinge is needed and the label-free one does its work. Round 7 put the repeat hinge on the register test's own setting, lite with Hebbian memory and no convolution (S90; S87's seeds 2700–2719, paired with S87's records, which this CPU reproduces bit for bit): it binds 17/20 against the key hinge's 20/20 (3 vs 0, $p = 0.125$), the hingeless register 4/20, the frequency hinge 17/20 (S87's record) with the two label-free hinges one pair apart each way, so the pre-fixed reading is "is weaker than the key hinge" and the specification's revision 2 carries the key hinge alone, dating that decision after S89, S89H and S90; at a 20/20 ceiling the rule's "within one pair" fires only 39% of the time for an arm whose true rate is 0.9, so "falls short" is the rule's output and not evidence of a rate below 0.9, and whether the task, the convolution or chance separates S90's three pairs from S89H's one is not asked. The referee checked all three reports against the records: every count, pair and reading holds and every reading is its rule's mechanical output, with a run count (84 for 44), a CHECK-row count and two descriptive ranges wrong beside them; S89H's `-allpool` arms had run 24,000 updates and not the 48,000 its docstring fixed, the budget never reaching the child, a harness defect session G corrected in the report and then fixed with an assert on each payload's budget; S89H itself ran with no pre-run review; and two of S89's names do not mean what they say (above), for which the referee's second reading, the hinge against the register alone, is now printed beside the first.

Contexts without fixed identity (S89, S89H, S91, S91b). On `-allpool`, where the two context tokens are drawn from sixteen types and no type maps to a stream, every learned arm of S89 and S89H binds routed 0/20 on both memories (bound at most 2/20, late and under a key split with margin near zero: delta memory binding without routing) while the perfect gate handed the per-sequence index binds 2/2 at 3600–9600: the pre-fixed "the labelled hinge itself fails here", printed with the caveat the referee asked for, that a fixed context-type→channel map routes at most 0.533 of sequences at $k = 2$, so the null does not separate rare keys from contexts without identity. The failures show the cap: on delta five REG3 and five key-hinge runs, and on Hebbian memory 11–17 runs per hinge arm, end with 0.33–0.57 of the probe's sequences routed, at or near the fixed-map cap, and no run learned the relative routing. S91 gave the gate what the task seems to ask for, on delta memory at $k = 2$ (ten paired seeds, descriptive): one scalar per layer for the cosine between the current token's embedding and the register's content, "the same document or the other", with and without the hinge, and a novelty scalar, whether the token's type has occurred earlier in the sequence. Every arm binds routed 0/10 against the control's 0/10, "no device here": the match term trains (to about 0.21 at the median), no run with it ended at a type-level map (0/10 against the control's 2/10) and none routed. Its Hebbian half was untested, the perfect gate binding one of two seeds at 48,000 (the other at 0.9375 and still rising, where S89H's had bound at 6000 and 9600 on other seeds), and was replaced rather than rerun. S91b removed the cap instead: $k = 16$, one channel per context type, on `-ctxpool` and `-allpool`, both memories, ten paired seeds

(2994–3003), with two perfect gates as ceilings, the per-sequence index and a channel per type, which within a sequence are one model and bind 2/2 on every task and memory, the type-keyed gate routing every sequence over its sixteen channels. Every learned arm, REG3 with no hinge, with the key hinge and with the repeat hinge, binds routed **0/10** on both tasks and both memories: the Hebbian key hinge's gate does key on the context type (η^2 by type 0.97) but spreads over about six effective channels on its mean gate, every run one-to-one in part at a held-out accuracy of 0.89 and short of separation, and the delta arms do not key on type at all, at 0.50–0.77 on a task a single delta channel binds 10/10 without routing. The committed rule names this "the channels do not suffice"; the referee's reading, which we adopt, is that the channels suffice for the memory and the task, the type-keyed ceiling showing it, and that no learned gate found such a map in 24,000 SLOW updates: a learning negative at this budget (each 0/10 excludes a true rate above 0.26), not a capacity limit. This is where the project's work on the distant cue ends. A gate trained on the task loss finds a register's partition when the cues are fixed types and, with a hinge that reads which types repeat, when the keys are not; when the cues themselves have no fixed identity, no device screened, with two channels or sixteen, on either memory, finds the routing that a handed index or a handed type map carries, and the one thing that binds there is a single delta channel at two documents, which routes nothing.

arm (the register gate at all three layers unless stated)	lite, Hebbian (S87, S90)	`-pool`, delta (S89)	`-pool`, Hebbian + conv (S89H)	`-allpool`, delta / Hebbian + conv (S89, S89H)	`-ctxpool`, k=16, Hebbian + conv / delta (S91b)
perfect gate, the per-sequence index	10/10[a]	2/2	2/2	2/2 / 2/2	2/2 / 2/2
perfect gate, a channel per context type	—	—	—	—	2/2 / 2/2
window gate + SLOW, no register	0/20	0/20 (14/20 bound unrouted)	0/20	0/20 / 0/20	—
the register, no hinge	4/20	16/20	9/20	0/20 / 0/20	0/10 / 0/10
with the key hinge (positions and identities)	**20/20**	**20/20**	18/20	0/20 / 0/20	0/10 / 0/10
with the frequency hinge (a corpus table)	17/20	7/20	18/20	0/20 / 0/20	—
with the repeat hinge (types repeated in the sequence)	17/20	**20/20**	**19/20**	0/20 / 0/20	0/10 / 0/10
a comparing gate, with and without the hinge; a novelty signal (S91, delta, k=2)	—	—	—	0/10, 0/10; 0/10 / —	—

Table 4: Pooled keys and pooled contexts (sessions F and G, rounds 6–7; exploratory). ROUTED-BOUND, in its within-sequence form on the pooled-context tasks; $k = 2$ except the last column; 24,000 updates throughout (S89H's `-allpool` arms ran 24,000, not the 48,000 first reported). `-pool`: lite with each sequence's four keys drawn from 32 types; `-allpool`: with its two context tokens drawn from 16 types as well; `-ctxpool`: lite's keys with the contexts drawn from 16. The frequency hinge selects the two context types on `-pool` (a hinge on the stream token) and the sixteen value types on `-allpool`. [a]S71, seeds 700–709 (Table 6).

The register test, specified and not run. Session G's specification of the register test went through two revisions on the referee's reviews (`spec_review_register_draft.md`, `_v2.md`): revision 2 (`6fc55b1`) resolves all thirteen items of the second review and makes the key hinge the hinged arm, with a dated statement, made after S89, S89H and S90, of why no label-free hinge is an arm; the third review (`spec_review_register_v3.md`) reads "ready for X's adoption after the fixes at the end", ten of them, all text, none changing an arm, a seed, a threshold or a claim. Nine of the ten fixes were not applied (the sixth is in the file in substance, through session G's edit of 22 October, `4314e35`), and the test was not adopted or run: the draft is kept at `specs/drafts/test_register_draft_rev2.md`

(G's branch tip, revision 2 plus that sentence), marked as not adopted, and `STATUS.md` says what running it takes. It would be Phase VI's fifth pre-registered test, and it is the nearest to running.

13 Where the mechanism stands

setting	perfect gate	recurrent gate, Rev. 7 recipe	window gate + SLOW	window gate + SLOW + split	the same on delta channels[d]	one Hebbian channel	one delta channel
S=2, P=4, no conv.	4/4	67/80	69/80	—	10/10 vs 10/10	0/60[c]	4/10[f]
S=4, P=4, k=16, conv.	4/4	27/40[w]	38/40	39/40[e]	10/10 vs 10/10	0/20	2/10[f]
S=8, P=4, k=16, conv.	4/4	0/40	15/40; 8/20[s]	**38**/**40**; **18**/**20**[s]	9/10 vs 10/10	0/20[s]	0/20[s], 0/10[f]

Table 5: The grouped layout: the main configurations of `test_window_gate` (pooled over X and L, disjoint seeds; bound routed, or discovered at $S = 2$), with `test_split_copy` (pooled over X and L, 20 pairs) and the screens. [w]With the early hinge window (WIN16_A); Revision 7's full-hinge arm bound 35/40 on shared seeds, routed 15/20 on X and 16/20 on L. [e]Session H's S58, exploratory, 40 seeds. [c]One Hebbian channel without the convolution, every such run on the grouped layout in `results/` (the blocked and shuffled layouts add 0/30); with the convolution at learning rate 4×10^{-3} it binds 18/40 and 10/20 at two streams (Phase IV's `conv_lr`; Revision 6 reported 34/80) and 0/20 at four (`test_scale_axes`, B4s). [d]Session F's S80 and S76, exploratory, ten paired seeds each, the delta recipe against the Hebbian one with $\beta = 1$, L2 keys and the exact-copy split at four and eight streams (none at two, where $k = S$); at eight streams the pre-registered `test_delta_recipe` (pooled over X and L, 40 pairs) has the delta recipe 35/40 against the Hebbian recipe 35/40 and, without a trigger, 38/40 against 17/40. [f]Session F's S53 and S68, exploratory, $\beta = 1$ at the fixed decay. [s]`test_split_copy`, pooled.

randomised header layout (S=2, P=4, k=2, 24,000; session G, seeds 700–719)	Hebbian memory	delta memory
perfect gate, all three layers	10/10	10/10
perfect gate, layers 2–3 only (window gate at layer 1)	0/10	10/10
perfect gate, layer 1 only	9/10	—
window gate + SLOW (ROUTED-BOUND; bound)	0/20 (1/20)	0/20 (14/20)
register gate at all three layers, labelled nudge	**20/20**	**10/10**
register gate at all three layers, label-free	4/20	4/20
the same with the key hinge for updates 1–2400 (S82, seeds 2100–2119; baseline there 0/20, register 2/20)	**20/20**	**10/10**
the same with a slow gate for 1200 updates / without the window input (S82)	0/20 / 5/20	—
the key hinge on the window gate, no register (S83) / a term reading key positions only / reading nothing / the key hinge for 1200 updates	0/20 / 1/20 / 0/20 / 18/20	—
the register with a hinge on a frequency table of token ids (S87, seeds 2700–2729; baseline there 0/20, key hinge 20/20) / a self-distance penalty reading nothing / a raised temperature	17/20 / 0/20 / 3/20	10/10 / — / —
residual gate at all three layers, no register	—	0/10
HM-RNN latch, label-free / nudged	—	0/10 / 9/10
one channel, no gate (bound)	—	7/10

Table 6: The distant-cue task. Exploratory (session G, S71–S73, S82, S83 and S87); the perfect-gate rows are BOUND, the others ROUTED-BOUND, and session F's window baseline on other seeds (S70, 330–349) is 0/20 routed on either memory with 1/20 and 6/20 bound.

The partition does what one channel cannot, and the gate finds it where the cue is local. Given the partition, every grouped-layout configuration tried with the $N = 256$ model binds, on either write rule. One Hebbian channel does not; one delta channel binds a minority at two streams and none at eight, and the pre-registered version of that comparison is SHOWN pooled over both machines. A gate that reads three tokens, trained with the memory held slow for 2400 updates and with a channel split when binding stalls, finds the partition at two, four and eight streams without stream labels or restarts, and the split reads the task's key positions.

Discovery is a race, and the recipe's parts each remove one way of losing it. Slow memory reduces the key splits (12 of 15 failures to 6 of 11 at two streams; the count itself, 7 vs 3, is not shown); the window gate cannot count positions, so position splits are gone; the split breaks the merges that remain at eight streams by giving an idle channel the busy channel's logits, and it is the copy that does it. Two ways of losing remain: at two streams a key split that the copy cannot undo, because, on our reading, there is no idle channel, and that the hinge's key term prevents on a screen (S85, 20/20 against 15/20); at a distance, a key split that in the records forms before the register's write at the cue has appeared, which a hinge on the gate's key-dependence during the slow phase prevents (20/20 on a screen).

The write rule and the layer. The delta write with a fixed write strength is not shown worse than the Hebbian one on the grouped layout at two, four and eight streams (one-sided bounds on ten paired seeds each, and the pre-registered test at eight: 35/40 against 35/40, $d = 0$, pooled over two machines), binds sooner, needs no split there ("no room": 38/40 without a trigger) where the Hebbian write does (35/40 against 17/40), and is better placed for distant cues, where a Hebbian

stack needs its first layer routed and a delta stack does not. The partition's claim is about the number of contexts on both rules: one delta channel binds the two-stream header layout 8/10 and the grouped one 4/10, by what we read as routes that need no partition, and binds 2/10 and 0/10 at four and eight streams.

Without marked keys, and without fixed contexts. Rounds 6 and 7 took away what the recipe reads. With the keys drawn from a pool, the hinge's label-free form exists and matches the labelled one within one pair where the hinge is needed (Section 12; Table 4), and the two write rules part: on two seeds per cell a Hebbian channel with its routing given binds four keys from 32 types only with the convolution and a delta channel without it; on the eight-stream grouped layout the delta recipe carries to eight key types where the Hebbian recipe does not decide, and from sixteen the delta perfect gate is the limit at 86,400 updates where the Hebbian one with the convolution is not (its recall rather than its routing, on session H's reading; Sections 10 and 11); neither write rule dominates. With the context tokens drawn from a pool, one delta channel binds two documents with no gate and no context identity; no learned gate, at two channels or sixteen, on either memory, routes them, while a handed index or a handed channel per type does on every seed; and at three or four documents one channel of either rule fails and no gate was screened. The partition's claim stands as stated: it is about the number of contexts, and its discovery by a gate trained only on the task loss has been shown where the cue is local and fixed, screened where it is distant and fixed, and not found where the cue has no identity of its own.

14 An independent replication

Design. A separate session (R) was given Revision 8's PDF and Pathway's public BDH repository and nothing else, with the rule that it must not look at this project's code, branches or web presence until its own records were pushed. It implemented the task, the model, the outcomes and the recipes from the text (Phase 1), logging every detail the report did not determine in a file of 44 entries (`UNSTATED.md`) before running; pre-registered its readings; ran the perfect gate on two seeds and the eight-stream recipe with and without the split on twenty fresh seeds (900–919) at the report's budget (Phase 2); and only then fetched the main line and diffed the two implementations (Phase 3), rerunning ten seeds with one discrepancy at a time set to the main line's choice. Its bar, fixed in advance: "replicated" at $\geq 18/20$ bound routed with the split beating the no-split arm at $p < 0.05$; "partially replicated" at $\geq 12/20$.

Result. The perfect gate bound 2/2. The recipe with the split bound routed **17/20** (Wilson $[0.640, 0.948]$); without it 7/20; every discordant pair favoured the split (10 vs 0, $p = 0.00098$); all 45 of its splits but one copied a channel holding two or more streams onto an empty one; every failure in both arms was a merge of two or three streams, as in ours. The mechanical reading is "partially replicated", one run short of the bar. Against the report's 38/40 the count is Fisher two-sided $p = 0.32$, and pooled over X, L and R the rate is 55/60 $[0.819, 0.964]$; the referee's assessment (Section 15) is that the bar could not separate the outcomes it was meant to (it fails a true 0.90 recipe a third of the time) and that the defensible statement is R's own: 17/20 is consistent with 38/40, and twenty seeds cannot tell 0.85 from 0.95. The two reruns with the main line's probe and with its key positions left the count unchanged on seeds 900–909 (9/10, 9/10), and were not run on the one failure a protocol difference plausibly explains (914, the probe reading of Section 6). A fourth phase ran the split with its probe and key positions as the main line specifies them (the fixed probe, the body's key positions; its other choices, among them the map on the held-out sequences,

R's own) on twenty fresh seeds (920–939) beside the no-split arm, with the single-rate oracle as validity (2/2 at 2400), under a rule pre-registered before any run (`464be8d`): pooled with Phase 2, the split arm bound routed **35/40** (Wilson $[0.739, 0.945]$) against 12/40 without the split, 23 vs 0 (one-sided $p = 1.2 \times 10^{-7}$), and the mechanical reading "consistent with the report" applies (the intervals overlap; the report's own pooled count is 38/40 against 15/40, also 23 vs 0). On the fresh seeds alone, with those two choices, the split arm bound 18/20, the count Phase 2's bar had asked for, which `phase4.py` prints as secondary without a reading; both failures were two streams sharing a channel after three splits, as X's were. R's own statement of what forty seeds can say: the point estimate 0.875 sits below 0.95, the interval reaches 0.945, just below 0.95 (R's report says it includes 0.95; the pre-registered reading, which tests overlap with the report's interval, is unaffected), it excludes rates below 0.74, and separating 0.85 from 0.95 as two arms against each other would need about 150 seeds per arm (against a fixed rate on fresh seeds, the 52 of Section 17 answer a different question). The rule itself, an interval-overlap test pooled with Phase 2, detects a true rate of 0.70 about one time in nine, which the referee had pointed out; an amended reading calibrated to its size (32 fresh seeds, "below 0.95" at $x \leq 27$, size 0.020, power 0.54 at 0.85) was written after the referee's review but existed in no commit until `db22857`, after Phase 4 had started, and was not used. R's Phase 4 also counted the probe's failure mode across its runs: with the main line's fixed probe, a check at which the probe read ≥ 0.95 while the evaluation did not occurred at 3 of 263 checks and never decided a run; with one probe drawn per seed (Phase 2) it occurred at 13 of 192 (13 of 282 with R's second rerun, which had none) and, on R's inference, decided one run in twenty (914); the rerun that would test that inference, 914 under the main line's protocol, was not run. R's advice: specify the probe as one fixed draw, say that 64 queries can over-read a merged model, and gate the trigger on more queries.

What the report determined, and what it did not. R loaded its weights into our model: the gates agree to 7×10^{-9} and the query logits to 7×10^{-8}. By R's own labels on its 44 entries, the text stated four outright and three only in part (the gate's input among the four) and left 34 to be guessed (the initialisation scales, the parameter dtype, the evaluation's sampling and the trigger's details among them): 20 on which it was silent, 12 on which it was ambiguous and 2 carried over from what the report states for another component, with 3 further entries of process; in the paths of our code it read (not the CHECK chain, the report printing or the hinge paths) R found nothing that contradicts the report and nothing it had misread. Every difference is protocol, and five could change an outcome: the identity of the split's probe (ours is one fixed set for every seed and arm; R drew one per run), the key positions whose gate mass picks the channels (ours the body's 32 keys; R's included the query's), the perfect gate's schedule (ours a single rate; R's SLOW, which explains its slower oracle), the order of the trigger and the early-stop test at an evaluation step, and the last eligible check. R lists eleven guesses that matched our choices, among them: decay rather than RoPE; that the gate reads the model's own raw embedding; the window gate's width and initialisation, carried over from the recurrent gate; the convolution as one shared width-4 identity filter on the layer input, feeding keys and values; Adam without weight decay and without dropout; the probe's reference at 2400; and the zeroed Adam step counter; the 0.02 embedding initialisation, which sets the scale of the gate's input, matched as well (R's report), and the map as the argmax of the mean gate at value positions is filed by R as a difference (D-10) that matched in statistic only, since R measured it on the 2048 held-out sequences and the main line on a 256-sequence probe. Appendix B states them, with the entries the referee found missing from this draft's first version (the window's generator, the frozen recurrent weight, the dtype, the perfect gate's model, the tie rules and the noise's estimator) and the three it added (the probe's composition, the outcome's

boundary rules, a record format an outside scorer can use).

Phase 5: `test_split_copy` on fresh seeds. After Phase 4, R was given `specs/test_split_copy.md` and the test's docstring and asked to reproduce that test's three arms on twenty fresh seeds (940–959) with its own implementation, its protocol and readings committed before any record (`550a736`; the records show no run finishing before it, though a start a few minutes earlier cannot be excluded, as in Phase 4). The copy with its reset bound routed **18/20** (Wilson $[0.699, 0.972]$), the reset alone 9/20 ($[0.258, 0.658]$), one delta channel 0/20 ($[0, 0.161]$); the perfect gates 2/2; paired, the copy against the reset 9 vs 0 ($p = 0.002$) and against one delta channel 18 vs 0 ($p = 3.8 \times 10^{-6}$), where the main line has 12 vs 0 and 18 vs 0. R's pre-fixed rule reads each arm "consistent" when its count lies inside the main line's pooled interval, and all three do (18/20, 6/20 and 0/20 there). Two qualifications, the referee's: the rule separates little at twenty seeds (the copy arm reads "consistent" with probability 0.61 at a true rate of 0.70 and 0.64 at 0.95), and "from the written specification alone" holds for the delta arm only, since the copy and reset arms are R's Phase 4 recipe, whose probe and key positions were taken from our code; R reads nothing beyond its rule, which is right. Every number reproduces from R's records with R's outcome functions and with the main line's, which agree (`docs/review_2026-10/check_R_phase5.md`). The 44 unstated details of Phases 2–4 became 65 with Phase 5's.

Caveats. Isolation rested on self-report. The PDF R was given lay inside a checkout of this repository in its container, and a filename search printed six of that checkout's filenames; R opened none of them and judged the replication not void, and so do we, but a second replication should be isolated by construction (Section 17). R used PyTorch 2.14.1 (ours 2.14.0), four workers, and 37 hours of compute, and its records carry no CPU model; bit-for-bit agreement across implementations was neither expected nor sought.

15 The referee's report and the claim registry

What the referee did. A session with no part in the work (V) was given the repository and asked to review Revision 8 adversarially, changing nothing outside its own directory, which is now `docs/review_2026-10/`. It recomputed every count, discordant pair, p-value, interval and band of the report's tables from the JSON records under outcome definitions it re-implemented (156 numbers: 140 match, 7 disagree and 6 partly, the 7 all statements corrected in Revision 8.1 and listed below; two later passes over F's reports 3–5, G's 3–4, H's 4–5 and I's 1, 808 rows, found every pre-registered reading re-deriving exactly and 13 disagreements, all in descriptive ranges; the earlier reports and E's batches were audited for when their readings were committed, not re-derived); audited the git history of every main-line claim (no claim or reading edited after a run; the split arm added by a dated amendment before any learned-gate result existed) and of 21 exploratory screens; reproduced one run of each Phase VI test bit for bit on a 2.10 GHz Xeon, the model of X's slower host; checked the literature against the project's own notes; and compiled the claim registry of Section 3. Its recommendation on the first draft was "major revision": the central experiment sound, the manuscript claiming more.

What it found wrong, corrected in Revision 8.1. Seven statements were false when the first draft was committed: that no single-channel run had been made at eight streams (session F's premise test was on its branch 82 minutes before the commit, and its counts, 0/10 at eight streams, bore on the claim); the Muon correction with the two machines the wrong way round (Revision 7's

result came from L, was confirmed on X's fresh seeds and reversed on L's); an argument about the convolution that compared an $N = 64$ ceiling model with the $N = 256$ model (the $N = 256$ perfect gate without the convolution binds on every seed recorded); batch 16's hardware; a stale count of single-evaluation binds; a claim that every test had a specification file; and Revision 7's routing "recorded only on X" (L's records carry it). Seven statements overstated their evidence and were reworded: "the reset adds nothing" (the looks cited showed only that the reset alone is not enough; Section 6 now has the look that shows it), "one channel per stream" (by largest mass; the sets are disjoint), "no labels" (no stream labels; the split reads key positions), Gumbel noise "on the read gate", "beat" for a screen whose verdict was "promising", the literature sentence on inferred cues, and the BDH-CQ reconstruction. The referee's check of the corrections found two slips in them (a run count; a phase number) and one older error both had missed (one Hebbian channel *had* been run at four streams: 0/20), corrected in a second pass.

What it asked for, and what Revisions 9 and 10 did with it. Scope (done: the title and Section 18); the copy-only arm as a pre-registered claim (Section 6; the copy against the reset is pre-registered and shown on both machines, the copy alone against the full split was not run); the split's dependence on key positions (stated everywhere it is claimed; a trigger that reads all positions was screened twice, session H's S86 and S87a, 24/30 against 26/30); an external baseline family (one delta channel and the delta write with its decay and write strength fixed are now run at two, four and eight streams on the grouped layout, and Gated DeltaNet's learned forget gate on the eight-key header layout; no external model, a Gated DeltaNet, Mamba or attention model, has been trained on the task; a residual-stream router was run and failed; Mixture-of-Memories' balance loss was run); paired-difference intervals and a stated error rate (Section 5, Section 3); routing by overlap (reported); the literature's remaining overstatements (Section 11); provenance (commits pinned; L's local start times noted; L's Phase III–IV records committed, Appendix A). Two requests remained open when the project concluded: the claim list's q-values are in the registry and not in the tables here, and BDH-CQ and Triadic Linear Attention were not read in full.

The registry's two findings about the records. L's result files for Phases III–IV were not in the repository: the commit that was meant to hold them (5 October) held byte-identical copies of X's files, naming X's processor, so every L verdict from those phases was known only from text written later. The user recovered twelve of the thirteen files from the laptop's working copies and reran the thirteenth; all 70 L rows the registry can now check against a file agree with it (38 verdicts, of which 17 had been second-hand, and the 32 bands, gates and readings recounted from the per-run records), eleven L tests gained a printed p, and L's family under correction improved (27 of 32 positive verdicts survive Benjamini–Hochberg). The main line's split probe is unbalanced across streams (Section 6).

The sessions' reports, after the referee. Statements the sessions made beyond their pre-fixed readings are quoted in this revision as descriptions, not results: among them, that S54's slow delta oracle was a learned-β artefact, that the register's write at the cue is what separates a discovering run, that the stack's stream tag lets the gate stop routing, and that the check interval and the first eligible check act through the flat start. Each is marked where it appears; the referee's check of this draft's first version listed the places where they were not, and those are now marked.

What it found in Revision 9's first draft. The referee checked the first draft of Revision 9 (commit `9bfa85a`) against the records, the docstrings and the code

(`docs/review_2026-10/revision_9_check.md`, 400 rows): every count, discordant pair, p-value and interval in its tables reproduces, every reading it quotes was committed before its first run, and its text repeated Revision 8's failure in kind. False when committed, against records already pushed: that the main line's records store neither the probe's reading nor the per-stream masses at each check (they store both; Section 6); that session G was still screening three devices whose result, 20/20, had been recorded fifteen minutes before the commit (Section 12); that session H's S85 was running (committed, not started); that session R's Phase 4 reading had been corrected (the amended reading existed in no commit until `db22857`; R's branch carries the first rule); that the referee's recomputation found "all" numbers to reproduce (140 of 156) and had re-derived every reading of every screen (the later reports; the earlier ones were audited for timing); that 90 L rows agree with the registry (70); that a run was reproduced on a third CPU model (on X's own slower model); and that R's model agrees with ours to 10^{-8} (the logits to 7×10^{-8}). Contradicted by the draft's own tables or by the record: that the reset-only arm bound no more often than no trigger in every look (S61: 4/10 against 3/10); that all 83 of S61's firings copied a row (57; the resets copy nothing); that a learned β collapses (it rose in two screens); that six delta splits fired before the map had merged (it had; five of the six copied the wrong channel); and three ranges stated for every run that held for the median run. Overstated: the delta write's "parity" and "interchangeable", the S61 pattern in a new place, now "not shown worse"; "settled" for screens; "supported" citing a screen whose reading did not apply. Unmarked descriptions stated as findings, and readings attributed to the wrong arm or quoted without their docstring's qualifier, in some fifteen places. The title still named the general problem. Every item is addressed, and each later version was checked again (`rev9/second_pass.md` to `fifth_pass.md`, with `resolution_*.md`): each pass found the previous version's own slips, nearly all in the text added since the pass before (among them a miscount of R's labels, the uncommitted Phase 4 reading, a one-pair power stated the wrong way round, a pre-amendment label quoted for D1, a pair of discordant counts attached to the wrong arms in the abstract, and a run count for S75 the records do not carry), corrected in turn; the fifth pass found every number of every pre-registered claim reproducing, and withdrew one of its own earlier items (the test-file check did precede every run of `test_delta_recipe`). Appendix B gained the six entries the check found missing. The sixth pass left two items, the draft contradicting itself on the state of L's half of `test_delta_recipe` (six statements on five lines) and the scope of R's 44 unstated details; the seventh version fixed both and the seventh pass passed it.

After Revision 9. The referee checked what this revision adds (`round6_A3.md`): every pre-registered number of `test_delta_recipe`'s L half and pooled block reproduces (66 rows: 55 match, 7 partial, 3 not record-checkable and one disagreement, a sentence in L's RESULT block saying the first start had printed its projection when it had printed only the heading, now corrected; the pooled D1 and D4 pairs, the D2 no-room count and D4's p recomputed independently), and Amendment 2's statement of what had been seen when it was committed is confirmed against X's run log to the minute; R's Phase 5 (38 rows) and I's GPU run (65 rows) reproduce, with the qualifications quoted in Sections 14 and 5. It reviewed three of the four specifications the sessions drafted, and none is ready to run as written. Session G's register test (`spec_review_register_draft.md`): the outcome has a definition but no named function tied to G's recorded verdicts; the model is written fresh, so L never asserts that it runs G's model; a rate claim at 18/20 supports 0.70, not "reliable", and "reliable on one machine" fires 44% of the time at a shared true rate of 0.90; the readings use "discovered" for an outcome the report reserves that name for elsewhere and credit the register for a contrast whose comparator lacks it; validity on two nudged seeds leaves a machine untested a tenth of the time; and the seed, pairing, resume and reference CHECKs are missing. Session H's two-stream key-term

test (spec_review_two_keyterm_draft.md): its structure is sound, but the baseline is the arm that discovered 69/80 in test_window_gate, so its primary claim is SHOWN with probability 0.15–0.27 at the main line's rates, and in a third of outcomes cannot be shown at all; "not shown" would mostly mean "no power", the S61 pattern again. Session I's S75b (spec_review_s75b_draft.md): Section 19. Session E's key-load draft was committed after those reviews and then failed its own validity screen (Section 10); it has not been reviewed. The project's next pre-registered test therefore has a specification to revise before it has a run.

What it found in Revision 10 as merged. The referee's pass over this revision (rev10/referee_pass.md, with check_rev10_A, _FG and _HE, 228 rows) found every number of every pre-registered claim and every count, pair, p-value and reading of the fifth round's screens to reproduce, every screen's readings committed before its first record, and the PDF to show the tex; and nine statements false in sixteen places, none a number of a claim: that the referee had checked this revision's additions (it had checked three of them); that every number had been recomputed by the checking agent (it recomputed test_delta_recipe, the GPU run and H's screens and read the other screens' reports); that the agent's independence from the author is shown (git shows the same session for both and cannot order the pass files before the third version); a count of 29 gated S75 runs after the tenth seed made it 30; "screened once" for the all-position trigger on three lines after S87a screened it again; the timing of the learned write strength's collapse, stated as 1200 updates where the records give 3600 in one arm and 1200–6000 in the other; the self-distance penalty described as a distance from uniform (it is from the sequence's own mean gate); provenance rows for E, F, G and H that stopped before the fifth round; and an index row saying the three drafted specifications were not ready, where the referee had reviewed three of four. It also found that the two passes by the checking agent had missed five of the nine, flagged two more without verifying they were taken, and could not see the two that came in the merged version, which no pass read; their numbers were right wherever they checked. Each statement is corrected in Revision 10.1, with the looser ones the pass listed (the author's account of L's reboot stated as such and the S75b stage's length restated from the specification's run times; the dose screen's ceiling; the key-load validity probabilities for fresh seeds; "the slow start hurt"; E's S69 distinguished from F's; the limits list updated for S87 and S88b; Revision 9's referents named). The referee's check of 10.1 found the nine corrected in all sixteen places and every new number reproducing, and listed about a dozen residues (two carried referents, two provenance rows for I and R that also stopped short, the pass commit cited at its first version, an enumeration of eight for nine, a statement that the referee reads every draft before its merge, which Revisions 10 and 10.1 contradicted); Revision 10.2 takes them and nothing else, and was passed by the referee before its merge.

After Revision 10.2: rounds 6 and 7. The referee reviewed each of the two rounds' screens before its learned arms where the branch gave it the time (screen_review_s89_F/G/H, s89bc_H, s90_F, s90_G, s92_H; S89H, S91 and S91b ran unreviewed) and checked every report but the last against its records (check_F_report9, _10; check_G_report8 to _11; check_H_report10, _11, check_H_s92_phase1), regenerating each report's tables from the stores with the session's own functions and recomputing the counts independently. The numbers behind the readings were right throughout: every count, pair, p-value, interval, transition and cap behind a reading reproduces in the nine check files, every reading is its committed rule's mechanical output, and the pre-registration order is clean on every screen; beside them the referee found a dozen other numbers wrong in session G's three reports (a restart count, a run count, a CHECK-row count, two descriptive ranges and the 48,000 budget), none a count or a reading. What it found was in the names and the process.

Five readings' names outrun their content: S89's "the repeat hinge replaces the key hinge" on delta memory, where the register alone binds 16/20 and neither hinge is shown needed over it; its "the frequency hinge needs frequent keys" on `-pool`, where that arm touches no key position and is a hinge on the stream token; "the labelled hinge itself fails here" on `-allpool`, uninformative about the hinge where a fixed type map is capped; S89c's "the channel is the limit", which asserts a cause the screen did not test; and S91b's "the channels do not suffice", a learning negative whose natural reading as a capacity claim the screen's own ceiling contradicts (each is quoted here with the referee's reading beside it). One budget defect: S89H's `-allpool` arms ran 24,000 updates where the report said 48,000, the harness never passing the budget to the child, corrected by session G with an erratum and an assert on each payload's budget. The process: session F's single-channel screen ran past the referee's hold because the queue had no stop (the review landed fifteen minutes before the stage that queued it); session H's S89 review landed inside the 58 seconds in which its learned arms were launched, and none of its eight fixes was taken before the runs; H's S92 fixes were applied after its second phase's first record; several of the sessions' pre-run fixes reached the text and the report path only, which the referee lists. Each of these is disclosed in the session's report. The referee also judged the register specification's revision 2 "ready for X's adoption after the fixes at the end", ten of them, all text (`spec_review_register_v3.md`). Its last file is `check_G_report11.md` (23 October). Session H's report 12 (S92's second phase), the two addenda to F's report 10 (the hold disclosure and a four-run pilot, written after its check) and this revision were not checked by it: the revision was checked by a separate checking agent run from the author's session, whose files git cannot show to be independent (the same session trailer, as in Revision 10), against the sessions' records and, for every number quoted here from rounds 6 and 7 that a referee check covers, against that check; its passes are `docs/review_2026-10/rev11/`. The round-6 prompts the author's session wrote, and its instructions of 20 October, carried four errors the referee caught before or as the runs started, listed in Section 16.3.

16 Retrospective

16.1 Revision 8's claims

"Eight streams bind without labels or restarts" (the main result). Stands, and was replicated, on our assessment, in session R: 17/20 from the text alone ("partially replicated" by R's bar), then 18/20 with the split's probe and key positions taken from our code, 35/40 pooled ("consistent with the report"; Section 14). Qualified: without *stream* labels; the split reads key positions; "one channel per stream" by largest mass, the sets disjoint.

"The copy, not the reset." Pre-registered and shown, pooled over two machines with disjoint seeds (C1 12 vs 0, $p = 0.00024$; C2 holds, 0 vs 2) and on each machine; the reading applies. The first draft's "the reset adds nothing" was not shown by the looks it cited; session H's S61 holds it as a one-pair bound on ten seeds (the copy with noise 9/10, the exact copy 9/10, the full split 9/10), and the pre-registered version of that comparison was not run.

"The Hebbian write stays on the main line." Withdrawn. With the write strength fixed, the delta write is not shown worse than the Hebbian one at two, four and eight streams on screens and binds sooner at two and eight (Section 11); the stall Revision 8 reported came from a screen with a learned write strength (and a different split and seeds; the attribution is post hoc). The pre-registered test is complete on both machines (Section 11): pooled over 40 pairs with disjoint seeds the delta recipe binds 35/40 against the Hebbian recipe's 35/40 ($d = 0$, "delta not shown

worse by more than 2 pairs"), the split on delta channels reads "no room" (38/40 without a trigger) and on Hebbian channels "helps" (19 vs 1, $p = 2 \times 10^{-5}$), and delta binds sooner on 24 of the 30 seeds both bind. A learned write strength, screened afterwards, collapses to about zero except at some value positions and one context position and binds 7/10 against the fixed one's 10/10 (no reading applies).

"The partition's claim is about the number of contexts." Supported, pooled and on each machine, by the pre-registered C3 (0/20 against the recipe's 18/20, 18 vs 0); session F's S68 had 0/10 at eight streams too (2/10 at four), but its own reading of that name did not apply.

"If the stream-tagged keys at the third layer hold up, the context is reaching depth." They did not (1 of 16 bound runs; Section 11); on the randomised header layout the context reaches depth in the delta solutions that bind without routing, and on the grouped two-stream layout it reaches depth at key positions in routed runs as well (Section 11).

"The next steps are a probe, a register and a per-layer residual gate." Done. The probe found the cue absent from the Hebbian stack; the residual gate alone bound nothing on Hebbian memory and routed nothing on delta; the register carries the cue once it also gates the first layer, which the first design did not do; that this design choice is what sank the Hebbian register is our interpretation, across two tasks and two gate inputs (Section 12).

"Scale-free" at four streams (batch 19). Stands as a screen; the referee notes that its one-pair rule on ten seeds reads "scale-free" 39% of the time when the larger model's rate is 0.7 against 0.9, and that "depth" is applications of one shared layer. Eight streams carry to $D = 128$ and two layers on a ten-seed screen (S66), whose one-pair rule misses a drop from 0.8 to 0.6 about two times in five, and the oracle binds sixteen keys per stream at $N = 256$ (S67, two seeds) where the learned recipe binds 0/10 against 4/10 at $D = 128$.

16.2 Revision 7's claims

"At eight streams the gate forgets the context" (subtitle). Superseded. True of the recurrent gate; the window gate carries the context at every write position by construction and binds 38/40.

Revision 7's recipe (slow memory and a hinge) binds without restarts at two streams and at four with sixteen channels. Stands, and is replaced by a recipe without the hinge, which is within eight points of it at two streams ($[-0.079, +0.121]$), beats its early-window form at four (G1) and beats it at eight (G2).

"The gate needs only one token of memory" (Section 11 of Revision 7). Corrected. One at the read, two at the write; the write-position decoders were not measured in Revision 7's screens S38–S41 (batch 16, S47, measured them).

"Under Muon the recipe binds four streams sooner." Not shown on disjoint seeds pooled (12 vs 8, $p = 0.25$), and the machines disagreed: confirmed on X's fresh seeds (7 vs 1), reversed on L's (5 vs 7), where Revision 7's result had been shown. Revision 8's first draft called it a seed effect, which the data do not establish; the referee's heterogeneity test between the machines ($p = 0.070$) is

the more interesting figure, and a seed-block swap between X and L would separate processor from seeds.

"A cap on the gate's recurrence is being screened." Resolved: not. No capped arm bound (0/10, 0/10, 0/10 and 0/5); the cap acted from update 1.

The row copy breaks merges (Section 10 of Revision 7). Supported with the right outcome and a reset-only control in four exploratory looks and by the pre-registered C1 (the copy with its reset against the reset alone: 12 vs 0 pooled, 7 vs 0 on X and 5 vs 0 on L); that the runs it rescues are merges is printed in their failure classes, not claimed.

16.3 Errors made during Phase VI

Statements that were false when committed. Listed in Section 15. The common cause was writing from a summary of the branches rather than from the branches: the premise test and the copy-only screen had both been pushed before the draft was committed, and neither was checked. The fact-check that preceded the draft was done by the author of the draft. Revision 9's first draft repeated the failure in kind: the referee's check of it found nine statements false against records already pushed, among them that the records do not store the probe's reading, that session G was still screening devices whose result was fifteen minutes old, that a screen was running that had not started, that a replication rule had been corrected that had not, and that the recomputation found "all" numbers reproducing; they are listed in Section 15 and corrected here. The cause was the same, and the remedy is the one the referee applied: every statement about a branch checked against that branch at its head, by a script, before the commit.

Predictions that the data overturned. We predicted that a single delta channel could not bind conflicting streams (it binds the two-stream header layout 8/10); that Gumbel noise on the gate's logits could replace the split (on both gates it collapsed routing; on the write gate it bound 0/10 at eight streams); that a balance loss would attack merges (it changed the key- and value-position maps instead); that a learned forget gate would widen the gap between the oracle and one channel (it shrank it, on the eight-key header layout); that the register at layers 2–3 would carry the cue on Hebbian memory (it needed layer 1, on our reading of S71); that the delta recipe would stay behind at eight streams (it keeps them 9/10 against 10/10 with the write strength fixed); that a single Hebbian channel's stream tag, if any, would be linearly readable (it is not); that a dense loss would need the partition at two sources (one channel self-tags); that a gate held slow at the start would let the register's write win the race against the key split (it binds 0/20; on our reading it slows the write too) and would prevent the two-stream key split (it has four key failures of its own and 14/20 against 15/20; its three onsets after update 0 come later than the baseline's seven, on two shared seeds); and, in the audit, that the window gate with slow memory would reach $\geq 36/40$ on seeds 160–199 with no key failures (it reached 31/40 there, and 33 and 36 of 40 on the main test's seeds, with key failures reduced).

A design choice that cost a round. Revision 8's register specification kept the first layer on the window gate on the reasoning that its residual input is the embedding and carries no cue; but the register is built from embeddings and could have fed the first layer's gate, and on Hebbian memory the first layer is the one whose routing matters. One screen (S71) settled it; it could have been part of the first round.

A replication bar that could not discriminate. Session R's "$\geq 18/20$" fails a true 0.90 recipe one time in three, and the first version of its Phase 4 reading, written by us, pooled the seeds already seen and would have detected only rates near 0.70 or below, and 0.70 itself one time in nine. The referee's review corrected both in principle; an amended Phase 4 reading was written after it but existed in no commit until `db22857`, after the referee's second pass had found no record of it, and R's branch carries the first rule. Section 17 gives the rule a replication should use.

A probe that can be wrong, and is unbalanced. The split's 64-sequence probe can read a plateau as bound (R's seed 914) and weights the streams unequally, in the same way for every seed (Section 6). Both could have been read from the project's own records, which store the probe's reading at every check beside the evaluation's; nobody read the two against each other until the referee did (6 of 353 checks; Section 6).

A distant-cue task that exceeded its oracle. Session F's first randomised header layout did not bind under the perfect gate within its budget; the lighter version with four keys per stream in two blocks did, and is the task of Section 12.

A classifier at its own threshold. Three batch-18 runs sit within 10^{-3} of $\eta^2 = 0.5$ by key and were labelled STREAM-PARTIAL; the key-first classifier relabels the one at or above 0.5 KEY (Section 3). The reading that depended on them is withdrawn.

Records that were not L's. A commit of "machine L's test results" held copies of X's files for 20 tests; the real files were recovered from the laptop and one test rerun (Section 15).

Branch discipline. Session I committed its first files to the main line instead of its branch; they were moved, byte-identical, and the main line cleaned. Two sessions shifted into the same seed block (1300–1359) after collisions with earlier blocks; the next round's blocks were checked against every branch before assignment.

Attribution of a number. An earlier working note put Pathway's 97.4% Sudoku figure beside TRM's 87.4% as if on one protocol; the figure is from Pathway's blog, on internal data, and the protocols differ.

Statements corrected after Revision 9. L's RESULT block for `test_delta_recipe` said its lost first start had printed its projection (it printed the heading; the referee's check), and `results/README.md` gave the commit of L's file as the test's rather than the one its records carry. Each is corrected where it stands (`76851eb`).

Errors made in rounds 6 and 7. The round-6 prompts the author's session wrote to the sessions, and its instructions of 20 October to session H (relayed by the author and not committed; S89c's docstring cites "the user's plan"), carried four errors, each caught by the referee: they described H's pooled-key screen as removing the key positions, when the pool makes the key types rare and the keys stay at $3j + 1$ (the caveat now printed with every reading); they asked for a repeat-set trigger as a second finding, when on that layout the repeat set is 96% of positions and the trigger is the all-position trigger; they named S89c's negative reading "the channel is the limit", a cause no arm tested, and set its first check from S89's curves; and they read S89's ALLPOOL null as the hinge's failure, when a fixed context-type map can route at most 0.533 of its sequences at $k = 2$, so the null

was confounded with the cap until S91b removed it. Session G's harness never passed a screen's budget to its child, so S89H's `-allpool` arms ran 24,000 updates where the docstring fixed 48,000 (every record carries 24,000; the perfect gate bound within it, so the null stands at that budget); session F's write-order statistic compared a context token's type with a stream index and was invalid on `-allpool` (withdrawn where used, no reading affected); session H's push after each saved run used `git pull --rebase`, which rewrote a running driver's log (the store was intact; the driver no longer pulls), and a gate-lookup defect in S89b would have left its learned arms unqueued had the oracle passed (it did not). The author's two GPU clones had diverged from session I's branch with local commits of old code, and were reset to it before the CUDA CHECKs; one benchmark was rerun on the author's inference that it had run on old code, which the pushed record disproved (both are on the branch, one archived). None of these changed a count or a reading; each is disclosed where it happened, except the GPU-clone episode, which is recorded here only.

Process. Container restarts cost in-flight runs on X (the test's first start), on L (`test_delta_recipe`'s first start, to a reboot that the author attributes to the OOM killer, with a GPU job beside it), on F, G and H (while sessions were idle with only detached processes running) and on E in several batches; a detached launcher with a watcher that resumes after a restart (`longrun.py`) now runs every main-line test, and every resumed segment begins by reproducing a recorded run bit for bit. Batch 18's Muon reference did not reproduce across hosts and was rerun fresh, as the rules require. In rounds 6 and 7 the sessions' containers restarted five times during G's S89 (G's report says four; the log has five, the referee's count), twice during H's S89c and once in each phase of H's S92; G's resumes re-ran every CHECK and H's the bit-identical reproduction check, skipping the CHECKs on the code-SHA match; every resume continued from the cached runs, re-ran the runs in flight from scratch, and no saved run changed.

17 Methodological findings

Revisions 5–7 recorded sixteen lessons and Revision 8 five; Revision 9 added seven, most of them learned from being reviewed, Revision 10 two, and Revision 11 four.

Disjoint seeds make the pooled test a test. From the Muon-recipe test on, each machine has its own seeds and the pooled McNemar is the primary claim. The window-gate test's G1 is the case this was for: not shown on X alone, shown on L and pooled.

Audit the records before the next screen. The window gate had been screened, had won, and had been dropped for a reason unrelated to the obstacle at hand; one reading of the records found it. A fixed prediction before the rerun made the audit falsifiable.

Control for the bundled action. A split that copies and resets needed a reset-only arm and a copy-only arm; so does every intervention with two parts.

Score routing at the write positions. A stream's channel at key positions can differ from its channel at value positions in a bound run (session H: 34 of the balance-loss arm's 36 bound-routed runs, and two to five of the 37–39 bound-routed runs in each of S58's other full arms); the writes are at the values.

Borrowed devices need the model's read path. Gumbel noise is the device of a router whose reads are dense; on our routed read it collapsed routing. A balance loss balances whatever is cheapest to balance.

Have the draft checked by someone who did not write it. The first draft's fact-check was done by its author and missed seven false statements, two of them about results that were already on the branches. An adversarial referee with the records found them in a day, recomputed the numbers of the tables, and found the numbers right; the text was the problem. The same happened to Revision 9's first draft, checked by the same referee against the branches at their heads: the numbers right, nine statements false; and to Revision 10, whose draft a separate checking agent had passed twice and whose merged text the referee then found to hold nine false statements of its own, none a number (Section 15). A checking agent that recomputes the numbers is not a referee: it did not read the merged text, did not verify that its own items had been taken, and skipped the pre-registration, seed and provenance checks. The referee read every main-line specification before its first run; Revisions 10 and 10.1 were merged before it read them and corrected after, and Revision 10.2 was merged only after the referee's pass, with a statement about a branch checked against that branch by a script before the commit. Revision 11, the final one, was written after the referee session's last file and checked by a checking agent instead, which the report states where it matters (Section 15); the rule stands, and this revision is the exception to it.

Fix the name of the outcome, not only the rule. A reading named "discovered" on a screen that also prints an outcome named DISCOVERED came out "does not apply" under its rule and would have applied under the outcome of the same name (4 vs 0 against 5 vs 0). Nothing was misread, but the next reader could have. A reading's outcome should be the only outcome that bears its name.

Report descriptions as descriptions. The sessions' reports, and ours, state mechanisms beside readings: that a learned write strength caused a stall, that the flat start wastes splits, that a write at the cue is what separates discovering runs. The referee found every such sentence to lack a pre-fixed rule, and some to rest on a count that no classification reproduces. They are kept, marked, and none is a result.

A replication needs a calibrated bar. "Replicated" at $\geq 18/20$ fails a true 0.90 recipe one time in three; an interval-overlap rule on pooled seeds detects a true rate of 0.70 about one time in nine and rarely any rate above 0.65. The rule for a replication of a rate r_0 on n fresh seeds is a one-sided exact test against r_0 with its size and its power at the alternative that matters stated in advance ($x \leq 46/52$ against 0.95 has size 0.045 and power 0.81 at 0.85), beside a Fisher comparison with the original count and a paired test of the mechanism's arms on the same seeds; isolation by construction, in a container that never holds the repository; records in a format the original's outcome code can score.

Read what the trigger saw. The records keep every check's probe reading beside the evaluation's, and nobody read the two against each other, so a probe that read a plateau as bound, and a probe that under-weights some streams, were found by an outsider. A test should print them side by side, with the count of checks at which the probe read ≥ 0.95 while the held-out accuracy was below it, as `test_delta_recipe` prints.

Branches and seeds are part of the protocol. A session that pushes to the wrong branch, a seed block that collides with another session's, and a commit of "L's results" that holds X's files are all provenance errors that cost nothing to prevent and hours to repair; each happened once.

Screen the validity check before drafting the test. The key-load draft rested on a perfect gate that had bound one of its two seeds; screened on ten, it binds four under the recorded recipe and none under the other, and the draft has no validity check at its budget (batch 21). A specification's oracle is a claim about the oracle, and ten seeds of it cost less than a review.

Pool before reading the machines. On `test_delta_recipe`'s primary comparison X read $d = -3$ and L $d = +3$: either half alone would have been reported as a three-pair lead for one write rule. Disjoint seeds and a pooled primary claim turned two leads into a zero, which is what the design is for, and a per-machine result quoted before the pool is a draw, not a finding.

Run the oracle at the budget before the learned arms, at every size. Batch 21's lesson, generalised: session H's S89b queued its learned arms only after the delta perfect gate had bound both validity seeds, and it bound one, so nothing ran on a configuration whose oracle was unreliable; S92 screened the oracles at four pool sizes first and named the largest pool at which both were reliable before any learned arm ran. Session F's pilots did the same for the pool tasks and found the Hebbian oracle failing on both, which sent round 6's learned arms to the memory on which the question could be asked. The lesson's edge is the budget: H's S89 ran its oracle first and it passed within the budget but late (medians about 2.5 times S87a's at four fixed keys), and the gate had no branch for "late", so the learned arms ran on a configuration whose oracle was slow and spent their budget on slow climbs; a gate on the oracle's transition and not only on its count is the form S92 then used.

State the ceiling the arm is read against. A null on a task where the gate under test cannot express the perfect gate's routing is not a null about the gate: S89's ALLPOOL null was confounded with a 0.533 cap on any fixed type→channel map at $k = 2$ until the cap was computed (the referee, 19 October; stated by session F in its module and tabulated over D and k in its report 10), printed with the reading and removed by giving the gate a channel per type (S91b). The two ceilings, a handed per-sequence index and a handed channel per type, should be run beside every learned arm whose task has a relative structure, and the cap stated in the docstring before the runs.

A rule's name should not outrun its content. "Replaces the key hinge" on a task where the register alone binds 16/20, "the channel is the limit" from a screen that varied the schedule, and "the channels do not suffice" beside a ceiling that shows they do, were each the committed rule's mechanical output and each true as a label (three of the five names the referee flagged); a reader of the name alone would have taken away a claim the records do not support. A reading whose name asserts a cause needs an arm that tests that cause; a reading on a hinge needs the register-alone comparison printed beside it (the referee's reading 2b); and a negative reading should say what it excludes (a true rate above 0.26 at 0/10) rather than name a mechanism.

A queue needs a stop the referee can pull. Four screens of rounds 6 and 7 ran, in whole or in part, past a review that asked them to wait: session F's single-channel screen (the review landed fifteen minutes before the stage that queued it; the queue had no stop and the session, by its own account, did not fetch the review branch during the run), session H's S89 (the review landed inside

the 58 seconds in which the learned arms were launched), its S89c (the review asked for its reading names to be fixed before the first record, 28 minutes before it, and none was) and its S92 (the fixes applied after the second phase's first record); and S89H, S91 and S91b ran with no review at all. None changed a reading, and each is disclosed, but a pre-run review is worth nothing if the run does not wait for it: the learned arms should be gated on a file the referee commits, as session H's S89b gated them on its oracle, and the sessions should fetch the review branch before each stage.

18 Limitations

Scope of the main claim. The result is that a gate trained only on the task loss finds a partition of the memory on the *grouped layout* of a synthetic binding task, where every write's context cue is within three tokens, at two, four and eight streams, with a split aimed by gate mass at the task's key positions. The title and subtitle say so. "Context-conditional binding" in general, natural data and the mechanism's role in a language model are not shown; the distant-cue task has a solution without stream labels on screens (20/20 with a hinge that reads key identities during the first 2400 updates) and no pre-registered test of it was run; its specification is ready (Section 12).

The recipe needs task structure. The split reads the key positions, and the hinge's key term, which on screens prevents the key split at two streams and for the register at a distance, reads key positions and key identities, and session G's S83 found that its KL terms reading positions only, or nothing, fail (1/20, 0/20) by clamping the gate, a weakness of the form its specification had allowed for (if not this one); a trigger that reads all positions was screened twice (session H's S86 and S87a): it keeps binding within one pair of the key-position rule on each screen (8/10 against 9/10; 16/20 against 17/20; 24/30 against 26/30 pooled), and of its three mistargets in 63 firings two cost their run. The main line's records had said what it would have done: every check of every split run stores the channel pair an all-position mass would have chosen beside the key-position pair, and at the 126 firings of the 60 recorded split runs at eight streams (`window_gate` X and L, `split_copy` X and L) the all-position pair was a labelled target, a channel holding two or more streams and an empty one, at 115 (46 of 47, 30 of 38, 21 of 22 and 18 of 19), the key-position pair at all 126; the two pairs coincide at 54. That is our count, not a reading, and a run that split differently would have gone differently; S86 then found 1 mistarget in 21 firings, consistent with that rate (11 in 126). None of the 126 fired on a map that was already one-to-one (session H's count), so the guard session I added to its split at $k = S$ (Section 19) has nothing to do at $k = 16$. A split that reads no task structure is therefore possible at a small cost in aim; a language model has no marked keys, and the hinge's analogue, which S83's one position-only term could not replace, is untested.

The model. Three layers with shared weights (two to six screened), one head, $d = 32$ (to 128 screened), $N = 256$ (to 1024 screened), sequences of at most 99 tokens on the main line and 480 in session I's pilot, a fixed memory half-life of about 14 tokens on the main line, which is the horizon of everything the memory can carry; a language model's would need to be thousands, and the one device screened against it, a learned forget gate, was screened on each write at one length: it raised one delta channel's binding (9/10 and 8/10 against 3/10) and not a Hebbian one's, and its pre-fixed reading on the horizon read "it does not" (Section 11).

Two streams. The hardest configuration relative to its size; every arm is at 65–69/80, the one repair device that works at eight streams did not work here (S78, "neither device"), and the prevention that works on a screen (the key term, 20/20) reads key identities.

Screens. Exploratory sessions use 10–40 runs per arm and lenient rules; their readings are labelled, their descriptions are descriptions, and nothing from them is a claim until a main-line test repeats it. Several screens in this revision have both arms at the ceiling and can detect only large differences. Rounds 6 and 7 are ten- and twenty-seed screens on tasks built during the round; five of their readings carry names the referee found to outrun their content, and are quoted here with the referee's reading beside them (Section 15).

Replication. One, from the text, by one implementer, on twenty seeds, isolated by self-report; it agrees in direction and size and is one run short of its own bar. Its fifth phase reproduces `test_split_copy`'s three counts on fresh seeds, the delta arm from the specification alone and the other two with its earlier recipe, by a rule that separates little at twenty seeds. The headline's arms on a GPU, by our own code, are a third machine class and not an independent implementation.

What was not done. The project ended with two tests specified and not run: the register test (Section 12), which would have been the first pre-registered test of a distant cue, and S75b, the dense-loss task at four sources in a configuration whose oracle can reach its bar (Section 19), whose pilot was never started. Session H's report 12 was not checked by the referee, and neither was this revision. The frontier rounds 6 and 7 named, contexts without fixed identity, has, at sixteen channels, a learning negative on it at one budget, and no device that crosses it. The two-stream key-term test (session H's draft) is underpowered against its baseline and the key-load test (session E's) has no validity check at its budget; neither was revised. BDH-CQ and Triadic Linear Attention were not read in full, and no external model was trained on the task.

19 Distance to a language model

What Phase VI adds to the case. The gate is a convolution: parallel, cheap, the form every modern linear-attention model already uses. The recipe is two learning-rate groups and a plateau rule. It finds an eight-way partition without stream labels, its constants read "scale-free" and "carries" by one-pair rules on ten-seed screens, to four times the width and to four applications of the layer at four streams and to $D = 128$ and two layers at eight, and its write rule can be the delta rule that the linear-attention literature already uses.

A dense loss (session I). Revision 8 conjectured that an end-of-sequence loss gives too little pressure to discover a distant cue, and that language, with a loss at every token, supplies more. Session I built a task to ask it: S sources, each with its own table of three successors per word drawn fresh for every sequence (so the sets must be learned in context), interleaved in blocks of random length and random order with a source token at each block's start, and a next-token loss at every word with a known same-source predecessor (the task family of [19, 20], cited for it; neither paper has been read in full). Its pilot ran the perfect gate (one channel per source), one channel and a single-source control at two sources, 12,000 updates, four seeds, and could not make the task usable by its own rule, because *one channel learns to carry the source*: in three of four runs of the shorter-block configuration a step transition raised the set accuracy by 0.09–0.22 and took a linear probe of the source, from the residual entering layer 3, from 0.54–0.58 to 0.96–0.98, closing 44–83% of each seed's gap to the perfect gate with no gate and no labels; the perfect gate's own stack never carried the source, having no need to. The sparse-loss stacks of Section 12 never did this. So the dense loss does put pressure on the stack to carry the cue, which is the conjecture's first direct evidence and is descriptive; whether a gate that reads such a stack then partitions the memory,

and whether four sources are too many for one channel to tag, are the questions, and four sources need sequences of about 770 tokens, which is a GPU's job. Session I's GPU package (its branch; a device-agnostic runner for the project's models and tasks with a CPU check against a recorded run and a CUDA check at a stated tolerance) passed its CUDA check on the user's GTX 1660 SUPER, and the screen at four sources (S75: 32 runs, about 16 hours of training on that card, the driver and every rule committed before the first run) then ran on it: the pilot's task per source at $S = 4$ and $L = 768$, 24,000 updates, the perfect gate on two seeds as the validity condition (both must end at a set accuracy of at least 0.9), one channel, the window gate at width 16 (the longest block plus two) with slow memory and the split on all word positions, and session G's register gate at all three layers, ten seeds each.

Four sources (S75). *The screen is untested by its own rule*: the perfect gate ended at 0.880 and 0.892 against a bound of 0.927. Session I's pre-run note, committed after the perfect-gate and one-channel runs and before any learned-arm record had been pushed (whether learned-arm runs had started on the card by then is not recorded), declined to amend the bar, the budget or the split threshold, each candidate rule being one chosen knowing those two numbers, and fixed the follow-up instead: fresh seeds from 840, a configuration changed so that 0.9 is reachable rather than a bar moved (its example, 32 blocks per source at $L = 1536$, has a bound of 0.964), a bar derived only from perfect-gate and one-channel quantities, and a split that does not fire on a one-to-one map. What the learned arms did is therefore a description. Neither routed on any seed: η^2 by source was below 0.003 at every evaluation of every gate layer in all twenty runs, no map was one-to-one at any evaluation, and both ended where one channel ends (0.529–0.536, and 0.535–0.540 on nine seeds with one at 0.588, against 0.534–0.540 on nine seeds of one channel with one at 0.595, and 0.880–0.892 for the perfect gate). The split fired its three permitted times in every window-gate run, at the first three checks at which the trigger allowed a fire (7200, 12,000 and 16,800 updates) in nine of ten, every run sitting on a plateau far below its threshold (0.88, set from the pilot's perfect gate; the trigger's probe read 0.518–0.542 at the fires), and each fire copied onto another channel a gate row that was the same for every source (the gates were source-blind rather than collapsed: the mass over the four channels was uneven, 0.05–0.38 at the fires, and identical across sources to within 0.024; margin at most 0.04); session I's note had declared before the runs that a split on a routed run overwrites a live channel, and that hazard did not arise, no run having routed. Nor did one channel learn to carry the source, as it had at two: on nine of ten seeds its accuracy rose by at most 0.033 after 4800 updates and a probe of the source from the residual stayed at chance, and on the tenth, as on one register seed, a late rise (0.09 and 0.08 after 4800) took the probe no higher than 0.35 (0.29 and 0.28 at the end), against 0.96–0.98 at two sources. The residual did hold the source at the first evaluation of every gated run (the probe from the residual entering layer 2 read 0.35–0.61 at 1200 updates, chance in the perfect-gate and one-channel runs) and all but one of the 30 (a register run, at 0.29) had lost it by 3600. Session I's audit of the perfect gate's shortfall puts half of it at a block's first word, where the source's last word must be recalled across the gap since its previous block, which the fixed decay fades (its decay-faded ideal learner scores 0.680 at four sources against 0.840 at two): the memory horizon of Section 11, measured on this task. The window gate without the split (an extended arm, printed and never read), the pairing by seed the note fixed to separate "the gate does not route at four sources" from "the split undid routing", matched the split arm seed for seed on all ten: 0.530–0.536 against 0.529–0.536, η^2 below 0.001 at every evaluation, no one-to-one map at any; the window gate does not route at four sources on this task, split or not. The follow-up the note fixed, S75b, is specified and reviewed (the referee found its provenance claim to hold by the commit graph, two design changes made after the learned-arm

records were visible to be disclosed rather than blind, and four pilot outcomes its rules did not name; the specification and its failure rules were revised through further review passes on session I's branch, the last with a mutation pass of 48 variants of the failure rules, all caught by its CHECKs), its final driver (`3cef609`, code SHA `ee04da11a164`) checked on the CPU; the referee's review points were then taken item by item in the specification's Appendix C (22 October, `561f5bf` to `c78d5d2`), and both cards passed the CUDA CHECK and the benchmark on that driver on 22–23 October (the GTX 1660 SUPER, whose server had left the project on 19 October and returned on 22 October, `a7e7e12` and `b06a81a`; the laptop's RTX 3070, `fb3066c` and `eb3e819`; every arm usable on both cards, the register arm in its scan mode by the specification's own rule), and session I's pre-run note (23 October, `005a59a`) states what had been seen before the pilot, S75's learned-arm records among it, and that no design constant was chosen from it. The pilot, stage 1 on the 1660 (about three to four hours), was never run: the project concluded there, and `STATUS.md` carries the commands. Session I corrected its pre-run note on 12 October: the note (committed at 00:46 UTC) said no window-gate run preceded it, and the card's timeline puts up to three before it, which the records cannot fix (the referee: between none and three); no learned-arm record was in git until `b649751` at 13:53 UTC, and session I states that the note's decisions were made blind. The note itself was not edited; its correction is in report 2.

What stands in the way, in order:

1. *Discovery of a distant cue without task structure.* The architecture exists and, with the key hinge, is found 20/20 (Section 12); without it the write at the cue is found on a fifth of seeds in S72 and S73 and on 2 of 20 fresh seeds in S82, and a key split, formed in the records before any write at the cue, ends fourteen of the sixteen others on each memory. The hinge reads key identities, and the one label-free hinge found so far, on a frequency table of token ids, discovers 17/20 on a task where that table selects the keys and the contexts (S87); a dense loss may change the race without it, and at four sources on the one GPU screen, untested by its rule, neither learned gate routed and one channel did not carry the source either. Rounds 6 and 7 moved the line and then found its end: on pooled keys a hinge that reads which token types repeat within the sequence does the labelled hinge's work where the hinge is needed (19/20 against 18/20 on Hebbian memory with the convolution) and falls short on the original task (17/20 against 20/20); and when the context tokens themselves have no fixed identity, no learned gate routes them, at two channels or sixteen, on either memory, while a handed index or a handed channel per type binds every seed (Section 12). That is the obstacle as the project leaves it.

2. *The split's nuisance variable.* The key positions come from the task; a trigger on all positions was screened twice (S86, S87a) and kept binding within one pair on each. At eight streams with the keys drawn from 32 types the key-position rule itself binds 1/10 with a reliable oracle, so at rare key types the Hebbian recipe fails before its nuisance variable matters; at eight key types the delta recipe with the split carries 10/10 (Section 10).

3. *Memory horizon.* A fixed decay; a learned forget gate raises one delta channel's binding at a fixed length and not a Hebbian one's, its reading on the horizon itself read "it does not" and the direct horizon screen (S88b) is untested by its rule, with its failures stream confusions at 0.5 rather than faded memory; the delta write is now a candidate for the main line, and on the dense-loss task at four sources half of the perfect gate's shortfall falls at the block's first word, across the gap the decay fades. The delta memory has a limit of its own: on the eight-stream grouped layout its perfect gate is unreliable from sixteen key types at 86,400 updates, where

the Hebbian write with the convolution is not, and a Hebbian channel with its routing given bound none of eight pilot runs on pooled keys without the convolution (Sections 10, 11).

4. *Baselines.* One channel of either write rule is run at two, four and eight streams; Gated DeltaNet's write is the delta rule; Mixture-of-Memories' balance loss and Raven's noise were run; a residual-stream router was run. The comparison that matters is whether their routers discover *contexts* rather than token types, which none of their papers tests, and which the register result now makes askable.

A staged path, as it stood. (i) On CPUs: the register test on the main line (the memory-rule test is done); the key-split devices; eight streams at the larger widths (screened once in S66) and at larger key pools (screened once in S92). (ii) On the user's GPUs, with session I's package: the dense-loss task at four sources in a configuration where the perfect gate reaches its bar (S75b, prepared through its pre-run note); the recall benchmarks [18]; a replication on a second machine class. (iii) Small language models, asking one question: do the channels specialize by context or by token type. The project stopped before the first step of (i) and the first run of (ii); both are ready for whoever takes them up.

20 Conclusion: where the project ends

A gate trained only on the task loss finds the partition of a Hebbian working memory that context-conditional binding needs, on the grouped layout of a synthetic task, at two, four and eight streams: a window gate, slow memory for 2400 updates, and a channel split when binding stalls, in 38 of 40 runs on two machines with disjoint seeds, where the previous recipe bound none, and in 17 of 20 in a replication from the text alone. Pre-registered on two machines with disjoint seeds, the copy with its reset beats the reset alone (18/20 against 6/20), the reset alone is within the bound of no trigger, and one delta channel binds none of twenty seeds where the recipe binds eighteen; both readings apply. The write rule: with its write strength fixed, the delta rule is not shown worse than the Hebbian one, pre-registered on two machines with disjoint seeds at eight streams (35/40 against 35/40), it needs no split there where the Hebbian write does (38/40 without a trigger against 17/40), and it binds sooner; a learned write strength collapses on a screen. Which write rule a language model should carry is not answered by a synthetic task, but on this one the delta rule with a fixed strength is the simpler recipe. At a distance, a register that overwrites on the cue and gates all three layers carries it when told where to split, is found label-free on a fifth of seeds (2 of 20 on the fresh seeds of the device screen), and is found on every seed of a screen when a hinge keeps the gate off key identity during the slow phase, which on a screen also prevents the two-stream key split that the copy did not repair; on Hebbian memory the first layer is the one that must be routed. Under a dense loss at two sources one channel learns to carry the cue by itself; at four, on a GPU screen that its validity rule leaves untested, neither one channel nor either learned gate did. A referee recomputed the numbers of Revisions 8, 9 and 10 from the records and found them to reproduce, and the statements it found wrong in each draft are corrected and listed; it checked every exploratory report of rounds 5 to 7 but the last, with the numbers right throughout and the names of three readings outrunning their content (Section 15). The headline arms bind 19/20, 6/20 and 0/20 on a GPU on fresh seeds, and the replication session reproduced the split test's three counts on fresh seeds, its delta arm from the specification alone.

The last two rounds took away what the recipe reads, on screens. With the keys drawn from 32 types, a Hebbian channel with its routing given did not bind them on two seeds per task at two budgets and a delta channel did; the convolution restores the Hebbian channel; at eight streams

both oracles are reliable to eight key types and the delta one is the limit from sixteen, and at eight the delta recipe carries (10/10) where the Hebbian recipe does not decide (6/10; 1/10 at 32 key types). A hinge that reads only which token types repeat within the sequence matches the labelled key hinge within one pair on pooled keys, where the hinge is needed (19/20 against 18/20 on Hebbian memory with the convolution; 20/20 against 20/20 on delta), and falls short of it on the original task (17/20 against 20/20). With the context tokens drawn from a pool, one delta channel binds two documents with no gate, and no learned gate, with two channels or sixteen, on either memory, routes them, while a handed index or a handed channel per type binds every seed: at sixteen channels a learning negative at the budget, not a capacity limit (at two, the null is confounded with the cap on a fixed type map). The sentence this project can defend is therefore bounded on three sides. A gate trained only on the task loss finds the partition of a channelled working memory that context-conditional binding needs when the cue is local and a fixed token (pre-registered, two machines, replicated); it finds it when the cue is distant and fixed, if a hinge holds the gate off key identity during the slow phase, and the hinge can read the sequence's own repeats instead of labels where the keys are not fixed types (screens of twenty seeds; a specification ready); and it has not been made to find it when the cue has no fixed identity, which is the case a language model presents. The author concluded the project on 1 November 2026 at that line.

What a successor does first, in order:

- Run the register test. The draft is `specs/drafts/test_register_draft_rev2.md`: take the referee's ten text fixes, adopt it into `specs/`, write the test file to `CONTRIBUTING.md`'s discipline, have the referee read it against the specification, then run X and L with disjoint seeds (Section 12; `STATUS.md` §4).
- Run S75b's pilot on the 1660 (`python -m explore_gpu.s75b --stage 1 --device cuda`, about three to four hours) and, on a PROCEED, stage 2 on both cards; session I reads the record (Section 19).
- The frontier: contexts without fixed identity. Start from session G's report 11 and session F's report 10: the channels exist at $k = 16$ and the type-keyed ceiling binds, so the question is how a gate is pushed to use them (a term on the gate's spread over channels, a longer budget), not whether they suffice; run the two ceilings beside every arm.
- The two drafts that need revision before a run (the two-stream key-term test's baseline; the key-load test's validity check), and BDH-CQ and Triadic Linear Attention read in full.

A Provenance

test	X: spec / test commit / result commit	L: results file (commit recorded)	runs, X; L
muon_recipe	— / 74f5907 / 3e2d171; pooled 2a6ba3d	L/muon_recipe_results.json (74f5907)	156; 166
window_gate	spec 9a769c7, amended d05f0ca / 2f98f06, Part D 886a668 / 628eb7c	L/window_gate_results.json (886a668; recorded 1cd20a1)	231; 231
split_copy	spec fb3acb7 / 1f52cd5 / 592c574 (X), ffb0771 (L and pooled; the classifier ba8901a, the launcher 56c44a7; L's docstring corrected after the referee's checks, 80bfc1d, c3ad769)	complete (L run at 592c574; one earlier start stopped at verification over an argument)	54; 54
delta_recipe	spec 05256c5, Amendment 1 32c121b / test a581027, Amendment 2 during the run 55dac50, 2225f00 / 8ae660d (X), b03d353 (L and pooled; L's docstring corrected after the referee's check, 76851eb)	L/delta_recipe_results.json (8ae660d; run at 8ae660d, the pooled block regenerated with --report --also, L/delta_recipe_L_report.log)	84; 84

Table 7: Phase VI main-line tests on branch claude/bdh-growth-hebbian-inference-w90069. L's results files for Phases III–IV are in results/L/ from 9a53302 (twelve files, recovered from the laptop's working copies) and 9c53e16 (channel_binding, rerun on L on 10 October with the test's code unchanged); the Phase V files at 00ac0f2, d0e6c85, the scale-axes file at 42af095. X: Intel Xeon at 2.80 GHz for the first two tests and 2.10 GHz for split_copy; L: Intel i7-12650H; PyTorch 2.14.0 (L's channel_binding rerun and its split_copy and delta_recipe runs 2.14.1). The GPU run of window_gate's eight-stream arms (session I, report 3; GTX 1660 SUPER, PyTorch 2.14.0+cu130, seeds 2540–2559) is on claude/explore-I at 148c161, its pre-run note at 30807ec; it is not a main-line record. L's recorded start times are local time (UTC−6); X's are UTC.

Table 8: Exploratory work and the review in Phase VI, one thread per run, each segment opened by a bit-for-bit reproduction of a recorded run; one commit per report as listed, the branch's commit column being the last report's. Branches claude/outside-ideas, claude/explore-F/G/H/I, claude/replicate-R, claude/review-V; the review is merged into the main line under docs/review_2026-10/. The audit is docs/audit_2026-10.md (b22da04); the reading notes and synthesis are docs/reading/ (ad8a92e); the sessions' prompts are docs/reading/parallel_sessions_prompts.md, rounds 6 and 7 last. The project's state at its conclusion is STATUS.md; specs/drafts/ holds the register specification's revision 2; this revision's check is docs/review_2026-10/rev11/.

batch or session	screens (report)	commit	runs
15–18 (E)	S41–S52 (Revision 8)	90c3a28, 93bdfe6, 2531480, 7ef4e15	379
19 (E)	S64 width, S65 depth, S66 eight streams, S67 capacity (complete, e3f5809)	e3f5809	186
20–21 (E)	S68 the sixteen-key runs continued to 86,400 (readings 4acf915; complete f5d3893); S69 the $D = 128$ oracle's validity (readings b93b73c; complete 419368a)	419368a	19; 20

batch or session	screens (report)	commit	runs
H	S58, S58b, S60 (reports 1–2); S61 copy without reset, S62 query gate, S63 hardness (report 3, `7e9197f`); S78 two streams (report 4, `72f0bbc`); S79 constants (report 5, `df57087`); S84 guard and evaluation trigger (report 6, `37c1fbf`); S85 prevention at two streams (report 7, `1e09ecd`, corrected `de11b2a`); S86 all-position targeting (report 8, `9b72bf6`); S87a the all-position trigger on 20 more seeds, S87c the key term's dose, and the one-to-one recount over the main line's 126 firings (report 9, `347bd25`); S89 the recipe, the all-position and repeat triggers and no trigger on 32 key types (report 10, `13fe610`; the referee's fixes to the text, `2a98def`); S89c the schedule, S89b the delta oracle (report 11, `4360caf`); S92 the oracles at pools 4–32 and the recipe at pool 8 (report 12, `fbc4f16`; unchecked by the referee)	`fbc4f16`	318; 300; 82; 62; 52; 82; 32; 84; 42; 32; 62
F	S53, S54, S59 (reports 1–2); S68 premise, S69 Hebbian decay, S70 lite task (report 3, `9a6c2bf`); S77 probe (report 4, `22ec912`); S76 eight streams on delta (report 5, `5b9bc2a`); S80 two and four streams (report 6, `ed76eea`); S81 the trigger on delta (report 7, `d5851b1`); S88a the write strength, S88b the horizon (report 8, `a199d5e`; readings `40087cb`); S89-F the pool tasks, their pilots, the no-memory check and the diagnostic (report 9, `52e2ea7`), the convolution and type-level pilots (`2279ca1`), the 48,000 fallback (`3e3b1bf`); S90-F the context-pool family and the single-channel screen (report 10, `d9783bb`; addenda `cb87c23`, `c9c7e48`); the task module G vendors, `50dc8e4`, `b0c6332`, `9017b82`	`6efd178`	322; 102; 30; 40; 48; 42; 78; 42; 100
G	S55 probe (report 1, `6cd36ff`); S56 register, S57 latch (report 2, `427db36`); S71 layers (report 3, `35de6db`); S73, S72 register at all layers (report 4, `93422cf`); S82 devices against the key split (report 5, `8973d48`; spec `83699a2`); S83 the hinge's inputs, the control and the window (report 6, `076005d`; spec `b2f9907`); S87 hinges that read no task labels (report 7, `e46799a`; spec `3c89f87`); S89 the hinges on pooled keys, delta (report 8, `8e9e318`); S89H the same on Hebbian memory with the convolution (report 9, `996e38b`; the budget erratum `4314e35`); S90 the repeat hinge on lite and S91 gates that compare (report 10, `cbca3e3`); the register specification's revision 2 (`6fc55b1`); S91b at $k = 16$ (report 11, `330290d`)	`330290d`	22; 139; 50; 150; 136; 82; 142; 204; 204; 60; 44; 136
I	S74 pilot, three configurations (report 1, `a2588da`); the GPU package (driver `5f03929`; CUDA check on the GTX 1660 SUPER `203a5ad`); S75 at four sources on that card (records `86652b1`, `b649751`, `4c3984a`; pre-run note `5bc6c2e`; report 2, `03bffdf`, `559b942`, the tenth seed `4371824`, `403538b`); `test_window_gate` on the GTX 1660 SUPER (note `30807ec`; records `148c161`; report 3, `3d7e68e`); S75b: the specification's Appendix C (`c78d5d2`), the CUDA CHECKs and benchmarks on the final driver `3cef609` (the 1660 `a7e7e12`, `b06a81a`; the 3070 `fb3066c`, `eb3e819`), the pre-run note (`005a59a`); no pilot run	`005a59a`	pilot; 42; 62; 0
R	Phase 2 (`de8df0f`), Phase 3 diff and reruns (`00990ea`, `100dced`); Phase 4, the 40-seed count (rule `464be8d`; report `1f8be04`); Phase 5, `test_split_copy` on fresh seeds (protocol `550a736`; report `31c39fc`)	`31c39fc`	42; 20; 42; 64

batch or session	screens (report)	commit	runs
V	review (`d2bb959`); 8.1 check (`0fdb363`); registry (`ebb9325`); replication review (`01bee1f`); session recomputes (`4bf85e9`); L addendum (`0e6c189`); delta spec reviews (`fad1489`, `16b04f9`); the test check (`6f2788d`); Revision 9's checks (`e8fbb25`, `66334b8`, `0d1fa60`, `907eb2c`, `e384a87`); round 6's A3 (`0e70640`); Revision 10's pass (`480a2de`); Revision 10.1's check (`70a7992`); the round-6 screen reviews (`3ae815b` F, `ee5217b` H, `dcd549d` G) and report checks (`adecd3d` H report 10, `e3749da` F report 9); Revision 10.2's check (`05dd56c`); rounds 6–7: the key-load options note (`11a78ee`), the screen reviews (`c42ace8` G v2, `43cea89` H S89b/c, `e20c4e7` G S90, `ecbaf77` F S90, `980498e` H S92) and the report checks (`ed3653b` H 11, `b2169dc` G 8 and the register spec v2, `a141e92` G 9, `773fa0d` H S92 phase 1, `0407d82` the register spec v3, `9cc6095` G 10, `d2bcd19` F 10, `6f8d1d6` G 11, its last)	`6f8d1d6`	2 reproductions

B What a replication needs: the protocol as this revision states it

The items a reader must have to score runs as the main line does, compiled from session R's `UNSTATED.md` (44 entries for Phases 2–4), its `DIFF.md` (17) and the referee's additions. Where the report had been silent, the main line's choice is given.

Model. Pathway's BDH forward pass in float32 with $x = \mathrm{LN}(\mathrm{emb})$ and, per layer, the sparse code $\sigma = \mathrm{ReLU}(xE)$, $y = \mathrm{LN}(\mathrm{attn}(\sigma, \sigma, x))$, $y_\sigma = \mathrm{ReLU}(yE_v)$, $z = \mathrm{LN}((\sigma \odot y_\sigma)D)$ and $x \leftarrow \mathrm{LN}(x + z)$, every LayerNorm without affine parameters, and logits xW_{head} after the last layer; one head, $N = 256$, $d = 32$, three applications of one shared layer; scalar decay 0.95^{t-u} in place of RoPE; strictly causal ($u < t$); no dropout; Pathway's initialisation (encoder, decoder, head and embedding at $\mathcal{N}(0, 0.02^2)$), which sets the scale of the gate's input; channel mixing as the score $(\sigma_t \cdot \sigma_u)(g_t \cdot g_u)\, 0.95^{t-u}$ on the sparse codes, with one gate per token for read and write, the same at every layer; the gate reads the model's own raw embedding (the same table), through a width-3 depthwise causal convolution (weights uniform in $\pm 1/\sqrt{3}$ from `Generator(seed + 31337)`, no bias, left-padded with zeros), a hidden layer of 32 units with tanh, $W_{\mathrm{in}}, W_g \sim \mathcal{N}(0, 0.1^2)$, no biases; the model is built as the recurrent-gate model and converted, so its recurrent weight W_h is drawn (which fixes the draw order of the parameters after it) and stays frozen, unused and in no optimizer group; the "conv" of the four- and eight-stream configurations is one shared depthwise causal filter of width 4 on the d-dimensional layer input, initialised to the identity, whose output feeds the keys (equal to the queries, through E) and the values; the perfect gate's model is `test_stream_recipe`'s `ceiling8k16` ($k = 16$, stream s to channel s, the context-token list padded with $16 - S$ ids that never occur so that channels S to 15 are unused), with the curriculum off.

Task. 28 tokens at eight streams and four keys: 16 value tokens, P key tokens, S context tokens, and no query token (the sequence of 99 tokens ends with the query's value; the model reads the first 98 and predicts the 99th from the query's KEY position); per sequence and key, S distinct values without replacement, assigned to streams in random order; the query's stream and key uniform and independent; the loss is cross-entropy over the full vocabulary at the query's KEY position; accuracy is argmax over the full vocabulary; 2048 held-out sequences from a fixed generator (`Generator(424242)`), the same for every run and arm; `torch.manual_seed(seed)` before initialisation, the training batches from `Generator(seed + 10000)`.

Training and evaluation. Adam with default betas, no weight decay, batch 32, constant rates, no warm-up, no clipping; SLOW's groups and its switch after the evaluation at 2400; evaluation every 1200 updates and at the budget; early stop after three consecutive evaluations ≥ 0.95; at a shared step the order is evaluation, statistics, the path's own check, the learning-rate switch, the split trigger, the early-stop test; the perfect gate trains at the single rate 10^{-3} without SLOW; the final per-stream accuracy and map come from a final evaluation of the final model.

Outcomes. Bound: the first evaluation ≥ 0.95 that holds to the end (a run can bind on its last evaluation); the stream-to-channel map: for each stream, the argmax over channels of the mean gate at the body's value positions on a 256-sequence probe (`Generator(seed + 99000)`), ties on unrounded values to the lowest channel index (`torch.argmax`); bound routed: bound, the map one-to-one, every stream's accuracy ≥ 0.9 on the held-out queries of that stream; failure labels as Section 3.

The split. The probe: 64 sequences from `BindTask.make_batch(64, Generator(12345))`, the same for every seed and arm, scored on their queries (5, 5, 6, 8, 10, 12, 5 and 13 per stream at eight streams); read at 2400 as the first reference and at every check from 4800 in steps of 2400 up to the budget minus 2400; fire if the probe's accuracy is below 0.95 and rose by less than 0.02 since the previous check; c^* and c_0 the argmax and argmin of the mean read-gate mass over the probe's 32 body key positions (not the query's), ties to the lowest index; $W_g[c_0] \leftarrow W_g[c^*]$ (the main line's Part D form adds $0.1\,\sigma$ noise to both rows, σ the copied row's standard deviation by `torch.std` with Bessel's correction, two draws of the row's shape from `Generator(12_000_000 + 1000*seed + n_splits)`, the first added to c^*'s row and the second to c_0's, and zeroes W_g's Adam state including its step counter); a split blocks further splits for 4800 updates; at most three; no guard against a target that carries key mass (none is needed at $k = 16$, $S = 8$).

Records. Per run: the curve at every evaluation, the per-stream gate mass at value positions at every evaluation and the per-stream accuracy at the end, each check's probe reading beside the evaluation's reading at the same step, each split's update, c^*, c_0 and the map before it, the CPU, the code commit and the start time with its time zone. The main line's records hold all of these except the zone (its start times are local to the machine, without one), and a replication should record it.

Statistics. Exact one-sided McNemar on the discordant pairs, $p = P[\mathrm{Bin}(b + c, \frac{1}{2}) \geq b]$; Wilson 95% intervals with $z = 1.96$; for a replication of a rate on n fresh seeds, a one-sided exact test against the reported rate with its size and power stated in advance, a Fisher comparison with the original count, and the mechanism's arms paired on the same seeds.

References

[1] A. Kosowski, P. Uznański, J. Chorowski, Z. Stamirowska, M. Bartoszkiewicz. *The Dragon Hatchling: The Missing Link between the Transformer and Models of the Brain.* arXiv:2509.26507, 2025.

[2] B. Engdahl, A. Kosowski, J. Chorowski, Z. Stamirowska, P. Uznański, J. Jiang, R. Phadke, R. Kinas, R. Zhong. *BDH-CQ: In-Context Learning with Recurrent Latent Reasoning.* arXiv:2608.09888, 2026.

[3] O. Sieberling et al. *Triadic Linear Attention.* arXiv:2609.36529, 2026.

[4] A. Gu, T. Dao. *Mamba: Linear-Time Sequence Modeling with Selective State Spaces*. arXiv:2312.00752, 2023.

[5] K. A. Wang, J. Shi, E. B. Fox. *Test-time regression: a unifying framework for designing sequence models with associative memory*. arXiv:2501.12352, 2025.

[6] S. Yang, J. Kautz, A. Hatamizadeh. *Gated Delta Networks: Improving Mamba2 with Delta Rule*. arXiv:2412.06464, 2025.

[7] A. Jolicoeur-Martineau. *Less is More: Recursive Reasoning with Tiny Networks*. arXiv:2510.04871, 2025.

[8] J. Geiping et al. *Scaling up Test-Time Compute with Latent Reasoning: A Recurrent Depth Approach*. arXiv:2502.05171, 2025.

[9] T. Flesch, D. G. Nagy, A. Saxe, C. Summerfield. *Modelling continual learning in humans with Hebbian context gating and exponentially decaying task signals*. arXiv:2203.11560, 2022.

[10] A. Iyer et al. *Avoiding Catastrophe: Active Dendrites Enable Multi-Task Learning in Dynamic Environments*. arXiv:2201.00042, 2022.

[11] M. Choraria et al. *Context-Gated Associative Retrieval: From Theory to Transformers*. arXiv:2605.10970, 2026.

[12] J. Du et al. *MoM: Linear Sequence Modeling with Mixture-of-Memories*. arXiv:2502.13685, 2025.

[13] A. Afzal, A. Bick et al. *Raven: High-Recall Sequence Modeling with Sparse Memory Routing*. arXiv:2607.25357, 2026.

[14] A. Basu. *When Does Content-Based Routing Work? Representation Requirements for Selective Attention in Hybrid Sequence Models*. arXiv:2603.20997, 2026.

[15] J. Chung, S. Ahn, Y. Bengio. *Hierarchical Multiscale Recurrent Neural Networks*. arXiv:1609.01704, 2017.

[16] A. Behrouz et al. *Nested Learning: The Illusion of Deep Learning Architectures*. arXiv:2512.24695, 2025.

[17] W. Fedus, B. Zoph, N. Shazeer. *Switch Transformers*. JMLR 23(120), 2022.

[18] S. Arora et al. *Zoology: Measuring and Improving Recall in Efficient Language Models*. arXiv:2312.04927, 2023.

[19] A. Bietti, V. Cabannes, D. Bouchacourt, H. Jégou, L. Bottou. *Birth of a Transformer: A Memory Viewpoint*. arXiv:2306.00802, 2023.

[20] B. L. Edelman, E. Edelman, S. Goel, E. Malach, N. Tsilivis. *The Evolution of Statistical Induction Heads: In-Context Learning Markov Chains*. arXiv:2402.11004, 2024.