

Navigation in Unknown Environments


Navigation

- In robotics, **navigation** is the act of moving a robot from one place to another in a collision-free path.
- When navigating, robots either:
 - I. **head towards goal** location(s) based on sensor input
 - II. follow a **fixed path** (known in advance)
- Robot usually relies on local sensor information and updates its location/direction according to the *perceived* “best” choice that will lead to the goal.
- Assumes there is no map of the environment, otherwise the problem becomes that of path-planning.



Path Planning

- When a fixed path is provided on which to navigate, the path is usually computed (i.e., planned) beforehand.
- **Path planning** is the act of examining known information about the environment and computing a path that satisfies one or more conditions.
 - e.g., avoids obstacles, shortest, least turns, safest etc...
- Key to “good” path planning is efficiency
 - in real robots, optimal solution is not always practical
 - approximate solutions are often sufficient and desired.



Path Planning

- To accomplish complicated tasks, a mobile robot usually **MUST** pre-plan it's paths.
- Many interesting problems are solved that make use of planned motion of the robot:
 - **Efficient collision-free travel** (e.g., shortest paths)
 - **Environment coverage** (e.g., painting, cleaning)
 - **Guarding and routing** (e.g., security monitoring)
 - **Completion of various tasks etc...**
- We will look first at **goal-directed** navigation in which the robot is trying to reach a goal location based on sensor readings.



Goal-Directed Navigation

- Approaches to goal-directed navigation vary depending on two important questions:
 - Are robot & goal locations (i.e., coordinates) known ?
 - if available, goal position given as a coordinate, otherwise the problem becomes one of searching.
 - robot would either maintain its own location as it moves (e.g., forward kinematics) or have this information provided externally (e.g., GPS system).
 - Are obstacles (i.e., locations and shape) known ?
 - if available, coordinates of all polygonal obstacle vertices would be given and known to the robot.
 - if unavailable, robot must be able to sense obstacles (sensing is prone to error and inaccuracies).

Goal-Directed Navigation

- Here is a summary of categories for navigating towards a goal location under various conditions:

- **Goal Location “Unknown”**

- **Obstacles Unknown**

- 1. Behaviors (wandering, ball-seeking, wall following etc...)

} Already discussed

- **Obstacles Known**

- 1. Search algorithms
 - 2. Coverage algorithms

Won't be discussed

} Discussed later

- **Goal Location “Known”**

- **Obstacles Unknown (i.e., local sensing information only)**

- 1. Reactive Navigation

} Discussed here

- **Obstacles Known (i.e., global information available)**

- 1. Feature-Based Navigation
 - 2. Potential Field Navigation
 - 3. Roadmap-Based Planning

Won't be discussed

} Discussed later

“Bug” Algorithms

- Simple navigation when goal location is **known** but obstacles locations are **unknown** (i.e., no map)
 - robot must know its **location** within the environment at all times
(i.e., using forward kinematics, beacon location, grid est., gps etc..)
 - robot must have **sensors** to detect and follow obstacle boundaries
- There are three simple algorithms for this scenario:
 - Bug1
 - Bug2
 - Tangent Bug

Not discussed here




The Bug1 Algorithm

■ Bug1 Strategy:

- Move toward goal unless obstacle encountered, then go around obstacle and find its closest point to the goal.
- Travel back to that closest point and move towards goal.

- Assumes robot knows goal location but is unable to see or detect it.

Robot doesn't know where the obstacles are, nor their shape.



The Bug1 Algorithm

- Here is the pseudo code for the algorithm:

```
WHILE (TRUE)
```

```
  REPEAT
```

```
    Move from r towards g
```

```
    r = robot's current location
```

```
  UNTIL ((r == g) OR (obstacleIsEncountered))
```

```
  IF (r == g) THEN quit      // goal reached
```

```
  LET p = r                // contact location
```

```
  LET m = r                // location closest to g so far
```

```
  REPEAT
```

```
    Follow obstacle boundary
```

```
    r = robot's current location
```

```
    IF ((distance(r, g) < distance(m, g)) THEN m = r
```

```
  UNTIL ((r == g) OR (r == p))
```



```
  IF (r == g) THEN quit      // goal reached
```

```
  Move to m along obstacle boundary
```

```
  IF (obstacleIsEncountered at m in direction of g)
```

```
    THEN quit      // goal not reachable
```

```
ENDWHILE
```



The Bug1 Algorithm

- This algorithm:
 - always finds goal location (if it is reachable).
 - performs an exhaustive search for the “best” point to leave the obstacle and head towards the goal.
- If we denote the perimeter of an obstacle Obj_i as $perimeter(Obj_i)$, then the robot may travel a distance of:


$$|\overline{sg}| + 1.5 * [perimeter(Obj_1) + perimeter(Obj_2) + \dots + perimeter(Obj_n)]$$

s = start location

Once around the obstacle to determine best position to leave from and up to $\frac{1}{2}$ times around to get back to that position (since we can take the shorter of the two choices).

The Bug2 Algorithm


- A variation to this algorithm will allow the robot to avoid traveling ALL the way around the obstacles.
- **Bug2 Strategy:**
 - Move toward goal unless obstacle encountered, then go around obstacle. Remember the line from where the robot encountered the obstacle to the goal and stop following when that line is encountered again.



The Bug2 Algorithm

- Here is the pseudo code for the algorithm:

```
WHILE (TRUE)
  LET L = line from r to g
  REPEAT
    Move from r towards g
    r = robot's current location
  UNTIL ((r == g) OR (obstacleIsEncountered))
  IF (r == g) THEN quit      // goal reached
  LET p = r                // contact location
  REPEAT
    Follow obstacle boundary
    r = robot's current location
    LET m = intersection of r and L
  UNTIL ((m is not null) AND (dist(m, g) < dist(p, g)) OR (r == g) OR (r == p))
  IF (r == g) THEN quit      // goal reached
  IF (r == p) THEN quit      // goal not reachable
ENDWHILE
```




The Bug2 Algorithm

- This algorithm:
 - also always finds goal location (if it is reachable).
 - performs a “greedy” search for the “best” point to leave the obstacle and head towards the goal.
- The robot may travel a distance of:


$$|\overline{sg}| + O(\text{perimeter}(\text{obj}_1) + \text{perimeter}(\text{obj}_2) + \dots + \text{perimeter}(\text{obj}_n))$$

In worst case, we choose the “wrong way to go around the obstacle, leading to almost a full perimeter traversal:



Amount of perimeter travel will depend on choice of left/right edge following:

What happens if robot follows on its left side instead of right ?




The Bug2 Algorithm

- Bug2 algorithm is quicker than Bug1.
- The algorithms do have practical problems:
 - Assumes perfect **positioning** (not really possible)
 - Assumes error-free **sensing** (not ever possible)
 - Real robots have limited angular **resolution**
- Algorithms assume that robot could only detect obstacle upon contact or close proximity.
 - Can improve algorithm when robot is equipped with a 360° range sensor that determines distances to obstacles around it.
 - If you have time, look up the **Tangent Bug** algorithm.



Coding With State Machine





**Start the
Lab ...**