NYX Daily forecast pipeline

J+1 = tomorrow | J+2 = the day after | FR / DE / BE / NL

```
.\.venv\Scripts\python.exe -m nyx_runtime forecast
```

cli.py > pipeline.py | preflight.py checks the setup

Run after 08:00 Paris. J is the Paris run date; the cutoff stays at 08:00.

1 Retrieve data

Get available prices and forecast inputs; restore the rolling history.

`production/runtime/annual_extension/nyx_saved_horizon_sources.py`
`production/runtime/annual_extension/nyx_daily_state_cache.py`

2 Build the J+1 / J+2 baseline

Frozen Chronos weights + residual correction + Kalman.

`production/runtime/annual_extension/nyx_daily_two_day_baseline.py`

3 Prepare model features

Turn the baseline, history and new inputs into model variables.

`production/runtime/annual_extension/nyx_daily_refit_history.py`
`production/runtime/chronos2_hourly/nyx_annual_feature_projection.py`

4 Refit models and forecast

Fit daily references, then price and negative-price experts.

`production/runtime/annual_extension/nyx_daily_refit.py`
`production/runtime/annual_extension/nyx_daily_refit_reference.py`
`production/runtime/annual_extension/nyx_daily_refit_experts.py`

5 Save forecasts and reports

Export hourly prices, country reports and the CWE overview.

`nyx_runtime/forecast.py`
`nyx_runtime/detail_reports.py`
`nyx_runtime/reporting.py`
`output/<run_id>/predictions.csv`
`output/<run_id>/reports/index.html`

snapshot/ = starting history, states and model weights

Fresh data is retrieved each run. Chronos weights stay fixed;
the final reference models and experts are refitted each run.

Main modules shown. nyx_daily_refit.py coordinates steps 1-4.

Scripts are clickable. Branch: cleanup/daily-j1-j2 | Version: 804081a4