

Learn mocp

MOC - Console audio player

- Config file location: `~/.moc/config`
- Open current directory: `mocp .`

Commonly used keybindings:

- `a` Add a file/directory to the playlist
- `TAB` Switch between playlist and file list
- `space` to pause/play
- `q` to exit player and continue playing in background
- `n` for next song, `b` for previous song.
- `s` to stop
- `LEFT` / `RIGHT` to **seek forward / backward by 5 seconds** (UPDATED in config file: `SeekTime = 5`)
- `,` and `.` to increase/decrease volume 5% (use `<` and `>` to increase by 1%)
- `[` and `]` to silent seek
- `[ / ]` to seek forward / backward by 5 seconds (UPDATED in config file: `SilentSeekTime = 5`)
- `z` Add (or remove) a file to (from) queue
- `Z` Clear the queue

From CLI:

<code># -m --music-dir</code>	Start in MusicDir
<code># -a --append</code>	Append the files/directories/playlists passed in
<code>#</code>	the command line to playlist and exit
<code># -q --enqueue</code>	Add the files given on command line to the queue
<code># -c --clear</code>	Clear the playlist and exit
<code># -p --play</code>	Start playing from the first item on the playlist
<code>#  -l --playit</code>	Play files given on the command line without modifying
<code>#</code>	the playlist

```
# 🚀 -s --stop           Stop playing
# -f --next             Play the next song
# -r --previous         Play the previous song
# -x --exit             Shutdown the server
```

Other helpful keybindings:

- Use `h` to show help as shown below:

```
q           Detach MOC from the server
ENTER      Start playing at this file or go to this directory
DOWN       Move down in the menu
UP          Move up in the menu
PAGE_DOWN  Move one page down
PAGE_UP    Move one page up
HOME        Move to the first item in the menu
END         Move to the last item in the menu
Q           Quit
s           Stop
n           Play next file
b           Play previous file
p SPACE     Pause
f           Toggle ReadTags option
S           Toggle Shuffle
R           Toggle Repeat
X           Toggle AutoNext
TAB         Switch between playlist and file list
l           Switch between layouts
            Switch on/off play time percentage [unassigned]
a           Add a file/directory to the playlist
C           Clear the playlist
A           Add a directory recursively to the playlist
Y           Remove playlist entries for non-existent files
<           Decrease volume by 1%
>           Increase volume by 1%
,           Decrease volume by 5%
.           Increase volume by 5%
RIGHT       Seek forward by n-s
LEFT        Seek backward by n-s
h ?         Show the help screen
M           Hide error/informative message
^r ^l       Refresh the screen
r           Reread directory content
H           Toggle ShowHiddenFiles option
m           Go to the music directory (requires config option)
d           Delete an item from the playlist
```

g /	Search the menu
V	Save the playlist
^t	Toggle ShowTime option
^f	Toggle ShowFormat option
o	Play from the URL
G	Go to the currently playing file's directory
i	Go to a directory
U	Go to '..'
^g ^n	Find the next matching item
^x ESCAPE	Exit from an entry
]	Silent seek forward by 5s
[	Silent seek backward by 5s
M-1	Set volume to 10%
M-2	Set volume to 20%
M-3	Set volume to 30%
M-4	Set volume to 40%
M-5	Set volume to 50%
M-6	Set volume to 60%
M-7	Set volume to 70%
M-8	Set volume to 80%
M-9	Set volume to 90%
'	Mark the start of a block
"	Mark the end of a block
!	Go to a fast dir 1
@	Go to a fast dir 2
#	Go to a fast dir 3
\$	Go to a fast dir 4
%	Go to a fast dir 5
^	Go to a fast dir 6
&	Go to a fast dir 7
*	Go to a fast dir 8
(	Go to a fast dir 9
)	Go to a fast dir 10
UP	Go to the previous entry in the history (entry)
DOWN	Go to the next entry in the history (entry)
^u	Delete to start of line (entry)
^k	Delete to end of line (entry)
x	Toggles the mixer channel
w	Toggles the software-mixer
E	Toggles the equalizer
e	Reload EQ-presets
K	Select previous equalizer-preset
k	Select next equalizer-preset
J	Toggle mono-mixing (when softmixer enabled)
u	Move playlist item up
j	Move playlist item down
^u	Add a URL to the playlist using entry
T	Switch to the theme selection menu

F1	Execute ExecCommand1
F2	Execute ExecCommand2
F3	Execute ExecCommand3
F4	Execute ExecCommand4
F5	Execute ExecCommand5
F6	Execute ExecCommand6
F7	Execute ExecCommand7
F8	Execute ExecCommand8
F9	Execute ExecCommand9
F10	Execute ExecCommand10
L	Display lyrics of the current song (if available)
P	Toggle displaying full paths in the playlist
z	Add (or remove) a file to (from) queue
Z	Clear the queue

Help

```

mocp -h
# Music On Console (version 2.5.2, revision 2930)
# Usage:
#  mocp [OPTIONS]... [FILE]...
#  -V --version          Print program version and exit
#  -h --help            Print usage and exit
#  -S --server          Only run the server
#  -F --foreground      Run server in foreground and log to stdout
#  -R --sound-driver LIST Use the first valid sound driver from LIST
#                      (sndio, oss, alsa, jack, null)
#  -m --music-dir       Start in MusicDir
#  -a --append          Append the files/directories/playlists passed in
#                      the command line to playlist and exit
#  -q --enqueue        Add the files given on command line to the queue
#  -c --clear           Clear the playlist and exit
#  -p --play            Start playing from the first item on the playlist
#  -l --playit         Play files given on the command line without modifying
#                      the playlist
#  -s --stop           Stop playing
#  -f --next           Play the next song
#  -r --previous       Play the previous song
#  -x --exit           Shutdown the server
#  -T --theme theme    Use the selected theme file (read from ~/.moc/themes
#                      if the path is not absolute)
#  -C --config FILE    Use the specified config file instead of the default
#  -O --set-option NAME=VALUE
#                      Override the configuration option NAME with VALUE
#  -M --moc-dir DIR    Use the specified MOC directory instead of the default
#  -P --pause          Pause

```

```
# -U --unpause           Unpause
# -G --toggle-pause      Toggle between playing and paused
# -v --volume (+/-)LEVEL Adjust the PCM volume
# -y --sync              Synchronize the playlist with other clients
# -n --nosync            Don't synchronize the playlist with other clients
# -A --ascii             Use ASCII characters to draw lines
# -i --info              Print information about the currently playing file
# -Q --format FORMAT     Print formatted information about the currently
#                        playing file
# -e --recursively       Alias for -a
# -k --seek N            Seek by N seconds (can be negative)
# -j --jump N{ PERCENTAGE_SIGN,s} Jump to some position of the current track
# -o --on <controls>     Turn on a control (shuffle, autonext, repeat)
# -u --off <controls>    Turn off a control (shuffle, autonext, repeat)
# -t --toggle <controls> Toggle a control (shuffle, autonext, repeat)
```

Manual

```
$ man mocp | cat
```

```
MOC(1)
```

```
NAME
```

```
    MOC - Console audio player
```

```
SYNOPSIS
```

```
    mocp [OPTIONS] [FILE|DIR ...]
```

```
DESCRIPTION
```

```
    MOC is a console audio player with simple ncurses interface. It supports O
file. The program will automatically play the rest of the files in the dir
```

```
    With no options and no file arguments the program begins in current directo
line, MOC will try to go there. If a playlist is given, then it is loaded.
tents of any playlist given). (Note that relative paths in playlists are r
```

```
OPTIONS
```

```
    If an option can also be set in the configuration file the command line over
```

```
    -D, --debug
```

```
        Run MOC in debug mode. The client and server log a lot of info
able-debug.
```

```
    -S, --server
```

```
        Run only the server and exit.
```

-F, --foreground
Implies -S. Run the server in foreground and log everything to stdout.

-R NAME[:...], --sound-driver NAME[:...]
Use the specified sound driver(s). They can be OSS, ALSA, JACK, SND: configuration file.

-m, --music-dir
Start in MusicDir (set in the configuration file). This can be also

-q, --enqueue
Add files given after command line options to the queue. Don't start

-a, --append
Append files, directories (recursively) and playlists given after cor

-c, --clear
Clear the playlist.

-p, --play
Start playing from the first item on the playlist.

-f, --next
Request playing the next song from the server's playlist.

-r, --previous
Request playing the previous song from the server's playlist.

-s, --stop
Request the server to stop playing.

-x, --exit
Bring down the server.

-P, --pause
Request the server to pause playing.

-U, --unpause
Request the server to resume playing when paused.

-G, --toggle-pause
Toggle between play and pause.

-k [+|-]N, --seek [+|-]N
Seek forward (positive) or backward (negative) by N seconds in the f:

-T THEME, --theme THEME
Use a theme file. If the path is not absolute, the file will be sea

-C FILE, --config FILE
 Use the specified configuration file instead of the default. As the current user, or if it is writable by anyone other than its owner.

-O NAME[+]=VALUE, --set-option NAME[+]=VALUE
 Override configuration option NAME with VALUE. This option can be used after the configuration file is processed (which allows the new values to be picked up if previous values are replaced or added to).

See the example configuration file (config.example) for a description of the options.

Examples: **-O AutoNext=no**
-O messagelintertime=1 -O XTerms+=xxt:xwt

Note that MOC does not perform variable substitution as it does for the

-M DIR, --moc-dir DIR
 Use the specified MOC directory instead of the default. This also changes the MOCDir option.

-y, --sync
 This copy of the interface will synchronize its playlist with other copies.

-n, --nosync
 This copy of the interface will not synchronize its playlist with other copies.

-A, --ascii
 Use ASCII characters to draw lines. (This helps on some terminals.)

-i, --info
 Print the information about the file currently being played.

-Q FORMAT_STRING, --format FORMAT_STRING
 Print information about the file currently being played using a format string.

%state	State
%file	File
%title	Title
%artist	Artist
%song	SongTitle
%album	Album
%tt	TotalTime
%tl	TimeLeft
%ts	TotalSec
%ct	CurrentTime
%cs	CurrentSec
%b	Bitrate

%r Rate

It is also possible to use variables from the FormatString configuration.

-e, --recursively

Alias of -a for backward compatibility.

-h, --help

Print a list of options with short descriptions and exit.

-V, --version

Print the program version and exit.

-v [+|-]N, --volume [+|-]N

Adjust the mixer volume. You can set (-v 50) or adjust (-v +10, -v -10).

-t OPTION[,...], --toggle OPTION[,...]

-o OPTION[,...], --on OPTION[,...]

-u OPTION[,...], --off OPTION[,...]

Followed by a list of identifiers, these will control MOC's playlist.

Example: -t shuffle,r,n

would toggle shuffle, repeat and autonext all at once.

-j N{s|PERCENTAGE_SIGN}, --jump N{s|PERCENTAGE_SIGN}

Jump to some position in the current file. N is the number of seconds.

Examples: -j 10s, -j 50%

FILES

~/.moc MOC directory for the configuration file, socket, the pid file and other files.

~/.moc/config

Configuration file for MOC. The format is very simple; to see how it is written, see the file config.h. This file describes all the configuration options, and so is a useful reference. This file is not owned by either root or the current user, or if it is writable by the current user.

~/.moc/themes

/usr/share/moc/themes

Default directories for the theme files.

/usr/share/moc/decoder_plugins

Default directories for the audio decoder plugins.

mocp_client_log

mocp_server_log

Client and server log files. These files are created in the directory specified by the --log-dir option.

BUGS

Command line options that affect the server behaviour (like `--sound-driver`)

HOMEPAGE

<http://moc.daper.net/>

AUTHOR

Damian Pietras <daper@daper.net>
MOC Maintainer(s) <mocmaint@daper.net>

Version 2.5.2

Thankyou.