



Run Control

☐ Continuous
☐ Single
☒ Stop

Power

Power is On

USB Power: 0.49 W

Channel 1

Ch1 On

Sensitivity: 1.0 V/div

Range: +5V, 0, -5V

Channel 2

Ch2 On

Sensitivity: 1.0 V/div

Range: +5V, 0, -5V

Channel 3

Ch3 Off

Sensitivity: 2.0 V/div

Range: +5V, 0, -5V

Channel 4

Ch4 Off

Sensitivity: 2.0 V/div

Range: +5V, 0, -5V

Analog Outputs

A1 Off

1 Hz Frequency

1.00 V Amplitude

☒ Sine
☐ Triangle
☒ Unipolar
☐ Bipolar

A2 Off

1 Hz Frequency

1.00 V Amplitude

☒ Sine
☐ Triangle
☒ Unipolar
☐ Bipolar

Pulse Outputs

P1 Off

1 Hz Frequency

50% Duty

P2 Off

1 Hz Frequency

50% Duty

Horizontal Control

☒ Y vs T
☐ X vs Y
☐ Roll

Time Scale: 50 ms/div

Trigger

Trigger Off

☒ Rising Edge
☐ Falling Edge

☒ Channel 1
☐ Channel 2
☐ Channel 3
☐ Channel 4

v0.7

