- The libmysqld embedded server library is removed, along with:
 - The mysql_options() MYSQL_OPT_GUESS_CONNECTION, MYSQL_OPT_USE_EMBEDDED_CONNECTION, MYSQL_OPT_USE_REMOTE_CONNECTION, and MYSQL_SET_CLIENT_IP options
 - The mysql config --libmysqld-libs, --embedded-libs, and --embedded options
 - The CMake WITH_EMBEDDED_SERVER, WITH_EMBEDDED_SHARED_LIBRARY, and INSTALL SECURE FILE PRIV EMBEDDEDDIR options
 - The (undocumented) mysql --server-arg option
 - The mysqltest --embedded-server, --server-arg, and --server-file options
 - The mysqltest embedded and mysql client test embedded test programs
- The mysql_plugin utility was removed. Alternatives include loading plugins at server startup using the --plugin-load or --plugin-load-add option, or at runtime using the INSTALL PLUGIN statement.
- The resolveip utility is removed. nslookup, host, or dig can be used instead.
- The resolve_stack_dump utility is removed. Stack traces from official MySQL builds are always symbolized, so there is no need to use resolve stack dump.
- The following server error codes are not used and have been removed. Applications that test specifically for any of these errors should be updated.

```
ER BINLOG READ EVENT CHECKSUM FAILURE
ER_BINLOG_ROW_RBR_TO_SBR
ER_BINLOG_ROW_WRONG_TABLE_DEF
ER CANT ACTIVATE LOG
ER CANT CHANGE GTID NEXT IN TRANSACTION
ER_CANT_CREATE_FEDERATED_TABLE
ER_CANT_CREATE_SROUTINE
ER CANT DELETE FILE
ER CANT GET WD
ER CANT_SET_GTID_PURGED_WHEN_GTID_MODE_IS_OFF
ER CANT SET WD
ER CANT WRITE LOCK LOG TABLE
ER CREATE DB WITH READ LOCK
ER CYCLIC REFERENCE
ER_DB_DROP_DELETE
ER DELAYED NOT SUPPORTED
ER DIFF GROUPS PROC
ER_DISK_FULL
ER_DROP_DB_WITH_READ_LOCK
ER DROP USER
ER DUMP NOT IMPLEMENTED
ER ERROR DURING CHECKPOINT
ER ERROR ON CLOSE
ER EVENTS DB ERROR
ER EVENT CANNOT DELETE
ER EVENT CANT ALTER
ER EVENT COMPILE ERROR
ER EVENT DATA TOO LONG
ER EVENT DROP FAILED
ER EVENT MODIFY QUEUE ERROR
ER EVENT NEITHER M EXPR NOR M AT
ER EVENT OPEN TABLE FAILED
ER EVENT STORE FAILED
ER EXEC STMT WITH OPEN CURSOR
```