

Analytics and Planning on Fiori

SAP Analytics Cloud style stories, analysis and planning, built as an ABAP RAP backend with a UI5 front end

Document	Current state and features
Date	6 October 2026
Repository	github.com/Yoga56/ZDEMO_SAC_FIORI , branch main
Package	ZSAC_FIORI (ABAP), apps zsac.lib and zsac.fiori (UI5 1.136)
Status	Running on the sample data (mock provider) and on a real S/4HANA Cloud system (OData V4), see chapter 8

Screenshots in this document come from the sample data (mock provider) running locally, unless a caption says otherwise.

Contents

1. Purpose and scope
2. Architecture
3. The application: pages and features
4. Planning in detail
5. Data actions and multi actions
6. Data sources: CDS views (live and import)
7. Analysis helpers: variance explainer and comments
8. Backend (ABAP RAP)
9. Installation, configuration and operation
10. Verification status
11. Known limits and open items
12. Appendix: repository layout, tests, glossary

1. Purpose and scope

The application brings the working model of SAP Analytics Cloud (SAC) to a Fiori environment on SAP S/4HANA Cloud: stories (dashboards), the data analyser, models (datasets), planning with versions, data actions and multi actions, a calendar, and a file catalogue. Everything a user builds, models, stories, data actions, multi actions and files, is data stored in the backend and edited in the app, so new content needs no code change.

Two design aims run through the whole code base: **modular and reusable** (the UI5 library `zsac.lib` can be used by any other Fiori app, widgets and data providers are plug-ins) and **usable without a backend** (a mock provider with sample data), so every feature can be tried and tested locally.


What is in this release

Area	Content
Home, Files	Landing page with metrics and recent items, file catalogue with folders, favourites, sharing flags, search
Stories	Designer and viewer: pages, grid canvas, widgets (charts, KPI, table, input control, text, planning table, triggers, variance explainer), story filters
Data Analyser	Free analysis of a model: rows, columns, filters, chart or table
Datasets, Modeller	SAC style modeller: measures, dimensions (types, attributes, hierarchies, Date hierarchy), preferences, related objects, CSV import and export, CDS source
Planning	Editable planning table with hierarchies, spreading, copy and paste, formulas, distribute values, unpublished buffer with undo and redo, publish, versions, version history, comments on cells
Data Actions	List, designer with step flow, parameters, 5 step types, validation, trace (dry run), run history
Multi Actions	Designer, parameters mapped onto data actions, 9 step types, validation, run dialog
CDS data sources	A model reads a CDS view live, or imports its rows into versions
Variance explainer	Why did a measure change between two versions or sets of months, by every dimension
Calendar	Planning tasks with assignee, due date and status

Out of this release: Predictive Scenarios, Compass, Just Ask, scripting (Analytics Designer), server side aggregation of the sample data, a real connection to PaPM.

2. Architecture

Browser (UI5 1.136)



Layer	Contents
core	DataProvider (contract), ProviderRegistry, QueryEngine (aggregation, exception aggregation, hierarchies, Date hierarchy), HierarchyEngine, ModelSchema, FilterEngine, StorySchema, WidgetRegistry, VarianceEngine, Format
provider	MockProvider, ODataV4Provider, LiveSource (CDS), FakeODataService (stand-in used by the sample and the tests)
planning	PlanBuffer, PlanEditor, Spreader, Distributor, FormulaEngine, PlanGrid, PlanToolbar, PlanPublisher, VersionEngine/Manager/History, DataActionSchema/Engine/Run, MultiActionSchema, StepRunners, ImportEngine, Forecaster, comments
widget	SvgChart, KpiTile, PivotTable, WidgetCard, chart builders, the widget registrations (chart.*, kpi, table, filter, text, planning.table, dataaction.trigger, multiaction.trigger, variance)
designer	StoryCanvas, StoryViewer, BuilderPanel, FilterEditor
app (zsac.fiori)	Component (chooses the provider), pages and controllers, Modeller helpers (master data dialog, CDS source dialog, CSV tools)

Key design decisions

- **Provider contract.** Pages and widgets only talk to `DataProvider`. Providers return raw facts; aggregation is the shared `QueryEngine`, so mock and backend behave identically.
- **Generic fact table.** Plan data is one table (version, period, measure, up to five dimension slots, value), so any model fits one RAP schema.
- **Data actions and multi actions run in the browser.** The engine works in memory and writes only the difference when every step succeeded.
- **Metadata is data.** Stories, models, actions and files are rows (with JSON for the parts that depend on type), edited by the same UI that shows them.

3. The application: pages and features

3.1 Home and Files

Home shows key metrics, recently changed objects and open tasks. Files lists all objects with folders, favourites, a search, and filters for stories, datasets and actions. Objects are opened, duplicated, moved or deleted from here.




Figure 1. Home: metrics, recently changed objects, tasks due




Figure 2. Files: folders, stories, datasets, actions

3.2 Stories

A story is a set of pages on a grid. Widgets come from a registry; each has a builder panel (model, measure, dimensions, filters, options). Story filters (input controls) apply to all widgets; a widget can override them. Stories can be viewed, edited, duplicated and published.

Widget	Purpose
chart.bar, line, donut, funnel, sankey, gauge	SVG charts with legends, hierarchy levels and hover values
kpi	Value with a comparison against a version, coloured by whether higher or lower is better; a Why? link opens the variance explainer
table	Cross-tab with hierarchies, totals, measure format (scale, decimals)
filter	Input control for a dimension
text	Explanatory text
planning.table	Editable planning table (chapter 4)
dataaction.trigger, multiaction.trigger	Buttons that run an action and ask for its parameters
variance	Headline and top contributors for the difference between two versions, with a link into the explorer




Figure 3. Story viewer: KPI tiles, charts, input control




Figure 4. Story page with tables and the variance explainer widget

3.3 Data Analyser

Pick a model, put dimensions on rows and columns, filter, and switch between table and chart. The same query engine as the stories is used, including hierarchies and the Date hierarchy (year, quarter, month).




Figure 5. Data Analyster

3.4 Datasets and Modeller

Datasets lists the models with their data. The Modeller follows the SAC layout: model structure on the left (measures, dimensions), details on the right.

Topic	What is possible
Measures	Aggregation (sum, average, minimum, maximum, count), exception aggregation by dimensions, data type, unit type, scale, decimals
Dimensions	Types (Generic, Organization, Account) with preset attributes, members with attributes and texts, one or more hierarchies per dimension, built-in Version, Date (with year > quarter > month) and Measure
Preferences	Planning capabilities, data locking, data audit
Data management	Preview, CSV import and export of facts, summary per version
Related objects	Stories, data actions, multi actions and tasks that use the model
CDS source	Live or import connection to a CDS view (chapter 6)




Figure 6. Datasets




Figure 7. Modeller: model structure and details

4. Planning in detail

The planning table (`planning.table`) is an editable cross-tab. Edits go to an unpublished buffer, are shown immediately in every widget of the page, and reach the backend only on **Publish Data**.

Feature	Behaviour
Editing	Type into a cell. A leaf cell writes that fact; a parent node, quarter or year spreads the value over the facts below it (proportional for sums, equal parts when the sum is zero)
Selection	Click, drag, or click a header to select a row, a column or the table; leaf cells only when an axis holds several levels
Copy and paste	Ctrl+C and Ctrl+V with the clipboard, plus toolbar buttons as fallback; paste spreads a block starting at the selected cell
Formula bar (fx)	Enter a number or an expression for the selected cells: <code>1200</code> , <code>*1.1</code> , <code>+500</code> , <code>-10%</code> , <code>=ACT*1.05</code> ; no eval, a small parser
Distribute values	Dialog to spread a total over the selection equally, by a reference version or proportionally
Undo and redo	Labelled steps; Version History lists the steps and undoes up to a step
Publish and discard	Publishes the buffer model by model; a locked version cannot be written; version work asks to publish first
Versions	Version Management dialog: public and private versions, create private copy, publish, revert, lock, unlock, delete
Version History	Unpublished steps of the session and, where the data source has one, the published change log (Data Audit)
Comments	Select one cell and press the comment button: list, add and delete comments; commented cells show a corner marker and the text as a tooltip




Figure 8. Planning story: editable table with a commented cell (corner marker)

5. Data actions and multi actions

5.1 Data actions

A data action is a flow of steps on one model, edited in a designer: the step flow on the left, the editor of the selected object on the right. The designer supports adding, duplicating, moving and deleting steps, undo and redo, Validate, Trace, Run and Save.

Concept	Detail
Parameters	Member parameters (a dimension, one or several members, defaults) and number parameters. In steps they are written @Name ; the run dialog and the trigger widget ask for them. The list shows where each is used
Copy	Rules per dimension (from, to; dates shift by whole years or quarters), aggregate-to, overwrite or append, copy factor
Allocation	Spread over target members equally, in proportion to existing values, or like a reference version; clear the source
Scale	Multiply the selected values by a factor
Fact Deletion	Delete the filtered facts (warning without a filter)
Embedded Data Action	Run another action of the same model with its own parameter values; loops are rejected
Validate	Errors and warnings per step: names, parameters, unknown dimensions or versions, locked targets, missing allocation fields, unused parameters; errors block Save
Trace	Dry run: per step created, updated and deleted counts and sample old and new values; nothing is written
Run history	Job Monitor: status, changed, duration, user, parameters, steps




Figure 9. Data Actions: list with last run




Figure 10. Data action designer: step flow and step editor




Figure 11. Trace: what every step would change

Run History

Status	Action	Type	Changed	Duration	User	Started
Succeeded	Forecast Q4 from run-rate Region=(all); Uplift=1.08	Data Action	960	20 ms	ME	10/6/2026, 1:59:46 AM
Succeeded	Statistical forecast	Multi Action	0	17 ms	ME	10/6/2026, 1:59:46 AM

Figure 12. Run History (Job Monitor)

5.2 Multi actions

A multi action runs steps in order; the first failing step stops the run and what earlier steps wrote stays written. Parameters of the multi action are asked for once and mapped onto the parameters of each data action step, onto fixed values, or left at the default of the data action.

Step type	What it does
Data Action	Run a data action with mapped parameters
Publish Version	Publish a version over another (ids or parameters)
Version Management	Create a private version, revert a private version, delete an unlocked version
Data Locking	Lock or unlock a version
Data Import	Load a CSV (pasted or from a file) into a version with a column mapping, long or wide format, checked row by row, stop or skip on errors, replace or add
Predictive	Statistical forecast per member combination: linear trend, moving average, exponential smoothing, same month last year; reports a back-test error
API	HTTP call with parameters in the URL, headers and body, expected status, timeout; no cookies are sent
PaPM Integration	Calls a PaPM function through a provider hook; the sample data source only simulates it
Comment Management	Copy the comments of a version to another version, or delete them
Import from Source	Copy rows of the CDS view behind an import model into a version for chosen months

Steps have a name, a description and an active switch. Validate checks existence, types, versions and locks and marks problem steps in the flow.

Analytics and Planning

Home

Files

Apps

Stories

Data Analyser

Datasets

Modeller

Planning

Data Actions

Multi Actions

Calendar

Predictive Scenarios

Compass

WA

Data: mock

Settings

Parameters (0)

Add Step

Validate

Run

Save

Statistical forecast

Start

1. Forecast Q4 from actuals
Predictive

2. Carry budget comments to ...
Comment Management

End

Predictive step

Forecast future months from the history of a version with a statistical method

Name
Forecast Q4 from actuals

Description
A straight line through Jan to Sep, continued to Oct to Dec

Step Active
☒ Step is active (inactive steps are skipped)

Model
Sales Plan

Measure to forecast
REVENUE

History from version
ACT

History from month
2026-01

History to month
2026-09

Write the forecast to version
FCT

Forecast from month
2026-10

Forecast to month
2026-12

Method
Linear trend

No problems found

A statistical forecast for every combination of members, from the months of the history. It is not SAP Smart Predict.

Figure 13. Multi action designer with Validate result

6. Data sources: CDS views (live and import)

A model can be connected to a CDS view, standard or custom, exposed as an OData V4 service. The same mapping serves two modes.

	Live	Import
Where the data is	In the CDS view, read when a story, table or analysis asks	Copied into versions of a planning model
Planning, versions, actions	No: read only, one locked version	Yes, on the copy
Currency of the data	Always current	As of the last import
Access control	CDS access control of the user who looks	CDS access control of the user who imports

Mapping

- Service URL (relative to the server, for example `/sap/opu/odata4/sap/zui_sac_gl/srvd_a2x/sap/zui_sac_gl/0001/`) and entity set; the dialog reads `$metadata` and lists the fields.
- Period field with its format: `202603` , `2026-03` or a date (summed by month).
- A field per dimension (with an optional text field) and per measure; a **currency field** because the service cannot add up an amount without it.
- Test reads a few values; *Also read the members and the period range* fills the dimensions from the source.

How it works

Live reads become `$apply=filter(...)/groupby((period, dimensions, currency),aggregate(field with sum as ZSAC_measure))` , so the service aggregates and only the result travels. If the service cannot aggregate it answers 501, 405 or a 400 that says so; the app then reads the rows as they are and aggregates them itself (up to MaxRows, 100 000 by default). Errors of the service are shown with their details and, for the currency case, a hint on what to set.

How to expose a CDS view

Wrap the standard or custom view in your own aggregating view entity (renaming fields, building the period, grouping), add a service definition and an OData V4 service binding, publish it. On ABAP Cloud only released views may be used. Details and an example for `I_JournalEntryItem` : `sap/docs/cds-sources.md` .




Figure 14. CDS source dialog (sample service): mapping and Test

Tested against a real service. The G/L view `ZI_SAC_GL_PERIOD` (service `ZUI_SAC_GL` , 1 092 rows, four company codes, two currencies, 182 accounts) was connected as a live model `GL_LIVE` and as an import model `GL_PLAN` . Findings from that test (alias clash, currency in the grouping) are fixed.

7. Analysis helpers: variance explainer and comments

7.1 Variance explainer (“why did it change?”)

Explains the difference of a measure between two versions or two sets of months, by the members of every dimension. It opens from the **Why?** link of a KPI tile with a comparison, or from the variance widget.

- **Headline** with the two values, the change and the sentence that names the biggest driver and, inside it, the next one (up to three levels, only while one member clearly leads), and what moves the other way.
- **Dimensions ranked** by how clearly one member holds the movement; shares are shares of all movement of the dimension, so they stay meaningful when changes cancel out.
- **Bars** per member with favourable and unfavourable colours (lower-is-better measures flip them); click a bar to drill into that member, chips remove a step.
- **Fair comparison:** when one version covers fewer months (actuals to September, budget to December) only the months both have are compared, with a note and a switch.
- A total that nets to zero still explains the parts that differ. Only measures that add up (sum, no exception aggregation) can be explained.




Figure 15. Variance explainer: headline, drivers, bars, drill chips

7.2 Comments on plan cells

A comment belongs to the coordinates of a cell (version, period, measure, member of each fixed dimension). The comment button of the planning toolbar opens the list, new comments get the user and time. Comment Management steps copy or delete the comments of a version. Stored in `ZSAC_COMMENT` (entity `CellComment`); the sample provider keeps them in browser storage.

8. Backend (ABAP RAP)

Sources are generated from one description (`sap/tools/sac_spec.py`) by `gen_rap.py` and `abapgit_meta.py` into the abapGit folder `sap/src` ; handlers and engines are written by hand.

Object	Contents
Tables	ZSAC_FILE, STORY, WIDGET, MODEL, DIM, MEASURE, VERSION, FACT, DATAACT, DASTEP, MULTIACT, MASTEP, RUN, COMMENT, CALTASK
Business objects	ZR_SAC_* managed (no draft, strict(2)), compositions Story-Widget, Model-Dimension/Measure, DataAction-Step, MultiAction-Step; ZC_SAC_* projections; external numbering, keys mandatory on create
Actions	Version: CreatePrivate (static), Publish, Revert. Fact: WriteFacts, DeleteFacts (bulk)
Classes	ZCL_SAC_FACT_WRITER, ZCL_SAC_VERSION_ENGINE, ZCL_SAC_SEED (sample data), behavior pools ZBP_R_SAC_*
Service	ZUI_SAC_O4 (OData V4 UI) with the binding created in ADT; UI5 app deployed as ZSAC_FIORI, launchpad descriptor in zsac_fiori_ui5r.uiad.json (ignored by abapGit)
Rules	Locked versions cannot be written; publish needs an unlocked target; the model structure is checked on save (a model with its dimensions in one request)

Lessons from the first activation

- Annotations in a view entity element list take no comma; abstract entity elements end with a semicolon.
- Column names LABEL and PAGES are reserved: DIM_LABEL, MEASURE_LABEL, PAGES_JSON.
- A dependent entity cannot have a field named like the etag master field: `ChildChangedAt` .
- A property must not be named like its entity type: FILE_KIND, WIDGET_KIND.
- Roots are written with their children in one request (deep insert) because the server validates a model when it is saved.

9. Installation, configuration and operation

9.1 Without a backend

```
cd sap/app/sacfiori
npm install
npm run start-mock      # sample data, nothing else needed
npm test                # in sap/app/saclib: unit tests of the engines and providers
```

9.2 With the backend

1. **ADT**: link the repository to package ZSAC_FIORI and pull (abapGit). Activate all. Where abapGit is not available, create the objects by other means.
2. Run the seed class `ZCL_SAC_SEED` (F9) in the client you use.
3. Create the service binding `ZUI_SAC_04` (OData V4 - UI) on the service definition and publish it. The service path is in `manifest.json`.
4. The user needs the business role with the IAM apps of the services (custom services on S/4HANA Cloud public edition are otherwise answered with 403).
5. **BAS**: clone the repository, then `npm install` and one of the start scripts below; open `index.html?provider=odata`.

Script	Backend destination
<code>npm start</code>	my402244 (ui5.yaml)
<code>npm run start-402225</code>	S4_402225_DEV (ui5-402225.yaml)
<code>npm run start-local, start-mock</code>	None (local proxy or sample data)
<code>npm run deploy, deploy-402225</code>	Deploys the app to the ABAP system of the destination (ui5-deploy*.yaml)

9.3 CDS source on another system

Use a relative service URL so the proxy and the destination add host and login. The app and the CDS data can live on different destinations only for testing (second backend entry in `ui5.yaml`); a deployed app reads the system it is deployed on.

9.4 Data provider

The provider is chosen by the URL parameter `?provider=odata` or `mock`, else by `sap.ui5/config/provider` of the manifest (mock). The header shows the active provider.

10. Verification status

10.1 Automated tests

221 unit tests in 31 files run with `node --test ( npm test in sap/app/saclib )`: engines, providers, schemas, planning, locking, sharing, CDS source, variance, steps, charts, story layout. All pass. The separate document *Unit Testing* (`sap/docs/SAC_Fiori_Unit_Testing.docx`) describes them.

10.2 Sample data (browser)

All pages and dialogs shown in this document were exercised in the browser on the sample data, also at phone width.

10.3 End-to-end test on the real system

The deployed app (S/4HANA Cloud, client 100, launchpad tile) was tested page by page with two accounts: the owner in one browser window and a second user in a private window. Everything created for the test is kept on the system as history data.

Area	Result
Home, Files, Stories (create, edit, save, publish, duplicate), pages and filters	works
All widget types on live CDS models (chart types, gauge, funnel, heatmap, treemap, variance, value driver tree, compass, KPI, table)	works after fixes 1, 2 and 9
Data Analyser: builder, result, CSV export, input control filter	works after fix 7
Datasets and Modeller: create, change currency and unit, refresh, delete	works after fix 5
Planning: private version, edit cells, publish, revert, spread, comments, data locking, CSV export	works after fixes 3, 4 and 8
Data actions and multi actions: dry run, run, large data and several currencies	works (329 facts, 8 steps)
Live and import models on the business CDS views (service <code>ZUI_SAC_BIZ</code>)	works after the new views
Calendar and reminders	works
Sharing and security with two users (read, edit, no access, everyone, delete, unshare)	works after fixes 5 and 6; the server refuses what the client hides
Phone layout (375 px): analyser, planning, designers, dialogs	works after fix 10
Excel and CSV download of the analyser and planning table	works , numbers rounded to six decimals
Multi action step PaPM	as designed : validates, then reports that no PaPM is connected (the test system has none)

10.4 Bugs found by the test and fixed

No.	Found	Fix
1	Explore pages failed with <i>500: No data retrieved from ABAP dictionary for entity ZI_SAC_GL_PERIOD</i> (the view was no longer active); several widgets stayed empty, gauge showed 0%	New business views and service <code>ZUI_SAC_BIZ</code> (<code>sap/data-cds</code>); the gauge shows the value or <i>No target set</i> instead of 0%; variance, value driver and compass get defaults from the model
2	<i>Not found: /Model ZTEST_PLAN</i> when a widget pointed at a deleted model	Plain error text in the widget; Planning and Analyser start with the first model that can be read
3	Publish of a private version: the server wanted a conditional request (<i>If-Match</i>)	The provider sends the action on the instance (<code>execute(undefined, true)</code>)
4	Planning: Export and Table Functions were disabled when the page opened	The table that was drawn is the active table (<code>plan.active</code>)
5	Delete of a model by a user who may only edit removed the data before the server refused; shares of the object stayed behind	The owner is checked first; shares are deleted with the object
6	Access was not enforced on the projections: a second user saw objects of the first	Projections are <code>#CHECK</code> and inherit the access controls of the entities (15 access controls, <code>sap/docs/adt-manual-access-controls.txt</code>)
7	Analyser CSV had numbers like 12345.6000000000001	Rounded to six decimals
8	Planning CSV had the expand and collapse triangles in the headers	The triangles are removed on export
9	Modeller panel got a height of 500 033 px; dialogs were clipped	Flex basis and dialog content rules in CSS
10	Phone: planning chart card wider than the screen, designers and analyser side by side	Cards fit the screen; flow and settings stack
11	Chart text (legend, axes) dark on dark in the dark theme	Chart text inherited a dark stroke from the page and was drawn with an outline; chart text never has a stroke now, and has explicit light colours in dark mode
12	The header burger looked like the menu of the SAP shell bar and expanded to the full width on a phone	A floating action button opens the navigation: a drawer over the page on narrow screens
13	Side navigation: no icons on the items under <i>Apps</i>	The items are first level, so every item shows its icon

The abapGit pull on the test system failed (conversion error, lock); the access controls were created by hand in ADT following the manual in `sap/docs/adt-manual-access-controls.txt` .

11. Known limits and open items

Open items

- Versions and cell comments are not owned objects; the run history is not filtered on the server (see `sharing-and-security.md`).
- The ABAP seed class registers no file entry for its story.
- No real PaPM connection (see below).

Limits

- Data actions run in one browser: large models read all facts of the model, there is no server job.
- The step flow of data and multi actions is linear (no branches or loops); cross-model copy is not included.
- Predictive is a plain statistical forecast (four methods, one back-test figure for the whole step), not SAP Smart Predict.
- The API step runs in the browser: CORS applies, no cookies or stored credentials; headers are stored with the step and must not hold secrets.
- PaPM is only simulated by the sample data source; a real connection means overriding `runPapm` in a provider. An own calculation engine is possible with the data and multi actions (allocations, formulas) or as ABAP, but it is not SAP PaPM.
- Data Locking works by regions (slices of versions, periods and members); private versions are not locked.
- CDS: members are read once when the dialog is confirmed; amounts of different currencies in one cell add up unless the currency is a dimension; the sum of all G/L accounts is zero because entries balance.
- Comments belong to cell coordinates (no replies or resolve state) and exist for the planning table only.
- Not included: Predictive Scenarios, Compass as a page, Just Ask, prompt insight widget, scripting, server side aggregation of the sample data.

12. Appendix

Repository layout

<code>.abapgit.xml</code>	abapGit configuration (folder <code>/sap/src/</code> , ignores binding, UIAD, BSP)
<code>README.md</code>	overview, features, deployment steps
<code>sap/src/</code>	ABAP sources, package <code>ZSAC_FIORI</code> (generated and hand written)
<code>sap/app/saclib/</code>	UI5 library <code>zsac.lib</code> (<code>src/zsac/lib</code> , <code>test/node</code>)
<code>sap/app/sacfiori/</code>	UI5 app <code>zsac.fiori</code> (<code>webapp</code> , <code>ui5*.yaml</code> , <code>uiad.json</code>)
<code>sap/tools/</code>	<code>sac_spec.py</code> , <code>gen_rap.py</code> , <code>abapgit_meta.py</code> , <code>make_mock_data.py</code>
<code>sap/docs/</code>	specifications and this document

Further documents

- `sap/docs/technical-specification.md` : details of every engine and the backend
- `sap/docs/cds-sources.md` : exposing and connecting CDS views
- `sap/docs/SAC_Fiori_Unit_Testing.docx` : the unit tests and end-to-end checks (built by `sap/tools/build_unit_testing_doc.py`)
- `sap/docs/widget-authoring.md` , `provider-authoring.md` : how to add a widget or a data source
- `sap/docs/SAC_Overview_and_PowerBI_Comparison.md` : SAC and Power BI compared

Glossary

Term	Meaning
Model, dataset	Dimensions and measures with their data (SAC: model)
Version	A set of plan values: actual, budget, forecast, private
Story	A dashboard of pages and widgets
Data action	Flow of steps that changes plan data, with parameters
Multi action	Ordered steps that run data actions, version work, imports and calls
CDS view	ABAP Core Data Services view; exposed as an OData V4 service to be used here
Live / Import	Read the CDS view on demand / copy its rows into versions
Deep insert	One request that creates a business object together with its children