



Features :-

- Irradiation Cross-Linking: Enhances thermal, mechanical, and chemical resistance.
- Global Standards Compliance: Meets IEC, RDSO, ISO 6722 & ISO 19642 requirements.
- Dual Coated Enameled Finish: Ensures superior insulation and durability.



Specifications :-

Parameters	Description
Voltage Rating	300V, 750V
Temperature Range	-40 C to +125 C
Mechanical Properties	High Flexibility, Vibration Resistance
Conductor Type	Tinned/ Bare Copper, Drawn Wires
Cross Linking Method	Electron Beam (E-Beam) Irradiation
Flame Retardance	Compliant with Flame Retardant low Smoke (FRLS) properties
Insulation Type	Irradiated XLPE, Dual Coated Enamel, PVC,
Standards	IEC Standards, RDSO (Railway), ISO 6722, ISO 19642 (Automotive)

WIRES

APPLICATIONS :-

- Refrigeration Compressors – Used in domestic & industrial cooling systems.
- Railway Coaches & Locomotives – For power, control, and signal wiring.
- Electric & Hybrid Vehicles – In high-performance automotive harnessing and battery systems.

Innovative Development for Quality Products

Works: Plot No. 101(HUDA), Sector-59, HSIIDC Industrial Estate, Faridabad- Haryana- 121004
Mob: +91-8448808000 | E-mail: info@technotrendz.co.in | Website: www.technotrendz.co.in