```
01.>
mysql>CREATE TABLE customer (
  custid int(11) NOT NULL,
  cname varchar(20) NOT NULL,
  adharnum varchar(20) NOT NULL UNIQUE,
  city varchar(20),
  state varchar(20),
 PRIMARY KEY ( custid ))
mysql>CREATE TABLE order1 (
  orderid int(11) NOT NULL,
  orderdate date NOT NULL,
  orderamt varchar(20),
 custid int(11),
 PRIMARY KEY ( orderid ),
 FOREIGN KEY ( custid ) REFERENCES customer ( custid ))
mysql> desc customer;
+----+
| Field | Type | Null | Key | Default | Extra |
+----+
| custid | int(11) | NO | PRI | NULL |
| adharnum | varchar(20) | NO | UNI | NULL |
+----+
mysql> desc order1;
+----+
| Field | Type | Null | Key | Default | Extra |
+----+
| orderamt | varchar(20) | YES |
                          | NULL
                                 custid | int(11) | YES | MUL | NULL
+----+
mysql> select * from customer;
+----+
| custid | cname | adharnum | city | state |
+----+
| 101 | Apurv | 1443223 | Jaipur | Raj
  102 | Akash | 3113123 | Jaunpur | UP | 103 | Omkar | 3463021 | Talegaon | Mahrashtra |
104 | Yogesh | 8885636 | Raipur | Chattisgarh |
105 | Pankaj | 3412900 | Jaipur | Raj |
  106 | Gurdeep | 9650003 | Jaunpur | UP
  107 | Pranav | 7500350 | Talegaon | Mahrashtra |
  108 | Gaurav | 7060405 | Mumbai | Maharashtra |
+----+
mysql> select * from order1;
+----+
| orderid | orderdate | orderamt | custid |
+----+

    1452 | 2017-01-23 | 150
    | 101 |

    1635 | 2018-06-01 | 55
    | 102 |

    1865 | 2018-08-01 | 32
    | 103 |

    2145 | 2018-12-01 | 345
    | 106 |
```

```
2345 | 2018-04-01 | 3242 | 103 | 2645 | 2018-09-01 | 788 | 104 | 3211 | 2018-02-01 | 456 | 101 | 3343 | 2018-07-01 | 8646 | 102 | 3413 | 2018-09-01 | 9545 | 106 | 6655 | 2018-05-01 | 98 | 102 | 7401 | 2018-10-01 | 552 | 104 | 7565 | 2018-03-01 | 654 | 101 | 7919 | 2018-12-01 | 999 | 105 | 2018-11-01 | 24
8090 | 2018-11-01 | 24
                             106 |
                         9711 | 2018-11-01 | 193 | 105 |
+----+
1.mysql> select * from customer
   -> where city in (select city from customer where cname like
'Akash');
+----+
| custid | cname | adharnum | city | state |
+----+
  102 | Akash | 3113123 | Jaunpur | UP | 106 | Gurdeep | 9650003 | Jaunpur | UP |
+----+
2.mysql> select * from customer c left join order1 o1
   -> on c.custid=o1.custid
   -> where ol.orderamt>(select avg(orderamt) from order1 o2 where
o2.custid=o1.custid group by o2.custid)
   -> order by 1;
+----+
----+
| custid | cname | adharnum | city | state | orderid |
orderdate | orderamt | custid |
+----+
----+
| 101 | Apurv | 1443223 | Jaipur | Raj |
                                             3211 | 2018-
02-01 | 456 | 101 |
| 101 | Apurv | 1443223 | Jaipur | Raj |
                                              7565 | 2018-
03-01 | 654 |
                101 |
| 102 | Akash | 3113123 | Jaunpur | UP
                                      3343 | 2018-
07-01 | 8646 | 102 |
| 103 | Omkar | 3463021 | Talegaon | Mahrashtra | 2345 | 2018-
04-01 | 3242 | 103 |
| 104 | Yogesh | 8885636 | Raipur | Chattisgarh | 2645 | 2018-
09-01 | 788 | 104 |
| 105 | Pankaj | 3412900
                      | Jaipur | Raj | 7919 | 2018-
12-01 | 999 | 105 |
| 106 | Gurdeep | 9650003
                      | Jaunpur | UP | 3413 | 2018-
09-01 | 9545 | 106 |
+----+
----+
3.mysql> select * from customer left join order1
   -> on order1.custid=customer.custid
   -> having order1.orderid is null;
---+----
| custid | cname | adharnum | city | state | orderid |
orderdate | orderamt | custid |
+----+
```

---+----+

```
NULL | NULL
   107 | Pranav | 7500350 | Talegaon | Mahrashtra |
        | NULL |
| NULL
| 108 | Gaurav | 7060405 | Mumbai | Maharashtra |
                                              NULL | NULL
      | NULL |
NULL
+----+
---+----+
_____
______
======
Q.2>
drop procedure if exists ordtype;
delimiter //
create procedure ordtype()
begin
declare otype varchar(20);
declare oid int;
declare oamt int;
declare odate date;
declare ocid int;
declare cend int default 0;
declare mycur cursor for select orderid, orderamt, orderdate, custid from
order1;
declare continue handler for NOT FOUND set cend=1;
open mycur;
label1:loop
fetch mycur into oid, oamt, odate, ocid;
if cend=1 then
leave label1;
end if;
if oamt>5000 then
set otype="express";
elseif oamt>=3000 then
set otype="fast";
else
set otype="regular";
end if;
select oid,odate,oamt,ocid,otype;
end loop;
close mycur;
end//
delimiter;
mysql> call ordtype();
```

```
+----+
-+----+
| 1452 | 2017-01-23 | 150 | 101 | regular |
+----+
1 row in set (0.01 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 1635 | 2018-06-01 | 55 | 102 | regular |
+----+
1 row in set (0.04 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 1865 | 2018-08-01 | 32 | 103 | regular |
+----+
1 row in set (0.09 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 2145 | 2018-12-01 | 345 | 106 | regular |
+----+
1 row in set (0.13 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 2345 | 2018-04-01 | 3242 | 103 | fast |
+----+
1 row in set (0.17 sec)
+----+
+----+
| 2645 | 2018-09-01 | 788 | 104 | regular |
+----+
1 row in set (0.21 sec)
+----+
+----+
| 3211 | 2018-02-01 | 456 | 101 | regular |
+----+
1 row in set (0.24 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 3343 | 2018-07-01 | 8646 | 102 | express |
+----+
1 row in set (0.27 \text{ sec})
+----+
+----+
| 3413 | 2018-09-01 | 9545 | 106 | express |
```

```
1 row in set (0.31 sec)
+----+
+----+
| 6655 | 2018-05-01 | 98 | 102 | regular |
+----+
1 row in set (0.35 sec)
+----+
| oid | odate | oamt | ocid | otype
+----+
| 7401 | 2018-10-01 | 552 | 104 | regular |
+----+
1 row in set (0.40 \text{ sec})
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 7565 | 2018-03-01 | 654 | 101 | regular |
+----+
1 row in set (0.45 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 7919 | 2018-12-01 | 999 | 105 | regular |
+----+
1 row in set (0.48 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 8090 | 2018-11-01 | 24 | 106 | regular |
+----+
1 row in set (0.51 sec)
+----+
| oid | odate | oamt | ocid | otype |
+----+
| 9711 | 2018-11-01 | 193 | 105 | regular |
+----+
1 row in set (0.54 sec)
_____
Q.3>
> use labexamb1
db.cust.insert({custid:111,custname:'Apurv',city:'Pune',creditamt:5000});
db.cust.insert({custid:222,custname:'Yogi',city:'Pune',creditamt:3000});
```

+----+

```
db.cust.insert({custid:333,custname:'Akash',city:'Apinapur',creditamt:250
db.cust.insert({custid:444,custname:'Omkar',city:'Talegaon',creditamt:100
db.cust.insert({custid:555,custname:'Vishal',city:'Kalyan',creditamt:8000
______
=====
> db.cust.find().pretty();
       " id" : ObjectId("5d9a17e540702a028ec29446"),
       "custid" : 111,
       "custname" : "Apurv",
       "city" : "Pune",
       "creditamt" : 5000
}
{
       " id" : ObjectId("5d9a189940702a028ec29447"),
       "custid" : 222,
       "custname" : "Yogi",
       "city" : "Pune",
       "creditamt" : 3000
}
{
       " id" : ObjectId("5d9a189940702a028ec29448"),
       "custid" : 333,
       "custname" : "Akash",
       "city" : "Apinapur",
       "creditamt" : 2500
}
{
       " id" : ObjectId("5d9a189940702a028ec29449"),
       "custid" : 444,
       "custname" : "Omkar",
       "city" : "Talegaon",
       "creditamt" : 1000
}
       " id" : ObjectId("5d9a189a40702a028ec2944a"),
       "custid" : 555,
       "custname" : "Vishal",
       "city" : "Kalyan",
       "creditamt": 8000
______
=====
> db.cust.find({city:/^.p.*/}).pretty();
       " id" : ObjectId("5d9a189940702a028ec29448"),
       "custid" : 333,
       "custname" : "Akash",
       "city" : "Apinapur",
```

```
"creditamt" : 2500
> db.cust.find({creditamt:{$in:[5000,3000,2500]}}).pretty();
        " id" : ObjectId("5d9a17e540702a028ec29446"),
        "custid" : 111,
        "custname" : "Apurv",
        "city" : "Pune",
        "creditamt" : 5000
}
{
        " id" : ObjectId("5d9a189940702a028ec29447"),
        "custname" : "Yogi",
        "city" : "Pune",
        "creditamt": 3000
}
{
        " id" : ObjectId("5d9a189940702a028ec29448"),
        "custid" : 333,
        "custname" : "Akash",
        "city" : "Apinapur",
        "creditamt" : 2500
}
```