Literature Review: The Evolution of P&ID Digitization

The academic and industrial pursuit of automated Piping and Instrumentation Diagram (P&ID) digitization has been the subject of intense, multidisciplinary research over the past decade. Within the highly complex, capital-intensive, and heavily regulated process industries—a domain encompassing oil and gas refineries, petrochemical manufacturing plants, nuclear power generation facilities, pharmaceutical manufacturing, and large-scale municipal water treatment utilities—P&IDs represent the absolute foundational blueprints for all engineering operations. These intricate, high-density schematic drawings serve as the primary reference documents that dictate the physical equipment layout, the overarching process control philosophy, the thermodynamic fluid flow connectivity, and the highly critical safety interlock systems required to maintain stable plant operations.

A P&ID acts as a visual manifestation of the plant's operational logic, illustrating the functional relationship between massive mechanical equipment and the delicate instrumentation and control loops that govern their behavior. From these two-dimensional visual representations, Electrical and Instrumentation (E&I) engineers are tasked with the massive responsibility of manually translating graphical schematics into an array of critical, downstream structured engineering deliverables. The most vital of these structured documents include the Instrument Index, the Input/Output (I/O) List, the Alarm List, and the automated Trip List, frequently formalized as a Cause and Effect Matrix. The financial burden of this manual process is staggering; industrial analyses indicate that manual instrument data extraction and cross-checking can cost a single engineering office upwards of $1.5 million annually just in expended labor hours.

Moreno-García et al. (2018) highlighted the profound disconnect between the rapid advancements in general machine vision and the persistent stagnation in the digitization of complex engineering drawings (EDs). Their foundational survey identified the fundamental necessity of defining a standardized framework for transforming raster drawings into "contextualized" digital knowledge, noting that the sheer high density and entanglement of information in P&IDs present unique computational challenges not found in standard object detection tasks. The literature collectively establishes that treating P&IDs merely as static collections of geometric shapes and isolated text strings leads to a systemic failure formally defined as the "Contextual Integrity Gap". A comprehensive review of the existing literature reveals that the methodological approaches to solving this problem have evolved through four distinct technical stages. However, despite rapid advancements in neural network architectures and natural language processing, a critical analysis demonstrates that pure machine vision and pure generative language models independently fail to bridge the semantic requirements of industrial process engineering without deterministic guardrails.

Evolutionary Paradigm	Primary Technological Mechanisms	Core Engineering Output	Fundamental Limitations
Stage 1: Classical Image Processing	Morphological thinning, Otsu's thresholding, Local Binary Patterns (LBP), Template Matching.	Vectorized geometric contours, isolated component identification.	Extreme algorithmic fragility, lack of scale invariance, destruction of semantic metadata.
Stage 2: Deep Learning Object Detection	Convolutional Neural Networks (CNNs), YOLOv3, Faster R-CNN, Generative Adversarial Networks (GANs).	High-precision bounding-box localization, mitigation of rare symbol class imbalance.	Yields only uncontextualized Cartesian coordinates; lacks functional engineering logic.
Stage 3: Topological & OCR Integration	Graph-based structural modeling, EAST text detectors, LSTM sequence recognizers.	Topological flow sequences, deep text extraction, dictionary-based connectivity.	Catastrophic failures in text-to-symbol association due to reliance on Euclidean proximity heuristics.
Stage 4: Vision-Language & Knowledge Graphs	Large Language Models (LLMs), Labeled Property Graphs (LPG), Graph-RAG, Text2Cypher.	Semantic reasoning, zero-hallucination querying, ISA-5.1 standard alignment.	Requires rigorous deterministic engineering guardrails to prevent unsafe probabilistic inferences.

Stage 1: Classical Rule-Based Image Processing and Morphological Analysis

The foundational era of engineering drawing digitization relied heavily on deterministic image processing, morphological mathematics, and hard-coded heuristic rules. These early computational frameworks typically utilized sequential preprocessing steps to clean noisy, degraded, and scanned legacy diagrams, which are frequently subject to scanning artifacts, faded drafting ink, and background discoloration.

Techniques such as global binarization, adaptive local thresholding (such as Otsu's method), and noise filtering were employed to mathematically separate the foreground drafting ink from the background paper artifacts. As outlined in the conceptual framework developed by Moreno-García et al. (2018), this was frequently followed by skeletonization or morphological thinning—a mathematical transformation designed to

iteratively reduce the pixel volume of thick process lines to a single-pixel width. Theoretically, this operation allowed algorithms to trace continuous line connectivity, map pipe routing, and construct rudimentary "netlists" where symbols act as nodes and interconnecting connectors act as edges.

For the recognition of equipment symbols, these classical approaches employed strict contour analysis combined with manually engineered visual descriptors. Pioneering research by Tan et al. (2016) demonstrated a highly specialized framework targeting the automated identification of process components in raster P&IDs with minimal pre-processing, an approach designed specifically for the marine and offshore industries where bespoke, non-standardized drafting styles are prevalent. Tan et al. (2016) utilized the Local Binary Pattern (LBP) as a primary visual descriptor, capturing the foundational shape information of a symbol regardless of ambient noise by comparing the intensity of neighboring pixels to a central pixel and thresholding the results into a binary string.

To achieve scale and rotation stability, Tan et al. (2016) integrated Spatial Pyramid Matching (SPM), a technique that divides the image into increasingly fine geometric grids, allowing the mathematical model to compute and compare local blocks of a sub-image rather than the entire global geometry. The system operated on a "linear sliding window" approach, calculating L1 distances between LBP-based descriptors of image patches and relying on exact geometric matching against a pre-registered library. A significant technical achievement of this work was its capacity to function utilizing only a single template example per component type, completely circumventing the requirement for the massive, manually labeled training datasets that constrain modern deep learning architectures.

As researchers recognized the limitations of pure template matching, attempts were made to augment classical heuristics with early machine learning classifiers. Elyan et al. (2018) investigated the classification of symbols within scanned P&IDs by focusing on the "within-class and cross-class similarity" problem, which makes functionally distinct instruments—such as pressure transmitters versus flow transmitters—difficult to distinguish. Their methodology introduced a semi-automatic approach relying on heuristic-based localization to isolate specific primitives, such as utilizing Hough transforms to detect circular sensor bubbles, followed by the extraction of features to train supervised classifiers including Random Forests (RF) and Support Vector Machines (SVM). A critical innovation within this research was the deployment of unsupervised k-means clustering for "class decomposition". By mathematically decomposing a broad class like "Valve" into multiple hidden morphological subclasses, the system significantly boosted the classification accuracy of traditional models, enabling the creation of structured symbol databases from legacy unstructured drawings.

Operating at the culmination of the Stage 1 paradigm, Kang et al. (2019) developed an end-to-end conversion tool designed to transform imaged drawings into "intelligent" P&IDs capable of direct integration with commercial industrial CAD platforms, such as Aveva P&ID. To overcome the degradation of primary process pipelines in poor-quality scans, Kang et al. (2019) applied a sliding-window blob analysis algorithm that tracked lines as continuous geometric masses rather than individual pixels. Filtering algorithms based on aspect ratios were then deployed to successfully distinguish between thick primary process lines and thin secondary utility lines. The system employed early OCR engines, specifically Tesseract, to recognize textual attributes and utilized a recursive algorithm to sort symbol connections by flow direction, successfully establishing logical "From-To" thermodynamic sequences. This pipeline demonstrated substantial industrial utility, yielding a reported 16-fold reduction in manual drafting hours during the front-end engineering design (FEED) stage through the automated generation of Bill of Materials (BOM) and initial Instrument Lists.

However, the literature from Stage 1 consistently documents extreme algorithmic fragility inherent to rule-based image processing pipelines. While these techniques achieved high precision in strictly controlled, highly standardized, and perfectly scanned drafting environments, they inherently lacked scale invariance and spatial generalization capabilities. As Tan et al. (2016) and Kang et al. (2019) explicitly noted, a slight shift in drafting style, a minor rotation of a symbol, or a transition from oil refinery symbol libraries to nuclear plant symbol libraries rendered template-matching algorithms completely obsolete. This fragility necessitated extensive, continuous manual recalibration by software engineers. Furthermore, morphological thinning operations, as detailed by Moreno-García et al. (2018), frequently destroyed vital semantic information, erasing the directionality of flow arrows or conflating the thickness of primary process lines with the thin dashed lines representing critical electrical signal wires, thereby ruining the downstream logic extraction required for complex functional safety modeling.

Stage 1 Algorithm	**Mathematical Function**	**Engineering Implementation**	**Documented Failure Modes**
Otsu's Thresholding	Adaptive variance minimization.	Separating drafting ink from paper artifacts.	Fails in heavily degraded, unevenly illuminated legacy scans.
Morphological Thinning	Iterative pixel reduction to central skeleton.	Tracing connectivity along process pipe lines.	Destroys flow directionality arrows and

Stage 1 Algorithm	Mathematical Function	Engineering Implementation	Documented Failure Modes
			obfuscates line thickness semantics.
Local Binary Patterns (LBP)	Thresholding neighbor pixels to build binary histograms.	Extracting scale-invariant shape descriptors.	Highly sensitive to arbitrary symbol rotation and variations in drafting scale.
Sliding Window Blob Analysis	Continuous mass tracking across Cartesian coordinates.	Reconstructing broken pipelines in faded drawings.	Computationally intensive; struggles with dense intersecting line intersections.

Stage 2: Deep Learning and Uncontextualized Object Detection

The democratization and hardware acceleration of deep Convolutional Neural Networks (CNNs) initiated a massive paradigm shift in the literature, reframing P&ID digitization from a brittle, pixel-matching exercise into a generic, multi-class object detection problem. Researchers aggressively pivoted away from manual feature engineering toward the robust, automatic feature learning capabilities of deep neural architectures, dramatically improving spatial localization across diverse drafting standards.

Extensive studies successfully applied single-stage detectors to localize dozens of symbol classes simultaneously across high-resolution industrial diagrams. Elyan et al. (2020) demonstrated the efficacy of the YOLOv3 (You Only Look Once) architecture for unified, real-time object detection. Unlike classical rule-based template matching, the YOLO architecture utilizes an advanced, anchor-free bounding-box regression algorithm operating over a Cross Stage Partial Network backbone, allowing the model to globally reason over an entire massive P&ID sheet ($7,500 \times 5,250$ pixels) simultaneously. Elyan et al. (2020) successfully customized the network to predict bounding boxes and class label vectors for 25 distinct P&ID symbol classes, achieving robust symbol recall rates exceeding 94% on complex engineering drawings.

Despite these remarkable successes in bounding-box localization, the application of CNNs exposed a severe "class imbalance" problem inherent to all industrial engineering datasets. Standard components, such as manual gate valves or simple temperature indicators, may appear thousands of times in a specific training set, providing ample empirical data for the optimization of neural weights. Conversely, critical, highly specialized instruments—such as self-actuating pressure regulators, specialized blow-down valves, or complex logic solvers—appear rarely. This causes the neural network to

remain biased toward majority classes, yielding low sensitivity for the exact rare equipment that is most crucial for plant safety analysis.

To systematically combat this statistical data scarcity bottleneck, Elyan et al. (2020) integrated Deep Generative Adversarial Networks (GANs) into the computer vision pipeline. Specifically, the researchers utilized a Multiple Fake Class Generative Adversarial Network (MFC-GAN) to synthesize highly realistic, artificial variations of minority-class symbols. The GAN architecture pits a generator network against a discriminator network, allowing the system to learn the underlying graphical distribution of a specific rare symbol. This innovation allowed the model to learn from as few as two real-world instances to generate thousands of plausible synthetic training samples. By artificially augmenting the training dataset, the MFC-GAN vastly improved the sensitivity of the classifiers to rare equipment, elevating detection rates for underrepresented minority classes from near-zero to statistically viable levels.

In a parallel methodological approach, researchers heavily explored two-stage detection frameworks to maximize precision on small, tightly clustered components. Gao et al. (2020) utilized the Faster R-CNN architecture equipped with a deep ResNet-50 backbone to automate the extraction of components specifically for Nuclear Power Plant (NPP) safety analysis. Because nuclear Design Control Documents (DCDs) contain highly dense, microscopic components scattered across massive schematic sheets, standard detectors frequently fail to localize small items like nozzles or spec breaks. Gao et al. (2020) proposed a novel "feature grouping strategy" that mathematically grouped and detected components based on similar aspect ratios and scales separately. Enhanced by multi-scale feature extraction and Region of Interest (RoI) Align optimization, this two-stage approach achieved an impressive 98% average precision (AP) for component localization, establishing an exceptionally reliable spatial baseline for downstream nuclear fault tree analysis.

The application of high-sensitivity CNNs to engineering drawings, however, introduced a secondary complication: the proliferation of false positives triggered by "dummy" graphical noise. Industrial schematics are heavily populated with revision clouds, intersecting coordinate grid lines, isolated flow arrows, and textual leader lines that mimic the geometric properties of physical instrumentation. To systematically filter out this nuisance data, Yun et al. (2020) proposed a strategy utilizing a specialized Deep Neural Network equipped with a custom Region Proposal Network (RPN). The system applied morphological transformations and bounding-box size constraints to extract candidate regions, followed by the deployment of unsupervised learning techniques, specifically Deep Adaptive Clustering (DAC) and k-means clustering. These clustering algorithms mathematically decomposed the broad feature space, aggressively grouping "dummy" instances into distinct nuisance patterns. By formally assigning these clusters as "negative classes," the subsequent CNN classifier was trained to actively distinguish

between true mechanical symbols and background drafting clutter. This innovative filtering approach achieved a dummy detection rate of only 0.39%, significantly outperforming contemporary models that relied exclusively on positive symbol training data.

However, the fundamental limitation of Stage 2 research remained pervasive across all surveyed deep learning literature: the models yielded only isolated spatial coordinates and localized class label vectors. The artificial intelligence successfully learned to answer "what" a symbol was and "where" it was located on the Cartesian plane, but completely failed to answer "how" that specific symbol functioned within a broader thermodynamic system or electrical control loop. Bounding-box detection identified the physical existence of instruments but provided no mechanism to logically tie those instruments to a Basic Process Control System. The contextual engineering intent—the critical requirement for generating an Instrument Index or an automated Trip List—was entirely absent, necessitating the next evolutionary leap into topological modeling.

Deep Learning Architecture	**Primary Function in P&ID Digitization**	**Dataset Optimization Strategy**	**Inherent Architectural Limitation**
YOLOv3 (Single-Stage)	Unified, real-time bounding-box regression across massive sheet resolutions.	Integration of MFC-GAN for synthetic minority-class augmentation.	Struggles with highly clustered, microscopic geometric features.
Faster R-CNN (Two-Stage)	High-precision region proposal followed by dedicated ResNet-50 classification.	Multi-scale feature grouping strategy for distinct aspect ratios.	Computationally heavy; patch-cropping frequently truncates symbols.
RPN with DAC Clustering	Explicit modeling and suppression of non-symbol drafting artifacts.	Unsupervised negative class generation for "dummy" noise.	Relies heavily on rigid, pre-defined spatial priors and aspect ratios.

Stage 3: Graph-Based Topological Modeling and Optical Character Recognition

Moving beyond flat, uncontextualized geometric object detection, subsequent academic research formally acknowledged that intelligent P&ID digitization required the explicit reconstruction of the diagram's physical topology alongside the robust extraction of its vital alphanumeric tagging data. Graph-based structural modeling emerged as the primary computational solution to resolve the semantic gap. In this

paradigm, physical equipment components, such as positive displacement pumps and instrument bubbles, are treated as vertices (nodes) within a directed graph, while the interconnecting primary process pipelines, secondary capillary lines, and electrical signal wires are treated as directional edges mapping fluid and signal flow.

To reconstruct this complex physical layout, researchers developed sophisticated connectivity algorithms. Gao et al. (2020) moved beyond isolated lists of valves by developing complex dictionaries representing component-to-pipe upstream and downstream relationships. By implementing a rigid bounding-box expansion rule based on geometric intersection, the system mapped which specific piping segment a component was located on, generating the structural data representation required for logical and physical flow analysis in nuclear facilities. Concurrently, Kang et al. (2019) applied recursive topological sorting algorithms to explicitly establish logical "from-to" fluid flow sequences across the schematic, ensuring that the directed graph accurately mirrored the true thermodynamic path of the process fluid.

The foundational identifiers of any critical E&I deliverable—such as the Instrument Index, the I/O List, or the Alarm List—are the textual annotations embedded within the P&ID. Extracting this data poses severe challenges, as standard commercial OCR engines perform notoriously poorly on engineering documents due to arbitrary text orientations, vertical stacking, extreme font variability, and text physically overlapping with dense geometric drafting lines.

To solve this, advanced text localization networks paired with deep learning sequence recognizers were deployed. Jamieson et al. (2020) tackled the digitization of highly dense text regions within complex Oil & Gas P&IDs by deploying the Efficient and Accurate Scene Text (EAST) detector. The EAST detector operates as a highly advanced fully convolutional network (FCN) capable of predicting precise bounding boxes and rotational angles for words regardless of their orientation amidst extreme graphical clutter. Once the multi-oriented text regions were localized and cropped, they were fed into the Tesseract v4 OCR engine, which utilized advanced Long Short-Term Memory (LSTM) sequence recognizers. The integration of recurrent neural networks like LSTM allowed the model to maintain sequence context and robustly decode complex pixel patterns into structured alphanumeric strings.

Jamieson et al. (2020) achieved an impressive 90% detection rate for text strings—including highly problematic vertical and diagonal orientations—and correctly recognized 86% of the detected instances. To further optimize text extraction in distinct industrial domains, Gao et al. (2020) successfully utilized the SegLink model, favoring its specific robustness against oriented text strings to extract line numbers and tag IDs in nuclear plant schematics.

Despite these monumental advancements in topological modeling and robust LSTM-based text extraction, a critical bottleneck prevented Stage 3 frameworks from achieving fully autonomous E&I deliverable generation. The accurate association of extracted text strings to their corresponding graphical symbols remained catastrophically unreliable. The vast majority of the literature, including the sophisticated pipelines developed by Kang et al. (2019) and Gao et al. (2020), relied heavily on crude "closest-distance" or Euclidean proximity heuristics to execute text-to-symbol mapping.

In highly dense, spatially compressed industrial schematics, these Euclidean proximity rules fail catastrophically. A textual tag for an instrument—such as Flow Indicator Controller "FIC-101"—might physically sit closer on the 2D Cartesian plane to the discharge nozzle of an entirely unrelated pump or an adjacent cooling water line. Because the algorithms lacked true semantic understanding, they blindly associated the tag with the closest geometry. A 10% failure rate in text-to-symbol association introduces unacceptable data integrity risks. In the context of the IEC 61511 functional safety standard, erroneously mapping a critical high-high level switch (LSHH) tag to the wrong safety shutdown valve (SDV) completely invalidates the boolean trip algebra required to populate a Cause and Effect Matrix. This Euclidean failure mode renders the automated output fundamentally dangerous, precluding Stage 3 systems from being autonomously deployed for safety-critical documentation.

Text Extraction Methodology	Computational Architecture	Key Advantage	Documented Limitation
EAST Text Detector	Fully Convolutional Network (FCN).	Robust localization of multi-oriented and vertical alphanumeric strings.	Misclassifies complex dashed line styles and flow arrows as text objects.
LSTM Sequence Recognizer	Recurrent Neural Network (RNN).	Maintains contextual sequence data to decode highly degraded font pixels.	Merges adjacent short strings; struggles with heavy text-to-line overlap.
SegLink Detector	Segment linking across oriented text maps.	Highly precise extraction of pipeline line numbers and complex tag IDs.	Requires extensive parameter tuning to handle extreme scaling variances.

Stage 4: Emerging Vision-Language Models and Knowledge Graphs

The most recent frontier in P&ID digitization research, documented heavily throughout 2024 and 2025, formally acknowledges that purely visual algorithms, isolated OCR engines, and Euclidean proximity heuristics cannot independently overcome the Contextual Integrity Gap. Modern engineering data extraction requires the computational ability to logically reason over the complex thermodynamic and electrical relationships embedded within the schematic. Consequently, contemporary literature has introduced the concept of querying and reasoning over P&IDs using Natural Language by deeply integrating structured Knowledge Graphs (KGs) with advanced Large Language Models (LLMs) and Vision-Language Models (VLMs).

Recognizing that generalized, off-the-shelf LLMs lack the domain-specific spatial awareness required to interpret engineering diagrams, researchers sought to establish dedicated benchmarking and training methodologies. Pioneering research by Gupta et al. (2025) addressed the critical gap between raw engineering design documentation and intuitive, natural language information retrieval. To systematically evaluate and train generative models on industrial schematics, the researchers introduced the PIDQA dataset.

The PIDQA dataset represents a massive compilation comprising 64,000 highly specialized question-answer pairs derived from 500 P&ID sheets. The queries within the dataset are rigorously categorized to benchmark varying levels of cognitive and spatial reasoning within generative models: (I) simple counting (e.g., tallying total specific valve types), (II) spatial counting, (III) spatial connections (e.g., verifying the topological link between an analog transmitter and a digital logic solver), and (IV) complex value-based entity reasoning. By forcing LLMs to engage with the PIDQA dataset, researchers demonstrated that dynamic, few-shot sampling and schema contextualization robustly elevated the accuracy of generative models by up to 43.5%, allowing the artificial intelligence to comprehend the syntactic rules of engineering connectivity even under conditions of high lexical diversity. This marked the crucial transition from treating P&IDs as flat images to treating them as interactive, queryable knowledge bases.

While VLMs demonstrate impressive reasoning capabilities, asking a multimodal generative model to visually interpret a raw, high-density PDF image inherently introduces the catastrophic risk of AI "hallucination"—the probabilistic generation of factually incorrect, physically impossible engineering connections. In the context of producing an automated Alarm List or Safety Instrumented System (SIS) verification document, generative hallucinations pose severe, unacceptable safety hazards.

To completely neutralize this risk, advanced frameworks documented in the current literature have moved to decouple the probabilistic visual perception phase from the deterministic reasoning phase. Cutting-edge systems now utilize standardized industrial data models, such as the DEXPI (Data Exchange in Process Industry) XML schema, to cast raw, YOLO-extracted geometries and OCR-extracted text into

semantically enriched Labeled Property Graphs (LPG) via tools like the pyDEXPI Python package. Within an LPG, physical equipment, pipelines, and decoded instrument tags are permanently serialized as rigid mathematical nodes and edges within a robust graph database structure, such as Neo4j.

This serialization enables the deployment of Graph-based Retrieval-Augmented Generation (Graph-RAG). When a user query or an automated backend script requests the generation of a complex engineering deliverable—such as tracing a multi-page safety shutdown loop to compile an I/O list—the system does not query the pre-trained, probabilistic internal weights of the LLM. Instead, the architecture utilizes a Text2Cypher retriever to translate the natural language prompt directly into a syntactically correct Cypher graph query language script. The system executes the Cypher query against the Neo4j database to retrieve the exact, deterministic topological relationships representing the true physical piping structure.

By passing this rigidly constrained, mathematically verified factual context into the context window of the LLM, the architecture forces the generative model to condition its reasoning strictly upon actual graph data. Furthermore, by embedding deterministic mathematical and lexical guardrails derived directly from global industrial engineering standards—specifically the exhaustive syntactical rules mandated by the ANSI/ISA-5.1 standard for instrument tagging and the IEC 61511 standard for safety logic—the architecture inherently prevents unsafe inferences. The deterministic logic maps detected process causes (e.g., a High-High pressure breach, PSHH) to hardwired automated effects (e.g., closing a Shutdown Valve, SDV), ensuring absolute compliance with safety doctrines.

This semantic orchestration via Graph-RAG entirely bypasses pixel-level visual ambiguity and proximity heuristic failures. It enables the hybrid AI system to accurately classify complex signal typologies and populate rigorous, audit-ready deliverables without fabricating non-existent safety interlocks, successfully bridging the Contextual Integrity Gap that hindered earlier stages of P&ID digitization.

References

C. F. Moreno-García, E. Elyan, and C. Jayne, "New trends on digitisation of complex engineering drawings," *Neural Comput. Appl.*, vol. 31, no. 6, pp. 1695–1712, 2019.

W. C. Tan, I.-M. Chen, and H. K. Tan, "Automated Identification of Components in Raster P&IDs with Minimal Pre-Processing," 2016.

E. Elyan, C. Moreno-García, and C. Jayne, "Symbols Classification in Engineering Drawings," in *Proc. Int. Joint Conf. Neural Netw. (IJCNN)*, 2018.

S.-O. Kang, E.-B. Lee, and H.-K. Baek, "A Digitization and Conversion Tool for Imaged Drawings to Intelligent P&ID," *Energies*, vol. 12, no. 13, p. 2593, 2019.

E. Elyan, L. Jamieson, and A. Ali-Gombe, "Deep learning for symbols detection and classification in engineering drawings," *Neural Netw.*, vol. 129, pp. 91–102, 2020.

W. Gao, Y. Zhao, and C. Smidts, "Component detection in P&IDs of nuclear power plants based on neural networks," 2020.

L. Jamieson, C. F. Moreno-García, and E. Elyan, "Deep Learning for Text Detection and Recognition in Complex Engineering Diagrams," in *Proc. Int. Joint Conf. Neural Netw. (IJCNN)*, 2020.

D.-Y. Yun, S.-K. Seo, U. Zahid, and C.-J. Lee, "Deep Neural Network for Automatic Image Recognition of Engineering Diagrams," *Appl. Sci.*, vol. 10, no. 11, p. 4005, 2020.

M. Gupta, C. Wei, T. Czerniawski, and R. Eiris, "PIDQA—Question Answering on Piping and Instrumentation Diagrams," *Mach. Learn. Knowl. Extr.*, vol. 7, no. 2, p. 39, 2025.