

# Lab: Amazon Cognito

## Lab overview and objectives

---

In this lab, you will use **Amazon Cognito** to create user pool and an application client.

After completing this lab, you should be able to:

- Create a user pool and application client from the **AWS Management Console**.
- Create a new **App Client**.
- Create a new user from Cognito App client login page.
- Connect an HTML page to the Cognito App client login page and use it to log in to your HTML page.
- Create a new user using Python SDK.

# Scenario


You will create a **User Pool** and **App Client** and connect an HTML page with the Cognito login page.

## Accessing the AWS Management Console

For this lab, we will use the **AWS Academy learner lab** and the **AWS Management Console**.

## Task 1: Create a User Pool

1. In the AWS Console search box to the right of **Services**, search for and choose **Cognito** to open the **Cognito** console.
2. Press **Create user pool**.



3. In the **Set up your application** screen, configure these settings:
  - In **Define your application** frame, set the **Name your application** name, as: **My First Cognito Web App**.

### Define your application

Choose an application type and give it a name.

**Application type** | [Info](#)

Choose the type of application that you're developing. Your choice determines the example i

☒ **Traditional web application**  
An application hosted on a webserver. Uses redirects and separate pages to display information. Examples are Java, Python, nodeJS.

☐ **Single-page application**  
Modifies the current web page interaction. Examples are JavaScript, Angular, React.

**Name your application** | [Info](#)

My First Cognito Web App

Names are limited to 128 characters or fewer. Names may only contain alphanumeric charac

- In **Configure options** frame, **Options for sign-in identifiers** check boxes, Select the check box **Email**.

### Configure options

You must make a few initial choices about

#### Options for sign-in identifiers [Info](#)

Choose sign-in attributes. Usernames can be an email address or a phone number. If a phone number is an option, users can sign in with any

☒ Email

☐ Phone number

☐ Username

4. Press the **Create** button.

Once done, an Upload succeeded message will appear.

✔ Your application "My First Cognito Web App" and user pool "User pool - ndqrhv" have been created successfully! Follow the instruction to continue the setup.


5. Press the **Overview** button.
6. Press the **Rename** button and set the **User pool name** to **My First User Pool**, and press **Save changes**. A success message will appear, and you will see your user pool name has changed.

✔ User pool name has been updated successfully.


**Overview: My First User Pool** [Info](#)

## Task 2: Create a user from Cognito application login page

1. In the AWS Console search box to the right of **Services**, search for and choose **Cognito** to open the **Cognito** console.
2. At the left menu, select the **User Pools** menu.




3. A list of all your User Pools will appear. Select the user pool you created **My First User Pool**.



The **Overview** page will appear.

4. At the left menu, under the **Applications** menu, select the **App Clients** sub menu. You will see your application:



5. Select the application, the **App Client** screen will open.
6. At the right, select the **View login page** link. The **Sign in** page will open.

## Sign in

Sign in to your account.

**Email address**

**Next**

New user? [Create an account](#)

- As the user pool is empty, select the **Create an account** link, fill up your details, and sign up.

## Sign up

Create a new account.

**Email address**

**Password**

- ✓ Password must be at least 8 characters
- ✓ Use a number
- ✓ Use a lowercase letter
- ✓ Use an uppercase letter
- ✓ Use a symbol

**Confirm password**

☐ Show password

**Sign up**

Have an account already? [Sign in](#)

- Go to your email inbox, look for You verification code email,

## Your verification code Inbox x




no-reply@verificationemail.com

to me ▼

Your confirmation code is 642616

copy the code and paste it into the **Confirm your account** screen and press **Confirm account**.

### Confirm your account



We have sent a code in an Email message to y\*\*\*@g\*\*\*. To confirm your account, enter your code.

**Code**

[Resend code](#)

**Confirm account**

**Back**

9. Your account is now created, and you should see a default successful login page.


## Successfully signed in

**This is the default redirect page for Amazon Cognito user pools.**

10. At the left menu, under the **User Management** menu, select the **Users** sub menu. You will see the user you have just created:

### Users [Info](#)

**Users (1)** [Info](#)

 [Delete user](#) [Create user](#)

View, edit, and create users in your user pool. Users that are enabled and confirmed can sign in to your user pool.


Property: User name ▼

	User name	Email address	Email verified	Confirmation status	Status
<input type="radio"/>	<a href="#">94b864d8-f061-70fc-d933-...</a>	yogevshani1@gmail.com	Yes	<span>Confirmed</span>	<span>Enabled</span>

## Task 3: Connect HTML page to Cognito application login page

You will connect the Cognito login page to a basic HTML page and view **Cognito** tokens based on **Cognito authorization code**.

1. We will now get the Cognito App **Client ID** & **Client Secret**. Go back to your application overview page and copy the **Client ID** & **Client Secret** values.



**Amazon Cognito** <

Current user pool [View all](#)

My First User Pool ▼

Overview

▼ **Applications**

App clients

▼ **User management**

Users

### App client: My First Cognito Web App [Info](#)

#### App client information

**App client name**  
My First Cognito Web App

**Client ID**  
2md7b64jhoaqqo59rafb7isi05

**Client secret**  
\*\*\*\*\*

☐ Show client secret

2. We will now get the Cognito User Pool **Domain**. At the left menu, under the **Branding** menu, select the **Domain** sub menu. Once **Domain** Overview is open, in the **Domain** frame, copy the **Domain** value:

## Domain

### Domain [Info](#)

Configure a domain for managed login. A domain is required for authenticat  
OIDC IdP.

### Cognito domain


#### Domain

https://us-east-1ynsi6eit0.auth.us-east-1.amazoncognito.com

#### Branding version

Managed login

3. . Additionally, note down your **region**, available at the top drop-down menu.



4. Create a basic HTML page that will be launched after Cognito successful login and query Cognito tokens with the token send back to the HTML.

Alternatively, use the following code. Make sure to replace the next tags: <Your-App-Client-ID >, <-App-Client-Secret >; your redirect URI; <Your-Cognito-Domain> & <region>.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Hello World with Cognito</title>
</script>
  async function exchangeCodeForTokens(code) {
    const clientId = '<Your-App-Client-ID>'; // Replace with your Cognito App Client ID
    const clientSecret = '<Your-App-Client-Secret>'; // Replace with your Cognito App Client Secret (if
applicable)
    const redirectUri = 'http://localhost:8000/index.html'; // Replace with your redirect URI
    const tokenUrl = 'https://<Your-Cognito-Domain>.auth.<region>.amazoncognito.com/oauth2/token'; //
Replace with your Cognito token endpoint

    const body = new URLSearchParams({
      grant_type: 'authorization_code',
      client_id: clientId,
      redirect_uri: redirectUri,
      code: code
    });

    try {
      const response = await fetch(tokenUrl, {
        method: 'POST',
        headers: {
          'Content-Type': 'application/x-www-form-urlencoded',
          Authorization: 'Basic ' + btoa(`${clientId}:${clientSecret}`)
        },
      },
```



```

        body
    });

    if (response.ok) {
        const data = await response.json();
        return data;
    } else {
        throw new Error('Failed to exchange code for tokens');
    }
} catch (error) {
    console.error('Error exchanging code:', error);
    document.getElementById('userInfo').innerText = 'Error retrieving user information';
}
}

function parseJwt(token) {
    const base64Url = token.split('.')[1];
    const base64 = base64Url.replace(/-/g, '+').replace(/_/g, '/');
    const jsonPayload = decodeURIComponent(atob(base64).split('').map(function(c) {
        return '%' + ('00' + c.charCodeAt(0).toString(16)).slice(-2);
    }).join(''));

    return JSON.parse(jsonPayload);
}

async function displayUserInfo() {
    const searchParams = new URLSearchParams(window.location.search);
    const code = searchParams.get('code');

    if (code) {
        // Handle Authorization Code Flow
        const tokens = await exchangeCodeForTokens(code);

        if (tokens && tokens.id_token) {
            const userDetails = parseJwt(tokens.id_token);
            const userInfoDiv = document.getElementById('userInfo');

            // Display all user details
            userInfoDiv.innerHTML = '<h3>User Details:</h3><ul>';
            for (const [key, value] of Object.entries(userDetails)) {
                userInfoDiv.innerHTML += `<li><strong>${key}</strong> ${value}</li>`;
            }
            userInfoDiv.innerHTML += '</ul>';
        } else {
            document.getElementById('userInfo').innerText = 'Unable to retrieve user details';
        }
    } else {
        document.getElementById('userInfo').innerText = 'No authorization information found';
    }
}


```

```
}

window.onload = displayUserInfo;
</script>
</head>
<body>
  <h1>Cognito - Authorization Code Flow Example</h1>
  <div id="userInfo">Loading user information...</div>
</body>
</html>
```

5. Save the html page as index.html and put it in any folder. Start a Local Web Server to access the HTML page from web browser.

1. Open the **Command Prompt** or **Terminal**.
2. Navigate to the folder containing your HTML file: `cd <path>`
3. Start the web server. Example with Python 3.x: `python -m http.server 8000`
4. Verify you can access your HTML file from a web browser (i.e. Chrome):  
`http://localhost:8000/index.html`



## Cognito - Authorization Code Flow Example

No authorization information found

6. Go back to your Cognito App Client overview page, select the **Login Pages** tab, and select the **Edit** button.

App client: My First Cognito Web App [Info](#)

[Delete](#) [View login page](#)

App client information [Edit](#)

App client name

My First Cognito Web App

Client ID

2md7b64jhoaqqo59rafb7isi05

Client secret

\*\*\*\*\*

☐ Show client secret

Authentication flows

[Choice-based sign-in](#)  
[Secure remote password \(SRP\)](#)  
[Get user tokens from existing authenticated sessions](#)

Authentication flow session duration

3 minutes

Refresh token expiration

5 day(s)

Access token expiration

60 minutes

ID token expiration

60 minutes

Advanced authentication settings

[Enable token revocation](#)  
[Enable prevent user existence errors](#)

Created time

December 14, 2024 at 18:14 GMT+2

Last updated time

December 14, 2024 at 18:14 GMT+2

Quick setup guide

Attribute permissions

**Login pages**

Threat protection

Analytics

Managed login pages configuration [Info](#)

[Edit](#) [View login page](#)

Configure the managed login pages for this app client.

7. In the Edit managed login pages configuration page, in the Managed login pages frame, set the URL to your html page, i.e. <http://localhost:8000/index.html> and press **Save changes**.

## Edit managed login pages configuration [Info](#)

Managed login is a convenient interface for adding sign-up and sign-in to your app. The interface includes a pool and third-party providers.

### Managed login pages

Configure the managed login pages for this app client.

#### Allowed callback URLs [Info](#)

Enter at least one callback URL to redirect the user back to after authentication. This is typically the URL of your application or a third-party provider.


#### URL

<http://localhost:8000/index.html>

8. A success message should appear:

✔ App client "My First Cognito Web App" has been updated successfully.

9. Press the **View login page**, and login, your HTML page should open with the tokens received using the **Cognito authorization code** passed to the HTML:



## Cognito - Authorization Code Flow Example

### User Details:

- **at\_hash:** I1CYu\_wc9kbqjY4EFydrfg
- **sub:** 94b864d8-f061-70fc-d933-802dbbd0c463
- **email\_verified:** true
- **iss:** https://cognito-idp.us-east-1.amazonaws.com/us-east-1\_Ynsi6EIT0
- **cognito:username:** 94b864d8-f061-70fc-d933-802dbbd0c463
- **origin\_jti:** e1c0f7ec-8f02-472a-baa4-70d087404a68
- **aud:** 2md7b64jhoaqqo59raf7isi05
- **token\_use:** id
- **auth\_time:** 1734464477
- **exp:** 1734468077
- **iat:** 1734464477
- **jti:** 1c205c4e-95c8-4b08-b5ea-b8d32ef899a0
- **email:** yogevshani1@gmail.com

# Task 4: Create a user from Python Boto3 SDK

---

In this task, you will create a user using Boto3. Python knowledge is required.

1. Create a Python script that interacts with an AWS Cognito and create a new user.

1.1 Import Required Libraries

- Import ``boto3`` for AWS SDK.
- Import ``hmac``, ``hashlib``, and ``base64`` for cryptographic operations.

2.1 Set Up Configuration Variables

- Define ``client_id``, ``client_secret``, ``username``, ``password``, and ``email`` with appropriate values.

3.1 Define Function to Calculate ``SECRET_HASH``:

- Create a function ``calculate_secret_hash`` that takes ``client_id``, ``client_secret``, and ``username`` as inputs.
- Concatenate ``username`` and ``client_id`` to create a message.
- Create a HMAC-SHA256 hash of the message using the ``client_secret``.
- Base64-encode the hash and return it.

4.1 Initialize Cognito Client:

- Use ``boto3`` to initialize a Cognito client with the specified AWS region (``us-east-1``).

5.1 Sign Up User:

- Use a ``try`` block to attempt to sign up the user with the ``sign_up`` method of the Cognito client.
- Pass ``ClientId``, ``Username``, ``Password``, and ``UserAttributes`` (which includes the email).
- Include the ``SECRET_HASH`` calculated earlier.
- Print the response if the sign-up is successful.
- Use an ``except`` block to catch any exceptions and print the error message.

- Alternatively, copy the following code, and paste it in your IDE:

**Note:** Replace **COGNITO\_APP\_CLIENT\_ID** and **COGNITO\_APP\_CLIENT\_SECRET**, with your actual AWS credentials, similarly, replace the region-name with the region-name you are using. Additionally, **replace** **USER\_NAME** and **USER\_EMAIL**.

```
import boto3
import hmac
import hashlib
import base64

# Configuration
client_id = '<COGNITO_APP_CLIENT_ID>' # Replace with your App Client ID
client_secret = '<COGNITO_APP_CLIENT_SECRET>' # Replace with your App Client Secret
username = '<USER_NAME>'
password = 'StrongPassword123!'
email = '<USER_EMAIL>'

# Function to calculate SECRET_HASH
def calculate_secret_hash(client_id, client_secret, username):
    message = username + client_id
    dig = hmac.new(client_secret.encode('utf-8'), message.encode('utf-8'), hashlib.sha256).digest()
    return base64.b64encode(dig).decode('utf-8')

# Initialize Cognito client
client = boto3.client('cognito-idp', region_name='us-east-1')

# Sign up user
try:
    response = client.sign_up(
        ClientId=client_id,
        Username=username,
        Password=password,
        UserAttributes=[
            {'Name': 'email', 'Value': email}
        ],
        SecretHash=calculate_secret_hash(client_id, client_secret, username)
    )
    print("User signed up successfully:", response)
except Exception as e:
    print("Error during sign up:", e)
```

3. Install boto3 module.

Verify if boto3 is installed, in your terminal run:

```
pip show boto3
```

if you're getting a warning:

WARNING: Package(s) not found: boto3

You should install boto3 by running the next command in your terminal:

```
pip install boto3
```

4. Run the code. You should get the following successful reply:

```
{'UserConfirmed': False, 'CodeDeliveryDetails': {'Destination': 'y***@m***', 'DeliveryMedium':  
'EMAIL', 'AttributeName': 'email'}, 'UserSub': '94f814f8-50a1-70b3-6095-b818c88fc7a1', 'Session':  
'AYABeIkToOKP72so58IwwO4ozEAHQABAAAdTZXJ2a WNIABBD2duaXRvVXNlcIBvb2xzAAEAB  
2F3cy1rbXMAS2Fybphd3M6a21zOnVzLWVhc3QtMT03NDU2MjM0Njc1NTU6a2V5L2IxNTVhZmNh  
LWJmMjktNGVlZC1hZmQ4LWE5ZTA5MzY1M2RiZQC4AQIBAHjHL4WD3WpekpFe85nxP9Nwg99u  
3bPN6BTsAB-  
uHZcTLAFewyP7GotYDSqP0ppayLvPAAAAfjB8BgkqhkiG9w0BBwagbzBtAgEAMGgGCSqGSIb3DQ  
EHATAeBgglghkgBZQMEAS4wEQQMDR0VySo8iOe9sytWAgEQgDs-  
UvEijQyIZHERXD9B72Dpn2DyOkOKPHVUKFfIY_DILLr_1A4_XDFQK0u2OFDy_piUy-  
jtOgvBYdV5jAIAAAAADAAAEAAAAAAAAAAAAAAAAAAATjEu3LGDK3dMuQWBMHh2l_____w  
AAAAEAAAAAAAAAAAAAAAAAAEAAAFcriKf1_9siy22hMD2YDe0BdQzvTGuoq9DXnzSDOq41syk7sj  
fUNN0Be82WIA6rxLTtWmxXrLPKLbMRj2eNpSKgVj9NAb-rcCPh-  
GA3NfjEeOf6uIgOyBbenfhWsuYwzpoG8gDT2h74Bg_NGby5f3MuCxDD78-cq3NlgGSAY-  
fDudw3CMYU3WsZijVIG_V3Gzde6tvsl1PKvRYAFY5bB8p8Suuf_uT_AGLouZy-dPb0-  
VJGoVWDII6VIUnjTIYowHv8vbR6lQfV8ElXJimluXwMV AhH6POAIL Y7inHJdikD6W52x2Znl0MwU  
S6NCqd9HH7seUBD_hOPGM5f1e_OWtnuzFkAHsQ08pp8mQsWRoP-  
_ayMmqhYuOxxd3X_cilWnyUJSh2Cs4O3dz-uMqmg1umwOS3RXPmiJcd3b3XPcaLNWP3iTfY-  
uOZqQEK_EUuBQTL67enwXPCgHym9RIFMKNasaqtuMnV-lkRvECwpJg', 'ResponseMetadata':  
{'RequestId': '23370591-dd75-4068-b829-6f1e04dfef74', 'HTTPStatusCode': 200, 'HTTPHeaders':  
{'date': 'Sat, 21 Dec 2024 15:11:06 GMT', 'content-type': 'application/x-amz-json-1.1', 'content-length':  
'1186', 'connection': 'keep-alive', 'x-amzn-requestid': '23370591-dd75-4068-b829-6f1e04dfef74'},  
'RetryAttempts': 0}}
```

## Task 5: Explore the new user created using AWS SDK (Boto3) from the AWS Console

---

1. In the AWS Console go back to Cognito to the User Pool and in the left menu, under the **User Management** menu, select the **Users** sub menu. You will see you're the user you have just created:

Users Info

Users (2) Info

Delete user
Create user

View, edit, and create users in your user pool. Users that are enabled and confirmed can sign in to your user pool.

Property: User name
Search users by attribute

User name

Email address

Email verified

Confirmation status

Status

94b864d8-f061-70fc-d933-...

yogevshani1@gmail.com

Yes

Confirmed

Enabled

94f814f8-50a1-70b3-6095-...


yogevsh@mta.ac.il

No

Unconfirmed

Enabled

- The user **Confirmation status** will be **Unconfirmed**. In your mailbox you should see a confirmation code email, that can be used to confirm the user from a python script.



## Activity complete

Congratulations! You have successfully completed the activity.