

Normalization

Database Normalization is a technique of organizing the data in the database. Normalization is a systematic approach of decomposing tables to eliminate data redundancy and undesirable characteristics like Insertion, Update and Deletion Anomalies. It is a multi-step process that puts data into tabular form by removing duplicated data from the relation tables. This module discuss the basic and higher normal forms.

4.1 Objectives

- ❖ To study the process of normalization and refine the database design
- ❖ To normalize the tables upto 4NF and 5NF
- ❖ To study lossless and lossy join operations
- ❖ To study inference rules
- ❖ To study other dependencies and Normal Forms.

4.2 Introduction to DB design

Each relation schema consists of a number of attributes, and the relational database schema consists of a number of relation schemas. So far, we have assumed that attributes are grouped to form a relation schema by using the common sense of the database designer or by mapping a database schema design from a conceptual data model such as the ER or Enhanced-ER (EER) data model. These models make the designer identify entity types and relationship types and their respective attributes, which leads to a natural and logical grouping of the attributes into relations.


Database Design deals with coming up with a 'good' schema. There are two levels at which we can discuss the goodness of relation schemas:

1. The logical (or conceptual) level—how users interpret the relation schemas and the meaning of their attributes.
2. The implementation (or physical storage) level —how the tuples in a base relation are stored and updated. This level applies only to schemas of base relations

An Example

- STUDENT relation with attributes: studName, rollNo, gender, studDept
- DEPARTMENT relation with attributes: deptName, officePhone, hod
- Several students belong to a department
- studDept gives the name of the student's department

Correct schema:



Incorrect schema:

Studdept

StudName	rollNo	gender	deptName	officePhone	HOD
----------	--------	--------	----------	-------------	-----

Problems with bad schema

- **Redundant storage of data:**
 - Office Phone & HOD info -stored redundantly once with each student that belongs to the department
 - wastage of disk space
- **A program that updates Office Phone of a department**
 - must change it at several places
 - more running time
 - error-prone

4.3 Informal Design Guidelines for Relation Schemas

- Four informal guidelines that may be used as measures to determine the quality of relation schema design:
 1. Making sure that the semantics of the attributes is clear in the schema
 2. Reducing the redundant information in tuples
 3. Reducing the NULL values in tuples
 4. Disallowing the possibility of generating spurious tuples
- These measures are not always independent of one another

4.3.1 Imparting Clear Semantics to Attributes in Relations

- **semantics** of a relation refers to its meaning resulting from the interpretation of attribute values in a tuple
- Whenever we group attributes to form a relation schema, we assume that attributes belonging to one relation have certain real-world meaning and a proper interpretation associated with them
- The easier it is to explain the semantics of the relation, the better the relation schema design will be

Guideline 1

- Design a relation schema so that it is easy to explain its meaning
- Do not combine attributes from multiple entity types and relationship types into a single relation

- if a relation schema corresponds to one entity type or one relationship type, it is straightforward to interpret and to explain its meaning
- if the relation corresponds to a mixture of multiple entities and relationships, semantic ambiguities will result and the relation cannot be easily explained.

Examples of Violating Guideline 1




Fig: schema diagram for company database

- Both the relation schemas have clear semantics
- A tuple in the EMP_DEPT relation schema represents a single employee but includes additional information—the name (Dname) of the department for which the employee works and the Social Security number (Dmgr_ssn) of the department manager.
- A tuple in the EMP_PROJ relates an employee to a project but also includes the employee name (Ename), project name (Pname), and project location (Plocation)
- logically correct but they violate Guideline 1 by mixing attributes from distinct real-world entities:
 - EMP_DEPT mixes attributes of employees and departments
 - EMP_PROJ mixes attributes of employees and projects and the WORKS_ON relationship
- They may be used as views, but they cause problems when used as base relations

4.3.2 Redundant Information in Tuples and Update Anomalies

- One goal of schema design is to minimize the storage space used by the base relations
- Grouping attributes into relation schemas has a significant effect on storage space
- For example, compare the space used by the two base relations EMPLOYEE and DEPARTMENT with that for an EMP_DEPT base relation
- In EMP_DEPT, the attribute values pertaining to a particular department (Dnumber, Dname, Dmgr_ssn) are repeated for every employee who works for that department

- In contrast, each department's information appears only once in the DEPARTMENT relation. Only the department number Dnumber is repeated in the EMPLOYEE relation for each employee who works in that department as a foreign key

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	gender	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

Figure 1: One possible database state for the COMPANY relational database schema

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

PROJECT				WORKS_ON		
Pname	Pnumber	Plocation	Dnum	Essn	Pno	Hours
ProductX	1	Bellaire	5	123456789	1	32.5
ProductY	2	Sugarland	5	123456789	2	7.5
ProductZ	3	Houston	5	666884444	3	40.0
Computerization	10	Stafford	4	453453453	1	20.0
Reorganization	20	Houston	1	453453453	2	20.0
Newbenefits	30	Stafford	4	333445555	2	10.0
				333445555	3	10.0
				333445555	10	10.0
				333445555	20	10.0
				999887777	30	30.0
				999887777	10	10.0
				987987987	10	35.0
				987987987	30	5.0
				987654321	30	20.0
				987654321	20	15.0
				888665555	20	NULL

DEPENDENT				
Essn	Dependent_name	gender	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse

Figure 1 : One possible database state for the COMPANY relational database schema

EMP_DEPT							Redundancy	
Ename	Ssn	Bdate	Address	Dnumber	Dname	Dmgr_ssn		
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555		
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555		
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321		
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321		
Narayan, Ramesh K.	666884444	1962-09-15	975 FireOak, Humble, TX	5	Research	333445555		
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555		
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321		
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555		

EMP_PROJ						Redundancy		Redundancy	
Ssn	Pnumber	Hours	Ename	Pname	Plocation				
123456789	1	32.5	Smith, John B.	ProductX	Bellaire				
123456789	2	7.5	Smith, John B.	ProductY	Sugarland				
666884444	3	40.0	Narayan, Ramesh K.	ProductZ	Houston				
453453453	1	20.0	English, Joyce A.	ProductX	Bellaire				
453453453	2	20.0	English, Joyce A.	ProductY	Sugarland				
333445555	2	10.0	Wong, Franklin T.	ProductY	Sugarland				
333445555	3	10.0	Wong, Franklin T.	ProductZ	Houston				
333445555	10	10.0	Wong, Franklin T.	Computerization	Stafford				
333445555	20	10.0	Wong, Franklin T.	Reorganization	Houston				
999887777	30	30.0	Zelaya, Alicia J.	Newbenefits	Stafford				
999887777	10	10.0	Zelaya, Alicia J.	Computerization	Stafford				
987987987	10	35.0	Jabbar, Ahmad V.	Computerization	Stafford				
987987987	30	5.0	Jabbar, Ahmad V.	Newbenefits	Stafford				
987654321	30	20.0	Wallace, Jennifer S.	Newbenefits	Stafford				
987654321	20	15.0	Wallace, Jennifer S.	Reorganization	Houston				
888665555	20	Null	Borg, James E.	Reorganization	Houston				

Fig: Sample states for EMP_DEPT and EMP_PROJ resulting from applying NATURAL JOIN to the relations in Figure 1

- Storing natural joins of base relations leads to an additional problem referred to as **update anomalies**. These can be classified into:
 - insertion anomalies
 - deletion anomalies,
 - modification anomalies

Insertion Anomalies

- Insertion anomalies can be differentiated into two types, illustrated by the following examples based on the EMP_DEPT relation:
 1. To insert a new employee tuple into EMP_DEPT, we must include either the attribute values for the department that the employee works for, or NULLs
 - For example, to insert a new tuple for an employee who works in department number 5, we must enter all the attribute values of department 5 correctly so that they are *consistent* with the corresponding values for department 5 in other tuples in EMP_DEPT
 - In the design of Employee in fig 1, we do not have to worry about this consistency problem because we enter only the department number in the employee tuple; all other attribute values of department 5 are recorded only once in the database, as a single tuple in the DEPARTMENT relation
 2. It is difficult to insert a new department that has no employees as yet in the EMP_DEPT relation. The only way to do this is to place NULL values in the attributes for employee
 - This violates the entity integrity for EMP_DEPT because Ssn is its primary key
 - This problem does not occur in the design of Figure 1 because a department is entered in the DEPARTMENT relation whether or not any employees work for it, and whenever an employee is assigned to that department, a corresponding tuple is inserted in EMPLOYEE.

Deletion Anomalies

- The problem of deletion anomalies is related to the second insertion anomaly situation just discussed
 - If we delete from EMP_DEPT an employee tuple that happens to represent the last employee working for a particular department, the information concerning that department is lost from the database
 - This problem does not occur in the database of Figure 2 because DEPARTMENT tuples are stored separately.

Modification Anomalies

- In EMP_DEPT, if we change the value of one of the attributes of a particular department—say, the manager of department 5—we must update the tuples of *all* employees who work in that department; otherwise, the database will become inconsistent
- If we fail to update some tuples, the same department will be shown to have two different values for manager in different employee tuples, which would be wrong

Guideline 2

- Design the base relation schemas so that no insertion, deletion, or modification anomalies are present in the relations
- If any anomalies are present, note them clearly and make sure that the programs that update the database will operate correctly
- The second guideline is consistent with and, in a way, a restatement of the first guideline
- These guidelines may sometimes have to be violated in order to improve the performance of certain queries.

4.3.3 NULL Values in Tuples


- If many of the attributes do not apply to all tuples in the relation, we end up with many NULLs in those tuples
 - this can waste space at the storage level
 - may lead to problems with understanding the meaning of the attributes
 - may also lead to problems with specifying JOIN operations
 - how to account for them when aggregate operations such as COUNT or SUM are applied
- SELECT and JOIN operations involve comparisons; if NULL values are present, the results may become unpredictable.
- Moreover, NULLs can have multiple interpretations, such as the following:
 - The attribute *does not apply* to this tuple. For example, Visa_status may not apply to U.S. students.
 - The attribute value for this tuple is *unknown*. For example, the Date_of_birth may be unknown for an employee.
 - The value is *known but absent*; that is, it has not been recorded yet. For example, the Home_Phone_Number for an employee may exist, but may not be available and recorded yet.

Guideline 3

- As far as possible, avoid placing attributes in a base relation whose values may frequently be NULL
- If NULLs are unavoidable, make sure that they apply in exceptional cases only and do not apply to a majority of tuples in the relation
- Using space efficiently and avoiding joins with NULL values are the two overriding criteria that determine whether to include the columns that may have NULLs in a relation or to have a separate relation for those columns with the appropriate key columns
- For example, if only 15 percent of employees have individual offices, there is little justification for including an attribute Office_number in the EMPLOYEE relation; rather, a relation EMP_OFFICES(Essn, Office_number) can be created to include tuples for only the employees with individual offices.

4.3.4 Generation of Spurious Tuples

- Consider the two relation schemas EMP_LOCS and EMP_PROJ1 which can be used instead of the single EMP_PROJ



- A tuple in EMP_LOCS means that the employee whose name is Ename works on *some project* whose location is Plocation
- A tuple in EMP_PROJ1 refers to the fact that the employee whose Social Security number is Ssn works Hours per week on the project whose name, number, and location are Pname, Pnumber, and Plocation.

EMP_LOCS

Ename	Plocation
Smith, John B.	Bellaire
Smith, John B.	Sugarland
Narayan, Ramesh K.	Houston
English, Joyce A.	Bellaire
English, Joyce A.	Sugarland
Wong, Franklin T.	Sugarland
Wong, Franklin T.	Houston
Wong, Franklin T.	Stafford
Zelaya, Alicia J.	Stafford
Jabbar, Ahmad V.	Stafford
Wallace, Jennifer S.	Stafford
Wallace, Jennifer S.	Houston
Borg, James E.	Houston

EMP_PROJ1

Ssn	Pnumber	Hours	Pname	Plocation
123456789	1	32.5	ProductX	Bellaire
123456789	2	7.5	ProductY	Sugarland
666884444	3	40.0	ProductZ	Houston
453453453	1	20.0	ProductX	Bellaire
453453453	2	20.0	ProductY	Sugarland
333445555	2	10.0	ProductY	Sugarland
333445555	3	10.0	ProductZ	Houston
333445555	10	10.0	Computerization	Stafford
333445555	20	10.0	Reorganization	Houston
999887777	30	30.0	Newbenefits	Stafford
999887777	10	10.0	Computerization	Stafford
987987987	10	35.0	Computerization	Stafford
987987987	30	5.0	Newbenefits	Stafford
987654321	30	20.0	Newbenefits	Stafford
987654321	20	15.0	Reorganization	Houston
888665555	20	NULL	Reorganization	Houston

- Suppose that we used EMP_PROJ1 and EMP_LOCS as the base relations instead of EMP_PROJ. This produces a particularly bad schema design because we cannot recover the information that was originally in EMP_PROJ from EMP_PROJ1 and EMP_LOCS
- If we attempt a NATURAL JOIN operation on EMP_PROJ1 and EMP_LOCS, the result produces many more tuples than the original set of tuples in EMP_PROJ
- Additional tuples that were not in EMP_PROJ are called **spurious tuples** because they represent spurious information that is not valid.
- The spurious tuples are marked by asterisks (*)

Ssn	Pnumber	Hours	Pname	Plocation	Ename
123456789	1	32.5	ProductX	Bellaire	Smith, John B.
* 123456789	1	32.5	ProductX	Bellaire	English, Joyce A.
123456789	2	7.5	ProductY	Sugarland	Smith, John B.
* 123456789	2	7.5	ProductY	Sugarland	English, Joyce A.
* 123456789	2	7.5	ProductY	Sugarland	Wong, Franklin T.
666884444	3	40.0	ProductZ	Houston	Narayan, Ramesh K.
* 666884444	3	40.0	ProductZ	Houston	Wong, Franklin T.
* 453453453	1	20.0	ProductX	Bellaire	Smith, John B.
453453453	1	20.0	ProductX	Bellaire	English, Joyce A.
* 453453453	2	20.0	ProductY	Sugarland	Smith, John B.
453453453	2	20.0	ProductY	Sugarland	English, Joyce A.
* 453453453	2	20.0	ProductY	Sugarland	Wong, Franklin T.
* 333445555	2	10.0	ProductY	Sugarland	Smith, John B.
* 333445555	2	10.0	ProductY	Sugarland	English, Joyce A.
* 333445555	2	10.0	ProductY	Sugarland	Wong, Franklin T.
* 333445555	3	10.0	ProductZ	Houston	Narayan, Ramesh K.
333445555	3	10.0	ProductZ	Houston	Wong, Franklin T.
333445555	10	10.0	Computerization	Stafford	Wong, Franklin T.
* 333445555	20	10.0	Reorganization	Houston	Narayan, Ramesh K.
333445555	20	10.0	Reorganization	Houston	Wong, Franklin T.

- Decomposing EMP_PROJ into EMP_LOCS and EMP_PROJ1 is undesirable because when we JOIN them back using NATURAL JOIN, we do not get the correct original information

- This is because in this case Plocation is the attribute that relates EMP_LOCS and EMP_PROJ1, and Plocation is neither a primary key nor a foreign key in either EMP_LOCS or EMP_PROJ1.

Guideline 4

- Design relation schemas so that they can be joined with equality conditions on attributes that are appropriately related (primary key, foreign key) pairs in a way that guarantees that no spurious tuples are generated
- Avoid relations that contain matching attributes that are not (foreign key, primary key) combinations because joining on such attributes may produce spurious tuples.

4.4 Functional Dependencies

- Formal tool for analysis of relational schemas that enables us to detect and describe some of the problems in precise terms

Definition of Functional Dependency

- A functional dependency is a constraint between two sets of attributes from the database.
- Given a relation R, a set of attributes X in R is said to **functionally determine** another attribute Y, also in R, (written $X \rightarrow Y$) if and only if each X value is associated with at most one Y value.
- X is the determinant set and Y is the dependent attribute. Thus, given a tuple and the values of the attributes in X, one can determine the corresponding value of the Y attribute.
- The abbreviation for functional dependency is FD or f.d. The set of attributes X is called the left-hand side of the FD, and Y is called the right-hand side.
- A functional dependency is a property of the semantics or meaning of the attributes.
- The database designers will use their understanding of the semantics of the attributes of R to specify the functional dependencies that should hold on all relation states (extensions) r of R.
- Consider the relation schema EMP_PROJ;

EMP_PROJ

SSN	PNUMBER	HOURS	ENAME	PNAME	PLOCATION
-----	---------	-------	-------	-------	-----------

- From the semantics of the attributes and the relation, we know that the following functional dependencies should hold:

- a. $Ssn \rightarrow Ename$
- b. $Pnumber \rightarrow \{Pname, Plocation\}$
- c. $\{Ssn, Pnumber\} \rightarrow Hours$

- These functional dependencies specify that
 - (a) the value of an employee's Social Security number (Ssn) uniquely determines the employee name (Ename)
 - (b) the value of a project's number (Pnumber) uniquely determines the project name (Pname) and location (Plocation), and
 - (c) a combination of Ssn and Pnumber values uniquely determines the number of hours the employee currently works on the project per week (Hours).
- Alternatively, we say that Ename is functionally determined by (or functionally dependent on) Ssn, or *given a value of Ssn, we know the value of Ename*, and so on.
- Relation extensions $r(R)$ that satisfy the functional dependency constraints are called **legal relation states** (or **legal extensions**) of R
- A functional dependency is a property of the relation schema R, not of a particular legal relation state r of R
- Therefore, an FD cannot be inferred automatically from a given relation extension r but must be defined explicitly by someone who knows the semantics of the attributes of R

Diagrammatic notation for displaying FDs

- Each FD is displayed as a horizontal line
- The left-hand-side attributes of the FD are connected by vertical lines to the line representing the FD
- The right-hand-side attributes are connected by the lines with arrows pointing toward the attributes.




Fig: diagrammatic notation for displaying FDs

Example:

A	B	C	D
a1	b1	c1	d1
a1	b2	c2	d2
a2	b2	c2	d3
a3	b3	c4	d3

- The following FDs *may hold* because the four tuples in the current extension have no violation of these constraints:
 - $B \rightarrow C$
 - $C \rightarrow B$
 - $\{A, B\} \rightarrow C$
 - $\{A, B\} \rightarrow D$
 - $\{C, D\} \rightarrow B$.
- The following *do not* hold because we already have violations of them in the given extension:
 - $A \rightarrow B$ (tuples 1 and 2 violate this constraint)
 - $B \rightarrow A$ (tuples 2 and 3 violate this constraint)
 - $D \rightarrow C$ (tuples 3 and 4 violate it)

Normal Forms Based on Primary Keys

We assume that a

- Set of functional dependencies is given for each relation
- Each relation has a designated primary key
- This information combined with the tests (conditions) for normal forms drives the normalization process for relational schema design
- First three normal forms for relation takes into account all candidate keys of a relation rather than the primary key

4.4.1 Normalization of Relations

- The normalization process, as first proposed by Codd (1972a), takes a relation schema through a series of tests to *certify* whether it satisfies a certain **normal form**.
- Initially, Codd proposed three normal forms, which he called first, second, and third normal form
- All these normal forms are based on a single analytical tool: the functional dependencies among the attributes of a relation
- A fourth normal form (4NF) and a fifth normal form (5NF) were proposed, based on the concepts of multivalued dependencies and join dependencies, respectively
- **Normalization of data** can be considered a process of analyzing the given relation schemas based on their FDs and primary keys to achieve the desirable properties of
 - (1) minimizing redundancy and
 - (2) minimizing the insertion, deletion, and update anomalies

- It can be considered as a "filtering" or "purification" process to make the design have successively better quality
- Unsatisfactory relation schemas that do not meet certain conditions—the **normal form tests**—are decomposed into smaller relation schemas that meet the tests and hence possess the desirable properties.
- Thus, the normalization procedure provides database designers with the following:
 - A formal framework for analyzing relation schemas based on their keys and on the functional dependencies among their attributes
 - A series of normal form tests that can be carried out on individual relation schemas so that the relational database can be normalized to any desired degree

Definition: The normal form of a relation refers to the highest normal form condition that it meets, and hence indicates the degree to which it has been normalized

4.4.2 Practical Use of Normal Forms

Normalization is carried out in practice so that the resulting designs are of high quality and meet the desirable properties

Database design as practiced in industry today pays particular attention to normalization only up to 3NF, BCNF, or at most 4NF.

The database designers *need not* normalize to the highest possible normal form

Relations may be left in a lower normalization status, such as 2NF, for performance reasons

Definition: Denormalization is the process of storing the join of higher normal form relations as a base relation, which is in a lower normal form.

4.4.3 Definitions of Keys and Attributes Participating in Keys

Superkey: specifies a uniqueness constraint that no two distinct tuples in any state r of R can have the same value

- **key** K is a superkey with the additional property that removal of any attribute from K will cause K not to be a superkey any more
- Example:
 - The attribute set $\{Ssn\}$ is a key because no two employees tuples can have the same value for Ssn

Any set of attributes that includes Ssn—for example, {Ssn, Name, Address}—is a superkey

- If a relation schema has more than one key, each is called a **candidate key**
- One of the candidate keys is arbitrarily designated to be the **primary key**, and the others are called **secondary keys**
- In a practical relational database, each relation schema must have a primary key
If no candidate key is known for a relation, the entire relation can be treated as a default superkey

For example {Ssn} is the only candidate key for EMPLOYEE, so it is also the primary key

Definition. An attribute of relation schema R is called a **prime attribute** of R if it is a member of *some candidate key* of R . An attribute is called **nonprime** if it is not a prime attribute—that is, if it is not a member of any candidate key

In WORKS_ON relation Both Ssn and Pnumber are prime attributes whereas other attributes are nonprime.

4.4.4 First Normal Form


Defined to disallow multivalued attributes, composite attributes, and their combinations

It states that the domain of an attribute must include only atomic (simple, indivisible) values and that the value of any attribute in a tuple must be a single value from the domain of that attribute

1NF disallows relations within relations or relations as attribute values within tuples

The only attribute values permitted by 1NF are single **atomic** (or **indivisible**) values.

Consider the DEPARTMENT relation schema shown in Figure below



- Primary key is Dnumber
- We assume that each department can have a number of locations

- The DEPARTMENT schema and a sample relation state are shown in Figure below

DEPARTMENT

Dname	<u>Dnumber</u>	Dmgr_ssn	Dlocations
Research	5	333445555	{Bellaire, Sugarland, Houston}
Administration	4	987654321	{Stafford}
Headquarters	1	888665555	{Houston}

- As we can see, this is not in 1NF because Dlocations is not an atomic attribute, as illustrated by the first tuple in Figure
- There are two ways we can look at the Dlocations attribute:
 - The domain of Dlocations contains atomic values, but some tuples can have a set of these values. In this case, Dlocations is not functionally dependent on the primary key Dnumber
 - The domain of Dlocations contains sets of values and hence is nonatomic. In this case, $Dnumber \rightarrow Dlocations$ because each set is considered a single member of the attribute domain
- In either case, the DEPARTMENT relation is not in 1NF

There are three main techniques to achieve first normal form for such a relation:

1. Remove the attribute Dlocations that violates 1NF and place it in a separate relation DEPT_LOCATIONS along with the primary key Dnumber of DEPARTMENT. The primary key of this relation is the combination {Dnumber, Dlocation}. A distinct tuple in DEPT_LOCATIONS exists for *each location* of a department. This decomposes the non-1NF relation into two 1NF relations.
2. Expand the key so that there will be a separate tuple in the original DEPARTMENT relation for each location of a DEPARTMENT. In this case, the primary key becomes the combination {Dnumber, Dlocation}. This solution has the disadvantage of introducing *redundancy* in the relation

DEPARTMENT

Dname	<u>Dnumber</u>	Dmgr_ssn	<u>Dlocation</u>
Research	5	333445555	Bellaire
Research	5	333445555	Sugarland
Research	5	333445555	Houston
Administration	4	987654321	Stafford
Headquarters	1	888665555	Houston

3. If a maximum number of values is known for the attribute—for example, if it is known that at most three locations can exist for a department—replace the Dlocations attribute by three atomic attributes: Dlocation1, Dlocation2, and Dlocation3. This solution has the disadvantage of introducing NULL values if most departments have fewer than three locations. Querying on this attribute becomes more difficult; for example, consider how you would write the query: List the departments that have 'Bellaire' as one of their locations in this design.

- Of the three solutions, the first is generally considered best because it does not suffer from redundancy and it is completely general, having no limit placed on a maximum number of values
- First normal form also disallows multivalued attributes that are themselves composite.
- These are called **nested relations** because each tuple can have a relation within it.

(a)

EMP_PROJ		Projs	
Ssn	Ename	Pnumber	Hours

- Figure above shows how the EMP_PROJ relation could appear if nesting is allowed
- Each tuple represents an employee entity, and a relation PROJS(Pnumber, Hours) *within each tuple* represents the employee's projects and the hours per week that employee works on each project.
- The schema of this EMP_PROJ relation can be represented as follows:
EMP_PROJ(Ssn, Ename, {PROJS(Pnumber, Hours)})
- Ssn is the primary key of the EMP_PROJ relation and Pnumber is the **partial** key of the nested relation; that is, within each tuple, the nested relation must have unique values of Pnumber
- To normalize this into 1NF, we remove the nested relation attributes into a new relation and *propagate the primary key* into it; the primary key of the new relation will combine the partial key with the primary key of the original relation
- Decomposition and primary key propagation yield the schemas EMP_PROJ1 and EMP_PROJ2,

EMP_PROJ1	
<u>Ssn</u>	Ename

EMP_PROJ2		
<u>Ssn</u>	<u>Pnumber</u>	Hours


EMP_PROJ

Ssn	Ename	Pnumber	Hours
123456789	Smith, John B.	1	32.5
		2	7.5
666884444	Narayan, Ramesh K.	3	40.0
453453453	English, Joyce A.	1	20.0
		2	20.0
333445555	Wong, Franklin T.	2	10.0
		3	10.0
		10	10.0
		20	10.0
999887777	Zelaya, Alicia J.	30	30.0
		10	10.0
987987987	Jabbar, Ahmad V.	10	35.0
		30	5.0
987654321	Wallace, Jennifer S.	30	20.0
		20	15.0
888665555	Borg, James E.	20	NULL

4.4.5 Second Normal Form


- **Second normal form (2NF)** is based on the concept of full functional dependency
- A functional dependency $X \rightarrow Y$ is a **full functional dependency** if removal of any attribute A from X means that the dependency does not hold any more; that is, for any attribute $A \in X$, $(X - \{A\})$ does not functionally determine Y
- A functional dependency $X \rightarrow Y$ is a **partial dependency** if some attribute $A \in X$ can be removed from X and the dependency still holds; that is, for some $A \in X$, $(X - \{A\}) \rightarrow Y$

EMP_PROJ



- In the above figure, $\{Ssn, Pnumber\} \rightarrow Hours$ is a full dependency (neither $Ssn \rightarrow Hours$ nor $Pnumber \rightarrow Hours$ holds)
- $\{Ssn, Pnumber\} \rightarrow Ename$ is partial because $Ssn \rightarrow Ename$ holds
- **Definition.** A relation schema R is in 2NF if every nonprime attribute A in R is fully functionally dependent on the primary key of R
- The test for 2NF involves testing for functional dependencies whose left-hand side attributes are part of the primary key
- If the primary key contains a single attribute, the test need not be applied at all

- The EMP_PROJ relation is in 1NF but is not in 2NF.
- The nonprime attribute Ename violates 2NF because of FD2, as do the nonprime attributes Pname and Plocation because of FD3
- The functional dependencies FD2 and FD3 make Ename, Pname, and Plocation partially dependent on the primary key {Ssn, Pnumber} of EMP_PROJ, thus violating the 2NF test.
- If a relation schema is not in 2NF, it can be *second normalized* or *2NF normalized* into a number of 2NF relations in which **nonprime attributes are associated only with the part of the primary key on which they are fully functionally dependent**.
- Therefore, the functional dependencies FD1, FD2, and FD3 lead to the decomposition of EMP_PROJ into the three relation schemas EP1, EP2, and EP3 shown in Figure below, each of which is in 2NF.




4.4.6 Third Normal Form

- **Transitive functional dependency**

A functional dependency $X \rightarrow Y$ in a relation schema R is a **transitive dependency** if there exists a set of attribute Z that are neither a primary nor a subset of any key of R (candidate key) and both $X \rightarrow Z$ and $Y \rightarrow Z$ holds

- **Example:**



- **SSN → DMGRSSN is a transitive FD** since SSN → DNUMBER and DNUMBER → DMGRSSN hold

Dnumber is neither a key itself nor a subset of the key of EMP_DEPT

- **SSN $\rightarrow$ ENAME is non-transitive** since there is no set of attributes X where $SSN \rightarrow X$ and $X \rightarrow ENAME$
- **Definition: A relation schema R is in third normal form (3NF) if it is in 2NF and no non-prime attribute A in R is transitively dependent on the primary key**
- The relation schema EMP_DEPT is in 2NF, since no partial dependencies on a key exist. However, EMP_DEPT is not in 3NF because of the transitive dependency of Dmgr_ssn (and also Dname) on Ssn via Dnumber

EMP_DEPT

We can normalize EMP_DEPT by decomposing it into the two 3NF relation schemas ED1 and ED2

ENAME	SSN	BDATE	ADDRESS	DNUMBER	DNAME	DMGRSSN

ED1 and ED2 represent independent entity facts about employees and departments

A NATURAL JOIN operation on ED1 and ED2 will recover the original relation EMP_DEPT without generating spurious tuples

Problematic FD

Left-hand side is part of primary key


Left-hand side is a non-key attribute

2NF and 3NF normalization remove these problem FDs by decomposing the original relation into new relations

- In general, we want to design our relation schemas so that they have neither partial nor transitive dependencies because these types of dependencies cause the update anomalies

Table 15.1 Summary of Normal Forms Based on Primary Keys and Corresponding Normalization

Normal Form	Test	Remedy (Normalization)
First (1NF)	Relation should have no multivalued attributes or nested relations.	Form new relations for each multivalued attribute or nested relation.
Second (2NF)	For relations where primary key con-	Decompose and set up a new relation for




4.5 General Definition of Second and Third Normal Form

- Takes into account all candidate keys of a relation into account
- **Definition of 2NF:** A relation schema R is in **second normal form (2NF)** if every nonprime attribute A in R is not partially dependent on any key of R
- Consider the relation schema LOTS which describes parcels of land for sale in various counties of a state

Suppose that there are two candidate keys: Property_id# and {County_name, Lot#}; that is, lot numbers are unique only within each county, but Property_id# numbers are unique across counties for the entire state.

Based on the two candidate keys Property_id# and {County_name, Lot#}, the functional dependencies FD1 and FD2 hold						
ENAME	SSN	BDATE	ADDRESS	DNUMBER	DNAME	DMGRSSN
We choose Property_id# as the primary key, but no special consideration will be given to this key over the other candidate key						
FD3 says that the tax rate is fixed for a given county (does not vary lot by lot within the same county)						
FD4 says that the price of a lot is determined by its area regardless of which county it is in.						

- The LOTS relation schema violates the general definition of 2NF because Tax_rate is partially dependent on the candidate key {County_name, Lot#}, due to FD3
- To normalize LOTS into 2NF, we decompose it into the two relations LOTS1 and LOTS2



We construct LOT1 by removing the attribute Tax_rate that violates 2NF from LOTS and placing it with County_name (the left-hand side of FD3 that causes the partial dependency) into another relation LOT2.

Both LOT1 and LOT2 are in 2NF.

Definition of 3NF: A relation schema R is in **third normal form (3NF)** if, whenever a

A is a prime attribute of R


According to this definition, LOT2 is in 3NF

FD4 in LOT1 violates 3NF because Area is not a superkey and Price is not a prime attribute in LOT1

To normalize LOT1 into 3NF, we decompose it into the relation schemas LOT1A and LOT1B

We construct LOT1A by removing the attribute Price that violates 3NF from LOT1 and placing it with Area (the lefthand side of FD4 that causes the transitive dependency) into another relation LOT1B.

Both LOT1A and LOT1B are in 3NF



4.6 Boyce-Codd Normal Form

- **Boyce-Codd normal form (BCNF)** was proposed as a simpler form of 3NF, but it was found to be stricter than 3NF
- Every relation in BCNF is also in 3NF; however, a relation in 3NF is not necessarily in BCNF

Definition. A relation schema R is in **BCNF** if whenever a nontrivial functional

The formal definition of BCNF differs from the definition of 3NF in that condition (b) of 3NF, which allows A to be prime, is absent from BCNF. That makes BCNF a stronger normal form compared to 3NF

In our example, FD5 violates BCNF in LOTS1A because AREA is not a superkey of LOTS1A

FD5 satisfies 3NF in LOTS1A because County_name is a prime attribute (condition b), but this condition does not exist in the definition of BCNF

We can decompose LOTS1A into two BCNF relations LOTS1AX and LOTS1AY. This decomposition loses the functional dependency FD2 because its attributes no longer coexist in the same relation after decomposition.

ENAME	SSN	BDATE	ADDRESS	DNUMBER	DNAME	DMGRSSN

In practice, most relation schemas that are in 3NF are also in BCNF

Only if $X \twoheadrightarrow A$ holds in a relation schema R with X not being a superkey and A being a prime attribute will R be in 3NF but not in BCNF

- Example: consider the relation TEACH with the following dependencies:

TEACH

Student	Course	Instructor
Narayan	Database	Mark
Smith	Database	Navathe
Smith	Operating Systems	Ammar
Smith	Theory	Schulman
Wallace	Database	Mark
Wallace	Operating Systems	Ahamad
Wallace	Database	Amir

-- means that each instructor teaches one course

{Student, Course} is a candidate key for this relation

The dependencies shown follow the pattern in Figure below with Student as A, Course as B, and Instructor as C

Hence this relation is in 3NF but not BCNF

Decomposition of this relation schema into two schemas is not straightforward because it may be decomposed into one of the three following possible pairs:

1. R1(Student, Instructor) and R2(Student, Course)
2. R1(Course, Instructor) and R2(Course, Student)
3. R1(Instructor, Course) and R2(Instructor, Student)

It is generally not sufficient to check separately that each relation schema in the database is, say, in BCNF or 3NF

Rather, the process of normalization through decomposition must also confirm the existence of additional properties that the relational schemas, taken together, should possess. These would include two properties:

- The **nonadditive join or lossless join property**, which guarantees that the spurious tuple generation problem does not occur with respect to the relation schemas created after decomposition.
- The **dependency preservation property**, which ensures that each functional dependency is represented in some individual relation resulting after decomposition.

- To keep the relation state consistent, and to avoid any spurious relationship between the two independent attributes, we must have a separate tuple to represent every combination of an employee's dependent and an employee's project
- In the relation state shown in the EMP, the employee Smith works on two projects 'X' and 'Y' and has two dependents 'John' and 'Anna' and therefore there are 4 tuples to represent these facts together

The relation EMP is an **all-key relation** (with key made up of all attributes) and relation

There is a redundancy in the relation EMP-the dependent information is repeated for every project and project information is repeated for every dependent

To address this situation, the concept of multivalued dependency(MVD) was proposed and based on this dependency, the fourth normal form was defined

Multivalued dependencies are a consequence of 1NF which disallows an attribute in a tuple to have a set of values, and the accompanying process of converting an unnormalized relation into 1NF

Informally, whenever two independent 1:N relationships are mixed in the same relation, R(A, B, C), an MVD may arise

4.7.1 Formal Definition of Multivalued Dependency

Definition.

are both subsets of R, specifies the following constraint on any relation state r of R: If two tuples t1 and t2 exist in r such that t1[X] = t2[X], then two tuples t3 and t4 should also exist in r with the following properties where we use Z to denote (R - (X ∪ Y))

$$t3[X] = t4[X] = t1[X] = t2[X].$$

$$t3[Y] = t1[Y] \text{ and } t4[Y] = t2[Y].$$

$$t3[Z] = t2[Z] \text{ and } t4[Z] = t1[Z].$$

Let X= Ename, Y=Pname

t1[Ename]=t2[ename]=Smith

Z= (EMP-(Ename ∪ Pname))

= Dname

Smith	Y	Anna
Smith	X	Anna
Smith	Y	John

- t3(Ename)=t4(Ename)=t1(Ename)=t2(Ename)=Smith

- $t3(Pname)=t1(Pname)=X$ and $t4(Pname)=t2(Pname)=Y$
- $t3(Dname)=t2(Dname)=Anna$ and $t4(Dname)=t1(Dname)=John$
- Whenever $X \twoheadrightarrow Y$ holds, we say that X **multidetermines** Y . Because of the symmetry in the definition, whenever $X \twoheadrightarrow Y$ holds in R , so does $X \twoheadrightarrow Z$. Hence, $X \twoheadrightarrow Y$ implies $X \twoheadrightarrow Z$, and therefore it is sometimes written as $X \twoheadrightarrow Y|Z$.
- An MVD $X \twoheadrightarrow Y$ in R is called a **trivial MVD** if
 - (a) Y is a subset of X , or
 - (b) $X \cup Y = R$

EMP_PROJECTS

<u>Ename</u>	<u>Pname</u>
Smith	X
Smith	Y

- For example, the relation EMP_PROJECTS has the trivial MVD

$$Ename \twoheadrightarrow Pname$$
- An MVD that satisfies neither (a) nor (b) is called a **nontrivial MVD**
- If we have a nontrivial MVD in a relation, we may have to repeat values redundantly in the tuples
- In the EMP relation the values 'X' and 'Y' of Pname are repeated with each value of Dname (or, by symmetry, the values 'John' and 'Anna' of Dname are repeated with each value of Pname)
- This redundancy is clearly undesirable.
- We now present the definition of **fourth normal form (4NF)**, which is violated when a relation has undesirable multivalued dependencies, and hence can be used to identify and decompose such relations
- **Definition:** A relation schema R is in 4NF with respect to a set of dependencies F (that includes functional dependencies and multivalued dependencies) if, for every **nontrivial multivalued dependency** $X \twoheadrightarrow Y$ in F^+ X is a superkey for R
- The process of normalizing a relation involving the nontrivial MVDs that is not in 4NF consists of decomposing it so that each MVD is represented by a separate relation where it becomes a trivial MVD

EMP_PROJECTS

<u>Ename</u>	<u>Pname</u>
Smith	X
Smith	Y

EMP_DEPENDENTS

<u>Ename</u>	<u>Dname</u>
Smith	John
Smith	Anna

- We decompose EMP into EMP_PROJECTS and EMP_DEPENDENTS
- Both EMP_PROJECTS and EMP_DEPENDENTS are in 4NF, because the MVDs $Ename \twoheadrightarrow Pname$ in EMP_PROJECTS and $Ename \twoheadrightarrow Dname$ in EMP_DEPENDENTS are trivial MVDs
- No other nontrivial MVDs hold in either EMP_PROJECTS or EMP_DEPENDENTS. No FDs hold in these relation schemas either
- We can state the following points:
 - An all-key relation is always in BCNF since it has no FDs
 - An all-key relation such as the EMP, which has no FDs but has the MVD $Ename \twoheadrightarrow Pname \mid Dname$, is not in 4NF
 - A relation that is not in 4NF due to a nontrivial MVD must be decomposed to convert it into a set of relations in 4NF
 - The decomposition removes the redundancy caused by the MVD

4.8 Join Dependencies and Fifth Normal Form

- A **join dependency (JD)**, denoted by $JD(R_1, R_2, \dots, R_n)$, specified on relation schema R , specifies a constraint on the states r of R . The constraint states that every legal state r of R should have a nonadditive join decomposition into $R_1, R_2, \dots, R_n$. Hence, for every such r we have

$$* (\pi_{R_1}(r), \pi_{R_2}(r), \dots, \pi_{R_n}(r)) = r$$

- A join dependency $JD(R_1, R_2, \dots, R_n)$, specified on relation schema R , is a **trivial JD** if one of the relation schemas R_i in $JD(R_1, R_2, \dots, R_n)$ is equal to R .

Fifth normal form (project-join normal form)

- A relation schema R is in **fifth normal form (5NF)** (or **project-join normal form (PJNF)**) with respect to a set F of functional, multivalued, and join dependencies if, for every nontrivial join dependency $JD(R_1, R_2, \dots, R_n)$ in F^+ every R_i is a superkey of R .
- A database is said to be in 5NF, if and only if,
 - It's in 4NF

