

```
mysql> use bike_rental;
```

Database changed

```
mysql> CREATE TABLE `tblbikeinfo` (  
  -> `bike_id` int(11) NOT NULL,  
  -> `bike_category_id` int(11) NOT NULL,  
  -> `shop_id` int(11) NOT NULL,  
  -> `bike_name` varchar(30) NOT NULL,  
  -> `specs` varchar(100) NOT NULL,  
  -> `rent_price` float NOT NULL,  
  -> `availability` int(1) NOT NULL,  
  -> `user_id` int(11) NOT NULL);
```

Query OK, 0 rows affected, 5 warnings (2.75 sec)

```
mysql> CREATE TABLE `tblbikecategory` (  
  -> `category_id` int(11) NOT NULL,  
  -> `category_name` varchar(30) NOT NULL,  
  -> `description` varchar(100) NOT NULL);
```

Query OK, 0 rows affected, 1 warning (1.36 sec)

```
mysql> CREATE TABLE `tblshopinfo` (  
  -> `shop_id` int(11) NOT NULL,  
  -> `shop_name` varchar(50) NOT NULL,  
  -> `owner_name` varchar(30) NOT NULL,  
  -> `address` varchar(100) NOT NULL,  
  -> `email_address` varchar(30) NOT NULL,  
  -> `contact_no` varchar(15) NOT NULL,  
  -> `website` varchar(30) NOT NULL,  
  -> `updated_by` int(11) NOT NULL);
```

Query OK, 0 rows affected, 2 warnings (1.54 sec)

```
mysql> CREATE TABLE `tblclient` (  
  -> `client_id` int(11) NOT NULL,  
  -> `client_code` varchar(15) NOT NULL,  
  -> `avatar` blob NOT NULL,
```

```
-> `client_name` varchar(30) NOT NULL,  
-> `email_address` varchar(30) NOT NULL,  
-> `contact_number` varchar(15) NOT NULL,  
-> `complete_address` varchar(100) NOT NULL,  
-> `username` varchar(30) NOT NULL,  
-> `password` varchar(30) NOT NULL,  
-> `status` int(1) NOT NULL);
```

Query OK, 0 rows affected, 2 warnings (1.42 sec)

```
mysql> CREATE TABLE `tblrental` (  
-> `rental_id` int(11) NOT NULL,  
-> `bike_id` int(11) NOT NULL,  
-> `client_id` int(11) NOT NULL,  
-> `rental_start_date` date NOT NULL,  
-> `rental_end_date` date NOT NULL,  
-> `total_amount` float NOT NULL,  
-> `payment_status` int(1) NOT NULL,  
-> `rental_status` int(1) NOT NULL,  
-> `remarks` varchar(100) NOT NULL,  
-> `user_id` int(11) NOT NULL);
```

Query OK, 0 rows affected, 6 warnings (1.63 sec)

```
mysql> CREATE TABLE `tblpayment` (  
-> `payment_id` int(11) NOT NULL,  
-> `rental_id` int(11) NOT NULL,  
-> `payment_type` int(1) NOT NULL,  
-> `paid_by` varchar(30) NOT NULL,  
-> `payment_date` date NOT NULL,  
-> `remarks` varchar(100) NOT NULL,  
-> `user_id` int(11) NOT NULL);
```

Query OK, 0 rows affected, 4 warnings (1.34 sec)

```
mysql> CREATE TABLE `tblpenalty` (  
-> `penalty_id` int(11) NOT NULL,
```

```
-> `rental_id` int(11) NOT NULL,  
-> `penalty_amount` float NOT NULL,  
-> `payment_status` int(1) NOT NULL,  
-> `remarks` varchar(100) NOT NULL,  
-> `paid_by` varchar(30) NOT NULL,  
-> `user_id` int(11) NOT NULL);
```

Query OK, 0 rows affected, 4 warnings (1.03 sec)

```
mysql> CREATE TABLE `tbladsmanagement` (  
-> `ads_id` int(11) NOT NULL,  
-> `ad_name` varchar(30) NOT NULL,  
-> `shop_id` int(11) NOT NULL,  
-> `banner_image` blob NOT NULL,  
-> `description` varchar(100) NOT NULL,  
-> `start_date` date NOT NULL,  
-> `end_date` date NOT NULL,  
-> `ad_location` int(1) NOT NULL,  
-> `amount` float NOT NULL,  
-> `user_id` int(11) NOT NULL);
```

Query OK, 0 rows affected, 4 warnings (0.93 sec)

```
mysql> CREATE TABLE `tbluser` (  
-> `user_id` int(11) NOT NULL,  
-> `username` varchar(30) NOT NULL,  
-> `password` varchar(30) NOT NULL,  
-> `avatar` blob NOT NULL,  
-> `fullname` varchar(50) NOT NULL,  
-> `contact` varchar(15) NOT NULL,  
-> `email` varchar(30) NOT NULL,  
-> `user_category_id` int(1) NOT NULL,  
-> `status` int(1) NOT NULL);
```

Query OK, 0 rows affected, 3 warnings (1.58 sec)

```
mysql> CREATE TABLE `tblusergroup` (
  -> `user_group_id` int(11) NOT NULL,
  -> `group_name` varchar(30) NOT NULL,
  -> `description` varchar(50) NOT NULL,
  -> `allow_add` int(1) NOT NULL,
  -> `allow_edit` int(1) NOT NULL,
  -> `allow_delete` int(1) NOT NULL,
  -> `allow_print` int(1) NOT NULL,
  -> `allow_import` int(1) NOT NULL,
  -> `allow_export` int(1) NOT NULL);
```

