

Email Security Posture Assessment

secure.example

100

A+

Low risk

Scan date	18 September 2026, 20:43 UTC
Scan ID	639f4e6f9cfa
Checks run	7
Findings	0 failing, 0 warnings, 5 passing
Narrative	Rule-based (built-in)
Engine version	1.0.0

Executive summary

secure.example passed every check this assessment was able to complete. SPF, DMARC, DKIM and TLS-RPT were examined and found correctly configured. There is nothing to remediate. BIMi does not apply to this domain and was excluded from the score. Note that MTA-STS and Mail Transport (MX / STARTTLS / TLS) could not be evaluated during this scan, so they are excluded from the score rather than counted as passing — a gap in coverage, not a clean result. Email security posture is not a one-time state: certificates expire, providers change their sending infrastructure, and DKIM keys need periodic rotation. The useful next step is scheduled re-assessment, not further hardening.

Narrative generated by the built-in rule-based writer. Reason: LLM disabled for this scan

Score by category

Category	Earned	Available	Result
Authentication	65.0	65.0	100%
Policy & Reporting	3.0	3.0	100%

Excluded from scoring because the check could not complete: mta_sts, transport. These are neither counted as passing nor as failing — the score is calculated over the checks that returned a conclusive result.

Findings

No failing or warning findings. Every check that returned a conclusive result passed.

Controls verified as correctly configured

- SPF record is present and well-formed
- DMARC alignment: adkim=s, aspf=s
- DMARC is published and enforcing
- DKIM keys are present and of adequate strength
- TLS-RPT is configured

Not assessed

- MTA-STS record found; policy file not retrieved: The DNS record is published, but policy-file retrieval was disabled for this scan, so the policy's mode could not be confirmed. MTA-STS is therefore excluded from the score rather than counted as passing.
- BIMi is not configured: No BIMi record found. BIMi displays a verified brand logo beside authenticated mail; it is optional, requires DMARC at enforcement first, and its absence is not a security weakness.
- TLS probing was disabled for this scan: 2 MX host(s) were discovered but not contacted.

Method and scope

This assessment is passive and read-only. It consists of public DNS lookups (SPF, DKIM, DMARC, MTA-STS, TLS-RPT and BIMi records), an HTTPS GET of the domain's published MTA-STS policy file, and SMTP connections to the mail hosts the domain itself advertises in its MX records, used to observe the server's own STARTTLS advertisement and complete a TLS handshake.

The assessment does not send test phishing messages, does not attempt authentication or authentication bypass, does not relay or deliver mail, does not access mailbox contents, and does not attempt to exploit any weakness it identifies. No credentials are used and no data is submitted to the target. Connections are closed with QUIT and are rate-limited per domain.

Scoring assigns each check a share of 100 points weighted by the attacker leverage a failure grants (dmarc 30, transport 25, spf 20, dkim 15, mta_sts 7, tls_rpt 3). Each finding removes a fraction of its check's points by severity: critical 100%, high 60%, medium 30%, low 10%. A check that could not complete is removed from the denominator rather than counted as a failure, so a network restriction on the scanner is never reported as a weakness in the assessed domain.

The narrative section is generated from the findings above and is constrained to them: it cannot introduce a finding the engine did not produce, and any generated text that references an unknown finding or states a score other than the computed one is rejected and replaced by the built-in rule-based writer.

Generated 18 September 2026 at 20:44 · Scan ID 639f4e6f9cfa