

Reconstructing Pore Networks Using Generative Adversarial Networks Kelly Guan

CS 229 Fall 2018

kmguan@stanford.edu Department of Energy Resources Engineering, Stanford University

Introduction


Motivation

- Flow properties (porosity and permeability) of porous media can vary due to rock heterogeneity
- Recreating variations of the pore network can be time-consuming (both in the lab and computationally)
- Recent advances in deep learning have shown promising use of generative adversarial networks (GANs) for rapid generation of 3D images with no a priori model [1]

Objective

- Investigate feasibility of generating 2D sandstone images by training a deep convolutional GAN model (DCGAN) [2]
- Try different architectures to determine optimal parameters
- Evaluate model performance against real images using morphological properties

Model Architecture and Training



DCGAN-1

(Log loss)

 $\min_{G} \max_{D} \mathbb{E}_{x \sim p_{\text{data}}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log (1 - D(G(z)))]$

DCGAN-2

 $\min_{G} \max_{D} \mathbb{E}_{x \sim p_{\text{data}}(x)}[D(x)] - \mathbb{E}_{z \sim p_{z}(z)}[D(G(z))] + \lambda \mathbb{E}_{x}[(||\nabla_{x}D(x)||_{2} - 1)^{2}]$ (Wasserstein)

DCGAN model: Based on [3]

Layer	Type	Filters	Kernel	Stride	Padding	Batch Norm	Activation
Generator							
1	ConvTransp2D	512	4 x 4	1	0	Yes	ReLU
2	ConvTransp2D	256	4 x 4	2	1	Yes	ReLU
3	ConvTransp2D	128	4 x 4	2	1	Yes	ReLU
4	ConvTransp2D	64	4 x 4	2	1	No	Tanh
Discriminator							
1	Conv2D	64	4 x 4	2	1	No	LeakyReLU
2	Conv2D	128	4 x 4	2	1	Yes	LeakyReLU
3	Conv2D	256	4 x 4	2	1	Yes	LeakyReLU
4	Conv2D	512	4 x 4	1	0	No	Sigmoid

Strategies:

 Modified generator loss function – prevent vanishing gradients


 $\log D(G(z))$

- One-sided label smoothing
- Wasserstein distance with gradient penalty shown to improve convergence [4]

Data Acquisition & Evaluation

Image size (voxels)	256 x 256 x 256		
Voxel size	6.12 um		
Subvolume spacing	16 pixels		
Training image size	64 x 64		
# of training images	36,869		

Fully trained $G(z) \rightarrow 64\ 100^2$ pixel synthetic realizations



Post-processing:

- filter (median)
- threshold (Otsu)



Evaluation metrics (2D Minkowski functionals)

- Area ~ available pore (white) space
- Perimeter ~ pore shape
- Euler characteristic, χ ~ connectivity

$$\chi = n_{connected} - n_{holes}$$

Results **DCGAN-1** Generator and Discriminator Loss During Training 10000 15000 20000 25000 30000 DCGAN-2 iterations D loss Pore area Perimeter, $\times 10^{-2}$ Euler characteristic, $\chi \times 10^{-4}$ Model -3.890.2206.94Train set -4.28DCGAN-1 0.217 6.82-88DCGAN-2 0.268 42.26

Conclusion

- Label smoothing had a noticeable effect on training stability
- DCGAN model performs well for 2D case using the log loss function
- Wasserstein distance does not work/leads to collapse, possibly due to binary nature of data

Future work

- Modify to train and generate 3D reconstructions of the pore network
- Explore other network architectures and the effect on training stability
- Evaluate performance using other metrics, e.g. single phase permeability

References and Acknowledgements

- [1] L. Mosser, O. Dubrule, and M. J. Blunt, "Reconstruction of three-dimensional porous media using generative adversarial neural networks," Physical Review E, vol. 96, no. 4, 2017.
- [2] A. Radford, L. Metz, and S. Chintala, "Unsupervised Representation Learning With Deep Convolutional Generative Adversarial Networks," arXiv:1511.06434, 2016.
- [3] N. Inkawhich, "DCGAN Tutorial,"
- https://pytorch.org/tutorials/beginner/dcgan_faces_tutorial.html.
- [4] I. Gulrajani, F. Ahmed, M. Arjovsky, V. Dumoulin, and A. Courville, "Improved Training of Wasserstein GANs," arXiv:1704.00028, 2017.

Thanks to Tim Anderson and Dr. Tony Kovscek for their guidance on this project. Part of this work was performed at the Stanford Nano Shared Facilities (SNSF), supported by the National Science Foundation under award ECCS-1542152.