

SongNet: Real-time Music Classification

Chen Chen, Chi Zhang, Yue Zhang {chenc2, czhang94, yzhang16}@stanford.edu

Overview

☐ Motivation

- ✓ Helps online music companies such as Spotify or Apple Music to mange their music base.
- ✓ Saves time and effort from manual classification.

□ Objectives

- ✓ Build deep learning (C-RNN) models to automatically classify music genres for real time.
- ✓ Improve baseline models accuracy by C-RNN.

Dataset

☐ Free Music Archive

✓ The dataset contains 8000 tracks of 30 seconds clips, with 8 balanced genres^[2] listed below.


Instrumental	Rock	Electronic
International	Pop	Experimental
Hip-pop	Folk	

✓ 70% training / 20% Validation / 10% Test


Features

☐ Mel-spectrogram

- ✓ Used librosa^[3] package to calculate mel-spectrogram.
- ✓ Designed CONV layers to extract features (DEMO)



C-RNN Model Architecture



☐ Architecture

- ✓ Input: mel-spectrogram
- ✓ 3 Convolutional layers
- Batch Normalization
- ReLU activation
- Dropout Regularization
- ✓ Recurrent layers
- ✓ Output: probability of each genre.

Results & Discussion

☐ Results

Models	Accuracy
Random guess	12.5%
K nearest neighbors	36.38%
Logistic regression	42.25%
Multilayer perceptron	44.88%
Support vector machine	46.38%
C-RNN	65.32%

electronic 205 9 6 29 22 16 11 16 experimental 40 77 40 17 28 30 16 84 folk 7 5 161 5 19 31 25 38 -160 hip-hop 23 1 1 200 4 9 11 20 instrumental 27 19 43 4 138 21 13 35 international 43 11 9 32 8 165 12 20 pop 38 9 20 23 16 38 69 95 rock 6 4 13 0 8 12 12 231 rock 6 4 13 0 8 12 12 231 -0

Discussion

- Genre "Experimental" is hard to be classified correctly.
- Classifications of other genres perform well.
- ✓ CONV layers extracted useful genre clips, listen to our demos.
- ✓ Recurrent models enable us to do real-time classification.
- ✓ C-RNN does not include music metadata, while baseline model does.

Future

- ✓ Understand why C-RNN cannot perform well on "Experimental" genre and improve the accuracy of that genre.
- Consider adding music metadata to C-RNN models and further improve the accuracy.
- ✓ Implement an user interface to allow users input a music clip and visualize the realtime music classification online.

Reference

- [1] Kozakowski, P., & Michalak, B. (2016, October 26). Music Genre Recognition.
- [2] K. Benzi, M. Defferrard, P. Vandergheynst, and X. Bresson. (2016). FMA: A dataset for music analysis.
- [3] LibROSA (n.d.). http://librosa.github.io/librosa/