

Fine-grained Sentiment Analysis of User Reviews in Chinese

Category: Natural Language Processing

Suofei Feng (suofeif@stanford.edu), Eziz Durdyev (eziz@stanford.edu)

CS229

2018 Fall

ABSTRACT

In this project we implemented 3 types of models (SVM, XGBoost, LSTM) for the fine-grained sentiment analysis of user reviews about restaurants in Chinese language. There are 20 elements, and 4 labels (positive, neutral, negative, not mentioned) for each of them. We trained one model of each type for each of the elements. On the whole, XGBoost has the best performance based on the accuracies, weighted f1 scores, and efficiencies.

DATASET

We used the datasets provided by AI challenger official. The training and validation data are manually labelled. We created validation and test sets from the original validation set. Training set (105,000), validation set (7500), and test set (7498) have roughly same class distributions.

For the limited space, we just list the 6 categories for the all 20 elements:


1. Location
2. Service
3. Price
4. Environment
5. Dish
6. Others

Within “Others”, the 2 elements are “overall experience” and “willing to consume again”.

LSTM FOR CLASSIFICATION


We constructed a two-layer LSTM (Long Short Term Memory) neural network. This model takes the 105,000 outputs of size (1, 400) from feature extraction step as the input. The embedding matrix takes weights from the Word2Vec model, and is not trainable. Apart from hyperparameters shown in the graph, we also modified class weights according to class distributions in each element. We used categorical cross entropy as the loss function:

$$L(\theta) = -\frac{1}{n} \sum_{i=1}^n \sum_{j=1}^4 y_{ij} \log(p_{ij})$$



RESULTS AND DISCUSSIONS

We used accuracies and weighted F1 scores as our metrics. The graph shows a very fluctuating test accuracies across 20 elements. In general, the XGBoost models have better results.



Possible problems with the models:

- Label qualities;
- Long sentences;
- Vocabulary size.

Test F1 scores for Top 3 Topics in Latent Dirichlet Allocation (LDA)

Models	Dish Recommendation	Service Wait Time	Location Traffic Convenience
LSTM	0.6524	0.8776	0.8389
SVM	0.7561	0.8381	0.8563
XGBoost	0.7582	0.8326	0.8382

FUTURE WORKS

1. Collect better-labelled data;
2. Improve the quality of language representation models; Implement contextual representation, e.g. BERT;
3. Apply Attention mechanism for long input texts.

REFERENCES

https://github.com/AIChallenger/AI_Challenger_2018
Ehrentraut, C., Ekholm, M., Tanushi, H., Tiedemann, J., & Dalianis, H. (2018). Detecting hospital-acquired infections: A document classification approach using support vector machines and gradient tree boosting. Health informatics journal, 24(1), 24-42.
Kaur, P., & Gurm, R. K. (2016). Design and Implementation of Boosting Classification Algorithm for Sentiment Analysis on Newspaper Articles. International Journal of Computer Science and Information Technologies, Vol. 7 (4) , 1767-1770.