
Design and implementation of a firewall device

Master's Thesis submitted to the
Faculty of Informatics of the *Università della Svizzera Italiana*
in partial fulfillment of the requirements for the degree of
Master of Financial Technology and Computing
main track

presented by
Bin Yong

under the supervision of
Prof. Student's Advisor
co-supervised by
Prof. Student's Co-Advisor

September 2023

I certify that except where due acknowledgement has been given, the work presented in this thesis is that of the author alone; the work has not been submitted previously, in whole or in part, to qualify for any other academic award; and the content of the thesis is the result of work which has been carried out since the official commencement date of the approved research program.

Bin Yong
Lugano, Yesterday September 2023

Abstract

Design and implementation of a firewall device based on Raspberry Pi. The firewall will monitor and encrypt network activities. It is designed for someone who would like to sacrifice some compatibility to pursue better security but still wants some balance between security and convenience. A sensitive target, like an investigative journalist, could be a potential user of this device.

Acknowledgements

This document is a draft version of a working thesis of Bin Yong.

Contents

Contents	vii
List of Figures	ix
List of Tables	xi
1 Introduction	1
2 Hardware	3
3 Operating system	5
4 Packet filtering and forwarding	7
4.1 Design	7
4.2 Implementation	8
5 Dynamic Host Configuration Protocol (DHCP)	9
5.1 Introduction	9
5.1.1 The issue	9
5.2 Design	9
5.3 Implementation	9
6 Domain Name System (DNS)	11
6.1 Introduction	11
6.2 Design	11
6.3 Implementation	11
6.3.1 Outgoing requests	11
6.3.2 Inside firewall	11
6.3.3 Incoming requests	12
7 Transport Layer Security (TLS)	13
7.1 Management of certificates	13
7.1.1 Introduction	13
7.1.2 Design	14
7.1.3 Implementation	14
7.2 Mismatch between the changing best current practice and the unchanged implementation	14

7.2.1 Problem	14
7.2.2 Solution	14
7.3 Proxy	14
7.4 Process view of traffics	18
8 Plaintext connections	19
8.1 HTTP	19
8.1.1 Implementation	19
9 Date time synchornization	23
9.1 Introduction	23
9.1.1 The issue	23
9.2 Design	23
9.3 Implementation	24
10 Behavioral simulation	25
10.1 Introduction	25
10.2 Design	25
10.3 Implementation	25
10.3.1 Action files	26
10.3.2 HoodExecutor	26
10.3.3 Browser	26
10.3.4 Hood action script	27
11 Conclusions	29
11.1 Possible improvements for future	29
11.1.1 LSM and seccomp	29
11.1.2 Compile time hardening	29
11.1.3 Network stack fingerprinting	29
11.1.4 Further use to libcomposite	29
12 The attacks that I have encountered during the time I was working on this thesis	31
12.1 Malicious hardwares	31
12.2 Sounds	31
13 Short title	33
13.1 The first section	33
13.2 The second, math section	33
13.3 third	33
A Some retarded material	35
A.1 It's over...	35
Glossary	37
Bibliography	39

Figures

7.1	Process view of TLS proxy	15
7.2	Process view of TLS traffics from user	18
8.1	Process view of OCSP over HTTP traffics from user	20
8.2	Process view of normal HTTP traffics from user	21
10.1	Logic view of hood-actor.py	28

Tables

7.1	Allowed cipher suites values	16
10.1	"type" field of action file objects	26
10.2	"properties" object of action file	26
10.3	"task" object of action file	26

Chapter 1

Introduction

Hacking and surveillance tools are widely deployed. The goal of this work is to increase the chance of survival of the user from hacking, eavesdropping, and digital fingerprinting. The device will work as a strict firewall which limits network activities and will also apply encryption standards to increase the difficulty of eavesdropping, and also to reduce the attack surface of fingerprinting. The device will run a TLS proxy to harden TLS protocol. It will use a screen to display selected real-time internet activities.

Using a hardware as a firewall has several advantages. Firstly, hardware firewall can provide complete isolation between highly unsafe code, like a browser, and firewall software (fun fact: I was hacked repeatedly through personally hardened latest version of Firefox while writing this thesis). This could also work as a mitigation of CPU/BIOS level threats: Firmware malwares, bootkits, and doubtful proprietary technologies like Intel ME and the AMD PSP. Second, it will also provide convenience to the user: the configuration of this portable device will be applied to protect everything behind it, so people do not need to do the time-consuming configuration work on different softwares and operating systems one by one.

Even things that could not be configured will be under the restriction of the firewall. In example, people cannot untrust a built-in trusted root certificate from iPhone via Settings app.

Chapter 2

Hardware

Commercial firewalls are more expensive than development boards that contains the same level of hardware functionality. It's acceptable because they provided additional values through their software and services and all of the development and maintenance of the product, the service, and the company are costing money. services are not If I was working on a commercial firewall, would In Switzerland, the price of an entry level firewall is more than twice of a Raspberry Pi. Raspberry Pi being used in this work could be replaced with some cheaper alternatives, making the cost will be even lower. Commercial firewalls also do not provide a screen to display network activities in real-time.

Chapter 3

Operating system

Due to its security-focused nature, OpenBSD would be a great choice when building a firewall. However, as a portable device, it is designed to work as a USB network device but OpenBSD does not contain a device mode in its USB stack. Linux provides USB gadget mode. Using the combination of ECM and RNDIS mode, most of Linux, Windows, BSD and MacOS could be supported. FreeBSD USB stack can run in device mode and provided 3 virtual network interface templates but none of them works with Microsoft Windows[Project, 2023]. Considering the large market share of Microsoft Windows, linux is decided as the base OS of this firewall device.

Chapter 4

Packet filtering and forwarding

4.1 Design

As the general principles, all traffics passed thorough should be checked to against evasdroping. A plaintext connection should be channeled through strong encryptions or be discarded if unable to ensure its integrity.

A modern browser can satisfy most of needs to interact with internet for working. So, allowing HTTP and HTTPS connections could make most of works done when facing a hostile network environment. Thus, everyting unnecessray to make this done are blocked. The fire-wall rules should be carefully made to filter out as much as possible and as early as possible, because everything on all layers of the Open Systems Interconnection model (OSI model) is protentialy vulnerable and the less network traffic being passed to the following components, the less chance a vulnerability can affect the firewall.

Proxies should be used to forward network traffics. There are advantages of using a proxy than forwarding packets like a router. First, a proxy can run under user level while packets forwarding run at kernel level. When there is a vulnerability, a userland one naturally to be less harmful than a kernel one. Second, proxies are easier and also safer to configure. It's hard to configure operatng system firewalls well. When the rules are not strict enough unexpected things may happen. In example, allowing any connection to 127.0.0.1 to success without a log, could cause potential problems if a malicious dhcp server assigned the address 127.0.0.1 to a physical network interface. Also, simply filtering packets by port numbers, addresses, and interfaces could not guarantee the packets being forwarded to the remote actually used by the protocols we are expecting. An attacker can simply let the receiving end of a reverse shell listen to an allowed port to bypass this kind of defense. By contrast, a proxy only works for the protocols that it can understand. when you are configuring a DNS proxy, the chance that your misconfiguration makes an attacker able to make http request over this proxy is very rare. They have to hack the firewall or create tunnels over those protocols to make their reverse shell work, which increased the difficulty of their operations. Third, the packets from the proxy will be encoded again by Linux network stack so the fingerprinting techniques that targeting TCP ad IP properties will useless to the devices under its protection.

4.2 Implementation

Nftables is integrated in modern linux systems. It can classify and filter network traffics. The firewall uses it to filter network packets. UDP 67 or 68 port and ARP packets are allowed for assigning IP addresses. UDP 53 is allowed from users to the firewall device for DNS requests, TCP 80, and TCP 443 are allowed for HTTP and HTTPS traffics. All other packets are filtered as early as possible.

Different proxies and RPC services are created to check connections, to forward traffics, and to apply encryptions. Details are included in the chapters of the corresponding protocol. See figs. 7.2, 8.1 and 8.2.

Chapter 5

Dynamic Host Configuration Protocol (DHCP)

5.1 Introduction

DHCP is widely used to dynamically assign a ip address to a new device connected to a network.

5.1.1 The issue

A client can expose its host name to the network from the 'client identifier' option or 'sname' field in the protocol. When in the same local network, the host name exposed by the DHCP protocol and other protocols can be used to locate the devices of the victim. If the name of a computer is straightforward enough, like "Yongbin's MacBoook Pro", the network administrator will be able to know the name of the owner of the computer from the first glance. The hardware address exposed to the network can also expose more information than just the address. Hardware address or Media Access Control (MAC) address can be used to reversly lookup the manufacturer and the manufacturer can help identify the owner. In example, the network administrator may lookup the MAC address of the a device to find out the manufacturer is company A and if the company A only sell its products in Country B and if C is the only person come from Country B then the chance that the device belongs to C would be high.

5.2 Design

Firewall should randomize both host name and MAC address. The randomized computer name should look normal to prevent being identified by potential attackers.

5.3 Implementation

NetworkManager is used to manage physical connections of the firewall. By adding 'ethernet.cloned-mac-address=random' and 'wifi.cloned-mac-address=random' to the 'connection' section of

NetworkManager.conf, the MAC address randomization will be done by NetworkManager. The 'ifconfig interface link random' command can also randomize the MAC address of a interface manually.

Host names of the firewall device is random generated while starting the system. The relevant code is inside rc.local. The name is crafted to look normal. The pattern of default computer name of Microsoft Windows and common names like iPad are used. Since the implementation of the client of the protocol could also be vulnerable, the combination of AppArmor and dhclient to mitigate this problem.

Dnsmasq is used to assign IP address of the users of the firewall it will also tell the devices behind the firewall to use the firewall as the DNS resolver.

Chapter 6

Domain Name System (DNS)

6.1 Introduction

DNS is a protocol that translates the human readable domain names to the ip addresses of the remote server. The default configuration of many devices are to use plaintexts to do requests, which could easily be monitored by simply recording the packets and be attacked by methods like DNS spoofing.

6.2 Design

From the network administrator's view, all DNS queries sent out from firewall should be encrypted. From the user's view, nothing should be specially configured.

6.3 Implementation

6.3.1 Outgoing requests

A name resolving service is created to resolve domain name queries from firewall services. It is a local RPC service that resolve domain name queries via public DNS-over-HTTPS (DoH) services. DoH can mitigate both passive surveillance and DNS spoofing attacks[Hoffman and McManus, 2018]. DoT (DNS-over-TLS) is another DNS encryption standard that can do almost the same as DoH. The reason why use DoH instead of DoT is that DoT uses a unique server port number, 853, that can be easily filtered and identified as an encrypted DNS connection, while DoH, with the help of using the same port number and protocol as HTTPS, makes it much harder to be identified and filtered than DoT.

6.3.2 Inside firewall

A dnsmasq is started locally to resolve everything to localhost to make the firewall proxy to be applied as system-wide.

6.3.3 Incoming requests

A dnsmasq is started to resolve everything to the firewall device to make the firewall proxy to be applied to devices behind it.

Chapter 7

Transport Layer Security (TLS)

7.1 Management of certificates

7.1.1 Introduction

All modern major operating systems managed a collection of trusted certificates issued by certificate authorities (CAs) they choose. Those certificates are used to prove the validity of a public key. When making a TLS connection, local applications will check the path of the certificate provided by remote with local trusted collection to ensure secure connections.

The issue

Almost all TLS clients do not alert its user when the remote website presented a different certificate, which gives CAs the power to do man in the middle (MITM) attacks. Even if do not want to do evil, their private key could still have been stolen. Thus, none of them are strictly trustworthy. However, whole TLS is based on it, if we trust none of those authorities, there will be almost no website we can use and things will be worse if without TLS.

Existing solutions

SSL-pinning can prevent MITM attacks from a trusted CA when the user know the remote endpoint should use the certificate from another authority. However, configuring SSL-pinning to all the endpoints is hard and time consuming to average users and without a basic trusted environment, it will be unable to certain whether the configuration has done correctly. Even if the configuration is correct, it is still not strange for an endpoint to switch to another CA. Thus, to a firewall, this technique cannot be used as a general solution of the issue that can be applied to all endpoints.

Removing suspicious CAs from the trusted list could protect people from MITM attacks initiated by those CA. However, some systems and devices do provide the function of untrusting a CA. In example, iPhone needs a computer to enable such configuration and most of Android variants.

7.1.2 Design

The firewall should trust only the CAs that are being widely used in the internet. People should be able to further decide which certificates to trust. One can consider untrust following when making such decisios: the CAs of the place you are staying, the CAs of the place you come from, and their enemies and allies.

7.1.3 Implementation

Since SSL-pinning can only be used on a small number of endpoints to an advanced user who can clearly know what is this meant to be, it is not implemented now. Manually management of the certificate can be done by Linux commands. The certificate of all outgoing TLS connection remote points are checked by TLS proxy.

7.2 Mismatch between the changing best current practice and the unchanged implementation

7.2.1 Problem

The mismatch problem has been existed everywhere whenever a public protocol standard updated a fix to a problem. There are delays between a deficiency of a protocol being published and the majority of the implementation fixed the problem. A living example is that in the latest version of python 3.12.1 released on December 2023, as part of its builtin libraries, the implementation of the function `create_default_context()` from the `ssl` library is still creating a context that supports TLS 1.0 and TLS 1.1 by default [Foundation, 2023], while they have already been deprecated by the best practice `rfc8996` since March 2021 [Moriarty and Farrell, 2021].

7.2.2 Solution

An idea to save the clients that contain severe deficiencies is to attack from their deficiencies then hijack and channel their communication to remote endpoints through the TLS connection with the current best practices applied. The application of this methodology to downgrade attack of Secure Socket Layer (SSL) version 2.0 was the initial motivation of the works on the TLS proxy, but the due to the drastic changes to the protocol, the final implementation is instead to use the proxy to check whether the best practice is applied.

7.3 Proxy

MITM attack

Despite using MITM attack to inspect or protect encrypted connections has been used in firewalls and proxies for many years [FORTINET, 2021], the `tls` proxy used in this firewall should not implement the same functionality. The reason is that when the firewall itself is compromised, the ability to decrypt TLS sessions will cause a disaster to the devices behind it: the attacker will be able to easily modify the encrypted data transferred over a MITM proxy while the devices behind the firewall will alert nothing about the modification. However, if the firewall could not

do MITM attack at all, the compromised still unable to see and modify encryptions, because the certificate verification of the devices behind this firewall is still working.

Filtering certificates

The `key_share` extension sometimes makes the certificate invisible to the proxy. Thus, in order to filter certificates, the proxy will handshake with remote server with a separate connection to verify the certificate used by the remote host. A cache of trusted endpoints is used to reduce delay caused by certificate check connections.

Checking connections

The proxy should parse handshake packets. It should check algorithms provided by ClientHello and ServerHello, to ensure strong encryption. Strengthen the connection by modifying handshake packets without MITM is not possible because the HMAC of all handshake packets is used for encryption.

Implementation




Figure 7.1. Process view of TLS proxy

Programming language Since TLS proxy in charge of processing and forwarding the majority traffic of the firewall, c++ is used to develop the proxy due to its high performance capability.

ClientHello Upon receiving ClientHello from a client, the proxy at first check the version of the protocol, and the `suppor_versions` extension to see if the client supports to establish a safe TLS channel, TLS 1.1 and TLS 1.2 are the only allowed versions [Sheffer et al., 2022], if a ClientHello shows that the client supports neither, it will be discarded. After the version check, the `ciphersuites` field will also be checked, if it contains none of the value listed in 7.1 [Sheffer et al., 2022], it will be considered unable to be safe and discarded. If the ClientHello passed all of the security checks, the proxy will extract the Server Name Indication (SNI) from ClientHello to dertermine the actual destination of the request.

- TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
- TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
- TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256
- TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384
- TLS_AES_128_GCM_SHA256
- TLS_AES_256_GCM_SHA384
- TLS_CHACHA20_POLY1305_SHA256

Table 7.1. Allowed cipher suites values

Name resolving and trused endpoint The proxy will at first check if there is any cached trused endpoints available, if not it uses a RPC call to `hood-name-service.py` to resolve the domain name. Then TLS handshakes following the the same restrictions to the ClientHello check will be made to all of the addresses returned from the name service. The handshake process will not only ensure remote endpoint meets the requirements (versions and ciphersuites) of applying the best practices described in `rfc9325`, it will also check whether the remote endpoint could provide a validate certificate of the hostname from a trusted CA of the firewall.

ServerHello After forwarding the ClientHello to the server, a ServerHello will be responded and the proxy will check the final result of the handshake applies to the best practice. If a naughty attacker made the negotiation result to use unsafe, TLS 1.0 or the cipher suite `RSA_WITH_NULL_MD5` for example, the connection will be blocked.

7.4 Process view of traffics




Figure 7.2. Process view of TLS traffics from user

Chapter 8

Plaintext connections

8.1 HTTP

8.1.1 Implementation

hood-http-handler.py is the proxy created to filter and protect HTTP plaintext connections. The proxy check the host name with a known list of OCSP (Online Certificate Status Protocol) and CRL (Certificate Revocatoin List) servers. Only the connections to those servers are allowed to be plaintext because those connections usually to be OCSP over HTTP connections, which have no reason to be protected. The connections to other servers will be tunneled via TLS protocol through hood-tls-proxy service. See figs. 8.1 and 8.2.




Figure 8.1. Process view of OCSP over HTTP traffics from user




Figure 8.2. Process view of normal HTTP traffics from user

Chapter 9

Date time synchornization

9.1 Introduction

A correct time is required for TLS protocol to check certificates. Network Time Protocol (NTP) is used by most of modern systems to synchornize the clock with a remote server.

9.1.1 The issue

A problem of using a hardware like a Raspberry Pi is that it does not have a battery to keep the clock ticking after the power source is cut. So a time synchornization mechanism is a must for this firewall.

Many of operating systems are pre-configured to use a NTP server which having a unique domain name that can be used by a network administrator to identify the operating systems being used by the client.

Both the unique port number (UDP 123) and the unique domain names (time.windows.com, time.apple.com, and ubuntu.pool.ntp.org) makes NTP a protocol that can be easily identified and targeted. Various attacks can be done to the protocol itself[Kwon et al., 2023]. The different in NTP behavior between different operating systems has been used in OS fingerprinting and tethering detection osandtether. Not to mention that the operating system being exposed by the domain name can also help an attacker to target the NTP client being used by the device.

9.2 Design

Give up on NTP, use HTTP/HTTPS instead. Use the "Date" header from the response of a HTTP server to synchornize date time in an acceptable accuracy. Usually, in order to hide, the attacks targeted to HTTP/HTTPS protocol do not want to make mistakes in the header of its attack vector.It's hard to say whether this request is made for time synchornization.

9.3 Implementation

Since TLS needs time to be correct to validate certificates, a plaintext HTTP request is made to do an initial synchornization. After the first step, the system clock is considered to be correct enough for making a TLS connection. So the second step is to extract date time from the header of a HTTPS response.

Chapter 10

Behavioral simulation

10.1 Introduction

In previous chapters, the fact that network activities can be used to detect the user has been proved in different protocols. However, the efforts to reduce the leak of the information on those protocols are not enough when facing a more sophisticated network analyzation. In example, the connections to Windows update servers and App Store servers can be used to detect Windows and Apple devices citeposandtether, but the firewall has no reason to stop those connections. Even if the firewall blocked all OS specific connections, the domain leaked from TLS handshakes can also tell the evasdroppers what websites a person is watching and then may infer what the person is doing. Thus, the leak of the information seems to be inevitable.

10.2 Design

A service to simulate different network activities is designed to solve ths issue. The goal is to hide user network activities inside the flood of fake network activities to increase the difficulty of an analyzer to produce useful reports. However, the risk of using this service is to produce a false alarm immediately and make the user blocked for tethering, make the user fired for browsing unrelated websites, etc.. To avoid the firewall to be compromised from browser vulnerabilities, browser-based simulation tools, like puppeteer, should not be used for implementation. It should also make plaintext traffics to attaract attentions from attackers and evasdroppers to make them less focused on the actual user traffics.

10.3 Implementation

The service is implemented in a python script named hood-actor.py. It can parse and execute action files. To simulate the behaviors of a human user or a computer service. All implemen-tations inside script are based on the base modules of python, to avoid the version management of thrid party libraries being involved in the installation process of the firewall.

10.3.1 Action files

Action files are in JSON format. An action file contains an array of objects. All objects in the array has a "type" field to let the parser know how to process it. Supported object types are described in tables 10.1 to 10.3.

Value	Descriptoin
properties	Properties of the action
task	Tasks to be done in the action

Table 10.1. "type" field of action file objects

Field	Type	Descriptoin
type	string	"properties"
safe_age	integer	Minimum age safe to do this
proper_age	list of two numbers [min, max]	Proper range of age to do this.

Table 10.2. "properties" object of action file

Field	Type	Descriptoin
type	string	"task"
name	string	Name of the task, must be unique in current file
before	list of strings	Names of tasks that should run no earlier than this.
after	list of strings	Names of tasks that should run before this.
delay_between_actions	list of two numbers [min, max]	Range of seconds to wait between actions.
actions	list of strings	list hood action script

Table 10.3. "task" object of action file

10.3.2 HoodExecutor

HoodExecutor is a general purpose multi-thread task executor for python. It can run and schedule tasks that has dependency relationships and delay requirements in parallel. It has a thread pool of workers to execute tasks and a single thread for scheduling delayed tasks. It is required to simulate the paralleled requests sent out from real world browsers if without third party HTTP client based on asyncio. It is also the cornerstone of fullfilling all the execution requirements of the tasks and actions in an action file.

10.3.3 Browser

A fake browser is creted to simulate network activities of browsing is a general purpose multi-thread task executor for python. It records the cookies specified in the HTTP response headers and sends them out like a real browser. It parses the HTML content of the webpage to extract

the resources to be loaded and load them in parallel just like a real browser. It uses headers that used by real browsers and uses different headers on different resources just like a real browser. Due to security concerns, and also to reduce the performance impacts caused by the actor, fake browser will neither render the webpage [CVE-2023-6707, CVE-2023-6351, CVE-2023-6869, CVE-2023-5170] nor evaluate scripts [CVE-2023-6702, CVE-2023-5997, CVE-2023-5728, CVE-2023-5723] used by the webpage.

10.3.4 Hood action script

Hood action script is a script to describe actions to be done to the actor. Each line of the script can be seen as three parts: namespaces, command, and argument. For example, "hood:browser:goto:http://www.example.com". "hood:browser:" is to refer browser namespace from hood namespace, "goto" is a command inside browser namespace to tell interpreter to use browser to load a webpage. "http://www.example.com" is the parameter of the "goto" command. In this example, it represents the url of the webpage to be loaded.

hood:browser:goto command

Its usage is "hood:browser:goto URL". Its will to use a fake browser to load a URL, all static resource described in HTML will be loaded, cookies will be stored and used in the running session, but by design, dynamic things like JavaScript, will not be executed. When the special value "random_link" is used as the argument, actor will randomly pick a link from the webpage currently loaded in the browser to go to, but nothing will be done if current webpage contains not links.

hood:loop command

Its usage is "hood:loop:CONDITION:COMMAND". It is used to declare a loop. Multiple conditions can be declared in CONDITION part by syntax "key=value[,key=value]". Currently only two types of conditions are implemented: "exit_chance" and "delay". "exit_chance" describes the chance of the loop to be stopped. "exit_chance=0.33" means the loop has 33




Figure 10.1. Logic view of hood-actor.py

Chapter 11

Conclusions

11.1 Possible improvements for future

11.1.1 LSM and seccomp

Use LSMs, like AppArmor, and seccomp to protect all as much process as possible. The programs that do not support seccomp can be changed by `LD_LOAD_LIBRARY`.

11.1.2 Compile time hardening

Use strict compiler options to harden everything, including kernel, like what Gentoo Linux is doing now, to try to mitigate some unpublished vulnerabilities, and also to increase the difficulty of attacking the firewall itself.

11.1.3 Network stack fingerprinting

Spoof network stacks, like TCP stacks and TLS stacks, to make the firewall and the devices behind it to be less detectable.

11.1.4 Further use to libcomposite

Libcomposite has the ability to make the device to show multiple roles to a host (a computer), which means the device can at the same time work as a USB mass storage device or as a USB CDROM, both of which can be used as a media of a Live DVD. Then the computer will be able to boot a live system from it. For a computer that password protected to boot from USB, we can also use this small device as a PXE server to make that computer boot from the network of the USB device.

Chapter 12

The attacks that I have encountered during the time I was working on this thesis

12.1 Malicious hardwares

Normal attackers will use network, bluetooth or wifi for communications between malware and the host. In example, casting the screen to another device via wifi or sending keyboard inputs via bluetooth. Those kind of attacks can be detected by a RF detector. RF sheilding fabrc, RF detectors, and signal jammers could be used to fight against such kind of attacks.

However, There are still other ways exist. Some even without wireless communications. Despite I have already bought a RF detector to alert me wireless communications between unknown hardwares, unknown attackers still managed to monitor my progress by modified hardwares. Take the devices that I am using to develop this project for example. Raspberry 4B has a usb chip that can communicate to the power source. If the charger is specially crafted with the ability to forward the usb connection to the remote endpoint via power lines, then, with the help from the malware installed on the pi itself, data can be leaked silently via power lines even without any network connections to the computer. The same story can also be happened to the portable screen that I am using now. I have found two counter measurements to this kind of attack: One is to use USB-C to DC adapter when connecting a USB-C charger to the laptop. Another is to tape the two pins in the middle of male USB-A port to prevent data communications.

12.2 Sounds

Another attack that can bypass a rfkilled computer is to use AI / ML to identify the sounds of keyboard hits. The detected types can be send to remote via power lines or mobile phones. The sound could even be recorded from the room of a neighbor which makes this attack more stealthy than other methods. I use cardboards to extend the pillar of the key cap to shorten

the key travel to lower the volume of the sound of the key hit to counter this attack but I am uncertain about the effect because I have no attack tools to test this. AliPay also used to use sound waves to transmit data between phones and vending machines. My raspberry pi recently started to emit strange noises from the speakers on the screen, which could be because of the same technology being used for hackers.

Chapter 13

A chapter title which will run over two lines — it’s for testing purpose

13.1 The first section

13.2 The second, math section

Theorem 1 (Residue Theorem). Let f be analytic in the region G except for the isolated singularities a_1, a_2, \dots, a_m . If γ is a closed rectifiable curve in G which does not pass through any of the points a_k and if $\gamma \approx 0$ in G then

$$\frac{1}{2\pi i} \int_{\gamma} f = \sum_{k=1}^m n(\gamma; a_k) \text{Res}(f; a_k).$$

Theorem 2 (Maximum Modulus). Let G be a bounded open set in \mathbb{C} and suppose that f is a continuous function on G^- which is analytic in G . Then

$$\max\{|f(z)| : z \in G^-\} = \max\{|f(z)| : z \in \partial G\}.$$

13.3 A very very long section, titled “The third section”, with a rather short text alternative (third)

Some Test

```
1 import IntSpec, ItemSpec;
2
3 sort cart;
4
5 constructors
6 create()  $\longrightarrow$  cart;
7 insert(cart, item)  $\longrightarrow$  cart;
8 observers
```

```
9 amount(cart)  $\longrightarrow$  int;
10 transformers
11 delete(cart, item)  $\longrightarrow$  cart;
12
13 axioms
14 forall c: cart, i, j: item
15
16 amount(create()) = 0;
17 amount(insert(c,i)) = amount(c) + price(i);
18 delete(create(),i) = create();
19 delete(insert(c,i),j) =
20 if (i == j) c
21 else insert(delete(c,j),i);
22 end
```

As you can easily see from the above listing Baresi et al. [2007a] define something weird based on the BPEL specification [Andrews et al., 2003].

Appendix A

Some retarded material

A.1 It's over...

Glossary

Bibliography

- Tony Andrews, Francisco Curbera, Hitesh Dholakia, Yaron Goland, Johannes Klein, Frank Leymann, Kevin Liu, Dieter Roller, Doug Smith, Satish Thatte, Ivana Trickovic, and Sanjiva Weerawarana. Business Process Execution Language for Web Services, Version 1.1. BPEL4WS specification, May 2003.
- L. Baresi, D. Bianculli, C. Ghezzi, S. Guinea, and P. Spoletini. Validation of web service compositions. *IET Software*, 1(6):219–232, 2007a. doi: 10.1049/iet-sen:20070027. URL <http://link.aip.org/link/?SEN/1/219/1>.
- Luciano Baresi, Domenico Bianculli, Carlo Ghezzi, Sam Guinea, and Paola Spoletini. A timed extension of WSCoL. In *Proceedings of the IEEE International Conference on Web Services (ICWS 2007)*, pages 663–670. IEEE Computer Society Press, July 2007b.
- Domenico Bianculli and Carlo Ghezzi. Monitoring conversational web services. In *Proceedings of the 2nd International Workshop on Service-Oriented Software Engineering (IW-SOSWE'07), co-located with ESEC/FSE 2007*, pages 15–21, New York, NY, USA, September 2007. ACM Press.
- Domenico Bianculli, Carlo Ghezzi, and Paola Spoletini. A model checking approach to verify BPEL4WS workflows. In *Proceedings of the 2007 IEEE International Conference on Service-Oriented Computing and Applications (IEEE SOCA 2007)*, pages 13–20. IEEE Computer Society Press, June 2007a.
- Domenico Bianculli, Radu Jorca, Walter Binder, Carlo Ghezzi, and Boi Faltings. Automated dynamic maintenance of composite services based on service reputation. In *Proceedings of ICSOC'07, International Conference on Service-Oriented Computing*, volume 4749 of *Lecture Notes in Computer Science*, pages 449–455. Springer-Verlag, September 2007b.
- Domenico Bianculli, Angelo Morzenti, Matteo Pradella, Pierluigi San Pietro, and Paola Spoletini. Trio2Promela: a model checker for temporal metric specifications. In *29th International Conference on Software Engineering (ICSE'07 Companion)*, pages 61–62, Los Alamitos, CA, USA, May 2007c. IEEE Computer Society. ISBN 0-7695-2892-9. doi: <http://doi.ieeecomputersociety.org/10.1109/ICSECOMPANION.2007.79>. Research Demo.
- Domenico Bianculli, Paola Spoletini, Angelo Morzenti, Matteo Pradella, and Pierluigi San Pietro. Model checking temporal metric specification with Trio2Promela. In *Proceedings of International Symposium on Fundamentals of Software Engineering (FSEN 2007)*, volume 4767 of *Lecture Notes in Computer Science*, pages 388–395. Springer Verlag, April 2007d.

Yi-Chao Chen, Yong Liao, Mario Baldi, Sung-Ju Lee, and Lili Qiu. Os fingerprinting and tethering detection in mobile networks. In *IMC '14: Proceedings of the 2014 Conference on Internet Measurement Conference*, pages 173–180, New York, NY, United States, November 2014. Association for Computing Machinery. doi: <https://doi.org/10.1145/2663716.2663745>.

FORTINET. Security profiles. In *FortiOS - Administration Guide*, chapter 9, pages 1026–1029. June 2021. URL <http://docs.freebsd.org/en/books/handbook/usb-device-mode/>.

Python Software Foundation. ssl - tls/ssl wrapper for socket objects. In *Python 3.12.1 documentation*. December 2023. URL <http://docs.freebsd.org/en/books/handbook/usb-device-mode/>.

Paul Hoffman and Patrick McManus. DNS Queries over HTTPS (DoH). RFC 8484, RFC Editor, October 2018. URL <https://www.rfc-editor.org/rfc/rfc8484>.

Jonghoon Kwon, Jeonggyu Song, Junbeom Hur, and Adrian Perrig. Did the shark eat the watchdog in the ntp pool? deceiving the ntp pool's monitoring system. In *USENIX Security'23*, USENIX Security Symposium. USENIX, August 2023. URL <https://www.usenix.org/system/files/usenixsecurity23-kwon.pdf>.

David C. Luckham, Friedrich W. von Henke, Bernd Krieg-Brueckner, and Olaf Owe. *ANNA: a language for annotating Ada programs*. Springer-Verlag, New York, NY, USA, 1987. ISBN 0-387-17980-1.

Kathleen Moriarty and Stephen Farrell. Deprecating tls 1.0 and tls 1.1. RFC 8996, RFC Editor, March 2021. URL <https://www.rfc-editor.org/rfc/rfc8996>.

The FreeBSD Documentation Project. Chapter 28.usb device mode/usb otg. In *FreeBSD Handbook*, chapter 28. July 2023. URL <http://docs.freebsd.org/en/books/handbook/usb-device-mode/>.

Yaron Sheffer, Peter Saint-Andre, and Thomas Fossati. Recommendations for secure use of transport layer security (tls) and datagram transport layer security (dtls). RFC 9325, RFC Editor, November 2022. URL <https://www.rfc-editor.org/rfc/rfc6176>.

Sean Turner and Tim Polk. Prohibiting secure socket layer (ssl) version 2.0. RFC 6176, RFC Editor, March 2011. URL <https://www.rfc-editor.org/rfc/rfc6176>.