

SA-1P-30A-24V



SA-1P-40A-24V



Product overview

SA Series DP Contactor is mainly used to control motor load for AC 50Hz/60Hz ,rated insulation voltage: 690V ,rated work current:90A Air Conditioner compressor, also applicable for other household and similar purposes device.

Features&benefits

◇Small size, compact structure, same installation dimensions, easy for replace.
◇High heat-resistant coil, suitable for both 50Hz/60Hz & wide voltage range.
◇Contact with excellent Arc resistance capacity.
◇Resist Arc effectively with patented Arc extinguishing technology.

Product certification

c UL us	**UL**	UL 60947-4-1	CE	**CE**	IEC 60947-4-1
c SP us	**CSA**	C22.2 No.60947-4-1	**A2L**	**A2L**	CSA C22.2 No.60335-2-40 UL 60335-2-40
S	**Semko**	IEC 60947-4-1	RoHS	**RoHS**	RoHS Compliant
CCC	**CCC**	GB/T 14048.4	Reach	**REACH**	REACH Compliant

Code explanation

SA – 1P – □A – □ V

Basic Model Designation: SA

Number of Pole: 1/1.5P: 1 Pole with shunt

Contact Rating (Full Load Amps-FLA): 20: 20A, 25: 25A, 30: 30A, 35: 35A, 40: 40A

Coil Voltag:
24: 24V AC, 50 Hz/ 60 Hz
36: 36V DC(Only for 1.5P,FLA=20A and 25A)
120: 120V AC, 50 Hz/ 60 Hz
208/240: 208/240V AC, 50 Hz/ 60 Hz
277: 277V AC, 50 Hz/ 60 Hz
380: 380 V ac, 50 Hz/60 Hz
480: 480 V ac, 50 Hz/60 Hz

Termination Code: AA: Screw mode and quick connect terminal for 1P&2P series
CC: Frame mode and quick connect terminal for 1P&2P series
BB: Screw mode and quick connect terminal except optional SEMS plate

Ambient condition

Ambient temperature (℃)	Operating	-40 ~ +65
	Storage	-40 ~ +70
Relative humidity	90% ~ 95%RH（Below 40℃）	
Pollution degree	3	
Enclosure rating	IP00	
Max Working Altitude（m）	2000	
Installation	M5 Screw installation，Horizontal or vertical installation of the base	

Technical Parameter

CONTACT RATING - Main Contact

Full Load Amps FLA	RES	LRA			
		240V	277V	480V	600V
A	A	A	A	A	A
1 POLE 20-40FLA(Include 1+N)					
20	30	120	120	100	80
25	35	150	150	125	100
30	40	180	180	150	120
40	50	240	240	200	160

CONTACT IEC RATING – Main Contact

Product specifications	AC-1	AC-3		AC-8a	AC-8b	Ith(A)
	240VAC	240VAC	277VAC	240VAC	240VAC	
1 Pole 20 FLA	30	20	20	20	7	30
1 Pole 25 FLA	35	25	25	25	8	35
1 Pole 30 FLA	40	30	30	30	10	40
1 Pole 40 FLA	50	40	40	40	15	50

Coil Rating(+25℃)

Product specifications	MaxInrush (V·A)		Max Seal (V•A)		Voltage (VAC)		
	60Hz	50Hz	60Hz	50Hz	Operate	Dropout	Max Voltage
SA 1 Pole 20-40FLA	20	25	6.5	7.5	≤0.8Us	≥0.2Us	1.1Us

Remark:

1.Coil Us=24VAC 50/60Hz or 120VAC 50/60Hz or 208/240VAC 50/60Hz or 277VAC 50/60Hz, 380VAC 50/60Hz or 480VAC 50/60Hz.

2.Starting and holding capacity are both measured at the rated voltage of the coil Us.

3.Pick-up & drop-off voltage are tested under the condition of the base being perpendicular to the horizontal (vertical installation).


Technical parameter description

Above data is based on the testing under standard condition with manufacturer's sample , actual use may vary due to differences in environment, on/off load, on/off frequency, and equipment.


Dimension

inch[mm]


SA-1P 20-40A




Terminals



20-40FLA
#10-32 Combination Screw



20-40FLA
#10-32 SEMS Screw




20-40FLA——Lug
#14-4 AWG Cu/Al


Remark:
1.The tolerance of wiring connector without specified dimensions shall be in accordance with ±0.2mm.
2.Main circuit screw locking torque for rated current 20-40FLA products: SCREWS 22 IN-LBS / LUGS 40 IN-LBS Main circuit screw locking torque for rated current 50-60FLA products: 50 IN-LBS
Main circuit screw locking torque for rated current 75-90FLA products: 50 IN-LBS
Auxiliary module screw locking torque: 10 IN-LBS
Coil screw locking torque for rated current 20-90FLA products: 10 IN-LBS
3.The quick connect socket terminal must comply with IEC60760 standard and ensure reliable connection between terminal and insert ,if insert wiring is used.

Diagram

Contactor



1 Pole 20-40 FLA



1+N Pole 20-40 FLA