

Support Vector Machines and Kernel Methods – Part 2

UNC-CH COMP 755


Slides adapted from: A. Zisserman, B. Schölkopf, D. Sontag,
L. Zettlemoyer, C. Guestrin, et al.

Dual SVM derivation (1) – the linearly separable case

Original optimization problem:

$$\begin{aligned} & \text{minimize}_{\mathbf{w}, b} \quad \frac{1}{2} \mathbf{w} \cdot \mathbf{w} \\ & (\mathbf{w} \cdot \mathbf{x}_j + b) y_j \geq 1, \quad \forall j \end{aligned}$$

Rewrite constraints One Lagrange multiplier per example



Lagrangian:


$$\begin{aligned} L(\mathbf{w}, \alpha) &= \frac{1}{2} \mathbf{w} \cdot \mathbf{w} - \sum_j \alpha_j [(\mathbf{w} \cdot \mathbf{x}_j + b) y_j - 1] \\ \alpha_j &\geq 0, \quad \forall j \end{aligned}$$

Our goal now is to solve: $\min_{\vec{w}, b} \max_{\vec{\alpha} \geq 0} L(\vec{w}, \vec{\alpha})$

Dual SVM derivation (2) – the linearly separable case

(Primal)

$$\min_{\vec{w}, b} \max_{\vec{\alpha} \geq 0} \frac{1}{2} \|\vec{w}\|^2 - \sum_j \alpha_j [(\vec{w} \cdot \vec{x}_j + b) y_j - 1]$$



Swap min and max

(Dual)

$$\max_{\vec{\alpha} \geq 0} \min_{\vec{w}, b} \frac{1}{2} \|\vec{w}\|^2 - \sum_j \alpha_j [(\vec{w} \cdot \vec{x}_j + b) y_j - 1]$$

Slater's condition from convex optimization guarantees that these two optimization problems are equivalent!

Dual SVM derivation (3) – the linearly separable case

$$(\text{Dual}) \quad \max_{\vec{\alpha} \geq 0} \min_{\vec{w}, b} \frac{1}{2} \|\vec{w}\|^2 - \sum_j \alpha_j [(\vec{w} \cdot \vec{x}_j + b) y_j - 1]$$

Can solve for optimal \mathbf{w} , b as function of α :

$$\frac{\partial L}{\partial w} = w - \sum_j \alpha_j y_j x_j \quad \Rightarrow \quad \mathbf{w} = \sum_j \alpha_j y_j \mathbf{x}_j$$

$$\frac{\partial L}{\partial b} = - \sum_j \alpha_j y_j \quad \Rightarrow \quad \sum_j \alpha_j y_j = 0$$

Substituting these values back in (and simplifying), we obtain:

$$(\text{Dual}) \quad \max_{\vec{\alpha} \geq 0, \sum_j \alpha_j y_j = 0} \sum_j \alpha_j - \frac{1}{2} \sum_{i,j} y_i y_j \alpha_i \alpha_j (\vec{x}_i \cdot \vec{x}_j)$$

Sums over all training examples scalars dot product

Dual SVM derivation (3) – the linearly separable case

$$\text{(Dual)} \quad \max_{\vec{\alpha} \geq 0} \min_{\vec{w}, b} \frac{1}{2} \|\vec{w}\|^2 - \sum_j \alpha_j [(\vec{w} \cdot \vec{x}_j + b) y_j - 1]$$

Can solve for optimal \mathbf{w} , b as function of α :

$$\frac{\partial L}{\partial w} = w - \sum_j \alpha_j y_j x_j \quad \Rightarrow \quad \mathbf{w} = \sum_j \alpha_j y_j \mathbf{x}_j$$

$$\frac{\partial L}{\partial b} = - \sum_j \alpha_j y_j \quad \Rightarrow \quad \sum_j \alpha_j y_j = 0$$

Substituting these values back in (and simplifying), we obtain:

$$\text{(Dual)} \quad \max_{\vec{\alpha} \geq 0, \sum_j \alpha_j y_j = 0} \sum_j \alpha_j - \frac{1}{2} \sum_{i,j} y_i y_j \alpha_i \alpha_j (\vec{x}_i \cdot \vec{x}_j)$$

So, in dual formulation we will solve for α directly!

- \mathbf{w} and b are computed from α (if needed)

Dual SVM derivation (3) – the linearly separable case

Lagrangian:

$$L(\mathbf{w}, \alpha) = \frac{1}{2}\mathbf{w} \cdot \mathbf{w} - \sum_j \alpha_j [(\mathbf{w} \cdot \mathbf{x}_j + b)y_j - 1]$$
$$\alpha_j \geq 0, \quad \forall j$$



$\alpha_j > 0$ for some j implies constraint is tight. We use this to obtain b :

$$y_j (\vec{w} \cdot \vec{x}_j + b) = 1 \quad (1)$$

$$y_j y_j (\vec{w} \cdot \vec{x}_j + b) = y_j \quad (2)$$

$$(\vec{w} \cdot \vec{x}_j + b) = y_j \quad (3)$$



$$\mathbf{w} = \sum_i \alpha_i y_i \mathbf{x}_i$$

$$b = y_k - \mathbf{w} \cdot \mathbf{x}_k$$

for any k where $\alpha_k > 0$

Classification rule using dual solution

$$y \leftarrow \text{sign}(\vec{w} \cdot \vec{x} + b)$$

Using dual solution

$$y \leftarrow \text{sign} \left[\sum_i \alpha_i y_i (\vec{x}_i \cdot \vec{x}) + b \right]$$

dot product of feature vectors of
new example with support vectors

$$\mathbf{w} = \sum_i \alpha_i y_i \mathbf{x}_i$$

$$b = y_k - \mathbf{w} \cdot \mathbf{x}_k$$

for any k where $C > \alpha_k > 0$

Dual for the non-separable case

Primal:

$$\begin{aligned} \text{minimize}_{\mathbf{w}, b} \quad & \frac{1}{2} \mathbf{w} \cdot \mathbf{w} + C \sum_j \xi_j \\ (\mathbf{w} \cdot \mathbf{x}_j + b) y_j \geq & 1 - \xi_j, \quad \forall j \\ \xi_j \geq & 0, \quad \forall j \end{aligned}$$

Solve for $\mathbf{w}, \mathbf{b}, \alpha$:

$$\begin{aligned} \mathbf{w} = & \sum_i \alpha_i y_i \mathbf{x}_i \\ b = & y_k - \mathbf{w} \cdot \mathbf{x}_k \\ \text{for any } k \text{ where } C > \alpha_k > 0 \end{aligned}$$

Dual: $\text{maximize}_{\alpha} \quad \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y_i y_j \mathbf{x}_i \mathbf{x}_j$

$$\begin{aligned} \sum_i \alpha_i y_i = & 0 \\ C \geq \alpha_i \geq & 0 \end{aligned}$$

What changed?

- Added upper bound of C on α_i !
- Intuitive explanation:
 - Without slack, $\alpha_i \rightarrow \infty$ when constraints are violated (points misclassified)
 - Upper bound of C limits the α_i , so misclassifications are allowed


Support vectors

- **Complementary slackness** conditions:

$$\alpha_j^* [y_j(\vec{w}^* \cdot \vec{x}_j + b) - 1 + \xi_j] = 0 \implies \alpha_j^* = 0 \vee y_j(\vec{w}^* \cdot \vec{x}_j + b) = 1 - \xi_j$$
$$\implies \alpha_j^* = 0 \vee y_j(\vec{w}^* \cdot \vec{x}_j + b) \leq 1$$

- **Support vectors**: points x_j such that $y_j(\vec{w}^* \cdot \vec{x}_j + b) \leq 1$
(includes all j such that $\alpha_j^* > 0$, but also additional points where $\alpha_j^* = 0 \wedge y_j(\vec{w}^* \cdot \vec{x}_j + b) \leq 1$)
- Note: the SVM dual solution may not be unique!

Dual SVM interpretation: Sparsity



Non-support Vectors:

- $\alpha_j = 0$
- moving them will not change w

$$\mathbf{w} = \sum_j \alpha_j y_j \mathbf{x}_j$$

Final solution tends to be sparse

- $\alpha_j = 0$ for most j
- don't need to store these points to compute w or make predictions

Support Vectors:

- $\alpha_j \geq 0$

SVM with kernels


$$\begin{aligned} \text{maximize}_{\alpha} \quad & \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y_i y_j K(\mathbf{x}_i, \mathbf{x}_j) \\ K(\mathbf{x}_i, \mathbf{x}_j) &= \Phi(\mathbf{x}_i) \cdot \Phi(\mathbf{x}_j) \\ \sum_i \alpha_i y_i &= 0 \\ C \geq \alpha_i &\geq 0 \end{aligned}$$

- Never compute features explicitly!!!
 - Compute dot products in closed form
- $O(n^2)$ time in size of dataset to compute objective
 - much work on speeding up


Predict with:

$$y \leftarrow \text{sign} \left[\sum_i \alpha_i y_i K(x_i, x) + b \right]$$

Quadratic kernel



Non-linear separator in the **original x-space**



Linear separator in the **feature ϕ -space**

[Tommi Jaakkola]

Quadratic kernel

$$\begin{aligned} k(\mathbf{x}, \mathbf{z}) &= (\mathbf{x}^T \mathbf{z} + c)^2 = \left(\sum_{j=1}^n x^{(j)} z^{(j)} + c \right) \left(\sum_{\ell=1}^n x^{(\ell)} z^{(\ell)} + c \right) \\ &= \sum_{j=1}^n \sum_{\ell=1}^n x^{(j)} x^{(\ell)} z^{(j)} z^{(\ell)} + 2c \sum_{j=1}^n x^{(j)} z^{(j)} + c^2 \\ &= \sum_{j,\ell=1}^n (x^{(j)} x^{(\ell)}) (z^{(j)} z^{(\ell)}) + \sum_{j=1}^n (\sqrt{2c} x^{(j)}) (\sqrt{2c} z^{(j)}) + c^2, \end{aligned}$$

Feature mapping given by:

$$\Phi(\mathbf{x}) = [x^{(1)2}, x^{(1)} x^{(2)}, \dots, x^{(3)2}, \sqrt{2c} x^{(1)}, \sqrt{2c} x^{(2)}, \sqrt{2c} x^{(3)}, c]$$

[Cynthia Rudin]

Common kernels

- Polynomials of degree exactly d

$$K(\mathbf{u}, \mathbf{v}) = (\mathbf{u} \cdot \mathbf{v})^d$$

- Polynomials of degree up to d

$$K(\mathbf{u}, \mathbf{v}) = (\mathbf{u} \cdot \mathbf{v} + 1)^d$$


- Gaussian kernels

$$K(\vec{u}, \vec{v}) = \exp\left(-\frac{\|\vec{u} - \vec{v}\|_2^2}{2\sigma^2}\right)$$

Euclidean distance,
squared


- And many others: very active area of research!
(e.g., structured kernels that use dynamic programming
to evaluate, string kernels, ...)

Gaussian kernel



[Cynthia Rudin]

Level sets, i.e. $w \cdot x = r$ for some r



Support vectors

[mblondel.org]


Kernel algebra

kernel composition	feature composition
a) $k(\mathbf{x}, \mathbf{v}) = k_a(\mathbf{x}, \mathbf{v}) + k_b(\mathbf{x}, \mathbf{v})$	$\phi(\mathbf{x}) = (\phi_a(\mathbf{x}), \phi_b(\mathbf{x})),$
b) $k(\mathbf{x}, \mathbf{v}) = fk_a(\mathbf{x}, \mathbf{v}), f > 0$	$\phi(\mathbf{x}) = \sqrt{f}\phi_a(\mathbf{x})$
c) $k(\mathbf{x}, \mathbf{v}) = k_a(\mathbf{x}, \mathbf{v})k_b(\mathbf{x}, \mathbf{v})$	$\phi_m(\mathbf{x}) = \phi_{ai}(\mathbf{x})\phi_{bj}(\mathbf{x})$
d) $k(\mathbf{x}, \mathbf{v}) = \mathbf{x}^T A \mathbf{v}, A$ positive semi-definite	$\phi(\mathbf{x}) = L^T \mathbf{x}$, where $A = LL^T$.
e) $k(\mathbf{x}, \mathbf{v}) = f(\mathbf{x})f(\mathbf{v})k_a(\mathbf{x}, \mathbf{v})$	$\phi(\mathbf{x}) = f(\mathbf{x})\phi_a(\mathbf{x})$

Q: How would you prove that the “Gaussian kernel” is a valid kernel?

A: Expand the Euclidean norm as follows:

$$\exp\left(-\frac{\|\vec{u} - \vec{v}\|_2^2}{2\sigma^2}\right) = \exp\left(-\frac{\|\vec{u}\|_2^2}{2\sigma^2}\right) \exp\left(-\frac{\|\vec{v}\|_2^2}{2\sigma^2}\right) \exp\left(\frac{\vec{u} \cdot \vec{v}}{\sigma^2}\right)$$



Then, apply (e) from above

The feature mapping is infinite dimensional!

To see that this is a kernel, use the Taylor series expansion of the exponential, together with repeated application of (a), (b), and (c):

$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!}$$

[Justin Domke]

Overfitting?

- Huge feature space with kernels: should we worry about overfitting?
 - SVM objective seeks a solution with large **margin**
 - Theory says that large margin leads to good generalization (we will see this in a couple of lectures)
 - But everything overfits sometimes!!!
 - Can control by:
 - Setting C
 - Choosing a better Kernel
 - Varying parameters of the Kernel (width of Gaussian, etc.)

Vapnik-Chervonenkis(VC)-Theory: Main Points

Necessary and sufficient conditions for **consistency of empirical risk minimization**: one-sided convergence, uniformly over all functions that can be implemented by the learning machine.

$$\lim_{m \rightarrow \infty} P\left\{ \sup_f (R[f] - R_{emp}[f]) > \epsilon \right\} = 0 \text{ for all } \epsilon > 0.$$

Vapnik, Chervonenkis and others give conditions for uniform convergence in terms of **capacity concepts**, e.g.

- the VC-entropy grows sublinearly with m
- the VC-dimension is finite
- the entropy numbers are well-behaved
- the classification “margin” is large

[e.g. 52, 50, 44, 61, 1]

Structure of the Growth Function

Either $G^{\mathcal{F}}(m) = \textcolor{red}{m} \cdot \ln(2)$ — this means that for any sample size m the points can be chosen such that by using functions of the learning machine, all 2^m possible loss vectors can be generated (i.e., they can be separated in all possible ways — “*shattered*”).

Or there exists some *maximal* m for which the above is possible. Call this number the *VC-dimension*, and denote it by h . Then one can prove that for $m > h$,

$$G^{\mathcal{F}}(m) \leq h \left(\ln \frac{\textcolor{red}{m}}{h} + 1 \right).$$

Nothing “in between” linear growth and logarithmic growth is possible [51].

A VC Bound for Pattern Recognition

For any $f \in \mathcal{F}$ and $m > h$, with a probability of at least $1 - \eta$,

$$R[f] \leq R_{\text{emp}}[f] + \phi \left(\frac{h}{m}, \frac{\log(\eta)}{m} \right)$$

holds, where ϕ is defined as

$$\phi \left(\frac{h}{m}, \frac{\log(\eta)}{m} \right) = \sqrt{\frac{h \left(\log \frac{2m}{h} + 1 \right) - \log(\eta/4)}{m}}.$$

(Derivation: in uniform convergence bounds, set RHS = η , and solve for ϵ to get the confidence term.)


The study of the consistency of ERM has thus led to concepts and results which lets us formulate a better induction principle: minimize the RHS of the bound.

VC-Dimension: Example

Half-spaces in \mathbb{R}^2 :

$$f(x, y) = \operatorname{sgn}(a + bx + cy), \quad \text{with parameters } a, b, c \in \mathbb{R}$$

- Clearly, we can shatter three non-collinear points.
- But we can never shatter four points.
- Hence the VC dimension is $h = 3$ (in this case, equal to the number of parameters)



VC-Dimension Example, ctd.

- more generally, separating hyperplanes in \mathbb{R}^N have a VC dimension of $N + 1$.
- hence: separating hyperplanes in high-dimensional feature spaces have extremely large VC dimension, and may not generalize well
- however, “*margin*” hyperplanes can still have a small VC dimension (see below)

The Kernel Trick: Feature Spaces

Preprocess the data with

$$\begin{aligned}\Phi : \mathcal{X} &\rightarrow \mathcal{H} \\ x &\mapsto \Phi(x),\end{aligned}$$



where \mathcal{H} is a dot product space, and learn the mapping from $\Phi(x)$ to y .

- usually, $\dim(\mathcal{X}) \ll \dim(\mathcal{H})$
- “Curse of Dimensionality”?
- crucial issue: *capacity*, not *dimensionality*

Example: All Degree 2 Monomials

$$\Phi : \mathbb{R}^2 \rightarrow \mathbb{R}^3$$

$$(x_1, x_2) \mapsto (z_1, z_2, z_3) := (x_1^2, \sqrt{2} x_1 x_2, x_2^2)$$



The Kernel Trick, $N = d = 2$

$$\begin{aligned}\langle \Phi(x), \Phi(x') \rangle &= (x_1^2, \sqrt{2} x_1 x_2, x_2^2) (x'^2_1, \sqrt{2} x'_1 x'_2, x'^2_2)^\top \\ &= \langle x, x' \rangle^2 \\ &=: k(x, x')\end{aligned}$$

→ the dot product in \mathcal{H} can be computed in \mathbb{R}^2

The Kernel Trick, II

More generally: $x, x' \in \mathbb{R}^N$, $d \in \mathbb{N}$:

$$\begin{aligned}\langle x, x' \rangle^d &= \left(\sum_{j=1}^N x_j \cdot x'_j \right)^d \\ &= \sum_{j_1, \dots, j_d=1}^N x_{j_1} \cdot \dots \cdot x_{j_d} \cdot x'_{j_1} \cdot \dots \cdot x'_{j_d} = \langle \Phi(x), \Phi(x') \rangle,\end{aligned}$$

where Φ maps into the space spanned by all ordered products of d input directions

Mercer's Theorem

If k is a continuous kernel of a positive definite integral operator on $L_2(\mathcal{X})$ (where \mathcal{X} is some compact space),

$$\int_{\mathcal{X}} k(x, x') f(x) f(x') \, dx \, dx' \geq 0,$$

it can be expanded as

$$k(x, x') = \sum_{i=1}^{\infty} \lambda_i \psi_i(x) \psi_i(x')$$

using eigenfunctions ψ_i and eigenvalues $\lambda_i \geq 0$ [34].

In that case

$$\Phi(x) := \begin{pmatrix} \sqrt{\lambda_1} \psi_1(x) \\ \sqrt{\lambda_2} \psi_2(x) \\ \vdots \end{pmatrix}$$

satisfies $\langle \Phi(x), \Phi(x') \rangle = k(x, x')$.

Positive Definite Kernels

It can be shown that (modulo some details) the admissible class of kernels coincides with the one of **positive definite (pd)** kernels: kernels which are symmetric, and for

- any set of training points $x_1, \dots, x_m \in \mathcal{X}$ and
- any $a_1, \dots, a_m \in \mathbb{R}$

satisfy

$$\sum_{i,j} a_i a_j K_{ij} \geq 0, \text{ where } K_{ij} := k(x_i, x_j).$$


The Feature Space for PD Kernels

[5, 2, 38]

- define a feature map

$$\begin{aligned}\Phi : \mathcal{X} &\rightarrow \mathbb{R}^{\mathcal{X}} \\ x &\mapsto k(., x).\end{aligned}$$

E.g., for the Gaussian kernel:



- turn $\Phi(\mathcal{X})$ into a linear space, $f(.) = \sum_{i=1}^m \alpha_i k(., x_i)$,
- endow it with a dot product satisfying
 $\langle k(., x_i), k(., x_j) \rangle = k(x_i, x_j)$
- complete the space to get a *reproducing kernel Hilbert space*

Some Properties of Kernels

If k_1, k_2, \dots are pd kernels, then so are

- αk_1 , provided $\alpha \geq 0$
- $k_1 + k_2$
- $k_1 \cdot k_2$
- $k(x, x') := \lim_{n \rightarrow \infty} k_n(x, x')$, provided it exists

Further operations to construct kernels from kernels: tensor products, direct sums, convolutions [23].

The Kernel Trick — Summary

- *any* algorithm that only depends on dot products can benefit from the kernel trick
- this way, we can apply linear methods to vectorial as well as *non-vectorial data*
- think of the kernel as a nonlinear *similarity measure*
- examples of common kernels:


$$\text{Polynomial} \quad k(x, x') = (\langle x, x' \rangle + c)^d$$

$$\text{Sigmoid} \quad k(x, x') = \tanh(\kappa \langle x, x' \rangle + \Theta)$$

$$\text{Gaussian} \quad k(x, x') = \exp(-\|x - x'\|^2 / (2 \sigma^2))$$

- Kernel are studied also in the Gaussian Process prediction community (covariance functions) [57, 54, 58, 33]

Separating Hyperplane




Note: if $c \neq 0$, then

$$\{\mathbf{x} \mid \langle \mathbf{w}, \mathbf{x} \rangle + b = 0\} = \{\mathbf{x} \mid \langle c\mathbf{w}, \mathbf{x} \rangle + cb = 0\}.$$

Hence $(c\mathbf{w}, cb)$ describes the same hyperplane as (\mathbf{w}, b) .

Definition: The hyperplane is in *canonical* form w.r.t. $X^* = \{\mathbf{x}_1, \dots, \mathbf{x}_r\}$ if $\min_{\mathbf{x}_i \in X} |\langle \mathbf{w}, \mathbf{x}_i \rangle + b| = 1$.

Canonical Optimal Hyperplane



Note:

$$\langle \mathbf{w}, \mathbf{x}_1 \rangle + b = +1$$

$$\langle \mathbf{w}, \mathbf{x}_2 \rangle + b = -1$$

$$\Rightarrow \langle \mathbf{w}, (\mathbf{x}_1 - \mathbf{x}_2) \rangle = 2$$

$$\Rightarrow \left\langle \frac{\mathbf{w}}{\|\mathbf{w}\|}, (\mathbf{x}_1 - \mathbf{x}_2) \right\rangle = \frac{2}{\|\mathbf{w}\|}$$

VC Dimension of Margin Hyperplanes



Theorem [48]. Consider hyperplanes $\langle \mathbf{w}, \mathbf{x} \rangle = 0$ where \mathbf{w} is normalized such that they are in canonical form w.r.t. a set of points $X^* = \{\mathbf{x}_1, \dots, \mathbf{x}_r\}$, i.e.,

$$\min_{i=1, \dots, r} |\langle \mathbf{w}, \mathbf{x}_i \rangle| = 1.$$

The set of decision functions $f_{\mathbf{w}}(\mathbf{x}) = \text{sgn} \langle \mathbf{x}, \mathbf{w} \rangle$ defined on X^* and satisfying the constraint $\|\mathbf{w}\| \leq \Lambda$ has a VC dimension satisfying

$$h \leq R^2 \Lambda^2.$$

Here, R is the radius of the smallest sphere around the origin containing X^* .



Formulation as an Optimization Problem

Hyperplane with maximum margin: minimize

$$\|\mathbf{w}\|^2$$

(recall: margin $\sim 1/\|\mathbf{w}\|$) subject to

$$y_i \cdot [\langle \mathbf{w}, \mathbf{x}_i \rangle + b] \geq 1 \quad \text{for } i = 1 \dots m$$

(i.e. the training data are separated correctly).

Lagrange Function

(e.g., [6])

Introduce Lagrange multipliers $\alpha_i \geq 0$ and a Lagrangian

$$L(\mathbf{w}, b, \boldsymbol{\alpha}) = \frac{1}{2} \|\mathbf{w}\|^2 - \sum_{i=1}^m \alpha_i (y_i \cdot [\langle \mathbf{w}, \mathbf{x}_i \rangle + b] - 1).$$

L has to minimized w.r.t. the *primal variables* \mathbf{w} and b and maximized with respect to the *dual variables* α_i

- if a constraint is violated, then $y_i \cdot (\langle \mathbf{w}, \mathbf{x}_i \rangle + b) - 1 < 0 \longrightarrow$
 - α_i will grow to increase L — how far?
 - \mathbf{w} , b want to decrease L ; i.e. they have to change such that the constraint is satisfied. If the problem is separable, this ensures that $\alpha_i < \infty$.
- similarly: if $y_i \cdot (\langle \mathbf{w}, \mathbf{x}_i \rangle + b) - 1 > 0$, then $\alpha_i = 0$: otherwise, L could be increased by decreasing α_i (*KKT conditions*)

Derivation of the Dual Problem

At the extremum, we have

$$\frac{\partial}{\partial b} L(\mathbf{w}, b, \boldsymbol{\alpha}) = 0, \quad \frac{\partial}{\partial \mathbf{w}} L(\mathbf{w}, b, \boldsymbol{\alpha}) = 0,$$

i.e.

$$\sum_{i=1}^m \alpha_i y_i = 0$$

and

$$\mathbf{w} = \sum_{i=1}^m \alpha_i y_i \mathbf{x}_i.$$

Substitute both into L to get the *dual problem*

The Support Vector Expansion

$$\mathbf{w} = \sum_{i=1}^m \alpha_i y_i \mathbf{x}_i$$

where for all $i = 1, \dots, m$ either

$$y_i \cdot [\langle \mathbf{w}, \mathbf{x}_i \rangle + b] > 1 \implies \alpha_i = 0 \rightarrow \mathbf{x}_i \text{ irrelevant}$$

or

$$y_i \cdot [\langle \mathbf{w}, \mathbf{x}_i \rangle + b] = 1 \text{ (on the margin)} \rightarrow \mathbf{x}_i \text{ "Support Vector"}$$

The solution is determined by the examples on the margin.

Thus

$$\begin{aligned} f(\mathbf{x}) &= \operatorname{sgn} (\langle \mathbf{x}, \mathbf{w} \rangle + b) \\ &= \operatorname{sgn} \left(\sum_{i=1}^m \alpha_i y_i \langle \mathbf{x}, \mathbf{x}_i \rangle + b \right). \end{aligned}$$

Dual Problem

Dual: maximize

$$W(\alpha) = \sum_{i=1}^m \alpha_i - \frac{1}{2} \sum_{i,j=1}^m \alpha_i \alpha_j y_i y_j \langle \mathbf{x}_i, \mathbf{x}_j \rangle$$

subject to

$$\alpha_i \geq 0, \quad i = 1, \dots, m, \quad \text{and} \quad \sum_{i=1}^m \alpha_i y_i = 0.$$

Both the final decision function and the function to be maximized are expressed in dot products \rightarrow can use a **kernel** to compute

$$\langle \mathbf{x}_i, \mathbf{x}_j \rangle = \langle \Phi(x_i), \Phi(x_j) \rangle = k(x_i, x_j).$$

The SV Expansion in Feature Space

- generally, the solution of kernel algorithms corresponds to a single vector in \mathcal{H} (“Representer Theorem” [30, 39]),

$$\mathbf{w} = \sum_{i=1}^m \alpha_i \Phi(x_i).$$

However, there is usually no $x \in \mathcal{X}$ such that


$$\Phi(x) = \mathbf{w},$$

i.e., $\Phi(\mathcal{X})$ is not closed under linear combinations — it is a nonlinear manifold (cf. [10, 40]).

- $\Phi(\mathcal{X})$ is contained in a non-isotropic shape whose sidelengths scale like the square roots of the eigenvalues of k or K [cf. 61, 60, 13, 59].

Toy Example with Gaussian Kernel

$$k(x, x') = \exp\left(-\|x - x'\|^2\right)$$



Nonseparable Problems

[4, 15]

If $y_i \cdot (\langle \mathbf{w}, \mathbf{x}_i \rangle + b) \geq 1$ cannot be satisfied, then $\alpha_i \rightarrow \infty$.

Modify the constraint to

$$y_i \cdot (\langle \mathbf{w}, \mathbf{x}_i \rangle + b) \geq 1 - \xi_i$$

with

$$\xi_i \geq 0$$

(“soft margin”) and add

$$C \cdot \sum_{i=1}^m \xi_i$$

in the objective function.

Same dual, with additional constraints $\alpha_i \leq C$.

SVM Training

- naive approach: the complexity of maximizing

$$W(\alpha) = \sum_{i=1}^m \alpha_i - \frac{1}{2} \sum_{i,j=1}^m \alpha_i \alpha_j y_i y_j \mathbf{k}(\mathbf{x}_i, \mathbf{x}_j)$$

scales with the third power of the training set size m

- only SVs are relevant \longrightarrow only compute $(\mathbf{k}(\mathbf{x}_i, \mathbf{x}_j))_{ij}$ for SVs. Extract them iteratively by cycling through the training set in chunks [48].
- in fact, one can use chunks which do not even contain all SVs [35]. Maximize over these sub-problems, using your favorite optimizer.
- the extreme case: by making the sub-problems very small (just two points), one can solve them analytically [37].
- <http://www.kernel-machines.org/software.html>

MNIST Error Rates

handwritten character benchmark (60000 training & 10000 test examples, 28×28)

Classifier	test error	reference
linear classifier	8.4%	[7]
3-nearest-neighbour	2.4%	[7]
SVM	1.4%	[11]
Tangent distance	1.1%	[45]
LeNet4	1.1%	[31]
Boosted LeNet4	0.7%	[31]
Translation invariant SVM	0.56%	[17]

Note: the SVM used a polynomial kernel of degree 9, corresponding to a feature space of dimension $\approx 3.2 \cdot 10^{20}$.

Other successful applications: [28, 26, 24, 12, 47, 8, 63, 22, 20, 14, 18, 36, 55, 62]

Unsupervised SVM Learning


$x_1, \dots, x_m \in \mathcal{X}$ i.i.d. sample from P

- extreme view: unsupervised learning = density estimation
- easier problem: for $\alpha \in (0, 1]$, compute a region R such that

$$P(R) \approx \alpha,$$

i.e., estimate *quantiles* of a distribution, not its density.

- becomes well-posed using a regularizer: find “smoothest” region that contains a certain fraction of the probability mass
- given only the training data, we will get a trade-off: try to enclose many training points (more than α) in a smooth region




Separating Unlabelled Data from the Origin

One can show: if $\Phi(x_1), \dots, \Phi(x_m)$ are separable from the origin in \mathcal{H} , then the solution of

$$\min_{\mathbf{w} \in \mathcal{H}} \frac{1}{2} \|\mathbf{w}\|^2 \quad \text{subject to } \langle \mathbf{w}, \Phi(x_i) \rangle \geq 1$$

is the normal vector of the hyperplane separating the data from the origin with maximum margin.



Toy Examples using $k(x, y) = \exp(-\frac{\|x-y\|^2}{c})$



$\nu, \text{ width } c$	0.5, 0.5	0.5, 0.5	0.1, 0.5	0.5, 0.1
SVs/OLs	0.54, 0.43	0.59, 0.47	0.24, 0.03	0.65, 0.38

Kernel PCA

[43]



The Challenge: Designing Kernels

- transformation invariances (cf. poster of Olivier Chapelle)
- kernels for discrete objects [23, 56, 32, 3]
- kernels based on generative models: Fisher kernel [27]
- local kernels [e.g., 63]
- other sophisticated kernels: e.g., [5, 16, 42]


In general, the choice of a kernel corresponds to

- choosing a similarity measure for the data, or
- choosing a (linear) representation of the data, or
- choosing a hypothesis space for learning,

and should reflect prior knowledge about the problem at hand.
There is ‘no free lunch’ in kernel choice.

Conclusion

- crucial ingredients of SV algorithms: **kernels** that can be represented as dot products, and **large margin** regularizers
- kernels allow the formulation of a multitude of geometrical algorithms (Parzen windows, SV pattern recognition, SV quantile estimation, kernel PCA,...)
- not only do these algorithms lend themselves well to theoretical study — they also perform well in practice



For further information, cf.
<http://www.kernel-machines.org>,
<http://www.learning-with-kernels.org>,
and [9, 16, 25, 42].

References

- [1] N. Alon, S. Ben-David, N. Cesa-Bianchi, and D. Haussler. Scale-sensitive dimensions, uniform convergence, and learnability. *Journal of the ACM*, 44(4):615–631, 1997.
- [2] N. Aronszajn. Theory of reproducing kernels. *Transactions of the American Mathematical Society*, 68:337–404, 1950.
- [3] P. L. Bartlett and B. Schölkopf. Some kernels for structured data. Technical report, Biowulf Technologies, 2001.
- [4] K. P. Bennett and O. L. Mangasarian. Robust linear programming discrimination of two linearly inseparable sets. *Optimization Methods and Software*, 1:23–34, 1992.
- [5] C. Berg, J. P. R. Christensen, and P. Ressel. *Harmonic Analysis on Semigroups*. Springer-Verlag, New York, 1984.
- [6] D. P. Bertsekas. *Nonlinear Programming*. Athena Scientific, Belmont, MA, 1995.
- [7] L. Bottou, C. Cortes, J. S. Denker, H. Drucker, I. Guyon, L. D. Jackel, Y. LeCun, U. A. Müller, E. Säckinger, P. Simard, and V. Vapnik. Comparison of classifier methods: a case study in handwritten digit recognition. In *Proceedings of the 12th International Conference on Pattern Recognition and Neural Networks, Jerusalem*, pages 77–87. IEEE Computer Society Press, 1994.
- [8] M. P. S. Brown, W. N. Grundy, D. Lin, N. Cristianini, C. Sugnet, T. S. Furey, M. Ares, and D. Haussler. Knowledge-based analysis of microarray gene expression data using support vector machines. *Proceedings of the National Academy of Sciences*, 97(1):262–267, 2000.
- [9] C. J. C. Burges. A tutorial on support vector machines for pattern recognition. *Data Mining and Knowledge Discovery*, 2(2):121–167, 1998.
- [10] C. J. C. Burges. Geometry and invariance in kernel based methods. In B. Schölkopf, C. J. C. Burges, and A. J. Smola, editors, *Advances in Kernel Methods — Support Vector Learning*, pages 89–116, Cambridge, MA, 1999. MIT Press.
- [11] C. J. C. Burges and B. Schölkopf. Improving the accuracy and speed of support vector learning machines. In M. Mozer, M. Jordan, and T. Petsche, editors, *Advances in Neural Information Processing Systems 9*, pages 375–381, Cambridge, MA, 1997. MIT Press.

- [12] O. Chapelle, P. Haffner, and V. Vapnik. SVMs for histogram-based image classification. *IEEE Transactions on Neural Networks*, 10(5), 1999.
- [13] O. Chapelle, V. Vapnik, O. Bousquet, and S. Mukherjee. Choosing kernel parameters for support vector machines. *Machine Learning*, 2002. Forthcoming.
- [14] S. Chen and C. J. Harris. Design of the optimal separating hyperplane for the decision feedback equalizer using support vector machines. In *IEEE International Conference on Acoustic, Speech, and Signal Processing*, Istanbul, Turkey, 2000.
- [15] C. Cortes and V. Vapnik. Support vector networks. *Machine Learning*, 20:273–297, 1995.
- [16] N. Cristianini and J. Shawe-Taylor. *An Introduction to Support Vector Machines*. Cambridge University Press, Cambridge, UK, 2000.
- [17] D. DeCoste and B. Schölkopf. Training invariant support vector machines. *Machine Learning*, 46:161–190, 2002. Also: Technical Report JPL-MLTR-00-1, Jet Propulsion Laboratory, Pasadena, CA, 2000.
- [18] H. Drucker, B. Shahraray, and D. C. Gibbon. Relevance feedback using support vector machines. In *Proceedings of the 18th International Conference on Machine Learning*. Morgan Kaufmann, 2001.
- [19] T. Evgeniou, M. Pontil, and T. Poggio. Regularization networks and support vector machines. In A. J. Smola, P. L. Bartlett, B. Schölkopf, and D. Schuurmans, editors, *Advances in Large Margin Classifiers*, pages 171–203, Cambridge, MA, 2000. MIT Press.
- [20] T. S. Furey, N. Duffy, N. Cristianini, D. Bednarski, M. Schummer, and D. Haussler. Support vector machine classification and validation of cancer tissue samples using microarray expression data. *Bioinformatics*, 16(10):906–914, 2000.
- [21] F. Girosi. An equivalence between sparse approximation and support vector machines. *Neural Computation*, 10(6):1455–1480, 1998.
- [22] I. Guyon, J. Weston, S. Barnhill, and V. Vapnik. Gene selection for cancer classification using support vector machines. *Machine Learning*, 2002. Forthcoming. Also: Biowulf Technologies TR.
- [23] D. Haussler. Convolutional kernels on discrete structures. Technical Report UCSC-CRL-99-10, Computer Science Department, University of California at Santa Cruz, 1999.
- [24] M. A. Hearst, B. Schölkopf, S. Dumais, E. Osuna, and J. Platt. Trends and controversies — support vector machines. *IEEE Intelligent Systems*, 13:18–28, 1998.

- [25] R. Herbrich. *Learning kernel classifiers*. MIT Press, Cambridge, MA, 2002.
- [26] T. S. Jaakkola, M. Diekhans, and D. Haussler. A discriminative framework for detecting remote protein homologies. *Journal of Computational Biology*, 7:95–114, 2000.
- [27] T. S. Jaakkola and D. Haussler. Probabilistic kernel regression models. In *Proceedings of the 1999 Conference on AI and Statistics*, 1999.
- [28] T. Joachims. Text categorization with support vector machines: Learning with many relevant features. In Claire Nédellec and Céline Rouveiro, editors, *Proceedings of the European Conference on Machine Learning*, pages 137–142, Berlin, 1998. Springer.
- [29] G. S. Kimeldorf and G. Wahba. A correspondence between Bayesian estimation on stochastic processes and smoothing by splines. *Annals of Mathematical Statistics*, 41:495–502, 1970.
- [30] G. S. Kimeldorf and G. Wahba. Some results on Tchebycheffian spline functions. *Journal of Mathematical Analysis and Applications*, 33:82–95, 1971.
- [31] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86:2278–2324, 1998.
- [32] H. Lodhi, J. Shawe-Taylor, N. Cristianini, and C. Watkins. Text classification using string kernels. Technical Report 2000-79, NeuroCOLT, 2000. Published in: T. K. Leen, T. G. Dietterich and V. Tresp (eds.), *Advances in Neural Information Processing Systems 13*, MIT Press, 2001.
- [33] D. J. C. MacKay. Introduction to Gaussian processes. In C. M. Bishop, editor, *Neural Networks and Machine Learning*, pages 133–165. Springer-Verlag, Berlin, 1998.
- [34] J. Mercer. Functions of positive and negative type and their connection with the theory of integral equations. *Philosophical Transactions of the Royal Society, London, A* 209:415–446, 1909.
- [35] E. Osuna, R. Freund, and F. Girosi. Support vector machines: Training and applications. Technical Report AIM-1602, MIT A.I. Lab., 1996.
- [36] P. Pavlidis, J. Weston, J. Cai, and W. N. Grundy. Gene functional classification from heterogeneous data. In *Proceedings of the Fifth International Conference on Computational Molecular Biology*, pages 242–248, 2001.
- [37] J. Platt. Fast training of support vector machines using sequential minimal optimization. In B. Schölkopf, C. J. C. Burges, and A. J. Smola, editors, *Advances in Kernel Methods — Support Vector Learning*, pages 185–208, Cambridge, MA, 1999. MIT Press.

- [38] S. Saitoh. *Theory of Reproducing Kernels and its Applications*. Longman Scientific & Technical, Harlow, England, 1988.
- [39] B. Schölkopf, R. Herbrich, A. J. Smola, and R. C. Williamson. A generalized representer theorem. Technical Report 2000-81, NeuroCOLT, 2000. Published in *Proceedings COLT'2001*, Springer Lecture Notes in Artificial Intelligence, 2001.
- [40] B. Schölkopf, S. Mika, C. Burges, P. Knirsch, K.-R. Müller, G. Rätsch, and A. J. Smola. Input space vs. feature space in kernel-based methods. *IEEE Transactions on Neural Networks*, 10(5):1000–1017, 1999.
- [41] B. Schölkopf, J. Platt, J. Shawe-Taylor, A. J. Smola, and R. C. Williamson. Estimating the support of a high-dimensional distribution. *Neural Computation*, 13:1443–1471, 2001.
- [42] B. Schölkopf and A. J. Smola. *Learning with Kernels*. MIT Press, Cambridge, MA, 2002.
- [43] B. Schölkopf, A. J. Smola, and K.-R. Müller. Nonlinear component analysis as a kernel eigenvalue problem. *Neural Computation*, 10:1299–1319, 1998.
- [44] J. Shawe-Taylor, P. L. Bartlett, R. C. Williamson, and M. Anthony. Structural risk minimization over data-dependent hierarchies. *IEEE Transactions on Information Theory*, 44(5):1926–1940, 1998.
- [45] P. Simard, Y. LeCun, and J. Denker. Efficient pattern recognition using a new transformation distance. In S. J. Hanson, J. D. Cowan, and C. L. Giles, editors, *Advances in Neural Information Processing Systems 5. Proceedings of the 1992 Conference*, pages 50–58, San Mateo, CA, 1993. Morgan Kaufmann.
- [46] A. J. Smola, B. Schölkopf, and K.-R. Müller. The connection between regularization operators and support vector kernels. *Neural Networks*, 11:637–649, 1998.
- [47] S. Tong and D. Koller. Support vector machine active learning with applications to text classification. In P. Langley, editor, *Proceedings of the 17th International Conference on Machine Learning*, San Francisco, California, 2000. Morgan Kaufmann.
- [48] V. Vapnik. *Estimation of Dependences Based on Empirical Data [in Russian]*. Nauka, Moscow, 1979. (English translation: Springer Verlag, New York, 1982).
- [49] V. Vapnik. *The Nature of Statistical Learning Theory*. Springer, NY, 1995.
- [50] V. Vapnik. *Statistical Learning Theory*. Wiley, NY, 1998.
- [51] V. Vapnik and A. Chervonenkis. On the uniform convergence of relative frequencies of events to their probabilities. *Theory of Probability and its Applications*, 16(2):264–280, 1971.

- [52] V. Vapnik and A. Chervonenkis. *Theory of Pattern Recognition [in Russian]*. Nauka, Moscow, 1974. (German Translation: W. Wapnik & A. Tscherwonenkis, *Theorie der Zeichenerkennung*, Akademie–Verlag, Berlin, 1979).
- [53] V. Vapnik and A. Lerner. Pattern recognition using generalized portrait method. *Automation and Remote Control*, 24:774–780, 1963.
- [54] G. Wahba. *Spline Models for Observational Data*, volume 59 of *CBMS-NSF Regional Conference Series in Applied Mathematics*. SIAM, Philadelphia, 1990.
- [55] M. K. Warmuth, G. Rätsch, M. Mathieson, J. Liao, and C. Lemmen. Active learning in the drug discovery process. In T.G. Dietterich, S. Becker, and Z. Ghahramani, editors, *Advances in Neural Information Processing Systems*, volume 14. MIT Press, 2002. To appear.
- [56] C. Watkins. Dynamic alignment kernels. In A. J. Smola, P. L. Bartlett, B. Schölkopf, and D. Schuurmans, editors, *Advances in Large Margin Classifiers*, pages 39–50, Cambridge, MA, 2000. MIT Press.
- [57] H. L. Weinert. *Reproducing Kernel Hilbert Spaces*. Hutchinson Ross, Stroudsburg, PA, 1982.
- [58] C. K. I. Williams. Prediction with Gaussian processes: From linear regression to linear prediction and beyond. In M. I. Jordan, editor, *Learning and Inference in Graphical Models*. Kluwer, 1998.
- [59] C. K. I. Williams and M. Seeger. The effect of the input density distribution on kernel-based classifiers. In P. Langley, editor, *Proceedings of the 17th International Conference on Machine Learning*, pages 1159–1166, San Francisco, California, 2000. Morgan Kaufmann.
- [60] R. C. Williamson, J. Shawe-Taylor, B. Schölkopf, and A. J. Smola. Sample-based generalization bounds. *IEEE Transactions on Information Theory*, 1999. Submitted. Also: NeuroCOLT Technical Report NC-TR-99-055.
- [61] R. C. Williamson, A. J. Smola, and B. Schölkopf. Generalization performance of regularization networks and support vector machines via entropy numbers of compact operators. Technical Report 19, NeuroCOLT, <http://www.neurocolt.com>, 1998. Accepted for publication in IEEE Transactions on Information Theory.
- [62] C.-H. Yeang, S. Ramaswamy, P. Tamayo, S. Mukherjee, R. M. Rifkin, M. Angelo, M. Reich, E. Lander, J. Mesirov, and T. Golub. Molecular classification of multiple tumor types. *Bioinformatics*, 17:S316–S322, 2001. ISMB’01 Supplement.
- [63] A. Zien, G. Rätsch, S. Mika, B. Schölkopf, T. Lengauer, and K.-R. Müller. Engineering support vector machine kernels that recognize translation initiation sites. *Bioinformatics*, 16(9):799–807, 2000.