

## Table of Contents

Table of Contents	1
ASPARK-STARTER	2
1. WHAT IS IT ?!	2
2. INSTALLATION AND CONFIGURATION	2
2.1. Fetch the source	2
2.2. Prerequisites	2
2.3. Ensure you have all the prerequisite binaries	2
2.4. Build the first aspark-starter instance	2
2.5. Check the runnable actions	3
2.6. Run the examples	3
2.7. Start hacking	3
3. PROJECT STATUS	4

# ASPARK-STARTER

## 1. WHAT IS IT ?!

A demo application which will help you to grasp the Apache Spark concept.

## 2. INSTALLATION AND CONFIGURATION

This section presents the steps needed to perform to deploy the aspark-starter tool. Note, that the commands are for Ubuntu, thus if you are on different OS choose , google the names of the packages applicable for your OS.

### 2.1. Fetch the source

Fetch the source from git hub as follows:

```
# create your product dir:
mkdir -p /opt/csiteda/
cd /opt/csiteda/

# fetch the source
git clone git@github.com:YordanGeorgiev/aspark-starter.git

# DO NOT CD into the new dir !!!!
```

### 2.2. Prerequisites

The must have binaries are:

bash, perl, zip

The nice to have are:

tmux, vim ,ctags

The examples are for Ubuntu - use you OS package manager ...

```
apt-get autoclean
apt-get install --only-upgrade bash
sudo apt-get install -y perl

apt-get upgrade
```

### 2.3. Ensure you have all the prerequisite binaries

Ensure you have all the prerequisite binaries by issuing the following command

```
# bootstrap the product instance dir
bash aspark-starter/src/bash/aspark-starter/install-prerequisites-for-aspark-starter-on-ubuntu.sh
```

### 2.4. Build the first aspark-starter instance

Build the aspark-starter instance by running the bootstrap script

```
# bootstrap the product instance dir
```

```
bash aspark-starter/src/bash/aspark-starter/bootstrap-aspark-starter.sh
```

```
# the script should prompt you to cd
```

## 2.5. Check the runnable actions

You could check the functions which could be run - aka "actions" by issuing the following command.

```
# check the runnable with the -a cmd arg actions
find . -name '*.func.sh' | sort
```

## 2.6. Run the examples

You can run all the examples by first checking which actions are configured for the next test run and perform the actual test run as follows:

```
# check the actions to run
cat src/bash/aspark-starter/tests/run-aspark-starter-tests.lst

# STDUOT
# sbt-compile-verbose
# sbt-clean-compile
# sbt-compile
# sbt-stage
# sbt-run

bash src/bash/aspark-starter/test-aspark-starter.sh

# now the tool will start producing output

# 2017-09-14 08:26:11   START test-aspark-starter test run report
#
# result start-time stop-time action-name
# ok 08:26:11 08:26:59 sbt-compile-verbose
# ok 08:27:00 08:27:25 sbt-clean-compile
# ok 08:27:25 08:27:34 sbt-compile
# ok 08:27:35 08:27:49 sbt-stage
# ok 08:27:49 08:27:59 sbt-run
```

## 2.7. Start hacking

Start hacking ... or wait check at least the test call running all the functions of the tool ...

```
# optionally if you are in the vim camp open the "project relative files list file"
vim meta/.dev.aspark-starter

# Ctrl + Z , to put it on the background
# check the actions to test ( uncomment line in include in test run )
less src/bash/aspark-starter/tests/run-aspark-starter-tests.lst

# Ctrl + Z to put in the background
# Action !!! - aka now run the tests
bash src/bash/aspark-starter/test-aspark-starter.sh
```

---

### 3. PROJECT STATUS

You could track the advancement of the project from the following url:

[https://docs.google.com/spreadsheets/d/e/2PACX-1vR0wo5N32EpubwxBfeFxi6X-eOmXwOPg4WSyA4qBSz1Yu0EyU34jl0xICgWzrFUSeEA\\_aC4RF7LRqx9/pubhtml](https://docs.google.com/spreadsheets/d/e/2PACX-1vR0wo5N32EpubwxBfeFxi6X-eOmXwOPg4WSyA4qBSz1Yu0EyU34jl0xICgWzrFUSeEA_aC4RF7LRqx9/pubhtml)

Note that the content on the url is updated on project actual status update ( i.e. meaningful work , milestones achieve )