My Chess Stats

My Chess Stats API

Base URL: `http://localhost:8000/api/`

All API endpoints require authentication. The API uses Django's session authentication with CSRF protection.

Authentication

Session Authentication

The API uses Django's session authentication. Include the session cookie and CSRF token in your requests.

Login Endpoint

```
POST /login/
Content-Type: application/json

{
    "username": "yourusername",
    "password": "yourpassword"
}
```

CSRF Token

For POST, PUT, DELETE requests, include the CSRF token:

```
// JavaScript function to get CSRF token
function getCookie(name) {
    let cookieValue = null;
    if (document.cookie && document.cookie !== '') {
        const cookies = document.cookie.split(';');
        for (let i = 0; i < cookies.length; i++) {
            const cookie = cookies[i].trim();
            if (cookie.substring(0, name.length + 1) === (name
+ '=')) {
                cookieValue =
decodeURIComponent(cookie.substring(name.length + 1));
                break;
            }
        }
    }
    return cookieValue;
}

// Include in request headers
headers: {
```

List Games

GET /api/games/

Retrieves a paginated list of the authenticated user's games.

Query Parameters

Parameter	Type	Description	Example
page	integer	Page number for pagination	`page=2`
platform	string	Filter by platform (chesscom/lichess)	`platform=chesscom`
result	string	Filter by result (W/L/D)	`result=W`
time_class	string	Filter by time control	`time_class=blitz`
search	string	Search opponent name	`search=magnus`
order_by	string	Sort field (+/- prefix for direction)	`order_by=-date_played`

Example Request

```
GET /api/games/?platform=chesscom&result=W&order_by=-date_played&page=1
```

Example Response

```
{
    "count": 150,
    "next": "http://localhost:8000/api/games/?page=2",
    "previous": null,
    "results": [
        {
            "id": 1234,
            "platform": "CH",
            "date_played": "2024-01-15",
            "white_player": "yourusername",
            "black_player": "opponent123",
            "my_color": "white",
            "result": "W",
            "result_figure": "Win",
            "opponent": "opponent123",
            "my_rating": 1850,
            "opponent_rating": 1820,
            "opening": "Sicilian Defense",
            "time_class": "blitz",
            "move_count": 45,
```


+ Create Game

POST /api/games/

Creates a new game for the authenticated user.

Request Body

Field	Type	Required	Description
platform	string	Required	'CH' for Chess.com, 'LI' for Lichess
game_id	string	Optional	Unique game identifier
date_played	date	Required	YYYY-MM-DD format
time_class	string	Required	bullet/blitz/rapid/classical
white_player	string	Required	White player name
black_player	string	Required	Black player name
my_color	string	Required	'white' or 'black'
result	string	Required	'W', 'L', or 'D'

Example Request

```
POST /api/games/
Content-Type: application/json

{
    "platform": "CH",
    "game_id": "chesscom_game_12345",
    "date_played": "2024-01-15",
    "time_class": "blitz",
    "white_player": "yourusername",
    "black_player": "opponent123",
    "my_color": "white",
    "result": "W",
```

```
    "my_rating": 1850,
    "opponent_rating": 1820,
    "opponent_name": "opponent123",
    "opening": "Sicilian Defense",
    "pgn": "[Event \"Live Chess\"]\n[Site
\"Chess.com\"]\n[Date \"2024.01.15\"]\n[White
\"yourusername\"]\n[Black \"opponent123\"]\n[Result
\"1-0\"]\n\n1.e4 c5 2.Nf3 d6 3.d4 cxd4 4.Nxd4 Nf6 5.Nc3 a6
```


Example Response (201 Created)


```
{
    "id": 1235,
    "platform": "CH",
    "game_id": "chesscom_game_12345",
    "date_played": "2024-01-15",
    "time_class": "blitz",
    "white_player": "yourusername",
    "black_player": "opponent123",
    "my_color": "white",
    "result": "W",
    "my_rating": 1850,
    "opponent_rating": 1820,
    "opponent_name": "opponent123",
    "opening": "Sicilian Defense",
    "fen": "",
    "pgn": "[Event \"Live Chess\"]\n[Site
\"Chess.com\"]\n[Date \"2024.01.15\"]\n[White
\"yourusername\"]\n[Black \"opponent123\"]\n[Result
\"1-0\"]\n\n1.e4 c5 2.Nf3 d6 3.d4 cxd4 4.Nxd4 Nf6 5.Nc3
a6 6.Bg5 e6 7.f4 Be7 8.Qf3 Qc7 9.O-O-O Nbd7 10.g4 b5
```


Get Game

GET /api/games/{id}/

Retrieves detailed information about a specific game.

Path Parameters

Parameter	Type	Description
id	integer	Game ID

Example Request

```
GET /api/games/1234/
```

Example Response


```
{
    "id": 1234,
    "platform": "CH",
    "game_id": "chesscom_game_12345",
    "game_url": "https://chess.com/game/live/12345",
    "date_played": "2024-01-15",
    "start_time": "14:30:00",
    "end_time": "14:45:00",
    "time_class": "blitz",
    "time_control": "300+0",
    "white_player": "yourusername",
    "black_player": "opponent123",
    "my_color": "white",
    "result": "W",
    "result_display": "Win",
    "termination": "checkmate",
    "win_method": "CHM",
    "win_method_display": "Checkmate",
    "my_rating": 1850,
    "opponent_rating": 1820,
```

Import Games

POST /api/games/import/

Bulk import games from Chess.com CSV or Lichess PGN files.

Request Format: `multipart/form-data`

Field	Type	Required	Description
file	file	Required	CSV or PGN file
platform	string	Required	'chesscom' or 'lichess'
username	string	Required for Lichess	Your username on the platform

Example Request (Chess.com)

```
POST /api/games/import/
Content-Type: multipart/form-data

file: @games_export.csv
platform: chesscom
```

Example Request (Lichess)

```
POST /api/games/import/
Content-Type: multipart/form-data

file: @lichess_games.pgn
platform: lichess
username: yourlichessusername
```

Example Response (201 Created)

```
{
    "imported_count": 25,
    "imported": [
        {
```

```
            "id": 1236,
            "game_id": "chesscom_game_12346",
            "opponent": "player1"
        },
        {
            "id": 1237,
            "game_id": "chesscom_game_12347",
            "opponent": "player2"
        }
    ],
    "errors": [
        {
            "row": 5,
            "error": "Could not determine game result",
            "data": {
                "result": "unknown".
```


Get Statistics

GET /api/games/stats/

Retrieves aggregated statistics for the authenticated user.

Example Request

```
GET /api/games/stats/
```

Example Response

```
{
    "total_games": 150,
    "wins": 85,
    "losses": 55,
    "draws": 10,
    "win_percentage": 56.67,
    "by_platform": [
        {
            "platform": "Chess.com",
            "code": "CH",
            "count": 100,
            "wins": 58,
            "avg_rating": 1825.5
        },
        {
            "platform": "Lichess",
            "code": "LI",
            "count": 50,
            "wins": 27,
            "avg_rating": 1880.2
        `
```

Board Image

GET /game/{id}/board/

Returns a base64-encoded SVG image of the final board position.

Path Parameters

Parameter	Type	Description
id	integer	Game ID

Example Request

```
GET /game/1234/board/
```

Example Response


```
{
    "success": true,
    "image": "
AwMC9zdmciIHdpZHRoPSI0MDAiIGhlaWdodD0iNDAwIj48IS0tIGNoZXN
zIGJvYXJkIHN2ZyBjb250ZW50IC0tPjwvc3ZnPg==",
    "fen": "r4rk1/1p3ppp/p1q5/3p4/8/PQ6/1P3PPP/2R2RK1 b -
- 0 25"
}
```


⚠ Error Handling

HTTP Status Codes

Code	Description	Example
200	OK	Request successful
201	Created	Resource created successfully
204	No Content	Successful delete
400	Bad Request	Missing required fields, validation errors
401	Unauthorized	Authentication required
403	Forbidden	CSRF token missing/invalid
404	Not Found	Game not found
500	Internal Server Error	Server-side error

Error Response Format

```
{
    "error": "Error message",
    "field_name": ["Specific field error"]
}
```

Example Validation Error

```
{
    "my_rating": ["Rating must be between 0 and 3500"],
    "date_played": ["This field is required"]
}
```

♜♛ My Chess Statistics © 2026