Table A8. The 17 historical configurations and their differences from the anchor.

#	Configuration	Axis	Change from anchor
1	Anchor	—	Full codebook, rule and six examples; label-only JSON; no scope declaration
2	Descriptions only	Codebook	Coding rule and examples removed
3	No few-shot examples	Codebook	Examples removed; coding rule retained
4	Reasoning and label	Reasoning	Reasoning returned before the label
5	Chain-of-thought	Reasoning	Reasoning returned before the label, plus an explicit step-by-step instruction
6	Time scope	Scope	Period covered by the questions declared
7	Speaker scope	Scope	Asking MP’s party declared
8	Free-text output	Output	Unstructured response parsed after generation
9	JSON mode	Output	Provider JSON mode enabled
10	Strict schema	Output	Function calling and strict schema
11	Self-consistency, n=5	Decoding	Five temperature-0.7 samples combined by majority vote
12	Single sample, T=0.7	Decoding	One non-greedy sample generated
13	Maximum 20 tokens	Decoding	Maximum output reduced from 500 to 20 tokens
14	Logit bias	Decoding	Positive bias applied to valid label tokens
15	Alternative topics	Examples	Examples drawn from different policy topics
16	Alternative exemplars	Examples	Different questions from the original example topics
17	Vendor swap	Provider	Anchor instructions applied to Claude Sonnet