

API Documentation

Getting a Token

The data layer sits behind Auth0 credentials. The `client_id` and `client_secret` will be provided on hackathon day.

Sanity Check - Request Token from Custom Domain

Important: Request your token from the custom domain, NOT the handler base URL. Our Auth0 domain and product domain are different.

```
curl -X POST 'https://auth.product.federato.ai/oauth/token' \
-H 'Content-Type: application/json' \
-d '{
  "client_id": "YOUR_CLIENT_ID",
  "client_secret": "YOUR_CLIENT_SECRET",
  "audience": "https://product.federato.ai/core-api",
  "grant_type": "client_credentials"
}'
```

Response:

```
{
  "access_token": "eyJhbGciOiJSUzI1NiIs...\"",
  "expires_in": 14400,
  "token_type": "Bearer"
}
```

Tokens are valid for **4 hours**.

Verify Your Token

To sanity-check what you were issued, decode the middle segment of the JWT and confirm that `iss` reads `https://auth.product.federato.ai/` and `aud` reads `https://product.federato.ai/core-api`:

```
python3 -c "
import base64,json,sys,time
p=sys.argv[1].split('.')[1]
d=json.loads(base64.urlsafe_b64decode(p+'*'*(-len(p)%4)))
print(json.dumps(d,indent=2))
print('expired' if d['exp']<time.time() else 'valid for %ds' % (d['exp']-time.time()))
" "$TOKEN"
```

Calling the API

```
POST https://product.federato.ai/integrations-api/handlers/federato-hack-north
```

Add `?outputOnly=true` to strip the workflow envelope and get just the payload. Without it, results come back wrapped as `{ "output": [ { "data": ... } ] }`.

The Request Envelope

The data layer is a single endpoint with multiple functions. `action` picks the operation, `payload` carries that action's argument.

```
{
  "action": "schema" | "query",
  "payload": "..."
```

action: “schema”

Fetches the data schema used by `action: "query"` in an OpenAPI-like format.

```
curl -X POST 'https://product.federato.ai/integrations-api/handlers/federato-hack-north?outputOnly=true' \
-H 'Authorization: Bearer $TOKEN' \
-H 'Content-Type: application/json' \
-d '{
  "action": "schema"
}'
```

action: “query”

Runs a query against Federato's database.

```
curl -X POST 'https://product.federato.ai/integrations-api/handlers/federato-hack-north?outputOnly=true' \
-H 'Authorization: Bearer $TOKEN' \
-H 'Content-Type: application/json' \
-d '{
  "action": "query",
  "payload": { "resource": "Policy", "pagination": { "limit": 5 } }
}'
```

See the Query Request Body documentation for everything that can go inside the `query` action's `payload`.

Troubleshooting

Symptom	Cause
<code>401 Invalid token.</code>	Token <code>iss</code> is the canonical tenant URL. Re-mint from <code>auth.product.federato.ai</code> . Or the token expired (they last 4 hours).
<code>301 Moved Permanently</code>	Wrong path shape. Check the <code>Location</code> header with <code>curl -i</code> , and use <code>--post301</code> if you want curl to follow it without dropping the body.
<code>404 Cannot POST /handlers/trigger/...</code>	Extra path segments after the handler slug. The 404 body echoes the internally rewritten path, which tells you what the router actually parsed.
<code>zsh: no matches found</code>	Not an API error. Your shell is glob-expanding the <code>?</code> in the URL. Quote the URL.
Query validates but returns zero results	Almost always a dot-path through an array field. Use <code>\$elemMatch</code> instead.
<code>Unknown action <x>.</code>	<code>action</code> is missing or misspelled; the endpoint only supports <code>schema</code> and <code>query</code> .
Errors arrive as a plain message, not a typed object	The workflow catches everything and rethrows <code>new Error(e.message)</code> , so the class, <code>code</code> and <code>details</code> properties are lost. The code and details survive inside the message text (<code>[VALIDATION_ERROR] Unknown operator "\$grt" {"operator":"\$grt"}</code>), so parse the string prefix if you need it machine-readable.

Key Points

- **Auth domain is critical:** Always use `auth.product.federato.ai`
- **Tokens last 4 hours:** Mint fresh if running long sessions
- **outputOnly=true:** Strips workflow envelope, gets just the data
- **Two actions only:** `schema` and `query`
- **Query troubleshooting:** Most issues are dot-paths on arrays (use `$elemMatch`)