

InnovAero Competition 2026

VIP Aircraft Cabin Acoustic Comfort Enhancement

Academic report structure prepared for technical review

Team	SlowWaveAero
Authors	Yossef Al Buni; Leander Meggers
Affiliation	Technische Universität Hamburg (TUHH) and NORDAKADEMIE Hochschule der Wirtschaft
Client context	Lufthansa Technik / InnovAero Competition 2026
Date	May 30, 2026

Abstract

This report consolidates the literature and design logic most relevant to the InnovAero task of improving acoustic comfort in a VIP aircraft cabin. The focus is on methods that are technically defensible and implementation-oriented: active noise control, adaptive filtering, virtual sensing, cabin-specific acoustic constraints, and hybrid passive-active concepts. The resulting structure is intended to support an academically rigorous submission that can be extended with competition-specific calculations, design assumptions, and verification data.

Contents

1	Introduction	1
1.1	Motivation	1
1.2	Report Purpose	1
1.3	Document Structure	1
2	Task Definition and Requirements	2
2.1	Competition Task	2
2.2	Key Requirements	2
2.3	Engineering Constraints	2
2.4	Success Criteria	2
3	Related Work	3
3.1	Problem Context	3
3.2	Active Noise Control Fundamentals	3
3.3	Aircraft-Cabin-Specific Constraints	3
3.4	Localized and Seat-Level Control	4
3.5	Passive, Active, and Hybrid Concepts	4
3.6	Data-Driven and Computational Approaches	4
3.7	Synthesis and Research Gap	5
3.8	Implications for the Competition Deliverable	5
3.9	Conclusion	5
4	System Concept	6
4.1	Concept Overview	6
4.2	Architecture	6
4.3	Why This Architecture Fits the Task	6
4.4	Design Principles	6
5	Methodology	7
5.1	Analysis Approach	7
5.2	Evaluation Metrics	7
5.3	Validation Plan	7
5.4	Expected Report Outputs	7
6	Conclusion and Outlook	8
6.1	Conclusion	8
6.2	Outlook	8

List of Tables

3.1	High-level comparison of cabin noise-control strategies	4
-----	---	---

1 Introduction

1.1 Motivation

Passenger comfort is a differentiating factor in premium aircraft cabins, especially in the VIP segment where the interior is expected to support work, rest, and quiet conversation. In this context, cabin noise is not only an engineering nuisance but also a design constraint that influences perceived quality, fatigue, and overall product value. The InnovAero task therefore requires a solution that is technically credible, compact, and compatible with aviation integration constraints.

1.2 Report Purpose

This report is structured to support a professional competition submission for Lufthansa Technik. It first defines the task and the relevant constraints, then reviews the literature, and finally derives a concept and a validation approach. The goal is not to present a finished certification package, but to establish a clear engineering argument that can be extended with calculations, simulations, and prototype data.

1.3 Document Structure

The following chapters provide a logical flow from context to solution.

- Chapter 2 summarizes the competition task and the engineering requirements.
- Chapter 3 reviews the most relevant literature on cabin noise control.
- Chapter 4 proposes a system-level concept for the VIP cabin use case.
- Chapter 5 outlines a methodology for analysis, simulation, and evaluation.
- Chapter 6 concludes the report and identifies the next development steps.

2 Task Definition and Requirements

2.1 Competition Task

The underlying task is to improve acoustic comfort in a VIP aircraft cabin using methods that are suitable for an engineering proposal delivered to Lufthansa Technik. The problem is inherently multidisciplinary because it combines acoustics, signal processing, structural integration, usability, and maintainability. A strong concept must therefore be evaluated not only by theoretical cancellation performance, but also by its feasibility as an aircraft interior solution.

2.2 Key Requirements

From an aerospace systems perspective, the most important requirements are low mass, low integration complexity, limited maintenance burden, robust operation under cabin variability, and a clear safety boundary around the active control functions. For a premium cabin, the design must also preserve the visual and spatial quality of the interior.

2.3 Engineering Constraints

The most relevant constraints are summarized below.

1. The solution should target the dominant low-frequency noise components where active methods are most effective.
2. The concept should remain localized enough to be installed around a seat group or premium zone rather than requiring full-cabin retrofit.
3. The architecture should tolerate model mismatch and operational variation, especially in the secondary path.
4. The design should allow passive trim to carry part of the load so that the active layer can remain compact.
5. The evaluation method should include both physical performance and passenger-facing acoustic quality.

2.4 Success Criteria

A successful submission should show that the chosen concept reduces the perceptually relevant noise components, can be integrated into a realistic cabin architecture, and is defensible against a review by aviation engineers. In practice, this means the report should explicitly connect the literature, the selected control strategy, and the expected implementation path.

3 Related Work

3.1 Problem Context

The InnovAero competition frames cabin acoustics as a practical systems-engineering problem rather than a purely theoretical signal-processing exercise. For a VIP aircraft interior, the objective is not simply to reduce overall sound pressure levels, but to improve perceived acoustic comfort under strong constraints on weight, maintenance, certification, reliability, and available installation volume. These constraints favor solutions that combine established acoustic engineering with computationally efficient control algorithms [1, 2].

The related literature shows that cabin noise reduction is usually approached through one of three routes: passive treatments, active control, or hybrid architectures. Passive measures are robust and low-risk, but they are limited in low-frequency performance and often add mass. Active methods can target the dominant tonal or quasi-stationary components more efficiently, yet they introduce dependency on sensors, reference signals, actuator placement, and controller stability. Hybrid concepts attempt to exploit the strengths of both approaches [3, 2].

3.2 Active Noise Control Fundamentals

Active noise control (ANC) is the central method family for low-frequency acoustic attenuation in confined environments. The classic feedforward ANC architecture uses a reference signal correlated with the disturbance, a secondary path from loudspeaker to error microphone, and an adaptive filter to generate anti-noise. Standard references describe the filtered-x least mean squares (FxLMS) family as the canonical implementation because it is computationally simple and robust enough for practical adaptive control [4, 5, 6].

In compact form, the controller seeks the coefficient vector $\mathbf{w}$ that minimizes the mean square error

$$J = \mathbb{E}\{e^2(n)\},$$

where the error $e(n)$ is measured at the control point after acoustic propagation through the secondary path. In practice, the controller update must account for the dynamics of the loudspeaker, amplifier, enclosure, and cabin geometry, because inaccurate secondary-path modelling quickly degrades stability and performance [5].

For aircraft applications, the literature repeatedly emphasizes that ANC is most effective at low frequencies where passive treatments are less efficient. This makes it suitable for engine-order noise, ventilation-related tonal components, and localized cabin resonances. However, broad spatial attenuation across an occupied cabin remains difficult because the acoustic field is nonuniform and the number of independently controllable zones is limited by hardware and computational cost [7, 8].

3.3 Aircraft-Cabin-Specific Constraints

The aircraft cabin is a strongly coupled acoustic-structural environment. Seats, trim panels, sidewalls, floor panels, and overhead monuments all contribute to the final sound field. In contrast to laboratory ANC test benches, a cabin contains many secondary paths and reflecting surfaces, and the disturbance spectrum is shaped by engines, airflow, structure-borne transmission, and interior furnishing. These characteristics create an implementation problem in which the acoustic model is only partially known and operational variability is high [9, 7].

This context has two important implications for a Lufthansa Technik-style design review. First, the control strategy must be modular so that it can be installed around premium seating or localized cabin zones without requiring a full aircraft-wide retrofit. Second, the solution should be tolerant to model mismatch and sensor drift, because maintenance access and calibration intervals in operational service are limited. The literature therefore favors localized control topologies over globally centralized ones when the target is a practical retrofit solution [10, 11].

3.4 Localized and Seat-Level Control

Recent work has moved ANC closer to the passenger rather than attempting to control the entire cabin volume. Seat-level and headrest-based approaches position error sensors and actuators near the listener, which reduces the number of required control points and improves the perceptual relevance of the cancellation zone. Studies on adjacent-seat control and headrest-based virtual sensing report that localized architectures can achieve meaningful perceived improvement with relatively low computational complexity [10, 12, 11].

Virtual sensing is especially relevant when physical microphones cannot be placed exactly at the ear location. In these systems, a model estimates the pressure at a desired point from measurements at accessible positions. That approach is attractive in VIP cabins because it preserves the interior design while still providing a controllable acoustic objective. The main trade-off is the need for a reliable transfer-function estimate between the measured and virtual locations [12, 13].

3.5 Passive, Active, and Hybrid Concepts

Passive and active methods should not be treated as competing absolutes. The literature increasingly presents them as complementary layers in a broader acoustic design. Passive trim can suppress structure-borne transmission and attenuate higher-frequency content, while active systems focus on the low-frequency residual that passive systems leave behind. This hybrid perspective is particularly suitable for aviation, where mass and certification pressure prevent purely passive overdesign [3, 2].

Table 3.1: High-level comparison of cabin noise-control strategies

Strategy	Strengths	Limitations
Passive treatment	Simple, robust, certification-friendly	Mass penalty and weak low-frequency performance
Active control	Strong low-frequency attenuation, adaptable	Requires sensors, actuators, and stable modelling
Hybrid approach	Balanced trade-off, system-level optimization	Higher integration complexity

Work on sidewall panels, trim panels, and hybrid structures shows that aircraft interior noise control can be embedded into cabin furniture and architectural elements. This is useful for premium cabins, where the acoustic solution must remain visually unobtrusive. The strongest results in the literature usually combine structural design, sensor placement strategy, and control-law tuning rather than relying on a single component in isolation [13, 14].

3.6 Data-Driven and Computational Approaches

More recent publications explore deep-learning-assisted or otherwise data-driven architectures for cabin noise control. These methods are promising where the acoustic environment is complex

and the mapping from disturbances to perception is difficult to model analytically. For example, learned control concepts can support trim-panel behavior or accelerate parameter selection in reduced-order models. However, the literature is still cautious: explainability, training data coverage, and certification suitability remain open issues for safety-critical aviation contexts [14].

From a systems perspective, data-driven methods are most useful when they are embedded in a physically interpretable framework. In other words, machine learning can support secondary-path estimation, fault detection, or parameter tuning, but the core safety-critical loop should remain bounded by transparent control logic and conservative validation procedures.

3.7 Synthesis and Research Gap

The literature points to a consistent research gap: a VIP cabin requires a solution that is localized, lightweight, adaptive, and operationally realistic. The most credible path is therefore a hybrid architecture that uses passive interior design to reduce the baseline noise floor and localized ANC to suppress low-frequency residuals at the passenger zone. Virtual sensing can expand the usable control region, while reduced-complexity adaptation keeps the implementation feasible on embedded hardware [5, 8, 12].

For the present competition, this suggests a design philosophy with four layers:

1. identify the dominant low-frequency disturbance components,
2. define a compact control zone around the passenger or seat group,
3. use passive treatments to address broadband and structural noise,
4. apply adaptive ANC only where the expected perceptual benefit justifies the complexity.

3.8 Implications for the Competition Deliverable

For an academically convincing submission to Lufthansa Technik, the report should make the control assumptions explicit, define measurable performance metrics, and separate established literature from the team's own design proposal. A strong structure would present the problem statement, review the three solution families, justify the selected architecture, and then provide a transparent evaluation plan. That format is more defensible than a purely descriptive summary because it demonstrates that the design choice is grounded in the state of the art rather than in intuition alone.

3.9 Conclusion

The related work indicates that no single noise-control technique is sufficient for a VIP aircraft cabin. Passive elements are necessary but insufficient, active control is powerful but localized, and data-driven enhancements are promising but not yet decisive for certification-oriented deployment. The most professional and technically credible approach is a hybrid, seat- or zone-level solution supported by robust modelling and conservative adaptation. This chapter can therefore serve as the literature basis for a more detailed concept, simulation section, and implementation strategy.

4 System Concept

4.1 Concept Overview

The proposed concept is a hybrid acoustic system for a VIP cabin zone. Passive interior elements provide broadband attenuation and structural damping, while a localized active control layer addresses the remaining low-frequency disturbance. This division of labor keeps the active system focused on the portion of the spectrum where it provides the highest value.

4.2 Architecture

A practical system can be organized into four blocks.

1. A reference path that captures or predicts the incoming disturbance.
2. A controller that computes the anti-noise signal.
3. Secondary-path actuators and loudspeakers placed near the passenger zone.
4. Error sensing or virtual sensing to evaluate the local residual sound field.

4.3 Why This Architecture Fits the Task

This architecture is suitable for the competition because it is modular, scalable, and easy to explain in an academic report. It can be deployed around a specific VIP seating area instead of the full aircraft interior, which reduces hardware count and integration effort. It also provides a natural bridge between classical ANC literature and a premium-cabin design context.

4.4 Design Principles

The concept should obey the following principles.

- Keep the control zone local and well-defined.
- Use passive treatment to reduce the required active effort.
- Favor low-order, computationally efficient adaptive control.
- Design for maintainability, not only for peak laboratory performance.

5 Methodology

5.1 Analysis Approach

The methodology should combine literature review, acoustic reasoning, and a validation-oriented design workflow. The first step is to identify the dominant cabin noise components and the likely transmission paths. The second step is to select a control topology that is compatible with the cabin layout. The third step is to estimate the benefit, complexity, and risk of the proposed design.

5.2 Evaluation Metrics

A professional assessment should use metrics that are meaningful for both engineering and passenger comfort.

- Residual sound pressure level in the target zone.
- Frequency-selective attenuation in the low-frequency band.
- Computational cost of the control update.
- Sensitivity to modelling errors and sensor placement.
- Integration impact on mass, volume, and maintenance effort.

5.3 Validation Plan

A clear validation plan can be built in three levels. First, a simplified analytical model is used to explain the control principle. Second, a simulation model evaluates the system under representative disturbance scenarios. Third, a hardware-oriented discussion checks whether the selected architecture can be integrated into a real cabin environment.

5.4 Expected Report Outputs

The final competition report should include the assumption set, the control block diagram, the evaluation criteria, and the rationale for choosing the final architecture. If data becomes available later, the same structure can be extended with simulation plots, frequency response results, and a comparison against alternative designs.

6 Conclusion and Outlook

6.1 Conclusion

The literature indicates that no single technique is sufficient for a premium aircraft cabin. Passive measures are robust, active control is effective in the low-frequency range, and hybrid systems provide the best balance between performance and feasibility. For an InnovAero submission, the strongest position is therefore a localized hybrid concept supported by a transparent methodology.

6.2 Outlook

The next development step should be a more detailed concept study with explicit geometry, control-zone definition, and disturbance assumptions. After that, the report can be expanded with simulation results, a comparison of candidate architectures, and a refined implementation discussion for Lufthansa Technik review.

Bibliography

- [1] Lufthansa Technik, “Innovaero competition 2026: Task description,” 2026, competition task document provided by the organiser.
- [2] Parker Aerospace, “Passive, active and hybrid solutions for aircraft interior noise problems,” White Paper, n.d., accessed for related-work preparation. [Online]. Available: https://www.parker.com/content/dam/Parker-com/Literature/noise-vibration---harshness-division/aerospace---defense/white-papers---case-studies/White-Paper---Passive-Active-and-Hybrid-Solutions-for-Aircraft-Interior-Noise-Problems_LL6007.pdf
- [3] Z. S. Liu, H. P. Lee, and C. Lu, “Passive and active interior noise control of box structures using the structural intensity method,” *Applied Acoustics*, vol. 67, no. 11–12, pp. 1121–1141, 2006.
- [4] S. J. Elliott and P. A. Nelson, “Active noise control,” *IEEE Signal Processing Magazine*, vol. 10, no. 4, pp. 12–35, 1993.
- [5] S. M. Kuo and D. R. Morgan, “Active noise control: A tutorial review,” *Proceedings of the IEEE*, vol. 87, no. 6, pp. 943–973, 1999.
- [6] P. A. Nelson and S. J. Elliott, *Active Control of Sound*. London: Academic Press, 1992.
- [7] S. Johansson, “Active noise control in aircraft,” Ph.D. dissertation, Blekinge Institute of Technology, 2015. [Online]. Available: <https://www.diva-portal.org/smash/get/diva2:838222/FULLTEXT01.pdf>
- [8] M. Misol, “Design of an active noise control system for aircraft interior noise,” in *Proceedings of the 29th International Congress on Sound and Vibration (ICSV29)*, 2023. [Online]. Available: <https://elib.dlr.de/195890/>
- [9] T. Kletschkowski, “Some insights in active control of noise and vibration in aircraft cabins,” in *Proceedings / Repository entry, Hamburg University of Applied Sciences*, 2020. [Online]. Available: <https://reposit.haw-hamburg.de/handle/20.500.12738/10681>
- [10] I. Dimino *et al.*, “Active noise control for aircraft cabin seats,” *Applied Sciences*, vol. 12, no. 11, p. 5610, 2022.
- [11] D. Mylonas *et al.*, “A low computational complexity local active noise control system for adjacent aircraft seats,” in *Forum Acusticum 2023*, 2023. [Online]. Available: <https://dael.euracoustics.org/confs/fa2023/data/articles/000022.pdf>
- [12] —, “A virtual sensing active noise control system based on a local headrest application,” *Journal of Vibration Engineering & Technologies*, 2024.
- [13] M. Misol and S. Algermissen, “Active sidewall panels with virtual microphones for aircraft interior noise reduction,” in *Conference paper / aircraft interior noise reduction*, 2020. [Online]. Available: https://www.researchgate.net/publication/344634967_Active_Sidewall_Panels_with_Virtual_Microphones_for_Aircraft_Interior_Noise_Reduction
- [14] B. Wang *et al.*, “Deep learning-based active trim panels for aircraft noise control,” in *AIAA Aviation Forum 2025*, 2025. [Online]. Available: <https://elib.dlr.de/215696/>