A Head Camera Is (Almost) All You Need

An electronics-free UMI glove labelled and observed by one moving camera

Yosub Shin[1] Yuan Liu[2] Igor Molybog[1] [1]University of Hawai'i at Mānoa [2]Independent

arXiv:2610.27622
The UMI Arena, CoRL 2026

Why a head camera only


- Wrist devices need a **second stream** to track the gripper: SLAM, an IMU, a controller or an external camera.
- **Gaze leads the hand**: the gripper stays in view, at arm's length, with the goal.
- The frames the policy sees are the frames that **carry the labels**.

No SLAM, no IMU, no wrist camera, no cables.

$144 glove, camera, strap

103 g on the head

One head camera: the policy's observation and the pose labels



(a) A $122 4K head camera, a $22 electronics-free glove, four paper tiles. (b) The camera's own frame: tiles give the camera pose, the ball the gripper pose, the jaw tags the opening. (c) At deployment the same camera rides a $122 six-joint arm (d) beside the robot.

Label accuracy

- **Camera pose** from the paper tiles, refit from the footage to 0.5 px.
- **Gripper pose** by PnP on a 15 mm ArUco dodecahedron.
- **Jaw width** from printed tails on the jaws.

6.5 mm tool point

1.6° orientation

3.5 % jaw width, of stroke

Median error against the robot's encoders; a label on 93–100 % of frames.

Collection

2–3× demos per minute vs teleop

198 demos in four sessions

6–8 s per demo; teleop 14 s

0 robot time

Continuous recording, episodes cut by a keypress; 0.7–7.4 % of frames dropped for tracking.


Deployment

- The same camera on a $122 six-joint arm beside the YAM.
- It follows the gripper **from the robot's encoders alone**, in teleoperation and in rollouts, so the policy sees what the collector saw.

46 mm head pose vs the collector


5.4° static camera: 87 mm, 7.0°

One placement, seen by each policy



Placement 23, each policy's own frames every 2 s on one clock, black once its episode ended. Head camera: gripper and bin in one frame through the carry, done in 16 s. Wrist fisheye: only block and wall after the grasp; drops the block before reaching the bin. Fixed camera: sees the whole scene but never closes the gripper (41 s, cut here).

Cheap glove demos complement a small teleop set



10/25
48 teleop episodes

17/25
48 teleop + 194 glove demos

1 ≈ 2–3
teleop episode ≈ glove demos

9 placements won to 2 lost ($p = 0.065$). On the curve (head-label chain, own held-out targets) the 194 glove demos are worth **65–100 teleop episodes**. With all 172 they still help: 18/25 → 20/25 (4 won to 2 lost, $p = 0.69$).

Head-camera labels can replace the encoders

teleop labelled by	encoders	head camera
validation loss	0.318	0.328 (+3 %)
rollouts	18/25	15/25 ($p = 0.58$)

Same 172 teleop episodes, same held-out encoder targets; 5 placements won to 8 lost ($p = 0.58$).

Where each view fails

failures of 25	no grasp	dropped	success
head camera	**5**	0	20
wrist fisheye (UMI)	6	**4**	15
wrist fisheye, head labels	3	**8**	14
fixed camera	**12**	1	12

Wrist-camera policies **drop the block mid-carry**, every time while the fisheye looked away from the bin. The head camera and the fixed camera keep the bin in frame and almost never drop; they fail by not grasping.

It is the view, not the labels

Same view, other labels
wrist fisheye observation

glove labels from	success	dropped
fixed camera	15/25	4
head camera	14/25	8

Same labels, other view
head-camera glove labels

observation	success	dropped
wrist fisheye	14/25	8
head camera	**20/25**	**0**

Limits and next

One task, one collector, one tile layout; teleoperation watched the head-camera view. Glove-only policies do not transfer: co-training is required. Next: bimanual, tile-free in the wild.

Setup: eight ACT policies, joint-space actions. Rollouts: 25 placements, one trial each, 60 s. Every co-trained mix uses the same 194 glove demos.