# **Insurance Damage Estimate**

Version: 1.0 Generated: 2025-08-18T00:00:00Z Currency: USD

Total Project Cost: USD 698.18

# Estimate reasoning

Toilet overflow resulted in contaminated water on the floor. Toilet shows heavy contamination/mineral buildup so full replacement is recommended. Perform moisture inspection and antimicrobial treatment of the affected floor area, contain the work area, remove/dispose contaminated items, caulk joints to restore seal, and perform final cleaning.

ID	Item	Qty	Unit	Unit Price	Tax	Total	Category
1	Moisture inspection + photos	1	USD 35.00	USD 0.00	USD 35.00	Inspection/ Documenta tion	
2	R&R Toilet	1	USD 541.5 3	USD 19.65	USD 561.18	Plumbing	
3	Antimicrobial treatment	20	USD 0.75	USD 0.00	USD 15.00	Mitigation	
4	Site protection & masking (small bath)	1	USD 40.00	USD 0.00	USD 40.00	Mitigation	
5	Debris bag & dispose (small)	1	USD 15.00	USD 0.00	USD 15.00	Debris/Disp osal	
6	Final clean	1	USD 20.00	USD 0.00	USD 20.00	Cleanup	
7	Caulk wall-to-tile joint	6	USD 2.00	USD 0.00	USD 12.00	Finishes	

# **Appendix: Item Details**

# 1 — Moisture inspection + photos

Initial moisture readings and photographic documentation of affected areas (floor, toilet, adjacent walls).

Tags: water, inspection

#### 2 - R&R; Toilet

Remove and replace contaminated/overflowed two-piece toilet including new wax ring. Replacement chosen due to heavy mineral/contamination and compromised seal.

Tags: toilet, replace

#### 3 — Antimicrobial treatment

Treat floor and immediate perimeter (approx. 20 SF) to mitigate microbial growth after sewage/dirty water exposure.

Tags: antimicrobial

## 4 — Site protection & masking (small bath)

Protect adjacent areas and contain dust/contaminants during work.

Tags: containment, dust

## 5 — Debris bag & dispose (small)

Bag and haul removed toilet and contaminated disposables.

Tags: disposal

#### 6 — Final clean

Remove masking, wipe down surfaces, tidy work area.

Tags: cleaning

# 7 — Caulk wall-to-tile joint

Re-seal wall-to-floor/tile joint around toilet area to restore watertight seal (approx. 6 LF).

Tags: sealant