## Model Checking: exercise set 12 - Dynamic fault trees

Due date: June 5

1. Prove that the exponential probability distribution is memoryless, i.e., that

$$\Pr(X > t + t' \mid X > t') = \Pr(X > t).$$


(The proof is in the article on Brightspace, but try it yourself first).

- 2. You are waiting for a package to arrive from the webshop Web-1. People have figured out that, for this webshop, the delivery time X is exponentially distributed with parameter  $\frac{1}{15}$  days (notation:  $X \sim Exp(\frac{1}{15})$  days).
  - (a) What is the expected amount you have to wait?
  - (b) What is the probability that you have to wait:
    - i. Less than 5 days?
    - ii. More than 10 days?
    - iii. Exactly 10 days?
    - iv. Between 10 and 25 days?
  - (c) You have been waiting for 15 days. What is the probability that from now on, you have to wait:
    - i. Less than 5 days?
    - ii. More than 10 days?
    - iii. Exactly 10 days?
    - iv. Between 10 and 25 days?
- 3. You are ordering, on the same day, a product from webshop Web-1 and a product from webshop Web-2. The delivery time X for Web-1 is still exponentially distributed with parameter  $\frac{1}{15}$  days  $(X \sim Exp(\frac{1}{15}) \text{ days})$ . The delivery time Y for Web-2 is also exponentially distributed with parameter  $\frac{1}{5}$  days  $(Y \sim Exp(\frac{1}{5}) \text{ days})$ .
  - (a) What is the probability that both packages will arrive at exactly the same moment?
  - (b) Give the delivery distribution for the first package to arrive, i.e., determine the probability of your package arriving within time t?
  - (c) What is the expected delivery time for the first package?
  - (d) What is the probability for the Web-1 package to arrive first?


Hint: Look at p181-182 of the paper on exponentials, as well as Example (a) on p183.

Reformulation: A completely different formulation of the same problem:

Your phone fails if either your connection fails or you have no power. The probability that your connection fails X is exponentially distributed with parameter  $\frac{1}{15}$  days  $(X \sim Exp(\frac{1}{15})$  days). The probability that you have no power Y is exponentially distributed with parameter  $\frac{1}{5}$  days  $(Y \sim Exp(\frac{1}{5})$  days). See the fault tree on the next page:



- (e) Consider the following four questions and explain why these answers are the same as for (a)-(d). Give one argument; there is no need to go into each question separately.
  - (a') What is the probability that your connection and power fail at the same time?
  - (b') Give the failure distribution for your phone, i.e., determine the probability for your phone to fail within time t?
  - (c') What is the expected time for your phone to fail?
  - (d') What is the probability that your phone fails due to your connection, i.e., your connection fails before you are out of power?
- 4. Consider a fault-tolerant system, as in the figure below.



- There are 4 types of processors: red, blue, yellow, and green.
- For each processor type (=color) there are 4 redundant copies, called A, B, C, and S, where S acts as a spare.
- The processors are connected via 4 network elements (NE), where each network element connects 4 processors, being one processor of each type.
- If the network element fails, then all elements connected to it also fail.

## Requirements:

• For the system to be up, at least 2 processors must be available for each type, as well as their associated network elements.

Construct a dynamic fault tree for this system. Use the dynamic spare and FDEP gates.