



courser

검색

- [설정](#)
- [업데이트](#)
- [성취도](#)
- [도움말 센터](#)
- [로그아웃](#)



Youngeun In ▾

Networks

nal)

◦



[테스트: The Basics of ConvNets](#)
[10개의 질문](#)

• **Programming Assignments**

• **Heroes of Deep Learning (Optional)**

테스트테스트 • 30 min30 minutes

The Basics of ConvNets



과제 제출
기한년 8월 23일 오후 3:59 KST년 8월 23일 오후 3:59 KST
시도하기8 hours당 3회

계속하기



성적 받기
통과 점수:80% 이상
성적
100%

피드백 보기

최고 점수가 유지됩니다.



탐색 확인

이 페이지에서 나가시겠습니까?

이 페이지에 머물기

이 페이지에서 나가기



The Basics of ConvNets
성적 평가 퀴즈 • 30 min



축하합니다! 통과하셨습니다!
통과 점수: 80% 이상

학습 계속하기

성적
100%

The Basics of ConvNets

최신 제출물 성적
100%

1.
질문 1

What do you think applying this filter to a grayscale image will do?

$$\begin{bmatrix} 0 & 1 & -1 & 0 \\ 1 & 3 & -3 & -1 \\ 1 & 3 & -3 & -1 \\ 0 & 1 & -1 & 0 \end{bmatrix}$$

$$\begin{bmatrix} 0 & 1 & -1 & 0 \\ 1 & 3 & -3 & -1 \\ 1 & 3 & -3 & -1 \\ 0 & 1 & -1 & 0 \end{bmatrix}$$

[[[[[01101331-1-3-3-10-1-10]]]]]

1 / 1점

☐ ☐

Detect horizontal edges

☐ ☐

Detect 45 degree edges

☒ ☐

Detect vertical edges

☐ ☐

Detect image contrast



맞습니다

Correct! As you can see the difference between values from the left part and values from the right of this filter is high. When convolving this filter on a grayscale image, the vertical edges will be detected.

2.
질문 2

Suppose your input is a 300 by 300 color (RGB) image, and you are not using a convolutional network. If the first hidden layer has 100 neurons, each one fully connected to the input, how many parameters does this hidden layer have (including the bias parameters)?

1 / 1점

☒ ☐

27,000,100

☐ ☐

9,000,001

☐ ☐

27,000,001

☐ ☐

9,000,100



맞습니다

Correct, the number of weights is $300 \times 300 \times 3 \times 100 = 27,000,000$ $300 \times 300 \times 3 \times 100 = 27,000,000$, when you add the bias terms (one per neurons) you get 27,000,10027,000,100.

3.

질문 3

Suppose your input is a 300 by 300 color (RGB) image, and you use a convolutional layer with 100 filters that are each 5x5. How many parameters does this hidden layer have (including the bias parameters)?

1 / 1점

☐ ☐

7500

☐ ☐

2600

☒ ☐

7600

☐ ☐

2501



맞습니다

Correct, you have $25 \times 3 = 75$ $25 \times 3 = 75$ weights and 11 bias per filter. Given that you have 100 filters, you get 7,600 parameters for this layer.

4.

질문 4

You have an input volume that is 63x63x16, and convolve it with 32 filters that are each 7x7, using a stride of 2 and no padding. What is the output volume?

1 / 1점

☐ ☐

29x29x16

☐ ☐

16x16x32

☒ ☐

29x29x32

☐ ☐

16x16x16



맞습니다

Yes, $\frac{63 - 7 + 0 \times 2}{2} + 1 = 29$ $263 - 7 + 0 \times 2 + 1 = 29$ and the number of channels should match the number of filters.

5.

질문 5

You have an input volume that is 15x15x8, and pad it using “pad=2.” What is the dimension of the resulting volume (after padding)?

1 / 1점

☐ ☐

19x19x12

☐ ☐

17x17x8

☒ ☐

19x19x8

☐ ☐

17x17x10



맞습니다

Correct, padding is applied over the height and the width of the input image. If the padding is two, you add 4 to the height dimension and 4 the width dimension.

6.

질문 6

You have an input volume that is 63x63x16, and convolve it with 32 filters that are each 7x7, and stride of 1. You want to use a “same” convolution. What is the padding?

1 / 1점

☐ ☐

1

☒ ☐

3

☐ ☐

7

☐ ☐

2



맞습니다

Correct, you need to satisfy the following equation: $n_H - f + 2 \times p = n_H$ as you want to keep the dimensions between the input volume and the output volume.

7.

질문 7

You have an input volume that is 32x32x16, and apply max pooling with a stride of 2 and a filter size of 2. What is the output volume?

1 / 1점

☐ ☐

15x15x16

☒ ☐

16x16x16

☐ ☐

32x32x8

☐ ☐

16x16x8



맞습니다

Correct, using the following formula: $n_H^{[l]} = \frac{n_H^{[l-1]} + f - 2p}{s}$ $n_H[l] = \text{snH}[l-1] + f - 2p$

8.
질문 8

Because pooling layers do not have parameters, they do not affect the backpropagation (derivatives) calculation.

1 / 1점

☐ ☐

True

☒ ☐

False

✓

맞습니다

Everything that influences the loss should appear in the backpropagation because we are computing derivatives. In fact, pooling layers modify the input by choosing one value out of several values in their input volume. Also, to compute derivatives for the layers that have parameters (Convolutions, Fully-Connected), we still need to backpropagate the gradient through the Pooling layers.

9.
질문 9

In lecture we talked about “parameter sharing” as a benefit of using convolutional networks. Which of the following statements about parameter sharing in ConvNets are true? (Check all that apply.)

1 / 1점

☒ ☐

It reduces the total number of parameters, thus reducing overfitting.

✓

맞습니다

Yes, a convolutional layer uses parameter sharing and has usually a lot less parameters than a fully-connected layer.

☐ ☐

It allows gradient descent to set many of the parameters to zero, thus making the connections sparse.

☐ ☐

It allows parameters learned for one task to be shared even for a different task (transfer learning).

☒ ☐

It allows a feature detector to be used in multiple locations throughout the whole input image/input volume.

✓

맞습니다

Yes, by sliding a filter of parameters over the entire input volume, we make sure a feature detector can be used in multiple locations.

10.
질문 10

In lecture we talked about “sparsity of connections” as a benefit of using convolutional layers. What does this mean?

1 / 1점

☐ ☐

Each layer in a convolutional network is connected only to two other layers

☐ ☐

Regularization causes gradient descent to set many of the parameters to zero.



Each filter is connected to every channel in the previous layer.



Each activation in the next layer depends on only a small number of activations from the previous layer.



맞습니다

Yes, each activation of the output volume is computed by multiplying the parameters from **only one filter** with a volumic slice of the input volume and then summing all these together.