

강좌 내에서 검색
강좌 내에서 검색

검색



coursera

Convolutional Neural Networks

>
3주 차
>

Detection Algorithms

< 이전 다음 >



- **Detection Algorithms**

- **Lecture Notes (Optional)**

- **Quiz**



테스트: [Detection Algorithms](#)
10개의 질문

- **Programming Assignments**

테스트테스트 • 30 min30 minutes

Detection Algorithms



과제 제출
기한년 9월 6일 오후 3:59 KST년 9월 6일 오후 3:59 KST
시도하기8 hours당 3회

다시 시도해주십시오



성적 받기
통과 점수:80% 이상
성적
100%

피드백 보기

최고 점수가 유지됩니다.



탐색 확인

이 페이지에서 나가시겠습니까?

이 페이지에 머물기

이 페이지에서 나가기



Detection Algorithms
성적 평가 퀴즈 • 30 min

만료 년 9월 6일 오후 3:59 KST



축하합니다! 통과하셨습니다!
통과 점수: 80% 이상

학습 계속하기

성적
100%

Detection Algorithms

최신 제출물 성적
100%

1.
질문 1

You are building a 3-class object classification and localization algorithm. The classes are: pedestrian (c=1), car (c=2), motorcycle (c=3). What should y be for the image below? Remember that “?” means “don’t care”, which means that the neural network loss function won’t care what the neural network gives for that component of the output. Recall $y = [p_c, b_x, b_y, b_h, b_w, c_1, c_2, c_3]$ $y = [p_c, b_x, b_y, b_h, b_w, c_1, c_2, c_3]$.



1 / 1점



$y = [0, ?, ?, ?, ?, ?, ?, ?]$ $y = [0, ?, ?, ?, ?, ?, ?, ?]$



$y = [1, ?, ?, ?, ?, ?, ?, ?]$ $y = [1, ?, ?, ?, ?, ?, ?, ?]$



$y = [0, ?, ?, ?, ?, 0, 0, 0]$ $y = [0, ?, ?, ?, ?, 0, 0, 0]$



$y = [?, ?, ?, ?, ?, ?, ?, ?]$ $y = [?, ?, ?, ?, ?, ?, ?, ?]$



$y = [1, ?, ?, ?, ?, 0, 0, 0]$ $y = [1, ?, ?, ?, ?, 0, 0, 0]$



맞습니다

Correct.

2.
질문 2

You are working on a factory automation task. Your system will see a can of soft-drink coming down a conveyor belt, and you want it to take a picture and decide whether (i) there is a soft-drink can in the image, and if so (ii) its bounding box. Since the soft-drink can is round, the bounding box is always square, and the soft drink can always appear as the same size in the image. There is at most one soft drink can in each image. Here’re some typical images in your training set:



What is the most appropriate set of output units for your neural network?

1 / 1점

☐

Logistic unit, $b_x b_x$, $b_y b_y$, $b_h b_h$ (since $b_w b_w = b_h b_h$)

☒

Logistic unit, $b_x b_x$ and $b_y b_y$

☐

Logistic unit, $b_x b_x$, $b_y b_y$, $b_h b_h$, $b_w b_w$

☐

Logistic unit (for classifying if there is a soft-drink can in the image)



맞습니다

Correct!

3.
질문 3

If you build a neural network that inputs a picture of a person's face and outputs N landmarks on the face (assume the input image always contains exactly one face), how many output units will the network have?

1 / 1점

☐

3N

☐

N

☐

$N^2 N^2$

☒

2N



맞습니다

Correct

4.
질문 4

When training one of the object detection systems described in lecture, you need a training set that contains many pictures of the object(s) you wish to detect. However, bounding boxes do not need to be provided in the training set, since the algorithm can learn to detect the objects by itself.

1 / 1점

☐

True

☒

False



맞습니다

Correct, you need bounding boxes in the training set. Your loss function should try to match the predictions for the bounding boxes to the true bounding boxes from the training set.

5.
질문 5

What is the IoU between these two boxes? The upper-left box is 2x2, and the lower-right box is 2x3. The overlapping region is 1x1.



1 / 1점

☒

1/9

☐ ☐

1/6

☐ ☐

1/10

☐ ☐

None of the above



맞습니다

Correct, the left box's area is 4 while the right box 's is 6. Their intersection's area is 1. So their union's area is $4 + 6 - 1 = 9$ which leads to an intersection over union of $1/9$.

6.
질문 6

Suppose you run non-max suppression on the predicted boxes above. The parameters you use for non-max suppression are that boxes with probability ≤ 0.4 are discarded, and the IoU threshold for deciding if two boxes overlap is 0.5. How many boxes will remain after non-max suppression?



1 / 1점

☐ ☐

3

☐ ☐

4

☐ ☐

6

☒ ☐

5

☐ ☐

7



맞습니다

Correct!

7.
질문 7

Suppose you are using YOLO on a 19x19 grid, on a detection problem with 20 classes, and with 5 anchor boxes. During training, for each image you will need to construct an output volume y as the target value for the neural network; this corresponds to the last layer of the neural network. (y may include some "?", or "don't cares"). What is the dimension of this output volume?

1 / 1점

☐ ☐

19x19x(5x20)

☐ ☐

19x19x(20x25)

☒ ☐

19x19x(5x25)

☐ ☐

19x19x(25x20)



맞습니다

Correct, you get a 19x19 grid where each cell encodes information about 5 boxes and each box is defined by a confidence probability (p_c pc), 4 coordinates (b_x, b_y, b_h, b_w bx, by, bh, bw) and classes (c_1, \dots, c_{20} c1, ..., c20).

8.
질문 8

What is Semantic Segmentation?

1 / 1점

☐

Locating an object in an image belonging to a certain class by drawing a bounding box around it.

☐

Locating objects in an image belonging to different classes by drawing bounding boxes around them.

☒

Locating objects in an image by predicting each pixel as to which class it belongs to.



맞습니다
9.
질문 9

Using the concept of Transpose Convolution, fill in the values of **X**, **Y** and **Z** below.

(padding = 1, stride = 2)

Input: 2x2

1 2

3 4

Filter: 3x3

1 0 -1

1 0 -1

1 0 -1

Result: 6x6

0 1 0 -2

0 **X** 0 **Y**

0 1 0 **Z**

0 1 0 -4

1 / 1점

☐

X = 2, Y = -6, Z = 4

☒

X = 2, Y = -6, Z = -4

☐

X = -2, Y = -6, Z = -4

☐

X = 2, Y = 6, Z = 4



맞습니다
10.
질문 10

Suppose your input to an U-Net architecture is $h \times h \times w \times w \times 3$, where 3 denotes your number of channels (RGB). What will be the dimension of your output ?

1 / 1점

☐

$h \times h \times w \times w \times n$, where n = number of input channels

☐

$h \times h \times w \times w \times n$, where n = number of filters used in the algorithm

☒

$h \times h \times w \times w \times n$, where n = number of output classes

☐

D: $h \times h \times w \times w \times n$, where n = number of of output channels



맞습니다